


Overview

HPE ProLiant DL580 Generation9 (Gen9)

The HPE ProLiant DL580 Gen9 Server is the Hewlett Packard Enterprise four socket (4S) enterprise standard x86 server offering commanding performance, rock-solid reliability and availability, and compelling consolidation and virtualization efficiencies.

Supporting Intel® Xeon® E7-4800/8800 v4/v3 processors, the HPE DL580 Gen9 offers enhanced processor performance, up to 6 TBs of memory, greater IO bandwidth (9 PCIe Gen3.0 slots), and 12 Gb/s of SAS speeds. HPE ProLiant DL580 Gen9 has security and data protection features for system resiliency that your business can depend on. All, making it ideal for mission-critical enterprise, business intelligence, and database applications.


Whether needed for highly virtualized or cloud based deployments, with intelligence and simplicity of automated management with HPE OneView and HPE iLO 4 your business can achieve agile and lower cost infrastructure management.



Front View

- | | |
|---|---|
| <ul style="list-style-type: none"> 1 CPU Memory Drawer Handle 3 Drive bays 6-10
<i>NOTE: Drives installed in these bays require the optional SAS backplane and cables.</i>
<i>NOTE: Optional NVMe drives are only supported in Drive bays 6-10.</i> 5 Health Status LED 7 NIC status LED 9 Fans 1-4 11 Discovery services connectors 13 USB connectors (2) | <ul style="list-style-type: none"> 2 Quick removal access panel 4 Systems Insight Display 6 Power On/Standby button and system power LED button 8 UID button 10 Drive bays 1-5 12 Video connector |
|---|---|

Overview




Rear View

- 1 Serial connector
- 2 Video connector
- 3 Power Supplies 1-4
- 5 Dedicated iLO connector
- 7 USB connectors (4)

- 4 PCI expansion slots 1-9
- 6 FlexibleLOM ports 1-4

NOTE: Port configuration is dependent on the installed FlexibleLOM and may differ from what is shown in the illustration.



Internal View

- 1 CPU Memory Drawer
- 3 Processors 1-4
- 5 I/O Card Auxiliary Power Connectors
- 7 PCI expansion slots 1-9
- 9 SPI board (houses iLO chip, FBWC, microSD slot, 2x USB slots, TPM, top SAS backplane connector)

- 2 Memory Cartridges 1-8
- 4 FBWC capacitor slots 1-4
- 6 Power Supplies
- 8 FlexibleLOM connector
- 10 MicroSD Slot

Standard Features

NOTE: For more information regarding Intel Xeon processors, please see the following <http://www.intel.com/xeon>.

Processor	Model	CPU frequency	Cores	L3 Cache	Power	QPI	DDR4 Hz
One or more of the following depending on model	E7-8893v3	3.2GHz	4	45MB	140W	9.6GT/s	1866
	E7-8891v3	2.8GHz	10	45MB	165W	9.6GT/s	1866
	E7-8890v3	2.5GHz	18	45MB	165W	9.6GT/s	1866
	E7-8880v3	2.3GHz	18	45MB	150W	9.6GT/s	1866
	E7-8880Lv3	2.0GHz	18	45MB	115W	9.6GT/s	1866
	E7-8870v3	2.1GHz	18	45MB	140W	9.6GT/s	1866
	E7-8867v3	2.5GHz	16	45MB	165W	9.6GT/s	1866
	E7-8860v3	2.2GHz	16	40MB	140W	9.6GT/s	1866
	E7-4850v3	2.2GHz	14	35MB	115W	8.0GT/s	1866
	E7-4830v3	2.1GHz	12	30MB	115W	8.0GT/s	1866
	E7-4820v3	1.9GHz	10	25MB	115W	6.4GT/s	1866
	E7-4809v3	2.0GHz	8	20MB	115W	6.4GT/s	1866
	E7-8893v4	3.2GHz	4	60MB	140W	9.6GT/s	1866
	E7-8891v4	2.8GHz	10	60MB	165W	9.6GT/s	1866
	E7-8890v4	2.2GHz	24	60MB	165W	9.6GT/s	1866
	E7-8880v4	2.2GHz	22	55MB	150W	9.6GT/s	1866
	E7-8870v4	2.1GHz	20	50MB	140W	9.6GT/s	1866
	E7-8867v4	2.4GHz	18	45MB	165W	9.6GT/s	1866
	E7-8860v4	2.2GHz	18	45MB	140W	9.6GT/s	1866
	E7-4850v4	2.1GHz	16	40MB	115W	8.0GT/s	1866
E7-4830v4	2.0GHz	14	35MB	115W	8.0GT/s	1866	
E7-4820v4	2.0GHz	10	25MB	115W	6.4GT/s	1866	
E7-4809v4	2.1GHz	8	20MB	115W	6.4GT/s	1866	

Chipset Intel® C602J Chipset
 Intel® Xeon® E7-4800/8800v3 Processor Family
 Intel® Xeon® E7-4800/8800v4 Processor Family
NOTE: For more information regarding Intel® chipsets, please see the following URL:
<http://www.intel.com/products/server/chipsets/>

On System Management Chipset HPE iLO (Firmware HPE iLO4 2.40 or later), 4GB NAND
NOTE: Read and learn more in the [iLO QuickSpecs](#).

Standard Features

Memory	Type:
One of the	HPE SmartMemory
following	DDR4 Registered (RDIMM) and Quad Rank Load Reduced (LRDIMM)
depending on	DIMM Slots Available 96
model	Maximum 6TB (96 x 64GB)

NOTE: Hewlett Packard Enterprise memory from previous generation servers are not qualified or warranted with this HPE ProLiant Server. HPE SmartMemory is required to realize the memory performance improvements and enhanced functionality listed in this document for Gen9. For additional information, please see the [HPE SmartMemory QuickSpecs](#).

NOTE: LRDIMM and RDIMM are distinct memory technologies and cannot be mixed within a server.

NOTE: Depending on the memory configuration and processor model, the memory speed may run at 1866MHz, 1600MHz, or 1333MHz. Please see Memory Population Table below or the Online Memory Configuration Tool at: [HPE Server Memory Configurator](#).

Network Controller	FlexibleLOM
--------------------	-------------

HPE ProLiant Gen9 servers offer a new flexible network technology - FlexibleLOMs, which offers customers a choice of 1Gb, 10Gb, or 10Gb base-T Ethernet or converged networking in their embedded adapter:

- HPE Ethernet 1Gb 4-port 331FLR FIO Adapter
- HPE Ethernet 1Gb 4-port 366FLR FIO Adapter
- HPE FlexFabric 10Gb 2-port 533FLR-T FIO Adapter
- HPE FlexFabric 10Gb 2-port 534FLR-SFP+ FIO Adapter
- HPE Ethernet 10Gb 2-port 546FLR-SFP+ FIO Adapter
- HPE FlexFabric 10Gb 2-port 556FLR-SFP+FIO Adapter
- HPE FlexFabric 10Gb 2-port 556FLR-T FIO Adapter
- HPE Ethernet 10Gb 2-port 560FLR-SFP+ FIO Adapter
- HPE Ethernet 10Gb 2-port 561FLR-T FIO Adapter
- HPE Ethernet 10Gb 2-port 562FLR-SFP+FIO Adapter

NOTE: For additional details see the Networking Section of this document.

NOTE: Wake-on-LAN feature is not supported on the DL580 Gen9 with FlexibleLOMs.

Expansion Slots

Standard Features

Primary Riser (Standard)	Expansion Technology Slots #	Bus Width	Connector Width	Bus Number	Form Factor	Notes
	1	PCIe 3.0	x16	x16	C0/03/0	Full length/full height Proc 4
	2	PCIe 3.0	x16	x16	C0/02/0	Full length/full height Proc 4
	3	PCIe 3.0	x16	x16	80/03/0	Full length/full height Proc 3
	4	PCIe 3.0	x8	x16	80/02/0	Full length/full height Proc 3
	5	PCIe 3.0	x8	x16	80/02/1	Full length/full height Proc 3
	6	PCIe 3.0	x16	x16	40/03/0	Full length/full height Proc 2
	7	PCIe 3.0	x8	x16	40/02/0	Full length/full height Proc 2
	8	PCIe 3.0	x8	x16	40/02/1	Full length/full height Proc 2
	9	PCIe 3.0	x16	x16	00/03/0	Full length/full height Proc 1

NOTE: PCIe slot availability is dependent on the number of processors installed.

NOTE: Inserting cards with PCI bridges may alter the actual bus assignment number.

NOTE: Slots are enumerated differently based on OS. MS OS's enumerate from lowest to highest Device ID by bus (starting with the lowest bus).

NOTE: Up to 9 slots supported; all full-length/full-height. Standard: 4 PCI-E 3.0 x8, 5 PCI-E 3.0 x16.

Internal Storage Devices One of the following depending on model	Hard Disk Drive Backplane	Internal SAS lower and upper backplanes support up to ten SFF hard disk drives or solid state drives or Express Bays (NVMe drives) NOTE: For Factory Integrated models, five (5) lower drive bays ship standard and five (5) upper drive bays can be ordered separately with a drive backplane kits. For Pre-configured models, please refer to the pre-configured models section below.
	Diskette Drive	None
	Optional Optical Drive	External
	Hard Drives	None ship standard

Standard Features

Maximum Internal Storage		CAPACITY	CONFIGURATION
	Hot Plug SFF SAS	20TB	10 x 2.0TB
	Hot Plug SFF SAS SSD	38.4TB	10 x 3.84TB
	Hot Plug SFF SATA SSD	38.4TB	10 x 3.84TB
	Hot Plug SFF NVMe PCIe SSD	8TB	5 x 1.6TB

NOTE: Optional support for 5 NVMe SSDs or 5 SFF drives are also available.

Power Supply One of the following depending on model	HPE 1500W Common Slot Platinum Plus Hot Plug Power Supply
	HPE 1500W Common Slot 48VDC Hot Plug Power Supply
	HPE 1200W Common Slot Platinum Plus Hot Plug Power Supply

NOTE: 1500W power supply supports high line voltage only.

NOTE: A minimum of two (2) power supplies are required. Four (4) 1500W power supplies offers N+N redundancy for highly loaded configurations.

Prior to making a power supply selection it is highly recommended that the HPE Power Advisor is run to determine the right size power supply for your server configuration. The HPE Power Advisor is located at: <http://www.hp.com/go/hppoweradvisor>.

The Hewlett Packard Enterprise Common Slot (CS) power supplies allow for commonality of power supplies across a wide range of ProLiant and Integrity servers, as well as HPE Storage solutions, and are designed to provide the highest power supply efficiency without degrading system performance. Hewlett Packard Enterprise CS power supplies are tested by the Electric Power Research Institute (EPRI) and certified through the ECOS 80 Plus power supply program. HPE CS power supply options provide efficiency ratings of up to 94% (80 Plus Platinum) and are available. All Hewlett Packard Enterprise Common Slot power sources are UL, CE Mark Compliant, hot-plug and support redundant configurations.

HPE CS Platinum Plus power supplies are required when enabling HPE's Intelligent Power Discovery (IPD) solution. IPD is the first technology to create an automated, energy-aware network between IT systems and facilities. This allows your company to reclaim millions of dollars in wasted power capacity and downtime costs across data centers. For more information on the Hewlett Packard Enterprise IPD solution, go to [HPE Intelligent Power Distribution Units](#).

NOTE: Mixing of power supplies in the same server is not supported. All power supplies must be of the same output and efficiency rating. If non-matched power supplies are inserted you will get errors and operation will fail.

Standard Features

Required Cabling Server Power Cords

Server ships with high-voltage server to PDU power cord.

NOTE: If customers require a local power cord, they can check the power cord matrix for the appropriate SKU. Please see the following power cord matrix for details:

<http://www.hp.com/go/powercordmatrix>.

System Fans	Non-redundant	Redundant
4 Hot Plug Fans (eight rotors with N+1 redundancy)		

Interfaces	Serial	1 back
	Video	1 front; 1 back
	FlexibleLOM Network Ports	Selection of FlexibleLOM options
	iLO 4 Remote Management	1 x 1Gbe dedicated
	Micro SD Slot	1 internal
NOTE: Dual microSD USB option kit also available (741279-B21).		
	USB 2.0 Ports	8 total: 2 front; 4 back; 2 internal

Operating Systems and Virtualization Software Support for ProLiant Servers	Microsoft Windows Server
	Red Hat Enterprise Linux (RHEL)
	SUSE Linux Enterprise Server (SLES)
	VMware
	CentOS
	Oracle Linux
NOTE: For more information on Hewlett Packard Enterprise Certified and Supported ProLiant Servers for OS and Virtualization Software and latest listing of software drivers available for your server, please visit our Support Matrix at:	
http://www.hp.com/go/ossupport and our driver download page	
http://h20565.www2.hp.com/hpsc/swd/public/readIndex?sp4ts.oid=8090151 .	

Upgradeability	Upgradeable to 4 processors
	Up to 96 DDR4 DIMM slots
	9 PCIe Gen3 expansion slots
	NOTE: PCIe slot availability is dependent on the number of processors installed. Please refer to the "Expansion Slots" section for more details.
	10 SFF internal HDD/SSD SAS drive bays or 5 SFF Internal Express Bays + 5 SFF Internal HDD/SSD drive bays
	NOTE: Five drive bays come standard. An optional five SAS drive or five Express backplane kit with five drive bays can be ordered for ten drives.
	5 NVMe SSD drive bays
4 redundant hot-plug power supplies	

Standard Features

Industry Standard ACPI 2.0. Compliant

Compliance

PCIe 2.0 Compliant

PXE Support

WOL Support

NOTE: Not supported with FlexibleLOMs on DL580 Gen9.

Physical Address Extension (PAE) Support

Microsoft® Logo certifications

USB 2.0 Support

ASHRAE A3/A4

NOTE: For additional technical thermal details regarding ambient temperatures, humidity and features support please visit: <http://www.hp.com/servers/ASHRAE>.

Graphics

Integrated Matrox G200 video standard

- 16 MB Flash
- 256 MB DDR 3 with ECC (112 MB after ECC and video)

HPE iLO 4 On System Management Memory

- 16 MB Flash
- 256 MB DDR 3 with ECC (112 MB after ECC and video)

HPE Server
UEFI/Legacy
ROM

Unified Extensible Firmware Interface (UEFI) is an industry standard that provides better manageability and more secured configuration than the legacy ROM while interacting with your server at boot time. HPE ProLiant Gen9 platform defaults to UEFI and can be factory or field configured for Legacy BIOS Boot Mode.

NOTE: The UEFI System Utilities function is analogous to the HPE ROM-Based Setup Utility (RBSU) of legacy BIOS. For more information, please visit <http://www.hpe.com/servers/uefi>.

UEFI enables numerous new capabilities specific to HPE ProLiant servers such as:

- Secure Boot
- Operating system specific functionality
- Support for > 2.2 TB (using GPT) boot drives
- USB 3.0 Stack
- Embedded UEFI Shell
- Mass Configuration Deployment Tool using RESTful API for iLO 4
- PXE boot support for IPv6 networks
- Boot support for option cards that only support a UEFI option ROM
- Network Stack configurations

NOTE: For UEFI Boot Mode, boot environment and OS image installations should be configured properly to support UEFI.

NOTE: UEFI FIO Setting (758959-B22) can be selected to configure the system in Legacy mode in the factory for your HPE ProLiant Gen9 Server.

Form Factor

4U rack

Standard Features

Embedded Management	HPE Integrated Lights-Out (HPE iLO)	Monitor your servers for ongoing management, service alerting, reporting and remote management with HPE iLO. Learn more at http://www.hpe.com/info/ilo .
	UEFI	Configure and boot your servers securely with industry standard Unified Extensible Firmware Interface (UEFI). Learn more at http://www.hpe.com/servers/uefi .
	RESTful API	RESTful API for iLO 4 is Redfish 1.0 conformance for simplified server management such as configuration and maintenance tasks based on modern industry standards. Learn more at http://www.hpe.com/info/restfulapi .
	Intelligent Provisioning	Hassle free server and OS provisioning for 1 or few servers with Intelligent Provisioning. Learn more at http://www.hpe.com/servers/intelligentprovisioning .
	Embedded Remote Support	The Hewlett Packard Enterprise embedded remote support, when used with Insight Online direct connect or HPE Insight Remote Support, allows HPE ProLiant servers to transmit hardware events directly to Hewlett Packard Enterprise or a Hewlett Packard Enterprise Authorized Partner for automated phone home support. Learn more at http://www.hpe.com/info/insightonline/explore .

Server utilities	Smart Update	Optimize firmware and driver updates with Smart Update solutions including Smart Update Manager (SUM) and Service Pack for ProLiant (SPP). Learn more at http://www.hpe.com/servers/smartupdatemanager .
	HPE Systems Insight Manager (HPE SIM)	HPE SIM allows you to monitor the health of your HPE ProLiant Servers and HPE Integrity Servers, and also provides you with basic support for non-HPE servers. HPE SIM also integrates with Smart Update Manager to provide quick and seamless firmware updates. Learn more at http://www.hpe.com/servers/hpsim .
	Scripting Tool Kit and Windows PowerShell	Provision 1 to many servers using your own scripts to discover and deploy them with Scripting Tool Kit (STK) for Windows and Linux or Scripting Tools for Windows PowerShell. Learn more at http://www.hpe.com/servers/proliant/stk or http://www.hpe.com/servers/powershell .
	RESTful Interface Tool	RESTful Interface tool is a scripting tool to provision using RESTful API for iLO 4 to discover and deploy servers at scale. Learn more at http://www.hpe.com/info/resttool .

Standard Features

HPE iLO Mobile Application	Enables the ability to access, deploy, and manage your server anytime from anywhere from select smartphones and mobile devices. For additional information please visit: http://www.hpe.com/info/ilo/mobileapp .
HPE Insight Online	HPE Insight Online, available at no additional cost as part of your Hewlett Packard Enterprise warranty or contractual support agreement with Hewlett Packard Enterprise, is a personalized dashboard for simplified tracking of IT operations and support information from anywhere, anytime. Learn more at http://www.hpe.com/info/insightonline/explore .

Security

- Power-on password
- Keyboard password
- External USB port enable/disable
- Network Server Mode
- Serial interface control
- Administrator's password
- Trusted Platform Module (TPM)
- TPM 2.0

NOTE: HPE Trusted Platform Module 2.0 Option (745823-B21) works with Gen9 servers with UEFI Mode not Legacy Mode. It is not compatible with HP ProLiant Gen8 servers or earlier generation variants. HPE Gen9 servers purchased earlier may need the latest firmware update to be compatible with the TPM 2.0 Option. The earlier HPE Trusted Platform Module Option (488069-B21) is the TPM 1.2 version, which is also available however TPM 2.0 has newer technology standards incorporated. The TPM 1.2 compatible server platforms include Gen8 and Gen9 servers. HPE server systems can have a TPM module (of any type) installed only once. It cannot be replaced with any other TPM module.

- Intel® Secure Key
- HPE Secure Encryption (Smart Array Controller)
- HPE Advanced Data Guard (Smart Array Controller)

Warranty

This product is covered by a global limited warranty and supported by HPE Services and a worldwide network of HPE Authorized Channel Partners resellers. Hardware diagnostic support and repair is available for three years from date of purchase. Support for software and initial setup is available for 90 days from date of purchase. Enhancements to warranty services are available through HPE Care Pack services or customized service agreements. Hard drives have either a one year or three year warranty; refer to the specific hard drive QuickSpecs for details.

NOTE: Server Warranty includes 3-Year Parts, 3-Year Labor, 3-Year Onsite support with next business day response. Warranty repairs may be accomplished through the use of Customer Self Repair (CSR) parts. These parts fall into two categories: 1) Mandatory CSR parts are designed for easy replacement. A travel and labor charge will result when customers decline to replace a Mandatory CSR part; 2) Optional CSR parts are also designed for easy replacement but may involve added complexity. Customers may choose to have HPE replace Optional CSR parts at no charge. Additional information regarding worldwide limited warranty and technical support is available at: <http://h18004.www1.hp.com/products/servers/platforms/warranty/index.html>.

Optional Features

Embedded Management	iLO Advanced	HPE iLO Advanced licenses offer smart remote functionality without compromise, for all HPE ProLiant servers. The license includes the full integrated remote console, virtual keyboard, video, and mouse (KVM), multi-user collaboration, console record and replay, and GUI-based and scripted virtual media and virtual folders. You can also activate the enhanced security and power management functionality. Learn more about HPE iLO Advanced at http://www.hpe.com/servers/iloadvanced .
Server Management	HPE Insight Control	HPE Insight Control, lets you deploy, migrate, monitor, remote control, and optimize your IT infrastructure through a single, simple management console. For more information, see http://www.hpe.com/info/insightcontrol .
	HPE Insight Cluster Management Utility (CMU)	HPE Insight Cluster Management Utility is a HyperScale management framework that includes software for the centralized provisioning, management and monitoring of nodes and infrastructure. Learn more at http://www.hpe.com/info/cmu .
Rack and Power Infrastructure	HPE Rack and Power Infrastructure products and services create highly efficient and intelligent solutions for existing or new IT data centers. HPE Rack and Power infrastructure solutions - rack infrastructure, power protection and management, performance optimized data centers (PODs) - are the foundation you are looking for to help secure your long-term IT success. These products are designed to help you react to changes in the industry. They deliver efficient, easy-to-use capabilities to manage, monitor, deploy and provision infrastructure from entry to enterprise. As an industry leader, Hewlett Packard Enterprise is uniquely positioned to address the key concerns of power, cooling, cable management and system access. Learn more at HPE Rack and Power Infrastructure .	
High Performance Clusters	HPE Cluster Platforms	HPE Cluster Platforms are specifically engineered, factory-integrated large-scale ProLiant clusters optimized for High Performance Computing, with a choice of servers, networks and software. Operating system options include specially priced offerings for Red Hat Enterprise Linux and SUSE Linux Enterprise Server, as well as Microsoft Windows HPEC Server. A Cluster Platform Configurator simplifies ordering. http://www.hp.com/go/clusters
	HPE HPEC Interconnects	High Performance Computing (HPC) interconnect technologies are available for this server as part of the HPE Cluster Platform portfolio. These high-speed InfiniBand and Gigabit interconnects are fully supported by Hewlett Packard Enterprise when integrated within a Hewlett Packard Enterprise cluster. Flexible, validated solutions can be defined with the help of configuration tools. http://www.hp.com/techservers/clusters/ucp/index.html
	HPE Insight Cluster Management Utility	HPE Insight Cluster Management Utility (CMU) is a Hewlett Packard licensed and supported suite of tools that are used for lifecycle management of hyperscale clusters of Linux ProLiant systems. CMU includes software for the centralized provisioning, management and monitoring of nodes. CMU makes the

Optional Features

administration of clusters user friendly, efficient, and effective.

<http://www.hp.com/go/cmu>

HPC
Interconnects

NOTE: High Performance Computing (HPC) interconnect technologies are available for this server under the HPE Cluster Platform product portfolio. These high-speed interconnects are fully supported by Hewlett Packard Enterprise when they are part of these configure to order clusters. Solutions can be defined with a lot of flexibility with the help of configuration tools. Please visit the following URL to configure HPEC Clusters with InfiniBand Interconnects: <http://www.hp.com/techservers/clusters/ucp/index.html>.

Storage Software Whether you need to solve a specific data protection, archiving, or storage command and control challenge, or deliver on strategic consolidation, compliance, or continuity initiatives, look no further than Hewlett Packard Enterprise storage software. Our storage software helps you reduce costs, simplify storage infrastructure, protect vital assets and respond faster to business opportunities.

Storage software that gets the job done:

- **Data Protection and Recovery Software**
Whether you're a large enterprise or a smaller business, Hewlett Packard Enterprise data protection and recovery software will cost-effectively protect you against disaster and ensure business continuity.
- **Data Archive and Migration Software**
Hewlett Packard Enterprise storage software enables you to comply with data retention and retrieval requirements, improve application performance, and reduce costs by efficiently migrating infrequently accessed or less valuable data to lower cost storage.
- **Storage Resource Management Software (SRM)**
Hewlett Packard Enterprise storage resource management software reduces operational costs and provides the command and control foundation you need to efficiently manage and visualize your physical and virtual environments.
- **Data Replication Software**
Hewlett Packard Enterprise offers array-based and host-based replication software for use in disaster recovery, testing, application development and reporting.
- **Storage Device Management Software**
Maximize your investment in Hewlett Packard Enterprise storage and networking with software that enables hardware-specific configuration, performance tuning and connectivity management.
- **HPE StoreVirtual VSA**
With HPE StoreVirtual VSA you can use the power of virtualization to turn a set of heterogeneous and disconnected physical disk drives in your servers and storage devices into a single pool of logical storage capacity.

NOTE: For more information available Storage Software including QuickSpecs, please see: <http://www.hp.com/go/storage/software>.

Optional Features

Solutions Factory Express Portfolio for Servers and Storage

HPE Factory Express offers configuration, customization, integration and deployment services for Hewlett Packard Enterprise servers and storage products. Customers can choose how their factory solutions are built, tested, integrated, shipped and deployed.

Factory Express offers service packages for simple configuration, racking, installation, complex configuration and design services as well as individual factory services, such as image loading, asset tagging, and custom packaging. Hewlett Packard Enterprise products supported through Factory Express include a wide array of servers and storage: HPE Integrity, HPE ProLiant, HPE ProLiant Server Blades, HPE BladeSystem, HPE 9000 servers as well as the MSAxxxx, VA7xxx, EVA, XP, rackable tape libraries and configurable network switches.

For more information on Factory Express services for your specific server model please contact your sales representative or go to: <http://www.hp.com/go/factory-express>.

One Config Simple (SCE)

SCE is a guided self-service tool to help sales and non-technical people provide customers with initial configurations in 3 to 5 minutes. You may then send the configuration on for configuration help, or use in your existing ordering processes. If you require "custom" rack configuration or configuration for products not available in SCE, please contact Hewlett Packard Enterprise Customer Business Center or an Authorized Partner for assistance. <https://h22174.www2.hp.com/SimplifiedConfig/Index>.

Service and Support

HPE Support Services

HPE Technology Services delivers confidence, reduces risk and helps customers realize agility and stability. Connect to Hewlett Packard Enterprise to help prevent problems and solve issues faster. HPE Support Services enable you to choose the right service level, length of coverage and response time as you purchase your new server, giving you full entitlement to the support for need for your IT and business.

Connect your devices

Unlock all of the benefits of your technology investment by connecting your products to Hewlett Packard Enterprise. Achieve up to 77%¹ reduction in down time, near 100%² diagnostic accuracy and a single consolidated view of your environment. By connecting, you will receive 24x7 monitoring, pre-failure alerts, automatic call logging, and automatic parts dispatch. HPE Proactive Care Service and HPE Datacenter Care Service customers will also benefit from proactive activities to help prevent issues and increase optimization. All of these benefits are already available to you with your server storage and networking products, securely connected to Hewlett Packard Enterprise support.

¹- IDC ² - HP CSC reports 2014 - 2015

Recommended Support

Standard: HPE Proactive Care* with 24x7 coverage, three year Support Service
HPE Proactive Care gives customers an enhanced call experience. When your products are connected to Hewlett Packard Enterprise, Proactive Care helps prevent problems and maintains IT stability by utilizing personalized proactive reports with recommendations and advice. This service combines three years proactive reporting and advice with our 24x7 coverage, four hour hardware response time when there is a problem. This service also includes collaborative software support for Independent Software Vendors (ISVs), (Red Hat, VMWare, Microsoft, etc.) running on your HPE servers.

<http://h20195.www2.hp.com/v2/GetPDF.aspx/4AA3-8855ENW.pdf>

Optimized HPE Proactive Care* with 6 hour call-to-repair commitment, three year Support Service

HPE Proactive Care gives customers an enhanced call experience. When your products are connected to Hewlett Packard Enterprise, Proactive Care helps prevent problems and maintains IT stability by utilizing personalized proactive reports with recommendations and advice. This service combines three years' proactive reporting and advice with our highest level of hardware support - Hewlett Packard Enterprise 24x7, six hour hardware call-to-repair. Hewlett Packard Enterprise is the only leading manufacturer who makes this level of coverage available as a standard service offering for your most valuable servers. This service also includes collaborative software support for Independent Software Vendors (ISVs), (Red Hat, VMWare, Microsoft, etc.) running on your HPE servers.

<http://h20195.www2.hp.com/v2/GetPDF.aspx/4AA3-8855ENW.pdf>

Parts and Materials

Hewlett Packard Enterprise will provide Hewlett Packard Enterprise-supported replacement parts and materials necessary to maintain the covered hardware product in operating condition, including parts and materials for available and recommended engineering improvements.

Parts and components that have reached their maximum supported lifetime and/or the maximum usage limitations as set forth in the manufacturer's operating manual, product QuickSpecs, or the technical product data sheet will not be provided, repaired, or replaced as part of these services.

Service and Support

The defective media retention service feature option applies only to Disk or eligible SSD/Flash Drives replaced by Hewlett Packard Enterprise due to malfunction.

Related Services HPE Server Hardware Installation

Provides for the basic hardware installation of Hewlett Packard Enterprise branded servers, storage devices and networking options to assist you in bringing your new hardware into operation in a timely and professional manner.

<http://h20195.www2.hp.com/V2/GetPDF.aspx/5981-9356EN.pdf>

HPE Installation and Startup Service

Provides for the installation and startup of Hewlett Packard Enterprise technology including BladeSystems, C-Class enclosure, HPE ProLiant c-Class and Integrity server blades, storage blades, SAN switch blades, HPE Virtual Connect modules (Ethernet and Fibre Channel), Ethernet network interconnects, and InfiniBand, as well as the installation of one supported operating system type (Windows® or Linux).

HPE Technology Services Support Credits

Offer flexible services and technical skills to meet your changing IT demands. With a menu of service that is tailored to suit your needs, you get additional resources and specialist skills to help you maintain peak performance of your IT. Offered as annual credits, you can plan your budgets while proactively responding to your dynamic business.

HPE Education Services

Keep your IT staff trained making sure they have the right skills to deliver on your business outcomes. Book on a class today and learn how to get the most from your technology investment. <http://www.hpe.com/ww/learn>

HPE Support Center

The HPE Support Center is a personalized online support portal with access to information, tools and experts to support Hewlett Packard Enterprise business products. Submit support cases online, chat with Hewlett Packard Enterprise experts, access support resources or collaborate with peers.

Learn more <http://www.hpe.com/support/hpesc>

The Hewlett Packard Enterprise Support Center Mobile App* allows you to resolve issues yourself or quickly connect to an agent for live support. Now, you can get access to personalized IT support anywhere, anytime.

HPE Insight Remote Support and HPE Support Center are available at no additional cost with a Hewlett Packard Enterprise warranty, HPE Support Service or Hewlett Packard Enterprise contractual support agreement.

*HPE Support Center Mobile App is subject to local availability.

For more information: <http://www.hpe.com/services>

Pre-configured Models

NOTE: For the Standard Features shipped in the "Factory Integrated Models," please see the "Configuration Information - Factory Integrated Models" section.

NOTE: Pre-configured models ship with the configurations below. Options can be selected from the Core or Additional options section of this QuickSpecs.

NOTE: HPE does not allow factory integration of options into pre-configured models. Any additional options purchased will be shipped separately.

NOTE: If you desire a custom configuration please see "Configuration Information - Factory Integrated Models" section of this QuickSpecs.

	High Performance Models				Database Models	
[SKU Number]	816815-B21	816814-B21	793312-B21	793314-B21	816816-B21	793310-B21
Model Name	HPE ProLiant DL580 Gen9 E7-8890v4 4P 256GB-R P830i/4G 534FLR-SFP 1500W RPS Server	HPE ProLiant DL580 Gen9 E7-8893v4 4P 256GB-R P830i/4G 534FLR-SFP 1500W RPS Server	HP ProLiant DL580 Gen9 E7-8890v3 4P 256GB-R P830i/4G 534FLR-SFP+ 1500W RPS Server	HP ProLiant DL580 Gen9 E7-8893v3 4P 256GB-R P830i/4G 534FLR-SFP+ 1500W RPS Server	HPE ProLiant DL580 Gen9 E7-4850v4 4P 128GB-R P830i/4G 534FLR-SFP 1200W RPS Server	HP ProLiant DL580 Gen9 E7-4850v3 4P 128GB-R P830i/4G 534FLR-SFP+ 1200W RPS Server
Processor	Intel® Xeon® E7-8890v4	Intel® Xeon® E7-8893v4	Intel® Xeon® E7-8890v3	Intel® Xeon® E7-8893v3	Intel® Xeon® E7-4850v4	Intel® Xeon® E7-4850v3
Number of Processors	Four					
Memory	256GB (16x16GB DIMMs) PC4-2400P-R DIMMs (DDR4) installed in (8) Memory Cartridges		256GB (16x16GB DIMMs) PC4-2133P-R DIMMs (DDR4) installed in (8) Memory Cartridges		128GB (8x16GB DIMMs) PC4-2400P-R DIMMs (DDR4) installed in (4) Memory Cartridges	128GB (8x16GB DIMMs) PC4-2133P-R DIMMs (DDR4) installed in (4) Memory Cartridges
Network Controller	HPE FlexFabric 10Gb 2P 534FLR-SFP+ Adapter					
Storage Controller	HPE Smart Array P830i/4GB FBWC 12 Gbps SAS controller					
Hard Drive	5 SFF HDD/SSD drive bays. No drives ship standard.					
Optical Drive	None					
PCI-Express Slots	9 PCIe Gen3.0 I/O Expansion slots (5x16 slots, 4x8 slots)					
Power Supply	(4) HPE 1500W Common Slot Platinum Plus Hot Plug Power Supplies			(4) HPE 1200W Common Slot Platinum Plus Hot Plug Power Supplies		
Fans	4 hot plug fans (eight rotors with N+1 redundancy)					
Management	iLO Management (standard), Intelligent Provisioning (standard), iLO Advanced (optional), Insight Control (optional), HPE OneView (optional)					

Pre-configured Models

Form Factor Rack (4U), rail kit and cable management arm are included
 Warranty Server Warranty includes 3-Year Parts, 3-Year Labor, 3-Year Onsite support with next business day response

Base Models

[SKU Number]	816817-B21	793308-B21
Model Name	HPE ProLiant DL580 Gen9 E7-4809v4 2P 64GB-R P830i/2G 331FLR-SFP 1200W RPS Server	HP ProLiant DL580 Gen9 E7-4809v3 2P 64GB-R P830i/2G 331FLR-SFP+ 1200W RPS Server
Processor	Intel® Xeon® E7-4809v4	Intel® Xeon® E7-4809v3
Number of Processors	Two	
Memory	64GB (4x16GB DIMMs) PC4-2400P-R DIMMs (DDR4) installed in (2) Memory Cartridges	64GB (4x16GB DIMMs) PC4-2133P-R DIMMs (DDR4) installed in (2) Memory Cartridges
Network Controller	HPE Ethernet 1Gb 4P 331FLR Adapter	
Storage Controller	HPE Smart Array P830i/2GB FBWC 12 Gbps SAS controller	
Hard Drive	5 SFF HDD/SSD drive bays. No drives ship standard.	
Optical Drive	None	
PCI-Express Slots	9 PCIe Gen3.0 I/O Expansion slots (5x16 slots, 4x8 slots)	
Power Supply	(2) HPE 1200W Common Slot Platinum Plus Hot Plug Power Supplies	
Fans	4 Hot Plug Fans (eight rotors with N+1 redundancy)	
Management	iLO Management (standard), Intelligent Provisioning (standard), iLO Advanced (optional), Insight Control (optional), HPE OneView (optional)	
Form Factor	Rack (4U), rail kit and cable management arm are included	
Warranty	Server Warranty includes 3-Year Parts, 3-Year Labor, 3-Year Onsite support with next business day response	

Smart Buy Models

[SKU Number]	816821-S01	816822-S01	793311-S01	793309-S01
Model Name	HPE ProLiant DL580 Gen9 E7-8880v4 2P 128GB-R P830i/2G 331FLR-T 1200W RPS US Server/S-Buy	HPE ProLiant DL580 Gen9 E7-8860v4 2P 128GB-R P830i/2G 331FLR-T 1200W RPS US Server/S-Buy	HP ProLiant DL580 Gen9 E7-8880v3 2P 128GB-R P830i/2G 331FLR-T 1200W RPS US Server/S-Buy	HP ProLiant DL580 Gen9 E7-8860v3 2P 128GB-R P830i/2G 331FLR-T 1200W RPS US Server/S-Buy
Processor	Intel® Xeon® E7-8880v4	Intel® Xeon® E7-8860v4	Intel® Xeon® E7-8880v3	Intel® Xeon® E7-8860v3
Number of Processors	Two, upgradeable to three or four			
Memory	128GB (8x16GB Registered DIMMs, 2400MHz) installed in (4) Memory Cartridges NOTE: The DIMMs will operate at maximum 1866MHz with these processors		128GB (8x16GB Registered DIMMs, 2133MHz) installed in (4) Memory Cartridges NOTE: The DIMMs will operate at maximum 1866MHz with these processors	
Network Controller	HPE Ethernet 1Gb 4-port 331FLR-T Adapter			
Storage Controller	HPE Smart Array P830i/2GB FBWC			
Hard Drive	None ship standard			
Internal Storage	Five (5) SFF SATA/SAS drive bays, upgradeable to ten (10) SFF SATA/SAS or max of five (5) SFF SATA/SAS + five (5) NVMe SSD bays			
Optical Drive	None included, (Optional: USB external DVD-RW Optical Drive)			
PCI-Express Slots	Nine (9) PCIe slots (5 x16 , 4 x8) NOTE: PCIe slot availability is dependent on the number of processors installed. Please refer to the expansion slots selection for more details.			
Power Supply	(2) HPE 1200W Common Slot Platinum Plus Hot Plug Power Supplies			
Fans	4 hot plug fans (eight rotors with N+1 redundancy)			
Management	Standard: iLO Management Optional: iLO Advanced, Insight Control, HPE OneView			
Form Factor	Rack (4U), HPE ball bearing rails with cable management arm			
Warranty	3-Year Parts, 3-Year Labor, 3-Year Onsite support with next business day response			

Configuration Information - Factory Integrated Models

This section lists some of the steps required to configure a Factory Integrated Model. To ensure only valid configurations are ordered, Hewlett Packard Enterprise recommends the use of an HPE approved configurator. Contact your local sales representative for information on configurable product offerings and requirements.

1. Factory Integrated Models must start with a CTO Server.
2. FIO indicates that this option is only available as a factory installable option.
3. All Factory Integrated Models will be populated with sufficient hard drive blanks based on the number of initial hard drives ordered with the server.
4. Some options may not be integrated at the factory. Contact your local sales representative for additional information.

Step 1: Base Configuration (choose one of the following configurable models)

[Chassis]	HP ProLiant DL580 Gen9 Configure-to-order Server
SKU Number	793161-B21
Processor	4U Server Chassis with front-accessible processor and memory drawer
Storage Controller	Embedded HPE Smart Array 12G P830i Controller
PCIe	9 PCIe Gen3.0 I/O Expansion slots (5x16 slots, 4x8 slots)
Drive Cage	5 Hot-plug SAS/SATA SFF SSD or HDD Bays (Lower)
Fans	4 hot plug fans (eight rotors with N+1 redundancy), front accessible
Management	iLO Management (standard), Intelligent Provisioning (standard)
USB	8 USB 2.0 ports (2 front, 4 rear, 2 internal)

(Base Configuration Continued)

- Intel® 602J Chipset
- (2) video ports (1 front, 1 rear)
- (1) microSD card slot
- (1) Trusted Platform Module (TPM) connector
- BIOS Legacy mode (field configurable) or Unified Extensible Firmware Interface (UEFI) mode (default)
- Rack rails and cable management arm

NOTE: PCIe slot availability is dependent on the number of processors installed. Please refer to the "Expansion slots" section for more details.

NOTE: A minimum of two processors are required. The system may have three or four processors installed.

NOTE: A minimum of two memory cartridges are required (one per processor).

NOTE: A minimum of two memory DIMMs are required per cartridge (minimum of four DIMMs per server).

NOTE: A minimum of two power supplies are required.

Step 2: Choose Required Options (only one of the following from each list unless otherwise noted)

HPE Processors **NOTE:** A minimum of two processors are required. The system may have three or four processors installed. First processor selection will be xxxxxx-L21 and subsequent processors will be xxxxxx-B21.

Four-Core Processors

Configuration Information - Factory Integrated Models

HP DL580 Gen9 Intel® Xeon® E7-8893v3 (3.2GHz/4-core/45MB/140W) FIO Processor Kit	788335-L21
NOTE: This is a lower core, higher frequency processor for software licensing cost optimization.	
HP DL580 Gen9 Intel® Xeon® E7-8893v3 (3.2GHz/4-core/45MB/140W) Processor Kit	788335-B21
NOTE: This is a lower core, higher frequency processor for software licensing cost optimization.	
HPE DL580 Gen9 Intel® Xeon® E7-8893v4 (3.2GHz/4-core/60MB/140W) FIO Processor Kit	816661-L21
NOTE: This is a lower core, higher frequency processor for software licensing cost optimization.	
HPE DL580 Gen9 Intel® Xeon® E7-8893v4 (3.2GHz/4-core/60MB/140W) Processor Kit	816661-L21
NOTE: This is a lower core, higher frequency processor for software licensing cost optimization.	
Eight-Core Processors	
HP DL580 Gen9 Intel® Xeon® E7-4809v3 (2.0GHz/8-core/20MB/115W) FIO Processor Kit	788331-L21
HP DL580 Gen9 Intel® Xeon® E7-4809v3 (2.0GHz/8-core/20MB/115W) Processor Kit	788331-B21
HPE DL580 Gen9 Intel® Xeon® E7-4809v4 (2.1GHz/8-core/20MB/115W) FIO Processor Kit	816657-L21
HPE DL580 Gen9 Intel® Xeon® E7-4809v4 (2.1GHz/8-core/20MB/115W) Processor Kit	816657-B21
Ten-Core Processors	
HP DL580 Gen9 Intel® Xeon® E7-8891v3 (2.8GHz/10-core/45MB/165W) FIO Processor Kit	788333-L21
NOTE: This is a lower core, higher frequency processor for software licensing cost optimization.	
HP DL580 Gen9 Intel® Xeon® E7-8891v3 (2.8GHz/10-core/45MB/165W) Processor Kit	788333-B21
NOTE: This is a lower core, higher frequency processor for software licensing cost optimization.	
HP DL580 Gen9 Intel® Xeon® E7-4820v3 (1.9GHz/10-core/25MB/115W) FIO Processor Kit	788329-L21
HP DL580 Gen9 Intel® Xeon® E7-4820v3 (1.9GHz/10-core/25MB/115W) Processor Kit	788329-B21
HPE DL580 Gen9 Intel® Xeon® E7-8891v4 (2.8GHz/10-core/60MB/165W) FIO Processor Kit	816659-L21
NOTE: This is a lower core, higher frequency processor for software licensing cost optimization.	
HPE DL580 Gen9 Intel® Xeon® E7-8891v4 (2.8GHz/10-core/60MB/165W) Processor Kit	816659-B21
NOTE: This is a lower core, higher frequency processor for software licensing cost optimization.	
HPE DL580 Gen9 Intel® Xeon® E7-4820v4 (2.0GHz/10-core/25MB/115W) FIO Processor Kit	816655-L21

Configuration Information - Factory Integrated Models

HPE DL580 Gen9 Intel® Xeon® E7-4820v4 (2.0GHz/10-core/25MB/115W) Processor Kit	816655- B21
Twelve-Core Processors	
HP DL580 Gen9 Intel® Xeon® E7-4830v3 (2.1GHz/12-core/30MB/115W) FIO Processor Kit	788327- L21
HP DL580 Gen9 Intel® Xeon® E7-4830v3 (2.1GHz/12-core/30MB/115W) Processor Kit	788327- B21
Fourteen-Core Processors	
HP DL580 Gen9 Intel® Xeon® E7-4850v3 (2.2GHz/14-core/35MB/115W) FIO Processor Kit	788325- L21
HP DL580 Gen9 Intel® Xeon® E7-4850v3 (2.2GHz/14-core/35MB/115W) Processor Kit	788325- B21
HPE DL580 Gen9 Intel® Xeon® E7-4830v4 (2.0GHz/14-core/35MB/115W) FIO Processor Kit	816653- L21
HPE DL580 Gen9 Intel® Xeon® E7-4830v4 (2.0GHz/14-core/35MB/115W) Processor Kit	816653- B21
Sixteen-Core Processors	
HP DL580 Gen9 Intel® Xeon® E7-8860v3 (2.2GHz/16-core/40MB/140W) FIO Processor Kit	788323- L21
HP DL580 Gen9 Intel® Xeon® E7-8860v3 (2.2GHz/16-core/40MB/140W) Processor Kit	788323- B21
HP DL580 Gen9 Intel® Xeon® E7-8867v3 (2.5GHz/16-core/45MB/165W) FIO Processor Kit	788339- L21
NOTE: This is a frequency optimized processor suited for high performance computing applications.	
HP DL580 Gen9 Intel® Xeon® E7-8867v3 (2.5GHz/16-core/45MB/165W) Processor Kit	788339- B21
NOTE: This is a frequency optimized processor suited for high performance computing applications.	
HPE DL580 Gen9 Intel® Xeon® E7-4850v4 (2.1GHz/16-core/40MB/115W) FIO Processor Kit	816651- L21
HPE DL580 Gen9 Intel® Xeon® E7-4850v4 (2.1GHz/16-core/40MB/115W) Processor Kit	816651- B21
Eighteen-Core Processors	
HP DL580 Gen9 Intel® Xeon® E7-8890v3 (2.5GHz/18-core/45MB/165W) FIO Processor Kit	788317- L21
HP DL580 Gen9 Intel® Xeon® E7-8890v3 (2.5GHz/18-core/45MB/165W) Processor Kit	788317- B21
HP DL580 Gen9 Intel® Xeon® E7-8880v3 (2.3GHz/18-core/45MB/150W) FIO Processor Kit	788319- L21
HP DL580 Gen9 Intel® Xeon® E7-8880v3 (2.3GHz/18-core/45MB/150W) Processor Kit	788319- B21
HP DL580 Gen9 Intel® Xeon® E7-8870v3 (2.1GHz/18-core/45MB/140W) FIO Processor Kit	788321- L21
HP DL580 Gen9 Intel® Xeon® E7-8870v3 (2.1GHz/18-core/45MB/140W) Processor Kit	788321- B21

Configuration Information - Factory Integrated Models

HP DL580 Gen9 Intel® Xeon® E7-8880Lv3 (2.0GHz/18-core/45MB/115W) 788337-
FIO Processor Kit L21

NOTE: This is a power optimized processor.

HP DL580 Gen9 Intel® Xeon® E7-8880Lv3 (2.0GHz/18-core/45MB/115W) 788337-
Processor Kit B21

NOTE: This is a power optimized processor.

HPE DL580 Gen9 Intel® Xeon® E7-8860v4 (2.2GHz/18-core/45MB/140W) 816649-
FIO Processor Kit L21

HPE DL580 Gen9 Intel® Xeon® E7-8860v4 (2.2GHz/18-core/45MB/140W) 816649-
Processor Kit B21

HPE DL580 Gen9 Intel® Xeon® E7-8867v4 (2.4GHz/18-core/45MB/165W) 816665-
FIO Processor Kit L21

HPE DL580 Gen9 Intel® Xeon® E7-8867v4 (2.4GHz/18-core/45MB/165W) 816665-
Processor Kit B21

Twenty-Core Processors

HPE DL580 Gen9 Intel® Xeon® E7-8870v4 (2.1GHz/20-core/50MB/140W) 816647-
FIO Processor Kit L21

HPE DL580 Gen9 Intel® Xeon® E7-8870v4 (2.1GHz/20-core/50MB/140W) 816647-
Processor Kit B21

Twenty-Two-Core Processors

HPE DL580 Gen9 Intel® Xeon® E7-8880v4 (2.2GHz/22-core/55MB/150W) 816645-
FIO Processor Kit L21

HPE DL580 Gen9 Intel® Xeon® E7-8880v4 (2.2GHz/22-core/55MB/150W) 816645-
Processor Kit B21

Twenty-Four- Core Processors

HPE DL580 Gen9 Intel® Xeon® E7-8890v4 (2.2GHz/24-core/60MB/165W) 816643-
FIO Processor Kit L21

HPE DL580 Gen9 Intel® Xeon® E7-8890v4 (2.2GHz/24-core/60MB/165W) 816643-
Processor Kit B21

NOTE: When v4 Processor is selected, then only PC4-2400T Memory Kit can be selected.

NOTE: When v3 Processor is selected, then only PC4-2133P Memory Kit can be selected.

HPE Memory

NOTE: A minimum of two memory cartridges are required (one per processor).

NOTE: A minimum of two memory DIMMs are required per cartridge (minimum of four DIMMs per server).

NOTE: Hewlett Packard Enterprise memory from previous generation servers is not qualified or warranted with this HPE ProLiant Server. HPE SmartMemory is required to realize the memory performance improvements and enhanced functionality listed in this document for Gen9. For additional information, please see the [HPE SmartMemory QuickSpecs](#).

NOTE: LRDIMM and RDIMM are distinct memory technologies and cannot be mixed within a server.

NOTE: Depending on the memory configuration and processor model, the memory speed may run at 1866MHz, 1600MHz, or 1333MHz. Please see Memory Population Table below or the Online Memory Configuration Tool at: <http://www.hp.com/go/ddr4config>.

Registered DIMMs (R-DIMMs) for E7-4800v3 and E7-8800v3 Series

HP 8GB (1x8GB) Single Rank x4 DDR4-2133 CAS-15-15-15 Registered 726718-
Memory Kit B21

Configuration Information - Factory Integrated Models

HP 16GB (1x16GB) Dual Rank x4 DDR4-2133 CAS-15-15-15 Registered Memory Kit	726719-B21
HP 32GB (1x32GB) Dual Rank x4 DDR4-2133 CAS-15-15-15 Registered Memory Kit	728629-B21
Registered DIMMs (R-DIMMs) for E7-4800v4 and E7-8800v4 Series	
HP 8GB (1x8GB) Single Rank x8 DDR4-2400 CAS-17-17-17 Registered Memory Kit	805347-B21
HP 16GB (1x16GB) Single Rank x4 DDR4-2400 CAS-17-17-17 Registered Memory Kit	805349-B21
HPE 16GB (1x16GB) Dual Rank x4 DDR4-2400 CAS-17-17-17 Registered Memory Kit	836220-B21
HPE 32GB (1x32GB) Dual Rank x4 DDR4-2400 CAS-17-17-17 Registered Memory Kit	805351-B21
Load Reduced DIMMs (LRDIMMS) for E7-4800v3 and E7-8800v3 Series	
HP 64 GB (1X64GB) Quad Rank x4 DDR4-2133 Load Reduced Memory Kit	726724-B21
HP 32GB (1x32GB) Quad Rank x4 DDR4-2133 CAS-15-15-15 Load Reduced Memory Kit	726722-B21
Load Reduced DIMMs (LRDIMMS) for E7-4800v4 and E7-8800v4 Series	
HP 64GB (1x64GB) Quad Rank x4 DDR4-2400 CAS-17-17-17 Load Registered Memory Kit	805358-B21
Memory Expansion Options	
HP DL580 Gen9 12 DDR4 DIMM Slots Memory Cartridge	788360-B21
NOTE: Up to eight (8) memory cartridges are supported for 96 DIMM slots.	
NOTE: A minimum of two (2) memory cartridges are required (one per processor).	
NOTE: A minimum of two (2) memory DIMMs are required per cartridge (minimum of four DIMMs per server).	
NOTE: A minimum of two (2) power supplies are required. Option kits contain the specified power supply and a PDU IEC cable. For a full list of optional HPE power cords please go to: http://www.hp.com/products/powercords	
NOTE: Prior to selecting a power supply option, it is highly recommended that you review your server configuration in the HPE Power Advisor tool to determine the right size power supply for your server configuration. The HPE Power Advisor is located at: http://www.hp.com/go/hppoweradvisor .	
NOTE: Mixing of power supplies in the same server is not supported. All power supplies must be of the same input voltage, output rating, and efficiency rating. If non-matching power supplies are installed, you may receive an error message and/or experience operational issues with your server.	
HPE Common Slot Platinum Plus Power Supply Kits	
HP 1500W Common Slot Platinum Plus Hot Plug Power Supply Kit	684532-B21
NOTE: This power supply only supports High Line Voltage.	
HP 1500W Common Slot 48VDC Hot Plug Power Supply Kit	746708-B21
NOTE: This power supply only supports High Line Voltage.	
HP 1200W Common Slot Platinum Hot Plug Power Supply Kit	748287-B21

HPE Power Supplies



Configuration Information - Factory Integrated Models

	HP 1200W Common Slot Platinum Plus Hot Plug Power Supply Kit	656364-
	NOTE: 94% efficiency with support for HPE Power Discovery Services.	B21
HPE FlexibleLOM	NOTE: Only one (1) FlexibleLOM can be added to the server. These options are upgradeable and can be changed from the original configuration after the server is shipped. NOTE: For 10Gb adapters, a minimum of two Gigabytes (2 GB) of server memory is required per each adapter. NOTE: Wake-on-Lan feature is not supported on the DL580 Gen9 with FlexLOMs	
	HP Ethernet 1Gb 4-port 331FLR FIO Adapter	684208-
		B21
	HP Ethernet 1Gb 4-port 366FLR FIO Adapter	684217-
		B21
	HP FlexFabric 10Gb 2-port 533FLR-T FIO Adapter	700760-
		B21
	HP FlexFabric 10Gb 2-port 534FLR-SFP+ FIO Adapter	700752-
		B21
	HP FlexFabric 10Gb 2-port 556FLR-SFP+ FIO Adapter	732456-
		B21
	HP Ethernet 10Gb 2-port 546FLR-SFP+ FIO Adapter	779800-
		B21
	HP Ethernet 10Gb 2-port 560FLR-SFP+ FIO Adapter	684218-
		B21
	HP Ethernet 10Gb 2-port 561FLR-T FIO Adapter	700700-
		B21
	HP Ethernet 10Gb 2-port 562FLR-SFP+ FIO Adapter	789006-
		B21
	HPE FlexFabric 10Gb 2-port 556FLR-T FIO Adapter	794526-
		B21
HPE Storage Controller FBWC	NOTE: One Flash Backed Write Cache is required for P830i SAS Controller NOTE: Max of 4 capacitor modules can be installed.	
	HP Smart Array 2GB 24in FIO Flashback Write Cache	758836-
		B21
	HP 4GB Flash Backed Write Cache FIO Kit for P-series Smart Array Controllers	698537-
		B21

Step 3: Choose Additional Factory Integratable Options (only one from each list unless otherwise noted).

HPE Smart Host Bus Adapter	HP H240 12Gb 2-ports Int FIO Smart Host Bus Adapter	761873-
	NOTE: This controller may be selected to support a secondary drive cage. NOTE: This controller can support up to 8 internal SAS/SATA devices. NOTE: HP DL580 Gen9 H240 Card Cable Kit (805356-B21) is required when ordering this HBA Controller.	B21
BIOS Mode	HP Legacy FIO Mode Setting	758959-
	NOTE: Selecting this option will change the default UEFI BIOS setting into Legacy BIOS setting	B22
Advanced Memory Protection	HP Lockstep Memory Mode FIO Setting	773559-
	NOTE: Minimum of four memory DIMMs per cartridge are required if selecting this mode. All cartridges must be configured with identical number of DIMMs.	B21

Configuration Information - Factory Integrated Models

HPE Insight Software	HP Insight Control including 1yr 24x7 Support ProLiant ML/DL/BL-bundle Single Server FIO License	C6N36A
	HP Insight Control including 1yr 24x7 Support ProLiant ML/DL/BL-bundle Single Server FIO E-LTU	C6N36ABE
HPE Converged Infrastructure Management Software	HPE OneView with iLO Advanced	
	HP OneView for ProLiant DL Server incl 3yr 24x7 Supp FIO Bundle Physical 1 Svr Lic	E5Y43A
	HPE OneView without iLO Advanced	
	HP OneView w/o iLO including 3yr 24x7 Support FIO 1 Server LTU	P8B31A

Step 4: Choose Additional Options for Factory Integration from Core and Additional Options Sections below.

CAUTION: Hewlett Packard Enterprise recommends that a minimum of two people are required for all Rack Server installations. Please refer to your installation instructions for proper tools and number of people to use for any installation.

Core Options

NOTE: Some options may not be integrated at the factory. To ensure only valid configurations are ordered, Hewlett Packard Enterprise recommends the use of an HPE approved configurator. Contact your local sales representative for additional information.

HPE Processors Four-Core Processors

HP DL580 Gen9 Intel® Xeon® E7-8893v3 (3.2GHz/4-core/45MB/140W) Processor Kit 788335-B21

HPE DL580 Gen9 Intel® Xeon® E7-8893v4 (3.2GHz/4-core/60MB/140W) Processor Kit 816661-B21

Eight-Core Processors

HP DL580 Gen9 Intel® Xeon® E7-4809v3 (2.0GHz/8-core/20MB/115W) Processor Kit 788331-B21

HPE DL580 Gen9 Intel® Xeon® E7-4809v4 (2.1GHz/8-core/20MB/115W) Processor Kit 816657-B21

Ten-Core Processors

HP DL580 Gen9 Intel® Xeon® E7-4820v3 (1.9GHz/10-core/25MB/115W) Processor Kit 788329-B21

HP DL580 Gen9 Intel® Xeon® E7-8891v3 (2.8GHz/10-core/45MB/165W) Processor Kit 788333-B21

HPE DL580 Gen9 Intel® Xeon® E7-8891v4 (2.8GHz/10-core/60MB/165W) Processor Kit 816659-B21

HPE DL580 Gen9 Intel® Xeon® E7-4820v4 (2.0GHz/10-core/25MB/115W) Processor Kit 816655-B21

Twelve-Core Processors

HP DL580 Gen9 Intel® Xeon® E7-4830v3 (2.1GHz/12-core/30MB/115W) Processor Kit 788327-B21

Fourteen-Core Processors

HP DL580 Gen9 Intel® Xeon® E7-4850v3 (2.2GHz/14-core/35MB/115W) Processor Kit 788325-B21

HPE DL580 Gen9 Intel® Xeon® E7-4830v4 (2.0GHz/14-core/35MB/115W) Processor Kit 816653-B21

Sixteen-Core Processors

HP DL580 Gen9 Intel® Xeon® E7-8860v3 (2.2GHz/16-core/40MB/140W) Processor Kit 788323-B21

HP DL580 Gen9 Intel® Xeon® E7-8867v3 (2.5GHz/16-core/45MB/165W) Processor Kit 788339-B21

HPE DL580 Gen9 Intel® Xeon® E7-4850v4 (2.1GHz/16-core/40MB/115W) Processor Kit 816651-B21

Eighteen-Core Processors

Core Options

HP DL580 Gen9 Intel® Xeon® E7-8890v3 (2.5GHz/18-core/45MB/165W) Processor Kit	788317-B21
HP DL580 Gen9 Intel® Xeon® E7-8880v3 (2.3GHz/18-core/45MB/150W) Processor Kit	788319-B21
HP DL580 Gen9 Intel® Xeon® E7-8870v3 (2.1GHz/18-core/45MB/140W) Processor Kit	788321-B21
HP DL580 Gen9 Intel® Xeon® E7-8880Lv3 (2.0GHz/18-core/45MB/115W) Processor Kit	788337-B21
HPE DL580 Gen9 Intel® Xeon® E7-8860v4 (2.2GHz/18-core/45MB/140W) Processor Kit	816649-B21
HPE DL580 Gen9 Intel® Xeon® E7-8867v4 (2.4GHz/18-core/45MB/165W) Processor Kit	816665-B21
Twenty-Core Processors	
HPE DL580 Gen9 Intel® Xeon® E7-8870v4 (2.1GHz/20-core/50MB/140W) Processor Kit	816647-B21
Twenty Two-Core Processors	
HPE DL580 Gen9 Intel® Xeon® E7-8880v4 (2.2GHz/22-core/55MB/150W) Processor Kit	816645-B21
Twenty Four-Core Processors	
HPE DL580 Gen9 Intel® Xeon® E7-8890v4 (2.2GHz/24-core/60MB/165W) Processor Kit	816643-B21

HPE Memory

NOTE: Hewlett Packard Enterprise memory from previous generation servers is not qualified or warranted with this HPE ProLiant Server. HPE SmartMemory is required to realize the memory performance improvements and enhanced functionality listed in this document for Gen9. For additional information, please see the [HPE SmartMemory QuickSpecs](#).

NOTE: LRDIMM and RDIMM are distinct memory technologies and cannot be mixed within a server.

NOTE: Depending on the memory configuration and processor model, the memory speed may run at 1866MHz, 1600MHz, or 1333MHz. Please see Memory Population Table below or the Online Memory Configuration Tool at: <http://www.hp.com/go/ddr4config>.

Registered DIMMs (RDIMMs)

HP 8GB (1x8GB) Single Rank x4 DDR4-2133 CAS-15-15-15 Registered Memory Kit	726718-B21
HP 16GB (1x16GB) Dual Rank x4 DDR4-2133 CAS-15-15-15 Registered Memory Kit	726719-B21
HP 32GB (1x32GB) Dual Rank x4 DDR4-2133 CAS-15-15-15 Registered Memory Kit	728629-B21
HP 8GB (1x8GB) Single Rank x8 DDR4-2400 CAS-17-17-17 Registered Memory Kit	805347-B21
HP 16GB (1x16GB) Single Rank x4 DDR4-2400 CAS-17-17-17 Registered Memory Kit	805349-B21
HPE 16GB (1x16GB) Dual Rank x4 DDR4-2400 CAS-17-17-17 Registered Memory Kit	836220-B21
HP 32GB (1x32GB) Dual Rank x4 DDR4-2400 CAS-17-17-17 Registered Memory Kit	805351-B21
Load Reduced DIMMs (LRDIMMs)	

Core Options

HP 32GB (1x32GB) Quad Rank x4 DDR4-2133 CAS-15-15-15 Load Reduced Memory Kit	726722-B21
HP 64GB (1x64GB) Quad Rank x4 DDR4-2133 CAS-15-15-15 Load Reduced Memory Kit	726724-B21
HP 64GB (1x64GB) Quad Rank x4 DDR4-2400 CAS-17-17-17 Load Registered Memory Kit	805358-B21
Memory Expansion Options	
HP DL580 Gen9 12 DDR4 DIMM Slots Memory Cartridge	788360-B21
NOTE: Up to Eight (8) memory cartridges are supported for 96 DIMM slots.	
NOTE: A minimum of two memory cartridges are required (one per processor).	
NOTE: A minimum of two memory DIMMs are required per cartridge (minimum of four DIMMs per server).	

HPE Optical Drives	HP Mobile USB Non Leaded System DVD RW Drive	701498-B21
--------------------	--	------------

HPE Drives

NOTE: The components of a storage subsystem (e.g. the drive, the HBA/controller, firmware, and the server backplane) should operate at the same data transfer rate or the system bandwidth will be negotiated down to an acceptable level for all components.

NOTE: Hard drives have either a one year or three year warranty; refer to the specific hard drive QuickSpecs for details.

12G SAS Value Endurance Hot Plug SFF (2.5-inch) Enterprise Value Solid State	
HP 1.6TB 12G SAS Value Endurance SFF 2.5-in SC Enterprise Value 3yr Wty Solid State Drive	762263-B21
HP 800GB 12G SAS Value Endurance SFF 2.5-in SC Enterprise Value 3yr Wty Solid State Drive	762261-B21
12G SAS Hot Plug SFF (2.5-inch) Midline Drives	
HPE 1TB 12G SAS 7.2K rpm SFF (2.5in) SC Midline 1yr Warranty Hard Drive	832514-B21
12G SAS Hot Plug SFF (2.5-inch) Enterprise Drives	
HP 1.2TB 12G SAS 10K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive	781518-B21
HP 900GB 12G SAS 10K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive	785069-B21
HP 600GB 12G SAS 10K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive	781516-B21
HP 600GB 12G SAS 15K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive	759212-B21
HP 450GB 12G SAS 15K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive	759210-B21
HP 300GB 12G SAS 10K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive	785067-B21
HP 300GB 12G SAS 15K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive	759208-B21
12G SAS Hot Plug SFF (2.5-inch) SC 512e Drives	

Core Options

HP 2TB 12G SAS 7.2K rpm SFF (2.5-inch) SC 512e 1yr Warranty Hard Drive	765466-B21
HP 1.8TB 12G SAS 10K rpm SFF (2.5-inch) SC Enterprise 512e 3yr Warranty Hard Drive	791034-B21
HP 1TB 12G SAS 7.2K rpm SFF (2.5-inch) SC 512e 1yr Warranty Hard Drive	765464-B21
HP 600GB 12G SAS 15K rpm SFF (2.5-inch) SC 512e Enterprise 3yr Warranty Hard Drive	748387-B21
12G SAS Mixed Use Hot Plug SFF (2.5-inch) Solid State Drives	
HPE 3.2TB 12G SAS Mixed Use-3 SFF 2.5-in SC 3yr Wty Solid State Drive	822567-B21
HPE 1.6TB 12G SAS Mixed Use-1 SFF (2.5in) SC 3yr Wty Solid State Drive	846436-B21
HPE 1.6TB 12G SAS Mixed Use-3 SFF 2.5-in SC 3yr Wty Solid State Drive	822563-B21
HPE 800GB 12G SAS Mixed Use-1 SFF (2.5in) SC 3yr Wty Solid State Drive	846434-B21
HPE 800GB 12G SAS Mixed Use-3 SFF 2.5-in SC 3yr Wty Solid State Drive	822559-B21
HPE 400GB 12G SAS Mixed Use-3 SFF 2.5-in SC 3yr Wty Solid State Drive	822555-B21
12G SAS Hot Plug SFF (2.5-inch) SC Write Intensive Solid State Drives	
HPE 1.6TB 12G SAS Write Intensive-1 SFF (2.5in) SC 3yr Wty Solid State Drive	846432-B21
HPE 800GB 12G SAS Write Intensive-1 SFF (2.5in) SC 3yr Wty Solid State Drive	846430-B21
HP 800GB 12G SAS Write Intensive SFF 2.5-in SC 3yr Wty Solid State Drive	802586-B21
HP 400GB 12G SAS Write Intensive SFF 2.5-in SC 3yr Wty Solid State Drive	802582-B21
HP 200GB 12G SAS Write Intensive SFF 2.5-in SC 3yr Wty Solid State Drive	802578-B21
12G SAS Read Intensive Hot Plug SFF (2.5-inch) Solid State Drives	
HPE 3.84TB 12G SAS Read Intensive-3 SFF 2.5-in SC 3yr Wty Solid State Drive	816576-B21
HP 1.92TB 12G SAS Read Intensive SFF 2.5-in SC 3yr Wty Solid State Drive	802891-B21
HPE 1.92TB 12G SAS Read Intensive-3 SFF 2.5-in SC 3yr Wty Solid State Drive	816572-B21
HPE 960GB 12G SAS Read Intensive-3 SFF 2.5-in SC 3yr Wty Solid State Drive	816568-B21
HPE 480GB 12G SAS Read Intensive-3 SFF 2.5-in SC 3yr Wty Solid State Drive	816562-B21
12G SAS Hot Plug SFF (2.5-inch) Enterprise Mainstream Solid State Drives	

Core Options

HP 1.6TB 12G SAS Mainstream Endurance SFF 2.5-in ENT Mainstream SC 3yr Wty H2 Solid State Drive	779176-B21
HP 800GB 12G SAS Mainstream Endurance SFF 2.5-in ENT Mainstream SC 3yr Wty H2 Solid State Drive	779172-B21
HP 400GB 12G SAS Mainstream Endurance SFF 2.5-in ENT Mainstream SC 3yr Wty H2 Solid State Drive	779168-B21
HP 200GB 12G SAS Mainstream Endurance SFF 2.5-in ENT Mainstream SC 3yr Wty H2 Solid State Drive	779164-B21
6G SAS Hot Plug with SmartDrive SFF (2.5-inch) Enterprise Drives	
HP 1.2TB 6G SAS 10K rpm SFF (2.5-inch) SC Dual Port Enterprise 3yr Warranty Hard Drive	718162-B21
HP 900GB 6G SAS 10K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive	652589-B21
HP 600GB 6G SAS 10K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive	652583-B21
HP 450GB 6G SAS 10K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive	652572-B21
HP 300GB 6G SAS 10K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive	652564-B21
HP 300GB 6G SAS 15K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive	652611-B21
HP 146GB 6G SAS 15K rpm SFF (2.5-inch) SC Enterprise 3yr Warranty Hard Drive	652605-B21
6G SAS Hot Plug SmartDrive SFF (2.5-inch) Midline Drives	
HP 1TB 6G SAS 7.2K rpm SFF (2.5-inch) SC Midline 1yr Warranty Hard Drive	652749-B21
HP 500GB 6G SAS 7.2K rpm SFF (2.5-inch) SC Midline 1yr Warranty Hard Drive	652745-B21
6G SATA Value Endurance Hot Plug SFF (2.5-inch) Enterprise Value Solid State Drives	
HP 600GB 6G SATA Value Endurance SFF 2.5-in SC Enterprise Value 3yr Wty Solid State Drive	739898-B21
HP 1.6TB 6G SATA Value Endurance SFF 2.5-in SC Enterprise Value 3yr Wty Solid State Drive	757339-B21
HP 100GB 6G SATA Mainstream Endurance SFF 2.5-in SC Enterprise Mainstream 3yr Wty Solid State Drive	691862-B21
HP 400GB 6G SATA Mainstream Endurance SFF 2.5-in SC Enterprise Mainstream 3yr Wty Solid State Drive	691866-B21
HP 800GB 6G SATA Mainstream Endurance SFF 2.5-in SC Enterprise Mainstream 3yr Wty Solid State Drive	691868-B21
6G SATA Value Endurance Hot Plug SFF (2.5-inch) SC Enterprise Value M1 Solid State Drives	

Core Options

HP 800GB 6G SATA Value Endurance SFF 2.5-in SC Enterprise Value 3yr Wty M1 Solid State Drive	764929-B21
HP 480GB 6G SATA Value Endurance SFF 2.5-in SC Enterprise Value 3yr Wty M1 Solid State Drive	764927-B21
HP 240GB 6G SATA Value Endurance SFF 2.5-in SC Enterprise Value 3yr Wty M1 Solid State Drive	764925-B21
HP 120GB 6G SATA Value Endurance SFF 2.5-in SC Enterprise Value 3yr Wty M1 Solid State Drive	764923-B21
6G SATA Hot Plug SFF (2.5-inch) SC Mixed Use Solid State Drives	
HP 1.92TB 6G SATA Mixed Use-3 SFF 2.5-in SC 3yr Wty Solid State Drive	817011-B21
HP 1.6TB 6G SATA Mixed Use-2 SFF 2.5-in SC 3yr Wty Solid State Drive	804631-B21
HP 960GB 6G SATA Mixed Use-3 SFF 2.5-in SC 3yr Wty Solid State Drive	816995-B21
HP 800GB 6G SATA Mixed Use-2 SFF 2.5-in SC 3yr Wty Solid State Drive	804625-B21
HP 480GB 6G SATA Mixed Use-3 SFF 2.5-in SC 3yr Wty Solid State Drive	816985-B21
HP 480GB 6G SATA Mixed Use-2 SFF 2.5-in SC 3yr Wty Solid State Drive	832414-B21
HP 240GB 6G SATA Mixed Use-3 SFF 2.5-in SC 3yr Wty Solid State Drive	816975-B21
HP 200GB 6G SATA Mixed Use-2 SFF 2.5-in SC 3yr Wty Solid State Drive	804613-B21
HP 120GB 6G SATA Mixed Use-3 SFF 2.5-in SC 3yr Wty Solid State Drive	816965-B21
6G SATA Hot Plug SFF (2.5-inch) SC Write Intensive Solid State Drives	
HP 1.2TB 6G SATA Write Intensive-2 SFF 2.5-in SC 3yr Wty Solid State Drive	804677-B21
HP 800GB 6G SATA Write Intensive-2 SFF 2.5-in SC 3yr Wty Solid State Drive	804671-B21
HP 400GB 6G SATA Write Intensive-2 SFF 2.5-in SC 3yr Wty Solid State Drive	804665-B21
HP 200GB 6G SATA Write Intensive-2 SFF 2.5-in SC 3yr Wty Solid State Drive	804639-B21
6G SATA Hot Plug SFF (2.5-inch) SC Read Intensive Solid State Drives	

Core Options

HP 3.84TB 6G SATA Read Intensive-3 SFF 2.5-in SC 3yr Wty Solid State Drive	816929-B21
HP 1.92TB 6G SATA Read Intensive-3 SFF 2.5-in SC 3yr Wty Solid State Drive	816919-B21
HP 1.6TB 6G SATA Read Intensive-2 SFF 2.5-in SC 3yr Wty Solid State Drive	804605-B21
HP 960GB 6G SATA Read Intensive-3 SFF 2.5-in SC 3yr Wty Solid State Drive	816909-B21
HP 800GB 6G SATA Read Intensive-2 SFF 2.5-in SC 3yr Wty Solid State Drive	804599-B21
HP 480GB 6G SATA Read Intensive-2 SFF 2.5-in SC 3yr Wty Solid State Drive	804593-B21
HP 480GB 6G SATA Read Intensive-3 SFF 2.5-in SC 3yr Wty Solid State Drive	816899-B21
HP 480GB 6G SATA Read Intensive SFF 2.5-in SC 3yr Wty Solid State Drive	789145-B21
HP 240GB 6G SATA Read Intensive-2 SFF 2.5-in SC 3yr Wty Solid State Drive	804587-B21
HP 240GB 6G SATA Read Intensive-3 SFF 2.5-in SC 3yr Wty Solid State Drive	816889-B21
HP 120GB 6G SATA Read Intensive-3 SFF 2.5-in SC 3yr Wty Solid State Drive	816879-B21
HP 120GB 6G SATA Read Intensive-2 SFF 2.5-in SC 3yr Wty Solid State Drive	804581-B21
HP 80GB 6G SATA Read Intensive-2 SFF 2.5-in SC 3yr Wty Solid State Drive	804575-B21
HPE NVMe PCIe Mixed Use SFF (2.5 inch) Solid State Drives	
HP 1.6TB NVMe PCIe Mixed Use SFF 2.5-in SC2 3yr Wty Solid State Drive	765038-B21
HP 800GB NVMe PCIe Mixed Use SFF 2.5-in SC2 3yr Wty Solid State Drive	765036-B21
HP 400GB NVMe PCIe Mixed Use SFF 2.5-in SC2 3yr Wty Solid State Drive	765034-B21

NOTE: To support NVMe PCIe SSDs you need to select the SSD Express Bay Kit (788359-B21), maximum of 5 drives supported.

NOTE: Hewlett Packard Enterprise has qualified the NVMe drive portfolio using the Operating System inbox drivers. For full details please see the Solid State Drive QuickSpecs: <http://www.hpe.com/h20195/v2/GetHTML.aspx?docname=c04154378>.

HPE NVMe PCIe Write Intensive SFF (2.5-inch) Solid State Drives	
HP 1.6TB NVMe PCIe Write Intensive SFF 2.5-in SC2 3yr Wty Solid State Drive	764892-B21
HP 800GB NVMe PCIe Write Intensive SFF 2.5-in SC2 3yr Wty Solid State Drive	736939-B21
HP 400GB NVMe PCIe Write Intensive SFF 2.5-in SC2 3yr Wty Solid State Drive	736936-B21

NOTE: To support NVMe PCIe SSDs you need to select the SSD Express Bay Kit (788359-B21), maximum of 5 drives supported.

NOTE: Hewlett Packard Enterprise has qualified the NVMe drive portfolio using the

Core Options

Operating System inbox drivers. For full details please see the Solid State Drive QuickSpecs: <http://www.hpe.com/h20195/v2/GetHTML.aspx?docname=c04154378>.

HPE NVMe PCIe Read Intensive SFF (2.5 inch) Solid State Drives	
HP 1.2TB NVMe PCIe Read Intensive SFF 2.5-in SC2 3yr Wty Solid State Drive	764906-B21
HP 400GB NVMe PCIe Read Intensive SFF 2.5-in SC2 3yr Wty Solid State Drive	764904-B21

NOTE: To support NVMe PCIe SSDs you need to select the SSD Express Bay Kit (788359-B21), maximum of 5 drives supported.

NOTE: Hewlett Packard Enterprise has qualified the NVMe drive portfolio using the Operating System inbox drivers. For full details please see the Solid State Drive QuickSpecs: <http://www.hpe.com/h20195/v2/GetHTML.aspx?docname=c04154378>.

Hard Drive Kits	
HP DL580 Gen9 NVMe 5 Solid State Drive Express Bay Enablement Kit	788359-B21
HP ProLiant DL580 5 Small Form Factor Drive Backplane Cage Kit	739405-B21
HP Small Form Factor Hard Drive Blank Kit	666987-B21

HPE Networking	Gigabit Ethernet Adapters	
	HP Ethernet 1Gb 4-port 331T Adapter	647594-B21
	HP Ethernet 1Gb 2-port 332T Adapter	615732-B21
	HP Ethernet 1Gb 2-port 361T Adapter	652497-B21
	HP Ethernet 1Gb 4-port 366T Adapter	811546-B21
	10 Gigabit Ethernet adapters	
	HP Ethernet 10Gb 2-port 530SFP Adapter	652503-B21
	HP Ethernet 10Gb 2-port 546SFP+ Adapter	779793-B21
	HP Ethernet 10Gb 2-port 557SFP+ Adapter	788995-B21
	HP Ethernet 10Gb 2-port 560SFP+ Adapter	665249-B21
	HP Ethernet 10Gb 2-port 530T Adapter	656596-B21
	HP Ethernet 10Gb 2-port 561T Adapter	716591-B21
	HPE Ethernet 10Gb 2-port 562SFP+ Adapter	727055-B21

NOTE: A minimum of two Gigabytes (2GB) of server memory is required per each adapter.

FlexibleLOM Adapters	
HP Ethernet 1Gb 4-port 331FLR Adapter	629135-B22
HP Ethernet 1Gb 4-port 366FLR Adapter	665240-B21
HP FlexFabric 10Gb 2-port 533FLR-T Adapter	700759-B21
HP FlexFabric 10Gb 2-port 534FLR-SFP+ Adapter	700751-B21

NOTE: This adapter does not support FCOE Boot from SAN functionality on VMWare and FCOE functionality with RHEL 5.9.

HP Ethernet 10Gb 2-port 560FLR-SFP+ Adapter	665243-B21
HP Ethernet 10Gb 2-port 561FLR-T Adapter	700699-B21
HP Ethernet 10Gb 2-port 546FLR-SFP+ Adapter	779799-B21
HPE FlexFabric 10Gb 2-port 556FLR-T Adapter	794525-B21
HP FlexFabric 10Gb 2-port 556FLR-SFP+ Adapter	727060-B21
HPE Ethernet 10Gb 2-port 562FLR-SFP+ Adapter	727054-B21

NOTE: Wake-On-LAN not supported with FlexibleLOMs on DL580 Gen9.

NOTE: Please see the QuickSpecs for Technical Specifications and additional information: <http://www.hp.com/go/ProLiantNICs>.

Core Options

HPE InfiniBand	HP InfiniBand FDR 2-port 545QSFP Adapter	702211-B21
	NOTE: Legacy and UEFI modes are supported.	
	HP InfiniBand FDR/Ethernet 10Gb/40Gb 2-port 544+QSFP Adapter	764284-B21
	NOTE: UEFI and Legacy modes are supported with Ethernet and InfiniBand functionality.	
	HP InfiniBand FDR/Ethernet 10Gb/40Gb 2-port 544+FLR-QSFP Adapter	764285-B21
	NOTE: UEFI and Legacy modes are supported with Ethernet and InfiniBand functionality.	
	HP InfiniBand QDR/Ethernet 10Gb 2-port 544+FLR-QSFP Adapter	764286-B21
	HPE InfiniBand EDR/Ethernet 100Gb 1-port 840QSFP28 Adapter	825110-B21
	HPE InfiniBand EDR/Ethernet 100Gb 2-port 840QSFP28 Adapter	825111-B21

HPE Power Supplies	HPE Common Slot Platinum Plus Power Supply Kits	
	HP 1500W Common Slot Platinum Plus Hot Plug Power Supply Kit	684532-B21
	HP 1500W Common Slot 48VDC Hot Plug Power Supply Kit	746708-B21
	HP 1200W Common Slot Platinum Hot Plug Power Supply Kit	748287-B21
	HP 1200W Common Slot Platinum Plus Hot Plug Power Supply Kit	656364-B21
	NOTE: 94% efficiency with support for HPE Power Discovery Services.	
	NOTE: Prior to making a power supply selection it is highly recommended that the HPE Power Advisor is run to determine the right size power supply for your server configuration. The HPE Power Advisor is located at: http://www.hp.com/go/hppoweradvisor.	
	NOTE: Minimum of two (2) power supplies are required.	
	NOTE: All power supplies in a server should match. Mixing Power Supplies is not supported.	
	NOTE: Option Kits contain the specified power supply and a PDU IEC cable.	
NOTE: 1500W Power Supplies only support High Line Voltage.		
NOTE: HPE ProLiant servers ship with an IEC-IEC power cord used for rack mounting with Power Distribution Units (PDUs). For a full list of optional Hewlett Packard Enterprise power cords please go to http://www.hp.com/products/powercords.		

HPE Computation and Graphics Accelerators	NVIDIA Tesla K40C 12GB Computational Accelerator	753960-B21
	NOTE: Up to 4 cards are supported on the DL580 Gen9. Supporting multiple number of cards on the DL580 Gen9 blocks some active IO cards as follows due to space constraints:	
	For 2P config: Max of 2 double-wide cards are supported on slot 6 and slot 9 (slot 8 is blocked)	
	For 3P config: Max of 3 double-wide cards are supported on slot 3, slot 6 and slot 9 (slot 5 and slot 8 are blocked)	
	For 4P config: Max of 4 double wide cards are supported on Slot 1, Slot 3, Slot 6 and Slot 9 (slot 5 and slot 8 are blocked).	
	NOTE: HPE DL580/DL585/DL980 Power Cable Kit (631660-B21) is required for Graphics cards. Each cable kit has two 8-pin connectors (one 150W and other 225W) and can support up to two cards. For three cards, two cable kits are required. For 4 cards, 2 cable kits are required. The cards pull up to 75W of power from the IO slot and the rest from the auxiliary power connectors.	
	NOTE: Supported at Gen2 speeds.	

Core Options

HP NVIDIA Quadro M6000 Graphics Accelerator

J0G92A

NOTE: Only four M6000 graphic cards are supported on DL580 Gen9.

NOTE: If any HPE ProLiant server is configured with an NVIDIA Graphics Processor Unit (GPU), it must have less than 1 TB of server host memory. If the memory equals or exceeds 1 TB, the GPU options will not function properly due to a memory addressing design limitation with the NVIDIA GPU. See [HPE Service Advisory](#) for more details.

NOTE: The DL580 Gen9 supports six auxiliary power connectors.

Additional Options

NOTE: Some options may not be integrated at the factory. To ensure only valid configurations are ordered, Hewlett Packard Enterprise recommends the use of an HPE approved configurator. Contact your local sales representative for additional information.

HPE Insight Software	HPE Insight Control	
	HPE Insight Control including 1yr 24x7 Technical Support and Updates 1-server LTU	C6N27A
	HPE Insight Control including 1yr 24x7 TSU E-LTU	C6N28ABE
	HPE Insight Management Media Kit	C6N31A

NOTE: Electronic and Flexible-Quantity licenses can be used to purchase multiple licenses with a single activation key.

NOTE: Customer will receive a license entitlement certificate. The license entitlement certificate must be redeemed online or via fax in order to obtain the license activation key(s). Includes one year of 24 x 7 HPE Software Technical Support and Update Service.

NOTE: Licenses ship without media. The HPE Insight Control Media Kit can be ordered separately, or can be downloaded at: <http://www.hp.com/go/insightupdates>.

NOTE: For additional license options please see the [HPE Insight Control QuickSpecs](#).

HPE Converged Infrastructure Management Software	HPE OneView Advanced (with HPE iLO Advanced)	
	NOTE: Full licenses of HPE OneView Advanced also provide the right-to-use HPE Insight Control without additional charge.	
	NOTE: Server provisioning (via 'HPE Insight Control server provisioning') is licensed as part of HPE OneView Advanced and provides multi-server OS and driver provisioning. Media kit #BD883A can be ordered for a physical copy of this software (USB flash drive).	
	NOTE: Licenses ship without media. The HPE OneView Media Kit can be ordered separately, or can be downloaded at: http://www.hp.com/go/oneview .	
	NOTE: Electronic and Flexible-Quantity licenses can be used to purchase multiple licenses with a single activation key.	
	HPE OneView Physical Media Kit LTU	E5Y37A
	HPE OneView including 3yr 24x7 Support Physical 1-server LTU	E5Y34A
	HPE OneView including 3yr 24x7 Support Flexible Quantity E-LTU	E5Y35AAE
	HPE OneView Advanced (without HPE iLO Advanced)	
	HPE OneView w/o iLO including 3yr 24x7 Support 1-server LTU	P8B24A
	HPE OneView w/o iLO including 3yr 24x7 Support Flexible Quantity E-LTU	P8B26AAE
	HPE OneView w/o iLO including 3yr 24x7 Support Track 1-server LTU	P8B25A
	HPE Operations Analytics for HPE OneView LTU	K8G29A
	HPE Operations Analytics for HPE OneView E-LTU	K8G29AAE
	NOTE: Please see the HPE OneView QuickSpecs for Technical Specifications and additional information.	

Additional Options

HPE iLO Advanced License	HPE iLO Advanced	
	HPE iLO Advanced including 3yr 24x7 Technical Support and Updates E-LTU	E6U64ABE
	HPE iLO Advanced including 1yr 24x7 Technical Support and Updates E-LTU	E6U59ABE
	HPE iLO Advanced including 3yr 24x7 Tech Support and Updates 1-server LTU	BD505A
	HPE iLO Advanced including 1yr 24x7 Technical Support and Updates 1-server LTU	512485-B21

HPE PCIe Workload Accelerator Options	Value Endurance (VE) PCIe Workload Accelerators	
	HP 6.4TB FH/HL Value Endurance (VE) PCIe Workload Accelerator	763840-B21
	HP 3.2TB HH/HL Value Endurance (VE) PCIe Workload Accelerator	763838-B21
	HP 1.6TB HH/HL Value Endurance (VE) PCIe Workload Accelerator	763836-B21
	Light Endurance (LE) PCIe Workload Accelerators	
	HP 5.2TB FH/HL Light Endurance (LE) PCIe Workload Accelerator	775672-B21
	HP 2.6TB HH/HL Light Endurance (LE) PCIe Workload Accelerator	775670-B21
	HP 1.3TB HH/HL Light Endurance (LE) PCIe Workload Accelerator	775668-B21
	HP 1.0TB HH/HL Light Endurance (LE) PCIe Workload Accelerator	775666-B21
	HPE Read Intensive PCIe Workload Accelerator	
	HPE 6.4TB Read Intensive-2 FH/HL PCIe Workload Accelerator	831739-B21
	HPE 3.2TB Read Intensive-2 HH/HL PCIe Workload Accelerator	831737-B21
	HPE 1.6TB Read Intensive-2 HH/HL PCIe Workload Accelerator	831735-B21
	HPE 1.3TB Read Intensive-2 HH/HL PCIe Workload Accelerator	831733-B21
	NVMe PCIe Workload Accelerators	
	HP 2.0TB NVMe Mixed Use HH/HL PCIe Workload Accelerator	803204-B21
	HP 1.6TB NVMe Mixed Use HH/HL PCIe Workload Accelerator	803202-B21
	HP 1.6TB NVMe Write Intensive HH/HL PCIe Workload Accelerator	803197-B21
	HP 800GB NVMe Mixed Use HH/HL PCIe Workload Accelerator	803200-B21
HP 800GB NVMe Write Intensive HH/HL PCIe Workload Accelerator	803195-B21	

NOTE: Both Legacy and UEFI BIOS modes are supported. Please see the [HPE PCIe Workload Accelerators for ProLiant Servers QuickSpecs](#) for Technical Specifications and additional information.

HPE Security	HP Trusted Platform Module 2.0 Kit	745823-B21
	<p>NOTE: HPE Trusted Platform Module 2.0 Option (745823-B21) works with Gen9 servers with UEFI Mode not Legacy Mode. It is not compatible with HPE ProLiant Gen8 servers or earlier generation variants. HPE Gen9 servers purchased earlier may need the latest firmware update to be compatible with the TPM 2.0 Option. The earlier HPE Trusted Platform Module Option (488069-B21) is the TPM 1.2 version, which is also available however TPM 2.0 has newer technology standards incorporated. The TPM 1.2 compatible server platforms include Gen8 and Gen9 servers. HPE server systems can have a TPM module (of any type) installed only once. It cannot be replaced with any other TPM module.</p>	

Additional Options

HPE Storage Controllers

SAS Controllers

HPE Smart Array Controllers

HP Smart Array P430/2GB FBWC 12Gb 1-port Int SAS Controller 698529-B21

HP Smart Array P430/4GB FBWC 12Gb 1-port Int SAS Controller 698530-B21

NOTE: Please see the [HPE Smart Array P430 Controller QuickSpecs](#) for Technical Specifications and additional information.

HP Smart Array P431/2GB FBWC 12Gb 2-ports Ext SAS Controller 698531-B21

HP Smart Array P431/4GB FBWC 12Gb 2-ports Ext SAS Controller 698532-B21

NOTE: Please see the [HPE Smart Array P431 Controller QuickSpecs](#) for Technical Specifications and additional information.

HP Smart Array P830/4GB FBWC 12Gb 2-ports Int SAS Controller 698533-B21

NOTE: Please see the [HPE Smart Array P830 Controller QuickSpecs](#) for Technical Specifications and additional information.

NOTE: A maximum of 4 HPE Smart Array Controllers (including embedded controller) can be installed.

HPE Smart Host Bus Adapters

HP H240 12Gb 2-ports Int Smart Host Bus Adapter 726907-B21

NOTE: Please see the [HPE H240 Smart Host Bus Adapter QuickSpecs](#) for Technical Specifications and additional information.

HP H241 12Gb 2-ports Ext Smart Host Bus Adapter 726911-B21

NOTE: Please see the [HPE H241 Smart Host Bus Adapter QuickSpecs](#) for Technical Specifications and additional information.

NOTE: For more information about HPE SmartCache, go to:

<http://www.hp.com/go/smartcache>.

NOTE: Both Legacy and UEFI modes are supported.

Optional Upgrades

HP DL580 PCIe Stand-up SAS Controller Upper Drive Backplane Cable Kit 748916-B21

Cable Kit

HP DL580 Gen9 H240 Card Upper SAS Backplane Cable Kit 805356-B21

HPE Tape Backup

NOTE: For the complete range of tape drives, autoloaders, libraries and media see: <http://www.hp.com/go/tape>. For hardware and software compatibility of HPE tape backup products see: <http://www.hp.com/storage/SPOCK> and <http://www.hp.com/go/ebs>.

NOTE: For Internal drives to be connected to DL servers please make sure that you order rack mount kits as well.

Additional Options

HPE StoreEver LTO-4 Ultrium 1760 SAS (1) in a 1U Rack Mount Kit	EH946C
HPE StoreEver LTO-7 Ultrium 15000 External Tape Drive	BB874A
HPE StoreEver LTO-7 Ultrium 15000 Internal Tape Drive	BB873A
HPE StoreEver LTO-6 Ultrium 6650 SAS External Tape Drive	EH964A
HPE StoreEver LTO-6 Ultrium 6250 Tape Drive in a 1U Rack Mount Kit	C0L99A
HPE StoreEver LTO-6 Ultrium 6250 External Tape Drive	EH970A
HPE StoreEver LTO-5 Ultrium 3000 SAS Tape Drive in a 1U Rack Mount Kit	EJ014B
HPE StoreEver LTO-5 Ultrium 3000 SAS External Tape Drive	EH958B
HPE StoreEver LTO-5 Ultrium 3280 SAS External Tape Drive	EH900B
HPE StoreEver LTO-4 Ultrium 1760 SAS External Tape Drive	EH920B
HPE StoreEver LTO-3 Ultrium 920 SAS External Tape Drive	EH848B
HPE StoreEver 1U SAS Rack Mount Kit	AE459B
HPE StoreEver Mini-SAS High Density to 4-lane Mini-SAS External Fanout 2m Cable	K2R09A
HPE StoreEver Mini-SAS High Density to 4-lane Mini-SAS External Fanout 4m Cable	K2R10A
HPE DAT Autoloader	
HPE StoreEver 1/8 G2 LTO-6 Ultrium 6250 Fibre Channel Tape Autoloader	C0H19A
HPE MSL2024 Tape Library	
HPE StoreEver MSL2024 0-drive Tape Library	AK379A
HPE MSL4048 Tape Library	
HPE StoreEver MSL4048 0-drive Tape Library	AK381A
HPE StoreEver MSL6480	
HPE StoreEver MSL6480 Scalable Base Module	QU625A
HPE StoreEver MSL6480 Scaleable Expansion Module	QU626A
NOTE: Please see the HPE StoreEver MSL6480 Tape Library QuickSpecs for Technical Specifications and additional information.	

HPE Disk Backup HP D3700 Enclosure	QW967A
HP D3600 Enclosure	QW968A
HPE StoreOnce 3100 8TB System	BB913A
HPE StoreOnce 3540 24TB System	BB914A
HPE StoreOnce 5100 48TB System	BB915A
HPE StoreOnce 3520 12TB System	BB922A
HPE RDX 3TB USB 3.0 Internal Disk Backup System	P9L71A
HPE RDX+ 3TB USB 3.0 External Disk Backup System	P9L72A

NOTE: For the complete range of RDX drives and media see: <http://www.hp.com/go/rdx>. For hardware and software compatibility of HPE disk backup products see: <http://www.hp.com/storage/SPOCK>.

NOTE: For Internal drives to be connected to DL servers please make sure that you order rack mount kit as well.

Additional Options

HPE Storage Options	<p>HPE Converged Network Adapters</p> <p>HPE StoreFabric CN1100R 10GBASE-T Dual Port Converged Network Adapter N3U52A</p> <p>HP StoreFabric CN1100R Dual Port Converged Network Adapter QW990A</p> <p>NOTE: FCOE boot from SAN is not supported with VMWare.</p> <p>HPE StoreFabric CN1200E 10GBASE-T Dual Port Converged Network Adapter N3U51A</p> <p>HP StoreFabric CN1200E 10Gb Converged Network Adapter E7Y06A</p> <p>NOTE: Both UEFI and Legacy mode are supported.</p> <p>Storage Fibre Channel HBA</p> <p>NOTE: The following is a list of all Fibre Channel Host Bus Adapters for Windows and Linux. For detailed compatibility information please see: http://h18006.www1.hp.com/storage/saninfrastructure/hba.html.</p> <p>QLogic Fibre Channel HBAs</p> <p>HP 81Q 8Gb 1-port PCIe Fibre Channel Host Bus Adapter AK344A</p> <p>HP 82Q 8Gb 2-port PCIe Fibre Channel Host Bus Adapter AJ764A</p> <p>HPE StoreFabric 84Q 4-port 8Gb Fibre Channel Host Bus Adapter P9D91A</p> <p>HP StoreFabric SN1000Q 16GB 1-port PCIe Fibre Channel Host Bus Adapter QW971A</p> <p>HPE StoreFabric SN1100Q 16Gb Single Port Fibre Channel Host Bus Adapter P9D93A</p> <p>HP StoreFabric SN1000Q 16GB 2-port PCIe Fibre Channel Host Bus Adapter QW972A</p> <p>HPE StoreFabric SN1100Q 16Gb Dual Port Fibre Channel Host Bus Adapter P9D94A</p> <p>Emulex Fibre Channel HBAs</p> <p>HP 81E 8Gb 1-port PCIe Fibre Channel Host Bus Adapter AJ762B</p> <p>HP 82E 8Gb 2-port PCIe Fibre Channel Host Bus Adapter AJ763B</p> <p>HP StoreFabric 84E 4-port 8Gb Fibre Channel Host Bus Adapter E7Y63A</p> <p>HP StoreFabric SN1100E 16Gb Single Port Fibre Channel Host Bus Adapter C8R38A</p> <p>HP StoreFabric SN1100E 16Gb Dual Port Fibre Channel Host Bus Adapter C8R39A</p>
---------------------	--

Additional Options

HPE Disk	Disk Enclosures	
Storage Systems	HP D6000 Dual I/O Module Disk Enclosure	QQ695A
	HP D6000 w/70 3TB 6G SAS 7.2K LFF Dual port MDL HDD 210TB Bundle	QQ700A
	HP D6000 w/35 3TB 6G SAS 7.2K LFF Dual port MDL HDD 105TB Bundle	QQ699A
	HP D6000 w/70 2TB 6G SAS 7.2K LFF Dual port MDL HDD 140TB Bundle	QQ698A
	HP D6000 w/35 2TB 6G SAS 7.2K LFF Dual port MDL HDD 70TB Bundle	QQ697A
	HP D6000 w/70 4TB 6G SAS 7.2K LFF Dual Port MDL HDD 280TB Bundle	E7W31A
	HP D6000 w/35 4TB 6G SAS 7.2K LFF Dual Port MDL HDD 140TB Bundle	E7W30A
	HP D6000 w/70 8TB 12G SAS 7.2K LFF (3.5in) Dual Port MDL HDD 560TB Bundle	M0T59A
	HP D6000 w/70 6TB 12G SAS 7.2K LFF (3.5in) Dual Port MDL HDD 420TB Bundle	M0T57A
	HP D6000 w/35 8TB 12G SAS 7.2K LFF (3.5in) Dual Port MDL HDD 280TB Bundle	M0T58A

NOTE: Please see the [HPE D6000 Disk Enclosure QuickSpecs](#) for Technical Specifications and additional information.

HPE Data Center	HPE Advanced Series Racks	
Racks	HPE 11648 1075mm Pallet Universal Rack	H6J87A
	HPE 11648 1075mm Shock Universal Rack	H6J88A
	HPE 11642 1075mm Pallet Universal Rack	H6J65A
	HPE 11642 1075mm Shock Universal Rack	H6J66A
	HPE 11642 1200mm Pallet Universal Rack	H6J67A
	HPE 11642 1200mm Shock Universal Rack	H6J68A
	HPE 11636 1075mm Pallet Universal Rack	H6J77A
	HPE 11636 1075mm Shock Universal Rack	H6J78A
	HPE 11622 G2 1075mm Pallet Universal Rack	H6J83A
	HPE 11622 G2 1075mm Shock Universal Rack	H6J84A
	HPE 11614 1075mm Shock Universal Rack	H6J82A

NOTE: Please see the [HPE Advanced Series Racks QuickSpecs](#) for information on additional racks options and rack specifications.

HPE Enterprise Series Racks

Additional Options

HPE 647 1075mm Pallet Intelligent Series Rack	BW911A
HPE 647 1075mm Shock Intelligent Series Rack	BW912A
HPE 647 1200mm Pallet Intelligent Series Rack	BW913A
HPE 647 1200mm Shock Intelligent Series Rack	BW914A
HPE 642 1075mm Pallet Intelligent Series Rack	BW903A
HPE 642 1075mm Shock Intelligent Series Rack	BW904A
HPE 642 1200mm Pallet Intelligent Series Rack	BW907A
HPE 642 1200mm Shock Intelligent Series Rack	BW908A
HPE 636 1075mm Pallet Intelligent Series Rack	BW895A
HPE 636 1075mm Shock Intelligent Series Rack	BW896A
HPE 842 1075mm Pallet Intelligent Series Rack	BW917A
HPE 842 1075mm Shock Intelligent Series Rack	BW918A

NOTE: Please see the [HPE Enterprise Series Racks QuickSpecs](#) for information on additional racks options and rack specifications.

HPE Standard Series Rack

HPE V142 1075mm deep Pallet 100 series Rack	AF046A
---	--------

NOTE: Please see the [HPE Standard Series Rack QuickSpecs](#) for information on additional racks options and rack specifications.

HPE Power Distribution Units (PDUs)	HPE Basic Power Distribution Units (PDU)	
	HPE Basic 1.9kVA/L5-20P 16A/120V Outlets (12) 5-20R/Horizontal NA/JP PDU	H5M54A
	HPE Basic 3.6kVA/60320 C20 Detachable 16A/230V Outlets (12) C13/Horizontal WW PDU	H5M56A
	HPE Basic 2.8kVA/L5-30P 24A/120V Outlets (18) 5-20R/Vertical NA/JP PDU	H5M55A
	HPE Basic 4.9kVA/60320 C20 Detachable 16A/230V Outlets (20) C13/Vertical WW PDU	H5M57A
	HPE Basic 4.9kVA/L6-30P 24A/208V Outlets (20) C13/Vertical NA/JP PDU	H5M58A
	HPE Basic 3Ph 8.6kVA/L15-30P 24A/208V Outlets (18) C13/Vertical NA/JP PDU	H5M61A
	HPE Basic 4.9kVA/L6-30P 24A/208V Outlets (24) C13 (6) C19/Vertical NA/JP PDU	H5M59A
	HPE Basic 8.3kVA/CS8265C 40A/208V Outlets (30) C13 (6) C19/Vertical NA PDU	H5M60A
	HPE Basic 9.2kVA/50A Terminal Block 40A/230V Outlets (30) C13 (6) C19/Vertical WW PDU	H5M75A
	HPE Basic 3Ph 5.7kVA/ L21-20P 16A/120-208V Outlets (24) C13 (3) 5-20R/Vertical NA/JP PDU	H5M63A
	HPE Basic 3Ph 8.6kVA/L21-30P 24A/120-208V Outlets (24) C13 (3) C19 (3) 5-20R/Vertical NA/JP PDU	H5M64A
	HPE Basic 3Ph 8.6kVA/L15-30P 24A/208V Outlets (24) C13 (6) C19/Vertical NA/JP PDU	H5M62A
	HPE Basic 3Ph 11kVA/60309 16A/240V Outlets (36) C13 (6) C19/Vertical NA PDU	H5M67A
	HPE Basic Modular 2.8kVA/L5-30P 24A/120V Outlets (4) C19/Horizontal NA/JP PDU	252663-D71

Additional Options

HPE Basic Modular 4.9kVA/L6-30P 24A/208V Outlets (4) C19/Horizontal NA/JP Core Only PDU	252663-D74
HPE Basic Modular 8.3kVA/CS8265C 40A/208V Outlets (4) C19/Horizontal NA/JP PDU	252663-D75
HPE Basic Modular 3Ph 8.6kVA/L15-30P 24A/208V Outlets (6) C19/Horizontal NA/JP PDU	AF512A
HPE Basic Modular 3Ph 14.4kVA/CS8365C 40A/208V Outlets (6) C19/Horizontal NA/JP PDU	AF519A
HPE Basic Modular 3Ph 17.3kVA/60309 60A 4-wire 48A/208V Outlets (6) C19/Horizontal NA/JP PDU	AF511A
HP 800VA - 277V Input / 230V Output NA Rack Mount Transformer	H3X09A
NOTE: Please see the HPE Basic Power Distribution Units (PDU) QuickSpecs for information on additional options and product specifications.	
HPE Metered Power Distribution Units (PDU)	
HPE Metered 2.8kVA/L5-30P 24A/120V Outlets (12) 5-20R/Horizontal NA/JP PDU	D9N43A
HPE Metered 3.6kVA/60320 C20 Detachable 16A/230V Outlets (12) C13/Horizontal WW PDU	D9N46A
HPE Metered 4.9kVA/L6-30P 24A/208V Outlets (12) C13/Horizontal NA/JP PDU	D9N44A
HPE Metered 3.6kVA/60320 C20 Detachable 16A/230V Outlets (16) C13/Vertical WW PDU	D9N45A
HPE Metered 4.9kVA/L6-30P 24A/208V Outlets (12) C13/Vertical NA/JP PDU	G9Z05A
HPE Metered 4.9kVA/L6-30P 24A/208V Outlets (20) C13 (4) C19/Vertical NA/JP PDU	D9N47A
HPE Metered 3Ph 8.6kVA/L15-30P 24A/208V Outlets (18) C13 (3) C19/Vertical NA/JP PDU	D9N51A
HPE Metered 3Ph 5.7kVA/L21-20P 16A/120-208V Outlets (13) C13 (3)5-20R/Vertical NA/JP PDU	D9N52A
HPE Metered 3Ph 8.6kVA/L21-30P 24A/120-208V Outlets (18) C13 (3) C19 (3) 5-20R/Vertical NA/JP PDU	D9N53A
HPE Metered 8.3kVA/CS8265C 40A/208V Outlets (30) C13 (3) C19/Vertical NA PDU	D9N49A
HPE Metered 3Ph 14.4kVA/CS8365C 40A/208V Outlets (12) C13 (12) C19/Vertical NA/JP PDU	D9N58A
HPE Metered 3Ph 16.6kVA/60309 32A-30A 5-wire 24A/230V Outlets (30) C13 (3) C19/Vertical NA/JP PDU	D9N61A
HPE Metered 3Ph 17.3kVA/60309 60A 4-wire 48A/208V Outlets (24) C13 (3) C19/Vertical NA/JP PDU	D9N54A
HPE Metered 3Ph 17.3kVA/60309 60A 4-wire 48A/208V Outlets (12) C13 (12) C19/Vertical NA/JP PDU	D9N59A
HPE Metered 3Ph 17.3kVA/60309 60A 4-wire 48A/208V Outlets (12) C13 (12) C19/Vertical NA/JP PDU	G9Z07A
HPE Metered 3Ph 16.6kVA/60309 32A-30A 5-wire 24A/230V Outlets (12) C13 (12) C19/Vertical NA/JP PDU	D9N62A
HPE Metered 3Ph 19.9kVA/L22-30P 24A/277V Outlets (30) RF-203P- HP/Vertical NA PDU	D9N63A

NOTE: Please see the [HPE Metered Power Distribution Units \(PDU\) QuickSpecs](#) for information on additional options and product specifications.



Additional Options

HP Environmental Sensor for Remote Monitored and Managed PDUs E2D53A

NOTE: Please see the [HPE Metered Power Distribution Units \(PDU\) QuickSpecs](#) for information on additional options and product specifications.

HPE Intelligent Power Distribution Unit (PDU)

HPE Intelligent Modular 4.9kVA/L6-30P 24A/208V Outlets (6) AF520A
C19/Horizontal NA/JP PDU

HPE Intelligent Modular 8.3kVA/CS8265C 40A/208V Outlets (6) AF521A
C19/Horizontal NA/JP PDU

HPE Intelligent Modular 3Ph 8.6kVA/L15-30P 24A/208V Outlets (6) AF522A
C19/Horizontal NA/JP PDU

HPE Intelligent Modular 3Ph 14.4kVA/CS8365C 40A/208V Outlets (6) AF533A
C19/Horizontal NA/JP PDU

HPE Intelligent Modular 3Ph 17.3kVA/60309 60A 4-wire 48A/208V (6) AF523A
C19/Horizontal NA/JP PDU

HPE Intelligent Modular 3Ph 11kVA/L22-20P 16A/240V Outlets (6) AF900A
C19/Horizontal NA/JP PDU

HPE Intelligent Modular 3Ph 17.3kVA/60309 30A 5-wire 24A/240V (6) AF901A
C19/Horizontal NA/JP PDU

HPE Intelligent Modular 3Ph 17.3kVA/IEC 60309 60A 4-wire 48A/208V AF535A
(12) C19/Horizontal NA/JP PDU

HPE Intelligent Modular 3Ph 17.3kVA/IEC 60309 30A 5-wire 24A/240V AF537A
(12) C19/Horizontal NA/JP PDU

HPE Intelligent Modular 4.9kVA/L6-30P 24A/208V Outlets (20) C13 (6) AF531A
C19/Horizontal NA/JP PDU

HPE Intelligent Modular 3Ph 8.6kVA/L15-30P 24A/208V Outlets (20) AF532A
C13 (6) C19/Horizontal NA/JP PDU

HP 5xC13 Intelligent PDU Extension Bar G2 Kit AF547A

HP 5xC13 Outlets Power and UID LEDs Pair Standard Extension Bar AF528A

NOTE: Please see the [HPE Intelligent Power Distribution Unit \(PDU\) QuickSpecs](#) for information on additional options and product specifications.

HPE Metered and Switched Power Distribution Units (PDU)

HPE Metered Switched 2.8kVA/L5-30P 24A/120V Outlets (24) 5-20R H8B48A
/Vertical NA/JP PDU

HPE Metered Switched 3.6kVA/60320 C20 Detachable 16A/230V H8B49A
Outlets (7) C13 (1) C19/Vertical WW PDU

HPE Metered Switched 4.9kVA/L6-30P 24A/208V Outlets (20) C13 (4) H8B50A
C19/Vertical NA/JP PDU

HPE Metered Switched 3Ph 8.6kVA/L15-30P 24A/208V Outlets (18) H8B52A
C13 (6) C19/Vertical NA/JP PDU

HPE Metered Switched 3Ph 8.6kVA/L2190-30P 24A/208V Outlets (23) H8B53A
C13 C19 (1) 520R/Vertical NA/JP PDU

HPE Metered Switched 3Ph 14.4kVA/CS8365C 40A/208V Outlets (12) H8B55A
C13 (12) C19/Vertical NA/JP PDU

HPE Metered Switched 3Ph 17.3kVA/60309 4-wire 48A/208V Outlets H8B56A
(12) C13 (12) C19/Vertical NA/JP PDU

NOTE: Please see the [HPE Metered and Switched Power Distribution Units \(PDU\) QuickSpecs](#)

for information on additional options and product specifications.

Additional Options

NOTE: To learn more, please visit the [HPE Uninterruptible Power Systems \(UPS\) web page](#).

HPE Rack Mount Consoles, KVM Switches, and Keyboards	<p>HPE Location Discovery Services HP Location Discovery Services LCD8500 Kit TL052A</p> <p>NOTE: Please see the HPE Location Discovery Services QuickSpecs for information on additional options and product specifications.</p> <p>HPE Rack Mount Consoles HP LCD8500 1U US Rackmount Console Kit AF630A HP LCD8500 1U US TAA Rackmount Console Kit AF645A</p> <p>NOTE: Please see the HPE LCD8500 Console Kit QuickSpecs for information on additional options and product specifications.</p> <p>HPE KVM Switches HP 0x1x8 G3 KVM Console Switch AF651A HP 0x2x16 G3 KVM Console Switch AF652A HP TAA 0x2x16 G3 KVM Console Switch AF653A HP USB Remote Access Key for G3 KVM Console Switches AF650A HP KVM Console USB Interface Adapter AF628A HP 0x2x16 KVM Server Console Switch G2 with Virtual Media CAC Software AF618A HP 0x2x32 KVM Server Console Switch G2 with Virtual Media CAC Software AF619A HP KVM Console USB 2.0 Virtual Media CAC Interface Adapter AF629A HP 1x4 USB/PS2 KVM Console Switch AF611A HP 1x1Ex8 KVM IP Console Switch G2 with Virtual Media CAC Software AF620A HP 2x1Ex16 KVM IP Console Switch G2 with Virtual Media CAC Software AF621A HP 4x1Ex32 KVM IP Console Switch G2 with Virtual Media CAC Software AF622A</p> <p>NOTE: To learn more, please visit the HPE KVM Switches web page.</p> <p>HPE KVM Console USB/Display Port Interface Adapter AF654A HPE KVM Console USB 8-pack Interface Adapter AF655A HPE USB Keyboard and Mouse HP USB BFR with PVC Free US Keyboard/Mouse Kit 631341-B21</p> <p>NOTE: Please see the HPE USB Keyboard and Mouse QuickSpecs for information on additional options and product specifications.</p> <p>HPE Other Options HP Rack LED Light Kit BW939A HP Kit LCD 1.83m Latch Display Port Cable G7T29A HP Advanced Power Manager Kit 741192-B21 HP ConvergedSystem Door Branding Kit TK815A HP ConvergedSystem Rack Light Kit TK816A HP ConvergedSystem Rack Side Panel 1075mm Kit TK817A</p>
--	--

HPE UninterruptibleHPE DirectFlow Three Phase UPS

Additional Options

Power Systems (UPS)	Power Unit (1U UPS)	
	HP R12000 DirectFlow - 1U Rackmount Uninterruptible Power System	G9Y75A
	HP R12000 DirectFlow - POD 1U Rackmount Uninterruptible Power System	AF478A
	Input/Output Module Options for 1U UPS	
	HP 30A 400-415 Volt Three Phase NA R10000 DirectFlow UPS IEC309 Input/Output Module	AF489A
	HP 30A 480 Volt Three Phase NA R12000 DirectFlow UPS L22-30 Input/Output Module	AF491A
	HP 30A 480 Volt Three Phase NA R12000 DirectFlow UPS IEC309 Input/Output Module	AF492A
	HP 30A 400-415 Volt Three Phase NA R12000 DirectFlow UPS IEC309 Input/Output Module	G9Y76A
	HP DirectFlow UPS Management Card	AF493A
	Power Unit (2U UPS)	
	HP R18000 DirectFlow - 2U Rackmount Uninterruptible Power System	AF479A
	Input/Output Module Options for 2U UPS	
	HP 30A 480 Volt Three Phase NA R18000 DirectFlow UPS IEC309 Input/Output Module	AF486A
	HP 30A 480 Volt Three Phase NA R18000 DirectFlow UPS IEC309 Input/Output Module	AF487A
	HP 30A 400 Volt Three Phase NA R18000 DirectFlow UPS IEC309 Input/Output Module	D9Q02A
	HP 30A 400-415V Three Phase NA R18000 DirectFlow UPS 1:1 IEC309 Input/Output Module	AF484A
	NOTE: All Input/Output Modules support dual output outlets except the AF484A.	
	Battery Pack Options	
	HP DirectFlow UPS - 1U Rackmount Lithium-ion Battery Pack	AF480A
	HP DirectFlow UPS - 3U Rackmount VRLA Battery Pack	AF482A
	HP WW DirectFlow Secondary Battery Cable	AF497A
	NOTE: Please see the HPE DirectFlow Three Phase Uninterruptible Power System QuickSpecs for information on additional options and product specifications.	
	HPE Tower UPS	
	HPE T750 G4 UPS Models	
	HP T750 G4 NA/JP Uninterruptible Power System	J2P85A
	HPE T1000 G4 UPS Models	
	HP T1000 G4 NA/JP Uninterruptible Power System	J2P86A
	HPE T1500 G4 UPS Models	
	HP T1500 G4 NA/JP Uninterruptible Power System	J2P87A
	HPE Rack-mountable UPS	

Additional Options

HPE R/T2200 G4 UPS Models		
HP R/T2200 G4 NA/JP Uninterruptible Power System		J2R00A
HPE R/T3000 G4 UPS Models		
HP R/T3000 G4 Low Voltage NA/JP Uninterruptible Power System		J2R01A
HP R/T3000 G4 High Voltage NA/JP Uninterruptible Power System		J2R02A
R1500 G4 Models		
HP R1500 G4 NA Uninterruptible Power System		J2Q99A
R7000 Uninterruptible Power System (UPS)		
HP R7000 4U 50A High Voltage NA/JP Uninterruptible Power System		AF462A
R5000 Uninterruptible Power System (UPS)		
HP R5000 3U L630 High Voltage NA/JP Uninterruptible Power System		AF460A
NOTE: Please see the HPE Line Interactive Single Phase UPS QuickSpecs for information on additional options and product specifications.		
HPE UPS Options		
HP R/T2200 G4 Extended Runtime Module		J2R09A
HP R/T3000 G4 Extended Runtime Module		J2R10A
HP 2U Rack/Tower UPS Shipping Kit		L4Q11A

NOTE: To learn more, please visit the [HPE Uninterruptible Power Systems \(UPS\) web page](#).

HPE Power Cords	HP 8AWG W/Ground Lug 48V DC 3.0m Power Cord	J6X42A
-----------------	---	--------

HPE USB and SDHPE Flash Media Kits for USB Drives		
Options	HP 8GB USB Enterprise Mainstream Flash Media Drive Key Kit	737953-B21
	HP Dual 8GB microSD Enterprise Midline USB Kit	741279-B21
HPE Enterprise Mainstream Flash Media Kits for Memory Cards		
	HP 32GB microSD Enterprise Mainstream Flash Media Kit	700139-B21
	HP 8GB microSD Enterprise Mainstream Flash Media Kit	726116-B21

Memory

HPE SmartMemory

New HPE SmartMemory now provides additional protection for your servers. With HPE Authentication it can verify that server. With HPE SmartMemory, your new HPE ProLiant server can take advantage of additional Gen9 enhancements System.

For detailed memory configuration rules and guidelines, please use the Online DDR4 Memory Configuration Tool: <http://>

Memory


As shown in the figure below, memory cartridge to processor association as follows:

Subsystem

Memory cartridges installed without a corresponding processor are not utilized:

Architecture

- o Processor 1 corresponds to memory cartridges 1 and 2.
- o Processor 2 corresponds to memory cartridges 3 and 4.
- o Processor 3 corresponds to memory cartridges 5 and 6.
- o Processor 4 corresponds to memory cartridges 7 and 8.




The server can operate in independent channel mode (performance) or combined channel mode (lockstep). Lockstep mode improves the system reliability and availability. If running with RDIMM (built with x4 DRAM devices), the system can survive the complete failure of two DRAM devices (DDDC). Running in independent mode, the server can only survive the complete failure of a single DRAM device (SDDC).

Memory performance depends on selected processor and whether the system is configured for independent channel mode (performance mode) or lockstep mode (RAS mode).

Memory

Memory
Population
guidelines

Each memory cartridge contains 12 DIMM slots as shown in figure below:



General Memory Population Rules and Guidelines:

- To maximize performance, install two memory cartridges per processor and balance the total memory capacity between all installed processors.
- When multiple processors are installed, HPE recommends installing the DIMMs in sequential alphabetical order: 4A, 9B, 1C, 12D, and so on.
- LRDIMMs support higher densities than single- and dual-rank RDIMMs, and higher speeds than quad-rank RDIMMs. This support enables you to install more high capacity DIMMs, resulting in higher system capacities and higher bandwidth.
- Do not mix LRDIMMs with any other DIMM type (RDIMM, LVDIMM).
- RDIMM population is limited to a maximum of eight logical ranks per channel. Therefore, only two quad rank RDIMMs are supported per channel. If there are more than eight physical ranks per channel, LRDIMMs rank multiplication provides support for three DIMMs per channel.
- Performance or Independent Mode: In this mode each DDR4 channel works independently and the SMI2 channel operates at twice the DDR4 speed (3200 MT/s max).
- Lockstep mode: In this mode, the memory controller operates two DDR4 channels behind one memory buffer as single channel and the SMI2 channel operates at the DDR4 transfer rate (1866 MT/s max).

NOTE: UDIMMs are not supported. This server does not support mixing LRDIMMs, RDIMMs, or UDIMMs. Attempting to mix any combination of these DIMMs can cause the server to halt during BIOS initialization. For detailed memory configuration rules and guidelines, use the Online DDR4 Memory Configuration Tool on the HPE website (<http://www.hp.com/go/ddr3memory-configurator>).

Intel Gen9 Supported Memory Bandwidth for HPE ProLiant Gen9 Intel® Xeon® E7-4800v3/v4 Series Processor Family

Memory

Memory Bandwidth and Capacity

[DIMM Type]

Registered DIMMs (RDIMMs)

HPE SKU P/N	726718-B21	726719-B21	728629-
DIMM Rank	Single Rank	Dual Rank	Dual Rank
DIMM Capacity	8GB	16GB	32GB
Voltage	Std Voltage 1.2V	Std Voltage 1.2V	Std Voltage 1.2V
DIMM Native Speed (MT/s)	2133	2133	2133
SLOTS THAT CAN BE POPULATED			
96 slot servers	96	96	96
MAXIMUM CAPACITY (GB)			
	768	1536	3072
POPULATED DIMM SPEED (MT/s)			
1 DIMM Per Channel	1600	1600	1600
2 DIMM Per Channel	1600	1600	1600
3 DIMM Per Channel	1600	1333	1333

Intel Gen9 Supported Memory Bandwidth for HPE ProLiant Gen9 Intel® Xeon® E7-8800v3/v4 Series Processor Family

Memory Bandwidth and Capacity

[DIMM Type]

Registered DIMMs (RDIMMs)

HPE SKU P/N	805347-B21	805349-B21	83622
DIMM Rank	Single Rank	Single Rank	Dual Rank
DIMM Capacity	8GB	16GB	16GB
Voltage	Std Voltage 1.2V	Std Voltage 1.2V	Std Voltage 1.2V
DRAM Depth [bit]	1G	1G	2G
DRAM Width [bit]	x8	x4	x8
DRAM Density	8Gb	8Gb	4Gb
CAS Latency	17-17-17	17-17-17	17-17-17
DIMM Native Speed (MT/s)	2400	2400	2400
SLOTS THAT CAN BE POPULATED			
96 slot servers	96	96	96
MAXIMUM CAPACITY (GB)			

Memory

	768	1536	15
POPULATED DIMM SPEED (MT/s)			
1 DIMM Per Channel	2400	2400	24
2 DIMM Per Channel	2133	2133	21
3 DIMM Per Channel	1600	1600	16

DIMM slot and configuration • The memory subsystem in this server is divided into channels. Each processor supports eight channels, and each channel supports three DIMM slots, as shown in the table below. White DIMM slots denote the first slot of a channel (Ch 4A, Ch 9B, Ch 1C, Ch 12D...).

CPU 1			CPU 2		
Slot #	population order		Slot #	population order	
Chnl 3	1 C		1 C		Chnl 3
	2 G		2 G		
	3 L		3 L		
CPU 1			CPU 2		
Slot #	population order		Slot #	population order	
Chnl 1	4 A		4 A		Chnl 1
	5 E		5 E		
	6 J		6 J		
CPU 1			CPU 2		
Slot #	population order		Slot #	population order	
Chnl 2	7 K		7 K		Chnl 2
	8 F		8 F		
	9 B		9 B		
CPU 1			CPU 2		
Slot #	population order		Slot #	population order	
Chnl 4	10 M		10 M		Chnl 4
	11 H		11 H		
	12 D		12 D		

Memory


Memory Speed by Processor Model	Processor Models	Supported Memory Speeds
	E7-4809v3, E7-4809v4, E7-4820v3, E7-4820v4, E7-4830v3, E7-4850v3, E7-4830v4, E7-4850v4	1600MHz
	E7-8893v3, E7-8893v4, E7-8891v3, E7-8891v4, E7-8860v3, E7-8867v3, E7-8890v3, E7-8880v3, E7-8870v3, E7-8880Lv3, E7-8860v4, E7-8867v4, E7-8870v4, E7-8880v4, E7-8890v4	1333/1600/1866MHz

Standard and Maximum Memory Capacity (Pre-configured Models)	Pre Configured Models	Standard Memory	Maximum Memory Plus Optional Memory	Standard Memory Replaced with Optional Memory
	E7-8890v4, E7-8893v4, E7-8890v3, E7-8893v3	256GB (16x16GB)	5376GB (80x64GB, 16x16GB)	6144GB (96x64GB)
	E7-4850v4, E7-4850v3	128GB (8x16GB)	5760GB (88x64GB, 8x16GB)	6144GB (96x64GB)
	E7-4809v4, E7-4809v3	64GB (4x16GB)	5952GB (92x64GB, 4x16GB)	6144GB (96x64GB)


DDR4 memory options part number decoder

NOTE: Capacity references are rounded to the common gigabyte (GB) values.

- 2GB = 2,048MB
- 4GB = 4,096MB
- 8GB = 8,192MB
- 16GB = 16,384MB
- 32GB = 32,768MB
- 64GB = 65,536MB



Storage



1-10

Ten (10) SFF Hot-plug HDD/SSD drive bays

NOTE: Drives installed in bays 6-10 require the optional SAS backplane kit.

NOTE: Optional NVMe drives are only supported in Drive bays 6-10.

Maximum Storage Capacity -

NOTE: Optional support for 5 NVMe PCIe SSDs or 5 SFF drives are also available.

Hot Plug SFF SAS 20 TB (10 x 2.0 TB)

Hot Plug SFF SAS 19.2 TB (10 x 1.92 TB)

SSD

Hot Plug SFF SATA 38.4 TB (10 x 3.84 TB)

SSD

Hot Plug SFF 8 TB (5 x 1.6 TB)

NVMe PCIe SSD

Technical Specifications

System Unit	Dimensions (H x W x D) (with bezel)	6.88" x 17.48" x 29" (17.5cm x 44.4cm x 73.6cm)
Weight (approximate)	Maximum: (all hard drives, power supplies, DIMMs and processors installed)	116.56 lb (52.87 kg)
	Minimum: (one hard drive, two power supplies, four DIMMs, and two processors installed)	70.94 lb (32.18 kg)
Input Requirements (per power supply)	Range Line Voltage Rated Input Current Rated Input Frequency Rated Input Power	100 - 120 VAC (1200W PS only) 200 - 240 VAC (1200W & 1500W PS) 9.2A (100 VAC), 6.6A (200 VAC) - 1200W PS 8.3A (200 VAC) - 1500W PS 50 to 60 Hz 1000 W (120 VAC), 1320 W (230VAC)- 1200W PS 1652 W (at 230 VAC) - 1500W PS
BTU Rating	Maximum	3408 BTU/hr (120 VAC), 4500 BTU/hr (at 230 VAC) - 1200W PS 5637 BTU/hr (230 VAC) - 1500W PS VAC), 3112 BTU/hr (at 240 VAC) for China Only
Power Supply Output (per power supply)	Rated Steady-State Power Maximum Peak Power	800 W (100 VAC low line), 900 W (120 VAC low line), 1200W (200 - 240 VAC) for 1200W PS 1500W (200 - 240V) for 1500W PS 1400W (at 240 VAC) input for China only

NOTE: To review typical system power ratings use the HPE Power Advisor which is available online located at url: <http://www.hp.com/go/proliant-energy-efficient> or <http://www.hp.com/go/hppoweradvisor>.

Technical Specifications

System Inlet Temperature	Standard Operating Support	10° to 35°C (50° to 95°F) at sea level with an altitude derating of 1.0°C per every 305 m (1.8°F per every 1000 ft) above sea level to a maximum of 3050 m (10,000 ft), no direct sustained sunlight. Maximum rate of change is 20°C/hr (36°F/hr). The upper limit and rate of change may be limited by the type and number of options installed. System performance during standard operating support may be reduced if operating with a fan fault or above 30°C (86°F).
	Extended Ambient Operating Support	For approved hardware configurations, the supported system inlet range is extended to be: 5° to 10°C (41° to 50°F) and 35° to 40°C (95° to 104°F) at sea level with an altitude derating of 1.0°C per every 175 m (1.8°F per every 574 ft) above 900 m (2953 ft) to a maximum of 3050 m (10,000 ft). The approved hardware configurations for this system are listed at the URL: http://www.hp.com/servers/Ashrae
		For approved hardware configurations, the supported system inlet range is extended to be: 40° to 45°C (104° to 113°F) at sea level with an altitude derating of 1.0°C per every 125 m (1.8°F per every 410 ft) above 900 m (2953 ft) to a maximum of 3050 m (10,000 ft). The approved hardware configurations for this system are listed at the URL: http://www.hp.com/servers/Ashrae
		System performance may be reduced if operating in the extended ambient operating range or with a fan fault.
Relative Humidity (non-condensing)	Non-operating	-30° to 60°C (-22° to 140°F). Maximum rate of change is 20°C/hr (36°F/hr).
	Operating	10% to 90% relative humidity (Rh), 28°C (82.4°F) maximum wet bulb temperature, non-condensing.
Altitude	Non-operating	5 to 95% relative humidity (Rh), 38.7°C (101.7°F) maximum wet bulb temperature, non-condensing.
	Operating	3048 m (10,000 ft). This value may be limited by the type and number of options installed. Maximum allowable altitude change rate is 457 m/min (1500 ft/min).
Acoustic Noise	Non-operating	9144 m (30,000 ft). Maximum allowable altitude change rate is 457 m/min (1500 ft/min).
		Listed are the declared A-Weighted sound power levels (LWAd) and declared average bystander position A-Weighted sound pressure levels (LpAm) when the product is operating in a 23°C ambient environment. Noise emissions were measured in accordance with ISO 7779 (ECMA 74) and declared in accordance with ISO 9296 (ECMA 109). Idle

Technical Specifications

L WAd	6.8 B
L pAm	51.2
Operating	
L WAd	6.9 B
L pAm	51.2

Emissions Classification (EMC)	FCC Rating Normative Standards	Class A CISPR 22; EN55022; EN55024; FCC CFR 47, Pt 15; ICES-003; CNS13438; GB9254; K22;K24; EN 61000-3-2; EN 61000-3-3; EN 60950-1; IEC 60950-1
--------------------------------	--------------------------------	---

NOTE: Product conformance to cited product specifications is based on sample (type) testing, evaluation, or assessment. This product or family of products is eligible to bear the appropriate compliance logos and statements.

HPE Smart Array P830i	Disk Drive and Enclosure Interface - Transfer rate	12 Gb/s SAS, 6 Gb/s SAS & SATA
	SAS Connectors	2 internal x8 Mini-SAS double-wide internal
	Cache Memory Speed	DDR2-1866 MHz with 72-bit wide bus at 14.9 GB/s (4 GB Cache Module) 12 Gb/s per physical link
	Cache Memory	FBWC cache is required. 2 GB is included with BTO models. For CTO, 2 GB or 4 GB FBWC cache is required.
	Logical Drives Supported	
	Host Memory Addressing	64-bit, supporting greater than 4GB server memory space
	RAID Support	RAID 6, 60 (Advanced Data Guarding) RAID 5, 50 (Distributed Data Guarding) RAID 1, 10 (Drive Mirroring), RAID 1 ADM, 10 ADM (Advanced Data Mirroring) RAID 0 (Striping)

HPE Ethernet 1Gb 4-port	Network Interface	10Base-T/100Base-TX/1000Base-TX
-------------------------	-------------------	---------------------------------

Technical Specifications

331FLR Adapter	Compatibility	IEEE 802.3 10Base-T	
		IEEE 802.3ab 1000Base-T	
		IEEE 802.3u 100Base-TX	
		IEEE 802.3x	
		IEEE 802.3ad 1000Base-TX	
		IEEE 802.3az	
		IEEE 1588	
	Data Transfer Method	PCI-Express 2.0 x4	
	Controller	BCM5719	
	Network Transfer Rate	10Base-T (Full-Duplex)	20 Mb/s
	100Base-TX (Full-Duplex)	200 Mb/s	
	1000Base-TX (Full-Duplex)	2000 Mb/s	
Connector	RJ-45		
Cable Support	10 Base-T	Categories 3, 4 or 5 UTP; up to 328 ft (100 m)	
	100 Base-TX	Category 5 or higher UTP; up to 328 ft (100 m)	
	1000 Base-TX	Category 5 or higher UTP; up to 328 ft (100 m)	

HPE FlexFabric 10Gb 2-port 534FLR-SFP+ Adapter	Network Interface	IEEE 802.3 SFP+ (SX, SR & LR)
	Compatibility	IEEE 802.3

Environment-friendly Products and Approach

End-of-life Management and Recycling

Hewlett-Packard offers end-of-life Hewlett Packard Enterprise product return, trade-in, and recycling programs in many geographic areas. For trade-in information, please go to: <http://www.hp.com/go/green>. To recycle your product, please go to: <http://www.hp.com/go/green> or contact your nearest Hewlett Packard Enterprise sales office. Products returned to Hewlett Packard Enterprise will be recycled, recovered or disposed of in a responsible manner.

The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard Enterprise web site at: <http://www.hp.com/go/green>. These instructions may be used by recyclers and other WEEE treatment facilities as well as Hewlett Packard Enterprise OEM customers who integrate and re-sell Hewlett Packard Enterprise equipment.





Summary of Changes

Date	Version History	Action	Description of Change
6-Jun-2016	From Version 10 to 11	Added Changed	Added new Processors, Memory, HPE Drives, and HPE Disk Backup options. HPE Processors, Chipset, Upgradeability, Graphics, Pre-configured Models, Configuration Information - Factory Integrated Models, HPE Memory, HPE Computation and Graphics Accelerators, and Storage sections were revised.
8-Apr-2016	From Version 9 to 10	Changed	HPE Processors section was revised.
31-Mar-2016	From Version 8 to 9	Added Changed Removed	Added new controllers, new HDD offering, new networking adapters, new security TPM module, and new transceiver. Network Controller, Embedded Management, Security, Service and Support, Pre-configured Models, and Storage Options sections were revised. Obsolete SKUs were removed from the QuickSpecs.
16-Feb-2016	From Version 7 to 8	Added Changed Removed	New HDD offering was added to HPE Drives. Operating Systems and Virtualization Software Support for ProLiant Servers, Pre-configured Models, Configuration Information - Factory Integrated Models, HPE Power Distribution Units (PDUs), and Technical Specifications were revised. Obsolete SKUs were removed from the QuickSpecs.
17-Dec-2015	From Version 6 to 7	Added	Smart Buy models were added to the NA version.
1-Dec-2015	From Version 5 to 6	Added Changed Removed	New SSD offering was added to HPE Drives. New options added to HPE Infiniband, HPE PCIe Workload Accelerator Options, and HPE Tape Backup. On System Management Chipset, Maximum Internal Storage, Embedded Management, Server Utilities, Obsolete SKUs were removed from the QuickSpecs.
9-Oct-2015	From Version 4 to 5	Changed	Memory, Maximum Internal Storage, HPE USB and SD Options, Storage, and Dimensions in Technical Specifications were revised.
2-Oct-2015	From Version 3 to 4	Changed	HPE Memory section was revised.

Summary of Changes

28-Sep-2015	From Version 2 to 3	Added	Added new 6Gb SATA Solid State Drives. Added new HPE OneView management software.
		Changed	Maximum Internal Storage, Interfaces, and HPE Memory were revised.
		Removed	Obsolete SKUs were removed from the QuickSpecs.
17-Aug-2015	From Version 1 to 2	Added	New Hard Drives offering was added to Core Options.
		Changed	Upgradeability and FlexibleLOM under Standard Features were revised. HPE Memory, HP Networking, and HPE Graphic Options under Core Options were revised. Memory section was revised.



[Sign up for updates](#)

© Copyright 2016 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

Intel® and Xeon® are registered trademarks of Intel Corporation in the U.S. and other countries.

Microsoft®, Windows®, and Windows Server® are U.S. registered trademarks of the Microsoft group of companies.

For hard drives, 1GB = 1 billion bytes. Actual formatted capacity is less

c04601209- 15187 - North America - V11 - 6-June-2016

