

HP Designjet T920 ePrinter series

Newly designed, web-connected ePrinter with breakthrough usability



Innovative user experience

- Eliminate the output clutter—get flat, collated prints thanks to the integrated output stacking tray.
- Gain full control—monitor media rolls, view printer status on the touchscreen, and track jobs during printing.
- Load paper rolls effortlessly—even when seated—with true front roll loading and automatic roll alignment.
- Print up to AO/E with a compact, 36-inch printer designed with a flat surface for quick checking of your printouts.

Fast and quality prints from the very first time

- Print fast—create professional A1/D-size prints in 21 seconds, and collate jobs with the output stacking tray.
- Complete your work efficiently by printing correctly—from the first time—thanks to true print previews.
- Get dark blacks, true neutral grays, and vivid colors with six Original HP inks and the HP printhead.
- Process complex files easily with up to 32 GB of virtual memory, HP-GL/2, and PDF support¹ for most OS.
 - Included with PostScript printers only.
 - Requires an HP Designjet ePrint & Share account, Internet connection to the printer, and connected Internet-capable device. When using the HP Designjet ePrint & Share mobile app, a compatible Apple® iOS or Android™ device and Internet connection are required. Data or connection charges may apply. Print times may vary. For more information, visit <u>hp.com/go/eprintandshare</u>.
 - 1. With Aurasma installed, please go to the HP Designjet channel at <u>http://auras.ma/s/ke25m</u>
 - 2. Without Aurasma installed, please download it:
 - a. Google Play http://auras.ma/s/android
 - b. Apple Store http://auras.ma/s/ios
 - Once done, go to the HP Designjet channel at http://auras.ma/s/ke25m
 - 3. Open the application and point to the image to view the HP Designjet video

Print from virtually anywhere²

- Use your Apple[®] or Android[™] smartphone or tablet to print from virtually anywhere².
- Access and print projects from the cloud when you're out of the office, using HP Designjet ePrint & Share².
- Automatically save copies of your projects to the cloud when you print using HP Designjet ePrint & Share².
- Print without drivers using a USB stick or directly email projects to your HP Designjet T920 ePrinter².

For more information, please visit hp.com/go/DesignjetT920



Kuker-Ranken Seattle 800-454-1310 Tacoma 888-562-3082 Portland 800-472-7007 www.krinc.net

Technical specifications

Print Line drawings ³ 21 sec/page on Al/D, 120 Al/D prints per hour Print resolution Up to 2400 x 1200 optimized dpi Margins (top x, Rult 5, S x 5, S mm (0.2 x 0.2 x 0.2 x 0.2 x 0.2 x 0.2 in) bottom xleft x Sheet: 5 x 22 x 5 x 5 mm (0.2 x 0.87 x 0.2 x 0.2 in) right) Technology HP Thermal Inkjet Ink types Dye-based (C, G, M, pK, Y); pigment-based (mK) Ink drop 6 pl (C, M, Y, G, pk); 9 pl (mK) Printheads 1 (C, G, M, mK, pK, Y) Line accuracy +/- 0.1% ² Minimum line 0.02 mm (0.0008 in) (HP-GL/2 addressable) width Guaranteed Guaranteed 0.07 mm (0.0028 in) (ISO/IEC 13660:2001(E)) ⁶ minimum Input: automatic front-loading roll feed, sheet feed; Output: integrated output stacking tray (from A4/A to A0/E, with up to 50 A1/D-size capacity), media bin, automatic cutter Weight 60 to 328 g/m ² Size Rolls: 279 to 914 mm (11 to 36 in) Sheets: 210 x 279 to 914 x 121 mm (8.3 x 11 to 36 x 48 in) Standard bit Sheets: 210 x 271 to 914 mm (11 to 36 in) Standard bit Sheets: 210 x 271 to 91 mm (8.3 x 11 to 36 x 48 in) Stanet: the transmit Gigabit Ethernet				
Margins (top x bottom xleft x Sheet: 5x 22x 5x 5 mm (0.2 x 0.2 x 0.2 x 0.2 in) right) Technology HP ThermalInkjet Ink types Dye-based (C, G, M, K, Y); pigment-based (mK) Ink drop 6 pl (C, M, Y, G, pK); 9 pl (mk) Printheads 1 (C, G, M, mK, pK, Y) Ink drop 6 pl (C, M, Y, G, pK); 9 pl (mk) Printheads 1 (C, G, M, mK, pK, Y) Line accuracy +/-0.196' Minimum line 0.02 mm (0.0028 in) (ISO/IEC 13660:2001(E))* minimum 0.07 mm (0.0028 in) (ISO/IEC 13660:2001(E))* minimum Inewidth Media Handling Handling Input: automatic front-loading roll feed, sheet feed; Out- put: integrated output stacking tray (from A4/A to A0/E, with up to 50 A1/D-size capacity), media bin, automatic cutter Weight 60 to 328 g/m² Size Rolls: 270 to 914 mm (11 to 36 in) Sheets: 210 x 279 to 914 x 1219 mm (8.3 x 11 to 36 x 48 in) Standard sheets: 41, A3, A2, A1, A0(A, B, C, D, E) Thickness Up to 0.5 mm (19.7 mil) Pasit Ceript ePrinter: 32 GB (virtual)* Standard) Print languages Basic ePrinter: HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GU, URF PostScript ePrinter: 32 GB (virtual)*, 320 GB hard disk	Print	Line drawings ³	21 sec/page on A1/D, 120 A1/D prints per hour	
bottom xleft x right) Technology HP Thermal Inkjet Ink types Dye-based (C, G, M, pK, Y): pigment-based (mK) Ink drop 6 pl (C, M, Y, G, pK); pl (mK) Printheads 1 (C, G, M, mK, PK, Y) Line accuracy +/-0.1%? Minimum line width Guaranteed 0.07 mm (0.0008 in) (HP-GL/2 addressable) width Guaranteed 0.07 mm (0.0028 in) (ISO/IEC 13660:2001(E))* minimum line width Media Handling Input: automatic front-loading roll feed, sheet feed, Out- put: integrade doutput stacking tray (from A4/A to A0/E, with up to 50 A1/D-size capacity), media bin, automatic Cutter Weight 60 to 328 g/m² Size Rolls: 279 to 914 mr (11 to 36 in) Sheets: 210 x 279 to 914 x 121 9 mm (B.3 x 11 to 36 x 48 in) Standard Sheets: A4, A3, A2, A1, A0 (A, B, C, D, E) Thickness Up to 0.5 mm (19.7 mi) Memory Basic ePrinter: 32 GB (virtual)* PostScript ePrinter: Adobe PostScript 3, Adobe PDF 1.7 Extension Level 3, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI, URF Printer driver, HP Designjet ePrint & Share, HP Embedded Web Server, HP Instant Printing, direct printing from USB fash drive, email printing Drivers HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI, URF Printer driver, HP Designjet ePrint & Share, HP Embedded Web Server, HP Instant Printing, direct printing from USB fash drive, email printing Drivers HP-GL/2, HP-RTL TIFF, JPEG, CALS G4, HP PCL 3 GUI, URF Printer driver, HP Designjet ePrint & Share, HP Embedded Web Server, HP Instant Printing, direct printing from USB fash drive, email printing Drivers HP-GL/2, HP-RTL TIFF, JPEG, CALS G4, HP PCL 3 GUI, URF Printer driver, HP Designjet A Printer driver, Share, HP ED, S GUI drivers [†] Dimensions Printer driver, HP Design (S 1 x 36.1 x 43.1 in) Shipping 152 Sk 2(247.5 lb) Mat's in the Printer 87 kg (191.8 lb) Shipping 152 Sk 2(247.5 lb) Mat's in the Deerating		Print resolution	Up to 2400 × 1200 optimized dpi	
Ink types Dye-based (C, G, M, pK, Y); pigment-based (mk) Ink drop 6 pl (C, M, Y, G, pK); 9 pl (mK) Printheads 1 (C, G, M, mK, pK, Y) Line accuracy +/-0.1% ² Minimum line 0.02 mm (0.0008 in) (HP-GL/2 addressable) width Guaranteed 0.07 mm (0.0028 in) (ISO/IEC 13660:2001(E)) ⁶ minimum line width Inext visual addresses Media Handling Input: automatic front-loading roll feed, sheet feed; Out-put: integrated output stacking tray (from A4/A to A0/E, with up to S0 A1/D-size capacity), media bin, automatic cutter Weight 60 to 328 g/m ² Size Size Rolls: 279 to 914 mm (11 to 36 in) Sheets: 210 x 279 to 914 x 1219 mm (8.3 x 11 to 36 x 48 in) Standard sheets: A4, A3, A2, A1, A0 (A, B, C, D, E) Thickness Up to 0.5 mm (19.7 mil) Memory Basic ePrinter: 32 GB (virtual) ⁶ , 320 GB hard disk Connectivity? Interfaces Gigabit Ethernet (1000Base-T) (standard) Print languages Basic ePrinter: HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP Standard bergits ePrinter: HP CL 3 GU, URF Printer driver, HP Designjet ePrint Share, HP Embedded Weis brivers HP-CL/2, HP-RTL drivers for Windows, L		bottom x left x		
Ink drop 6 pl (C, M, Y, G, pk); 9 pl (mk) Printheads 1 (C, G, M, mk, pk, Y) Line accuracy -4/-0.1% ² Minimum line 0.02 mm (0.0028 in) (HP-GL/2 addressable) width Guaranteed Inimum line width Guaranteed Media Handling Hut: integrated output stacking tray (from A4/A to A0/E, with up to 50 A1/D-size capacity), media bin, automatic cutter Weight 60 to 328 g/m ² Size Rolls: 279 to 914 x 1219 mm (8.3 x 11 to 36 x 48 in) Stenets: 210x 279 to 914 x 1219 mm (8.3 x 11 to 36 x 48 in) Stenets: 210x 273 to 914 x 1219 mm (8.3 x 11 to 36 x 48 in) Stenets: 210x 273 to 914 x 1219 mm (8.3 x 11 to 36 x 48 in) Stenets: 210x 273 to 914 x 1219 mm (8.3 x 11 to 36 x 48 in) Stenets: 210x 273 to 914 x 1219 mm (8.3 x 11 to 36 x 48 in) Stenets: 210x 273 to 914 x 1219 mm (8.3 x 11 to 36 x 48 in) Stendard sheets: A4, A3, A2, A1, A0 (A, B, C, D, E) Thickness Up to 0.5 mm (19.7 mil) Memory Basic ePrinter: HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP Vistandard) Printer driver, HP Designjet ePrint, TF, JPEG, CALS G4, HP Vistandard) Printer driver, HP Designjet ePrint & Share, HP Enbedded <td></td> <td>Technology</td> <td>HP Thermal Inkjet</td>		Technology	HP Thermal Inkjet	
Printheads 1 (C, G, M, mK, pK, Y) Line accuracy +/- 0.1%² Minimum line 0.02 mm (0.0008 in) (HP-GL/2 addressable) width Guaranteed Inimium 0.07 mm (0.0028 in) (ISO/IEC 13660:2001(E))* minimum Input: automatic front-loading roll feed, sheet feed; Out- put: integrated output stacking tray (from A4/A to A0/E, with up to 50 A1/O-size capacity), media bin, automatic cutter Weight 60 to 328 g/m² Size Rolls: 279 to 914 mm (11 to 36 in) Steadard sheets: A4, A3, A2, A1, A0 (A, B, C, D, E) Thickness Up to 0.5 mm (19.7 mil) Memory Basic ePrinter: 32 GB (virtual)*, 320 GB hard disk Connectivity Interfaces Gigabit Ethernet (1000Base-T) (standard) Print languages Basic ePrinter: HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI, URF Printal grugges Basic ePrinter: HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI, URF Printal grugges Basic ePrinter: HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI, URF Printer Printer, HP Besingiet Printt & Share, HP Embedded Web Server, HP Instart Printing, direct printing from USB ftash drive, email printing Dimensions Printer T399 x 916 x 1110 mm (55.1 x 36.1 x 43.7 in) Wex d k h S		Ink types		
Printheads 1 (C, G, M, mK, pK, Y) Line accuracy +/- 0.1%² Minimum line 0.02 mm (0.0008 in) (HP-GL/2 addressable) width Guaranteed Inimium 0.07 mm (0.0028 in) (ISO/IEC 13660:2001(E))* minimum Input: automatic front-loading roll feed, sheet feed; Out- put: integrated output stacking tray (from A4/A to A0/E, with up to 50 A1/O-size capacity), media bin, automatic cutter Weight 60 to 328 g/m² Size Rolls: 279 to 914 mm (11 to 36 in) Steadard sheets: A4, A3, A2, A1, A0 (A, B, C, D, E) Thickness Up to 0.5 mm (19.7 mil) Memory Basic ePrinter: 32 GB (virtual)*, 320 GB hard disk Connectivity Interfaces Gigabit Ethernet (1000Base-T) (standard) Print languages Basic ePrinter: HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI, URF Printal grugges Basic ePrinter: HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI, URF Printal grugges Basic ePrinter: HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI, URF Printer Printer, HP Besingiet Printt & Share, HP Embedded Web Server, HP Instart Printing, direct printing from USB ftash drive, email printing Dimensions Printer T399 x 916 x 1110 mm (55.1 x 36.1 x 43.7 in) Wex d k h S		Ink drop	6 pl (C, M, Y, G, pK); 9 pl (mK)	
Line accuracy +/-0.1%² Minimum line 0.02 mm (0.0008 in) (HP-GL/2 addressable) width Guaranteed 0.07 mm (0.0028 in) (ISO/IEC 13660:2001(E)) ⁵ minimum ine width Ine width Media Handling Input: automatic front-loading roll feed, sheet feed; Out-put: integrated output stacking tray (from A4A to A0/E, with up to S0 A1/D-size capacity), media bin, automatic cutter Weight 60 to 328 g/m² Size Size Rolls: 27 to 914 mm (11 to 36 in) Sheets: 210 x 279 to 914 x 1219 mm (8, 3 x 11 to 36 x 4B in) Standard sheets: A4, A3, A2, A1, A0 (A, B, C, D, E) Thickness Up to 0.5 mm (19.7 mil) Memory Basic ePrinter: 32 GB (virtual) ⁶ PostScript ePrinter: 32 GB (virtual) ⁶ , 320 GB hard disk Connectivity Interfaces Gigabit Ethernet (1000Base-T) (standard) PCL 3 GU, URF Print languages Basic ePrinter: HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP Prit graph Printer driver, HD Designjet ePrint & Share, HP Embedded Web Server, HP Instant Printing, direct printing from USB Ensh drive, email printing Drivers HP-GL/2, HP-RTL drivers for Windows, Linux, and Mac drivers ⁶ <				
width Guaranteed minimum line width 0.07 mm (0.0028 in) (ISO/IEC 13660:2001(E))* minimum line width Media Handling Input: automatic front-loading roll feed, sheet feed; Out- put: integrated output stacking tray (from A4/A to A0/E, with up to 50 A1/D-size capacity), media bin, automatic cutter Weight 60 to 328 g/m² Size Rolls: 279 to 914 mm (11 to 36 in) Stendard sheets: A4, A3, A2, A1, A0 (A, B, C, D, E) Thickness Up to 0.5 mm (19.7 mil) Memory Basic ePrinter: 32 GB (virtual)* PostScript ePrinter: 32 GB (virtual)* PostScript ePrinter: 32 GB (virtual)* PostScript ePrinter: 32 GB (virtual)* PostScript ePrinter: Adobe PostScript 3, Adobe PDF 1.7 Extension Level 3, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI, URF Print anguages Basic ePrinter: Adobe PostScript 3, Adobe PDF 1.7 Extension Level 3, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI, URF Printing paths Printer driver, HP Designjet ePrint & Share, HP Embedded for Mac OS X; PostScript Windows, Linux, and Mac drivers ⁶ Dimensions Printer 1399 x 916 x 1110 mm (55.1 x 36.1 x 43.7 in) (w x d x h) Shipping 1502 x 759 x 775 mm (59.1 x 29.9 x 30.5 in) Weight Printer 87 kg (191.8 lb) Shipping 1502 x 759 x 775 mm (59.1 x 29.9 x 30.5 in) Wet S in the box HP Designjet T920 ePrinter, printhead		Line accuracy		
minimum line width Media Handling Input: automatic front-loading roll feed, sheet feed; Out- put: integrated output stacking tray (from A4/A to A0/E, with up to 50 A1/D-size capacity), media bin, automatic cutter Weight 60 to 328 g/m ² Size Rolls: 279 to 914 mm (11 to 36 in) Steets: 210 x 279 to 914 x 1219 mm (6.3 x 11 to 36 x 48 in) Standard sheets: A4, A3, A2, A1, A0 (A, B, C, D, E) Memory Basic ePrinter: 32 GB (virtual) ⁶ PostScript ePrinter: 32 GB (virtual) ⁶ PostScript ePrinter: A00e PostScript 3, Adobe PDF 1.7 Extension Level 3, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PostScript ePrinter: AD0e PostScript 3, Adobe PDF 1.7 Extension Level 3, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI, URF Printing paths Printer driver, HP Designjet ePrint & Share, HP Embedded Web Server, HP Instant Printing, direct printing from USB flash drive, email printing Dirvers HP-GL/2, HP-RTL drivers for Windows ⁶ ; HP PCL 3 GUI drive (included Frinter Printer 1399 x 916 x 1110 mm (55.1 x 36.1 x 43.7 in) Shipping 1502 x 759 x 759 x 755 x 752 x 752 x 70.5 x 30.5 in) Weight Printer 87 Ag (191.8 lb) Shipping 1502 x 759 x 755 x 755 x 752 x 30.5 (x 43.7 in) Stard and media bin			0.02 mm (0.0008 in) (HP-GL/2 addressable)	
 put: integrated output stacking tray (from A4/A to A0/E, with up to 50 A1/D-size capacity), media bin, automatic cutter Weight 60 to 328 g/m² Size Rolls: 279 to 914 mm (11 to 36 in) Sheets: 210 x 279 to 914 x 1219 mm (8.3 x 11 to 36 x 48 in) Standard sheets: A4, A3, A2, A1, A0 (A, B, C, D, E) Thickness Up to 0.5 mm (19.7 mil) Memory Basic ePrinter: 32 GB (virtual)⁶, 320 GB hard disk Connectivity⁷ Inter: Ace Gigabit Ethernet (1000Base-T) (standard) Print languages Basic ePrinter: HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI, URF PostScript ePrinter: 32 GB (virtual)⁶, 220 GB hard disk Connectivity⁷ Interfaces Gigabit Ethernet (1000Base-T) (standard) Print languages Basic ePrinter: HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI, URF Printing paths Printer driver, HP Designjet ePrint & Share, HP Embedded Web Server, HP Instant Printing, direct printing from USB flash drive, email printing Drivers HP-GL/2, HP-RTL drivers for Windows[®]; HP PCL 3 GUI drive (included) for Mac OS X; PostScript Windows, Linux, and Mac drivers⁹ Dimensions (w x d x h) Shipping 1502 x 759 x 775 mm (59.1 x 29.9 x 30.5 in) Weight Printer 87 kg (191.8 lb) Shipping 112.5 kg (247.5 lb) Storage temperature: 25 to 40°C (41 to 104°F) Storage temperature: 26 0 awas (main), < 4 watts (61 hardswitch) input voltage (auto ranging) 100 to 240 VAC (+- 10%), 50/60 Hz (+- 3 Hz), 4.2 A max (peak current) Certification bedded bigital Front End) (sleep). Cound power: 6.5 B(A) (printing); 3.8 B(A) (ready); <1.9 B(A) (sleep) Sound power: 6.5 B(A) (print		minimum	0.07 mm (0.0028 in) (ISO/IEC 13660:2001(E))⁵	
Size Rolls: 279 to 914 mm (11 to 36 in) Sheets: 210 x 279 to 914 x 1219 mm (8.3 x 11 to 36 x 48 in) Standard sheets: A4, A3, A2, A1, A0 (A, B, C, D, E) Thickness Up to 0.5 mm (19.7 mil) Memory Basic ePrinter: 32 GB (virtual) ⁶ PostScript ePrinter: 32 GB (virtual) ⁶ , 320 GB hard disk Connectivity7 Interfaces Gigabit Ethernet (1000Base-T) (standard) Print languages Basic ePrinter: HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP (standard) PCL 3 GUI, URF PostScript @Printer: Adobe PostScript 3, Adobe PDF 1.7 Extension Level 3, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI, URF Printing paths Printer driver, HP Designjet ePrint & Share, HP Embedded Web Server, HP Instant Printing, direct printing from USB flash drive, email printing Drivers HP-GL/2, HP-RTL drivers for Windows [®] ; HP PCL 3 GUI drive (included) for Mac OS X; PostScript Windows, Linux, and Mac drivers [®] Dimensions (w x d xh) Printer Printer 1399 x 916 x 1110 mm (55.1 x 36.1 x 43.7 in) What's in the HP Designjet T920 ePrinter, printhead, ink cartridges, stacking tray, printer stand and media bin, spindle, quick reference guide, setup poster, startup software, power cord Environmen- tal ranges Operating temperature: 25 to 55°C (-13 to 131°F) Operating temperature: 25 to 40°C (41 to 104°F) Storage temperature: 25 to 40°C (41 to 104°F) </td <td>Media</td> <td>Handling</td> <td>put: integrated output stacking tray (from A4/A to AO/E, with up to 50 A1/D-size capacity), media bin, automatic</td>	Media	Handling	put: integrated output stacking tray (from A4/A to AO/E, with up to 50 A1/D-size capacity), media bin, automatic	
Sheets: 210 x 279 to 914 x 1219 mm (8.3 x 11 to 36 x 48 in) Standard sheets: A4, A3, A2, A1, A0 (A, B, C, D, E) Thickness Up to 0.5 mm (19.7 mil) Memory Basic ePrinter: 32 GB (virtual) ⁶ PostScript ePrinter: 32 GB (virtual) ⁶ Standard) Ornectivity? Interfaces Gigabit Ethernet (1000Base-T) (standard) Print languages Basic ePrinter: HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI, URF PostScript [®] ePrinter: Adobe PostScript 3, Adobe PDF 1.7 Extension Level 3, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI, URF Printing paths Printer driver, HP Designjet ePrint & Share, HP Embedded Web Server, HP Instant Printing, direct printing from USB flash drive, email printing Dimensions Printer 1399 x 916 x 1110 mm (55.1 x 36.1 x 43.7 in) Weight Printer 87 kg (191.8 lb) Shipping 1502 x 759 x 775 mm (59.1 x 29.9 x 30.5 in) Weight Printer 87 kg (191.8 lb) Shipping 1502 x 759 x 755 mc (59.1 x 29.1 x 29.9 x 30.5 in) Weight Printer 87 kg (191.8 lb) Shipping 1302 x 2759 x 715 mm (59.1 x 29.9 x 30.5 in) Weight Printer 87 kg (191.8 lb) Shipping 1302 x 250 086 RH Acoustic Sound pressure: 47 dB(A) (printing);		Weight	60 to 328 g/m ²	
Standard sheets: A4, A3, A2, A1, A0 (A, B, C, D, E) Thickness Up to 0.5 mm (19.7 mil) Memory Basic ePrinter: 32 GB (virtual) ⁶ , 320 GB hard disk Connectivity' Interfaces Gigabit Ethernet (1000Base-T) (standard) Print languages Basic ePrinter: HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP Print languages Basic ePrinter: HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP VestScript® Perinter: Adobe PostScript 3, Adobe PDF 1.7 Extension Level 3, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI, URF Printing paths Printer driver, HP Designjet ePrint & Share, HP Embedded Web Server, HP Instant Printing, direct printing from USB flash drive, email printing Dirvers HP-GL/2, HP-RTL drivers for Windows, Linux, and Mac drivers ⁶ Dirvers HP-GL/2, HP-RTL drivers for Sindows, Linux, and Mac drivers ⁶ Meight Printer 1399 x 916 x 1110 mm (55.1 x 36.1 x 43.7 in) Shipping 1502 x 759 x 775 mm (59.1 x 29.9 x 30.5 in) Weight Printer 87 kg (191.8 lb) Shipping 112.5 kg (247.5 lb) What's in the Designjet T920 ePrinter, printhead, ink cartridges, stacking tray, printer stand and media bin, spindle, quick reference guide, setup poster, startup software, power cord		Size	Rolls: 279 to 914 mm (11 to 36 in)	
ThicknessUp to 0.5 mm (19.7 mil)MemoryBasic ePrinter: 32 GB (virtual)6 PostScript ePrinter: 32 GB (virtual)6, 320 GB hard diskConnectivityiInterfacesGigabit Ethernet (1000Base-T) (standard)Print languagesBasic ePrinter: HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI, URFPrint languagesBasic ePrinter: Adobe PostScript 3, Adobe PDF 1.7 Extension Level 3, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI, URFPrinting pathsPrinter driver, HP Designjet ePrint & Share, HP Embedded Web Server, HP Instant Printing, direct printing from USB flash drive, email printingDirversHP-GL/2, HP-RTL drivers for Windows*; HP PCL 3 GUI drive (included)for Mac OS X; PostScript Windows, Linux, and Mac drivers*DimensionsPrinter1399 x 916 x 1110 mm (55.1 x 36.1 x 43.7 in)WeightPrinterPrinter87 kg (191.8 lb)Shipping112.5 kg (247.5 lb)What's in the to software, power cordEnvironmentOperating temperature: 5 to 40°C (41 to 104°F) Sound power: 6.5 B(A) (printing); 39 dB(A) (ready); <16 dB(A) (sleep) Sound power: 6.5 B(A) (printing); 5.8 B(A) (ready); <1.9 B(A) (sleep)				
Memory Basic ePrinter: 32 GB (virtual) ⁶ PostScript ePrinter: 32 GB (virtual) ⁶ , 320 GB hard disk Connectivity' Interfaces Gigabit Ethernet (1000Base-T) (standard) Print languages Basic ePrinter: HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP (standard) PCL 3 GUI, URF PostScript® ePrinter: Adobe PostScript 3, Adobe PDF 1.7 Extension Level 3, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI, URF Printing paths Printer driver, HP Designjet ePrint & Share, HP Embedded Web Server, HP Instant Printing, direct printing from USB flash drive, email printing Drivers HP-GL/2, HP-RTL drivers for Windows, Linux, and Mac drivers® Dimensions Printer 1399 x 916 x 1110 mm (55.1 x 36.1 x 43.7 in) Kw x d x h) Shipping 1502 x 759 x 775 mm (59.1 x 29.9 x 30.5 in) Weight Printer 87 kg (191.8 lb) Shipping 112.5 kg (247.5 lb) What's in the box HP Designjet T920 ePrinter, printhead, ink cartridges, stacking tray, printer stand and media bin, spindle, quick reference guide, setup poster, startup software, power cord Corrating temperature: -5 to 40°C (41 to 104°F) Storage temperature: -25 to 55°C (-13 to 131°F) Operating temperature: -5 to 40°C (41 to 104°F) Storage temperature: -25 to 55°C (-13 to 131°F) Operating humidity: 20 to 80% RH				
PostScript ePrinter: 32 GB (virtual) ⁶ , 320 GB hard disk Connectivityi Interfaces (standard) Gigabit Ethernet (1000Base-T) (standard) Print languages (standard) Basic ePrinter: HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI, URF PostScript® ePrinter: Adobe PostScript 3, Adobe PDF 1.7 Extension Level 3, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI, URF Printing paths Printer driver, HP Designjet ePrint & Share, HP Embedded Web Server, HP Instant Printing, direct printing from USB flash drive, email printing Direves HP-GL/2, HP-RTL drivers for Windows®; HP PCL 3 GUI drive (included) for Mac OS X; PostScript Windows, Linux, and Mac drivers [®] Dimensions (w x d x h) Printer Shipping 1502 x 759 x 775 mm (59.1 x 29.9 x 30.5 in) Weight Printer Ark (g 191.8 lb) Shipping 112.5 kg (247.5 lb) What's in the box PD Designjet T920 ePrinter, printhead, ink cartridges, stacking tray, printer stand and media bin, spindle, quick reference guide, setup poster, startup software, power cord Environmen- tal ranges Operating temperature: -5 to 40°C (41 to 104°F) Storage temperature: -2 to 55°C (-13 to 131°F) Operating humidity: 20 to 80% RH Acoustic Sound pressure: 47 dB(A) (printing); 39 dB(A) (ready); <16 dB(A) (sleep)				
(standard) Print languages Basic ePrinter: HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP (standard) PCL 3 GUI, URF PostScript® ePrinter: Adobe PostScript 3, Adobe PDF 1.7. Extension Level 3, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI, URF Printing paths Printer driver, HP Designjet ePrint & Share, HP Embedded Web Server, HP Instant Printing, direct printing from USB flash drive, email printing Drivers HP-GL/2, HP-RTL drivers for Windows; HP PCL 3 GUI drive (included) for Mac OS X; PostScript Windows, Linux, and Mac drivers® Dimensions Printer Mipping 1502 x 759 x 775 mm (59.1 x 29.9 x 30.5 in) Weight Printer Printer 87 kg (191.8 lb) Shipping 112.5 kg (247.5 lb) What's in the HP Designjet T920 ePrinter, printhead, ink cartridges, stacking tray, printer stand and media bin, spindle, quick reference guide, setup poster, startup software, power cord Environmen- tal ranges Operating temperature: -25 to 55°C (-13 to 131°F) Operating humidity: 20 to 80% RH Sound power: 6.5 B(A) (printing); 5.8 B(A) (ready); <16 dB(A) (sleep)	Memory			
(standard) PCL 3 GUI, URF PostScript® ePrinter: Adobe PostScript 3, Adobe PDF 1.7 Extension Level 3, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI, URF Printing paths Printer driver, HP Designjet ePrint & Share, HP Embedded Web Server, HP Instant Printing, direct printing from USB flash drive, email printing Drivers HP-GL/2, HP-RTL drivers for Windows®; HP PCL 3 GUI drive (included) for Mac OS X; PostScript Windows, Linux, and Mac drivers® Dimensions Printer 1399 x 916 x 1110 mm (55.1 x 36.1 x 43.7 in) (w x d x h) Shipping 1502 x 759 x 775 mm (59.1 x 29.9 x 30.5 in) Weight Printer 87 kg (191.8 lb) Shipping 112.5 kg (247.5 lb) What's in the box HP Designjet T920 ePrinter, printhead, ink cartridges, stacking tray, printer stand and media bin, spindle, quick reference guide, setup poster, startup software, power cord Environmen- Operating temperature: -25 to 55°C (-13 to 131°F) Operating humidity: 20 to 80% RH Acoustic Sound pressure: 47 dB(A) (printing); 39 dB(A) (ready); <16 dB(A) (sleep)	Connectivity ⁷		Gigabit Ethernet (1000Base-T)	
Printing paths Printer driver, HP Designjet ePrint & Share, HP Embedded Web Server, HP Instant Printing, direct printing from USB flash drive, email printing Drivers HP-GL/2, HP-RTL drivers for Windows®; HP PCL 3 GUI drive (included) Dirivers HP-GL/2, HP-RTL drivers for Windows, Linux, and Mac drivers® Dimensions (w x d x h) Printer 1399 x 916 x 1110 mm (55.1 x 36.1 x 43.7 in) Weight Printer 87 kg (191.8 lb) Shipping 112.5 kg (247.5 lb) What's in the box HP Designjet T920 ePrinter, printhead, ink cartridges, stacking tray, printer stand and media bin, spindle, quick reference guide, setup poster, startup software, power cord Environmen- tal ranges Operating temperature: 5 to 40°C (41 to 104°F) Storage temperature: -25 to 55°C (-13 to 131°F) Operating humidity: 20 to 80% RH Acoustic Sound pressure: 47 dB(A) (printing); 39 dB(A) (ready); <16 dB(A) (sleep)			PCL 3 GUI, URF PostScript® ePrinter: Adobe PostScript 3, Adobe PDF 1.7 Extension Level 3, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4,	
(included) for Mac OS X; PostScript Windows, Linux, and Mac drivers [®] Dimensions (w x d x h) Printer 1399 x 916 x 1110 mm (55.1 x 36.1 x 43.7 in) Weight Printer 87 kg (191.8 lb) Shipping 112.5 kg (247.5 lb) What's in the box PD pesignjet T920 ePrinter, printhead, ink cartridges, stacking tray, printer stand and media bin, spindle, quick reference guide, setup poster, startup software, power cord Environmen- tal ranges Operating temperature: 5 to 40°C (41 to 104°F) Storage temperature: -25 to 55°C (-13 to 131°F) Operating humidity: 20 to 80% RH Acoustic Sound pressure: 47 dB(A) (printing); 39 dB(A) (ready); <16 dB(A) (sleep) Sound power: 6.5 B(A) (printing); 5.8 B(A) (ready); <1.9 B(A) (sleep) Consumption Safety USA and Canada (CSA certified), EU (LVD and EN60950-1 compliant), Russia (GOST), Singapore (PSB), China (CCC), Argentina (IRAM), Mexico (NYCE), Korea (KATS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICSS), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea (KCC)		Printing paths	Printer driver, HP Designjet ePrint & Share, HP Embedded Web Server, HP Instant Printing, direct printing from USB	
(w x d x h) Shipping 1502 x 759 x 775 mm (59.1 x 29.9 x 30.5 in) Weight Printer 87 kg (191.8 lb) Shipping 112.5 kg (247.5 lb) What's in the box HP Designjet T920 ePrinter, printhead, ink cartridges, stacking tray, printer stand and media bin, spindle, quick reference guide, setup poster, startup software, power cord Environmen- Operating temperature: 5 to 40°C (41 to 104°F) Storage temperature: -25 to 55°C (-13 to 131°F) Operating humidity: 20 to 80% RH Acoustic Sound pressure: 47 dB(A) (printing); 39 dB(A) (ready); <16 dB(A) (sleep)			HP-GL/2, HP-RTL drivers for Windows [®] ; HP PCL 3 GUI drive for Mac OS X; PostScript Windows, Linux, and Mac drivers [®]	
Weight Printer 87 kg (191.8 lb) Shipping 112.5 kg (247.5 lb) What's in the box HP Designjet T920 ePrinter, printhead, ink cartridges, stacking tray, printer stand and media bin, spindle, quick reference guide, setup poster, startup software, power cord Environmen- Derating temperature: 5 to 40°C (41 to 104°F) Storage temperature: 20 to 55°C (-13 to 131°F) Operating humidity: 20 to 80% RH Acoustic Sound pressure: 47 dB(A) (printing); 39 dB(A) (ready); <16 dB(A) (sleep)		Printer	1399 x 916 x 1110 mm (55.1 x 36.1 x 43.7 in)	
Shipping 112.5 kg (247.5 lb) What's in the box HP Designjet T920 ePrinter, printhead, ink cartridges, stacking tray, printer stand and media bin, spindle, quick reference guide, setup poster, startup software, power cord Environmen- tal ranges Operating temperature: 5 to 40°C (41 to 104°F) Storage temperature: -25 to 55°C (-13 to 131°F) Operating humidity: 20 to 80% RH Acoustic Sound pressure: 47 dB(A) (printing); 39 dB(A) (ready); <16 dB(A) (sleep)	(w x d x h)	Shipping	1502 x 759 x 775 mm (59.1 x 29.9 x 30.5 in)	
What's in the box HP Designjet T920 ePrinter, printhead, ink cartridges, stacking tray, printer stand and media bin, spindle, quick reference guide, setup poster, startup software, power cord Environmen- tal ranges Operating temperature: 5 to 40°C (41 to 104°F) Storage temperature: -25 to 55°C (-13 to 131°F) Operating humidity: 20 to 80% RH Acoustic Sound pressure: 47 dB(A) (printing); 39 dB(A) (ready); <16 dB(A) (sleep) Power consumption <120 watts (printing), <260 watts (maximum), <4 watts (<7 watts with em- bedded Digital Front End) (sleep), 0.1 watts (auto-off), 0 watts (off hardswitch) Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 4.2 A max (peak current) Certification Safety USA and Canada (CSA certified), EU (LVD and EN60950-1 compliant), Russia (GOST), Singapore (PSB), China (CCC), Argentina (IRAM), Mexico (NYCE), Korea (KATS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea (KCC) Environmental ENERGY STAR, WEEE, EU RoHS, China RoHS, REACH, EuP,	Weight	Printer	87 kg (191.8 lb)	
box stand and media bin, spindle, quick reference guide, setup poster, startup software, power cord Environmen- tal ranges Operating temperature: 5 to 40°C (41 to 104°F) Storage temperature: -25 to 55°C (-13 to 131°F) Operating humidity: 20 to 80% RH Acoustic Sound power: 6.5 B(A) (printing); 39 dB(A) (ready); <16 dB(A) (sleep)		Shipping	112.5 kg (247.5 lb)	
Environmental ranges Operating temperature: 5 to 40°C (41 to 104°F) Storage temperature: -25 to 55°C (-13 to 131°F) Operating humidity: 20 to 80% RH Acoustic Sound pressure: 47 dB(A) (printing); 39 dB(A) (ready); <16 dB(A) (sleep)		stand and media bin, spindle, quick reference guide, setup poster, startup		
tal ranges Storage temperature: -25 to 55°C (-13 to 131°F) Operating humidity: 20 to 80% RH Acoustic Sound pressure: 47 dB(A) (printing); 39 dB(A) (ready); <16 dB(A) (sleep) Sound power: 6.5 B(A) (printing); 5.8 B(A) (ready); <1.9 B(A) (sleep)	Environmen-			
Operating humidity: 20 to 80% RH Acoustic Sound pressure: 47 dB(A) (printing); 39 dB(A) (ready); <16 dB(A) (sleep)				
Acoustic Sound pressure: 47 dB(A) (printing); 39 dB(A) (ready); <16 dB(A) (sleep)				
Sound power: 6.5 B(A) (printing); 5.8 B(A) (ready); <1.9 B(A) (sleep)	Acoustic	Sound pressure: 47 dB(A) (printing); 39 dB(A) (ready); <16 dB(A) (sleep)		
Power < 120 watts (printing), < 260 watts (maximum), < 4 watts (< 7 watts with embedded Digital Front End) (sleep), 0.1 watts (auto-off), 0 watts (off hardswitch)				
consumption bedded Digital Front End) (sleep), 0.1 watts (auto-off), 0 watts (off hardswitch) Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 4.2 A max (peak current) Certification Safety USA and Canada (CSA certified), EU (LVD and EN60950-1 compliant), Russia (GOST), Singapore (PSB), China (CCC), Argentina (IRAM), Mexico (NYCE), Korea (KATS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea (KCC) Environmental ENERGY STAR, WEEE, EU RoHS, China RoHS, REACH, EuP,		< 120 watts (printing), < 260 watts (maximum), < 4 watts (< 7 watts with em-		
4.2 A max (peak current) Certification Safety USA and Canada (CSA certified), EU (LVD and EN60950-1 compliant), Russia (GOST), Singapore (PSB), China (CCC), Argentina (IRAM), Mexico (NYCE), Korea (KATS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea (KCC) Environmental ENERGY STAR, WEEE, EU RoHS, China ROHS, REACH, EuP,		bedded Digital Front End) (sleep), 0.1 watts (auto-off), 0 watts (off hardswitch)		
compliant), Russia (GOST), Singapore (PSB), China (CCC), Argentina (IRAM), Mexico (NYCE), Korea (KATS) Electromagnetic Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea (KCC) Environmental ENERGY STAR, WEEE, EU RoHS, China RoHS, REACH, EuP,				
rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea (KCC) Environmental ENERGY STAR, WEEE, EU RoHS, China RoHS, REACH, EuP,	Certification	Safety	compliant), Russia (GOST), Singapore (PSB), China (CCC),	
Environmental ENERGY STAR, WEEE, EU RoHS, China RoHS, REACH, EuP,		Electromagnetic	Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as	
		Environmental	ENERGY STAR, WEEE, EU RoHS, China RoHS, REACH, EuP,	

One-year limited hardware warranty Warranty

For more information, please visit hp.com/go/DesignjetT920

Ordering information

Product	CR354A	HP Designjet T920 36-in ePrinter
	CR355A	HP Designjet T920 36-in PostScript ePrinter
Accessories	CN538A	HP Designjet 3-in Core Adapter
	COE65A	HP Designjet T9x0/Tx500 36-in Spindle
	CQ654B/ CQ654C	HP Designjet HD Scanner
Original HP printhead	B3P06A	HP 727 Designjet Printhead
Original HP ink	B3P17A	HP 727 40-ml Photo Black Designjet Ink Cartridge
cartridges	B3P13A	HP 727 40-ml Cyan Designjet Ink Cartridge
	B3P14A	HP 727 40-ml Magenta Designjet Ink Cartridge
	B3P15A	HP 727 40-ml Yellow Designjet Ink Cartridge
	B3P18A	HP 727 40-ml Gray Designjet Ink Cartridge
	C1Q11A	HP 727 69-ml Matte Black Designjet Ink Cartridge
	B3P23A	HP 727 130-ml Photo Black Designjet Ink Cartridge
	B3P19A	HP 727 130-ml Cyan Designjet Ink Cartridge
	B3P20A	HP 727 130-ml Magenta Designjet Ink Cartridge
	B3P21A	HP 727 130-ml Yellow Designjet Ink Cartridge
	B3P24A	HP 727 130-ml Gray Designjet Ink Cartridge
	B3P22A	HP 727 130-ml Matte Black Designjet Ink Cartridge ⁹
	C1Q12A	HP 727 300-ml Matte Black Designjet Ink Cartridge
Original HP large format	C1861A	HP Bright White Inkjet Paper (FSC® certified) ¹⁰
printing materials	C6020B	HP Coated Paper (PEFC™ certified) ¹⁰ ⁶ ¹¹ 914 mm x 45.7 m (36 in x 150 ft)
	C6030C	HP Heavyweight Coated Paper (PEFC™ certified) ¹⁰ o ¹¹ 914 mm x 30.5 m (36 in x 100 ft)
	Q1421A	HP Universal Satin Photo Paper 🐉 1 914 mm x 30.5 m (36 in x 100 ft)
Service and	U7Y82E	HP 3 year Next Business Day Onsite Support ¹²
support	U7Y85E	HP 3 year Next Business Day Onsite Support with Defective Media Retention ¹³
	U7Y87E	HP 5 year Next Business Day with Defective Media Retention Hardware Support ¹³
	U7Y94E	HP 3 year 4-hour response, 9x5 Onsite Support ¹²
	U7Y97E	HP 3 year 4-hour response, 13x5 Onsite Support ¹²
	U7Z00PE	HP 1 year Post Warranty, Next Business Day Onsite Support ¹²
	U7Z01PE	HP 1 year Post Warranty, Next Business Day Defective Media Retention Hardware Support ¹³
	U7Z05PE	HP 1 year Post Warranty, 4-hour response, 13x5 Onsite Support ¹¹
	H4518E	HP Network Installation Service
	HC132PE	HP 1 year Post Warranty Phone Assistance

HP Designjet Support Services offer solutions for business critical environments installation, extended support and maintenance, as well as variety of value added services

For more information, please visit hp.com/go/designjet/support.

Use Original HP inks and printheads to experience consistent high quality and reliable performance that enable less downtime. These critical components are designed and engineered together as an optimized printing system to provide precise line accuracy as well as dark blacks and true neutral grays For more information, visit hp.com/go/OriginalHPinks.

For the entire HP Large Format Printing Materials portfolio, please see globalBMG.com/hp.

Mechanical printing time. Printed in Fast mode on, using HP Bright White Inkjet Paper (Bond) and Original HP inks.

+/-0.1% of the specified vector length or +/-0.2 mm (whichever greater) at 23°C (73°F), 50-60% relative humidity, on A0/E printing material in Best or Normal mode with HP Matte Film and Original HP inks. Measured on HP Matte Film.

Based on 1.5 GB RAM.

Includes an embedded Jetdirect print server.

- Included with PostScript printers only. Available only in Europe, Middle East, and Africa.
- SSC[®] trademark license code FSC[®]-C017543, see fsc.org. PEFC[™] trademark license code PEFC[™]/29-31-198, see <u>pefc.org</u>. Not all FSC[®]- or PEFC[™]-certified products are available in all regions. 10
- Can be recycled through commonly available recycling programs.
- 12 Not available in North America and Latin America.
- 13 Not available in Europe, Middle East, and Africa.
- 14 Applicable to HP Designjet T-series Printers, ePrinters, and eMFPs. True neutral grays produced by printers compatible with the HP Three-black ink set.



© Copyright 2013-2014 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Adobe and Adobe PostScript 3 are trademarks of Adobe Systems Incorporated. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. Windows is a U.S. registered trademark of Microsoft Corporation. PANTONE is the property of Pantone, Inc. Mac and the Mac logo are trademarks of Apple Computer, Inc., registered in the U.S. and other countries.



4AA4-5693EEW, February 2014, Rev. 5