



Overview

Lead time	Usually Ships within 2 Weeks
-----------	------------------------------

General

Provided equipment	Installation guide User Manual
--------------------	-----------------------------------

Physical

Depth	36.42 in (92.5 cm)
Height	59.02 in (149.9 cm)
Net Weight	1710.79 lb(US) (776 kg)
Width	20.59 in (52.3 cm)

Input

Input Frequency	50/60 Hz
Nominal Input Voltage	3 phase 400 V 3 phases

Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Ambient air temperature for storage	32...86 °F (0...30 °C)

Batteries & Runtime

Battery Placement	External Frame
Battery Slots Empty	0
Included Battery Modules	6
Device mounting	Enclosed battery cabinet
Battery type	Lead-Acid battery

Ordering and shipping details

Package weight(Lbs)	1779.13 lb(US) (807 kg)
---------------------	-------------------------

Packing Units

Package 1 Height	64.69 in (164.3 cm)
Package 1 width	25.59 in (65 cm)
Package 1 Length	41.81 in (106.2 cm)

Offer Sustainability

EU RoHS Directive

Pro-active compliance (Product out of EU RoHS legal scope)  [EU RoHS Declaration](#)

Contractual warranty

Warranty

1 year repair or replace