

# Epson EB-1965



## DATASHEET



An ideal device for corporate or educational use, the EB-1965 is a great combination of quality output and features at an affordable price.

### Convenient use

The Epson EB-1965 combines high-quality output, value-added features and affordability, into a compact and portable projector. It is perfect for corporate or educational use, as it can be easily installed in meeting rooms or used portably from a desktop.

### High quality picture

Utilising Epson's 3LCD technology to ensure clearly projected images, the EB-1965 produces vivid, natural colours and an equally high White and Colour Light Output, even in daylight.

### Connectivity

The EB-1965 boasts Wi-Fi connectivity and a DisplayPort connector, allowing you to show high definition audio and video content with ease.

### Easy calibration

New to Epson is the convenient 'focus help' feature, which calibrates using a test pattern to allow any meeting room set up to be catered for quickly and easily. This process is made even easier with a wide controller manufacturer compatibility, so the EB-1965 can integrate into an existing system with ease. Also new to Epson is real time auto vertical and horizontal keystone correction, adjusting images in real time, with visible results in seconds. When used with the screen fit function, which corrects images to any framed screen within seconds, calibration of the EB-1965 is quick and simple.

### Enhanced productivity

Productivity can be greatly increased with a range of features available with the EB-1965, with the Multi-PC feature allowing content from up to four computers to be shown.

## KEY FEATURES

- **Ultra bright output**  
5,000 lumens White/Colour Light Output
- **Picture quality**  
3LCD technology for vivid colours
- **Clock / Schedule**  
Program projector actions in advance
- **Focus help**  
Easy to use focus pattern
- **PC free/Slide show**  
Read PDFs directly from a USB stick



**EPSON**<sup>®</sup>  
EXCEED YOUR VISION

## PRODUCT SPECIFICATIONS

|                          |  |
|--------------------------|--|
| <b>TECHNOLOGY</b>        |  |
| Projection System        | 3LCD Technology, RGB liquid crystal shutter  |
| LCD Panel                | 0,63 inch with MLA (D7)  |
| <b>IMAGE</b>             |  |
| Colour Light Output      | 5.000 lumen-3.470 lumen (economy)  |
| White Light Output       | 5.000 lumen - 3.470 lumen (economy)  |
| Resolution               | XGA, 1024 x 768, 4:3   |
| Contrast Ratio           | 3.000 : 1  |
| Lamp                     | 245 W, 2.500 h durability, 4.000 h durability (economy mode)   |
| Keystone Correction      | Auto vertical: $\pm 30^\circ$ , Auto horizontal $\pm 20^\circ$   |
| <b>OPTICAL</b>           |  |
| Projection Ratio         | 1,38 - 2,24:1  |
| Zoom                     | Manual, Factor: 1 - 1,6  |
| Projection Size          | 30 inches - 300 inches   |
| Projection Distance Wide | 0,8 m - 8,4 m (60 inch screen)   |
| Projection Distance Tele | 1,4 m - 13,9 m (60 inch screen)  |
| Projection Lens F Number | 1,51 - 1,99  |
| Focal Distance           | 18 mm - 29 mm  |
| Focus                    | Manual   |
| Offset                   | 8,6 : 1  |
| <b>CONNECTIVITY</b>      |  |
| USB Display Function     | 3 in 1: Image / Mouse / Sound  |
| Interfaces               | USB 2.0 Type B, USB 2.0 Type A, HDMI in, RGB in (2x), RGB out, Stereo mini jack audio out, Stereo mini jack audio in (2x), RS-232C, WLAN, VGA in (2x), VGA out, Composite in, Display Port, Ethernet interface (100 Base-TX / 10 Base-T), Gigabit ethernet interface |
| <b>ADVANCED FEATURES</b> |  |
| Security                 | Kensington lock, Security bar, Control panel lock, Password lock   |
| Features                 | AV Mute Slide, Automatic input selection, Automatic keystone correction, Direct Power on/off, Document Camera Compatible, Screen Fit, Instant on/off, JPEG Viewer, PC Free, Quick Corner, Slide show, Split-Screen-Function  |
| Video Colour Modes       | Blackboard, Dynamic, Photo, Presentation, sRGB, Theatre, Whiteboard, DICOM SIM   |
| <b>GENERAL</b>           |  |
| Energy Use               | 337 W, 250 W (economy), 0,44 W (standby)   |
| Product dimensions       | 377 x 271 x 108 mm (Width x Depth x Height)  |
| Product weight           | 3,9 kg   |
| <b>OTHER</b>             |  |
| Warranty                 | 36 months Carry in or 8.000 h, Lamp: 12 months or 1.000 h<br>Optional warranty extension available   |

## LOGISTICS INFORMATION

|                          |                    |
|--------------------------|--------------------|
| SKU                      | V11H470040         |
| EAN code                 | 8715946512471      |
| Dimensions Single Carton | 517 x 342 x 196 mm |
| Carton Weight            | 5,69 Kg            |
| Multiple Order Quantity  | 1 Units            |
| Country of Origin        | China              |
| Pallet Size Euro         | 40 Units (4 x 10)  |



Epson Europe B.V. (Holland) Filial Sverige  
Produktinformation: 0771-400135  
Support: 0771-400134  
Fax Support: 0771-400136  
level.one@epson.se  
www.epson.se

Finlandsgatan 10  
164 74 Kista  
Öppettider Support: 09.00 – 17.00

Varumärken och registrerade varumärken tillhör Seiko Epson Corporation eller Epsons respektive ägare.  
Produktinformation kan ändras utan förvarning.

## Epson EB-1965

### WHAT'S IN THE BOX

- Computer cable
- Power cable
- Remote control incl. batteries
- Software (CD)
- User manual
- User manual (CD)
- Wireless LAN unit

### OPTIONAL ACCESSORIES

- Air Filter - ELPAF41 - New EB-19 Series  
V13H134A41
- Lamp - ELPLP75 - EB-196x/195x/194xW  
V13H010L75
- Adapter - ELPAP07 Wireless LAN b/g/n  
V12H418P13
- Soft Carry Case - ELPKS65 - New EB-19xx  
V12H001K65
- Quick Wireless Connect USB key - ELPAP09  
V12H005M09
- Ceiling Mount - ELPMB23 - White  
V12H003B23
- Ceiling pipe - ELPPFP13 - 668-918mm  
V12H003P13
- Ceiling pipe - ELPPFP14 - 918-1168mm  
V12H003P14