

APC SERVICE BYPASS PDU, 230V 16AMP Hardwire

SBP3000RMHW

Call for More Information 13 73 28



- Includes: Rack mounting brackets, User manual

Output	
Nominal Output Voltage	230V
Efficiency at Full Load	99 % %
Overload Protection	Yes
Cord Length	1meters
Maximum Total Current Draw	16
Output Connections	(1) IEC Jumpers (1) Hard wire 3-wire (H N + E)

Input	
Nominal Input Voltage	230V
Input frequency	50/60 Hz
Acceptable Input Voltage	220 - 240VAC
Efficiency at Full Load	99 % %
Load Power Factor Range	0 to 1
Load Capacity	3000VA
Maximum Input Current	16A
Maximum Line Current	16A

Physical	
Maximum Height	89MM, 8.9CM
Maximum Width	432MM, 43.2CM
Maximum Depth	76MM, 7.6CM

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Physical	
Rack Height	2U
Net Weight	2.27KG
Shipping weight	3.45KG
Shipping Height	151MM, 15.1CM
Shipping Width	463MM, 46.3CM
Shipping Depth	295MM, 29.5CM
Color	Black
Units per Pallet	56.0

Environmental	
Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0 - 4572meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0 - 15240meters

Conformance	
Approvals	VDE
Standard warranty	2 years repair or replace

Sustainable Offer Status	
RoHS	Compliant

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.