



Release your inner Savage.

Attack the competition with HyperX® Savage memory. Its unique, asymmetrical red heat spreader is made from high-quality aluminum and has a black PCB and a diamond cut finish to make your game shine and help you stand out in the crowd. The heat spreader dissipates heat so your system stays cool and reliable and its low profile fits under oversized CPU coolers.

Featuring a design that works well with the latest trends in gaming, HyperX Savage comes in a wide range of high-performance speeds, from 1600MHz to 2400MHz, and capacities from 4GB to 8GB in single modules and 8GB to 32GB kits. In CL9–CL11 latencies, it delivers ultra-responsive multitasking and an overall faster system. Dual and quad channel kits are available.

Built-in, hand-tuned XMP profiles let users reach higher-performing frequencies, timings and voltages simply by enabling Intel's XMP tool. Even noobs can overclock their platforms with no need for manual adjustments in BIOS.

HyperX Savage is backed by a lifetime warranty and free technical support.

- > Eye-catching color and asymmetrical design
- > Speeds up to 2400MHz and capacities up to 32GB
- > Low profile heat spreader
- > Intel XMP Ready

HyperX Savage



Ideal for:

- Workstations and high-performance gaming systems
- Gaming while streaming and overall ultra-responsive multitasking
- Reduced workload times

Features/specs on reverse >>

CONTENT CREATOR
ENTHUSIAST
HYPERX
OVERCLOCKING
FAST
OVERCLOCKING
FAST
LOW VOLTAGE
UPGRADE
HIGH PERFORMANCE
UPGRADE

HyperX Savage

FEATURES/BENEFITS

- > **Fast** — top-performing modules available with low-profile heat spreader
- > **Unique** — red, asymmetrical heat spreader sets new trends for PC builds
- > **Quality** — aluminum die-cast heat spreader with a diamond cut finish
- > **Design** — low profile to fit under oversized CPU coolers
- > **Reliable** — 100-percent factory tested
- > **Guaranteed** — lifetime warranty, free technical support

SPECIFICATIONS

- > **Capacity** 4GB–8GB (single), 8GB–32GB (kits)
- > **Frequency Speed** 1600MHz, 1866MHz, 2133MHz and 2400MHz
- > **CAS Latency** CL9-CL11
- > **Voltage** 1.5V, 1.65V
- > **Operating Temperature** 0°C to 85°C
- > **Storage Temperature** -55°C to 100°C
- > **Dimensions** 133.35mm x 32.8mm
- > **Compatible** with H67, H97, P67, Z68, Z77, Z87, Z97 and H61 Intel chipsets, as well as A75, A87, A88, A89, A78 and E35 AMD chipsets



HYPERX PART NUMBERS

HX316C9SR/4
HX316C9SR/8
HX316C9SRK2/16
HX316C9SRK2/8
HX316C9SRK4/32
HX318C9SR/4
HX318C9SR/8
HX318C9SRK2/16
HX318C9SRK2/8
HX318C9SRK4/32
HX321C11SR/4
HX321C11SR/8
HX321C11SRK2/16
HX321C11SRK2/8
HX321C11SRK4/32
HX324C11SR/4
HX324C11SR/8
HX324C11SRK2/16
HX324C11SRK2/8
HX324C11SRK4/32

HYPERX[®]



HyperX is a division of Kingston.

THIS DOCUMENT SUBJECT TO CHANGE WITHOUT NOTICE.

©2014 Kingston Technology Corporation. 17600 Newhope Street, Fountain Valley, CA 92708 USA. All rights reserved. All trademarks and registered trademarks are the property of their respective owners. MKD-298US