

2m (6 ft) Certified SuperSpeed USB 3.0 (5Gbps) A to B Cable - M/M

Product ID: USB3CAB2M



The USB3CAB2M 2-meter USB 3.2 Gen 1 A-to-B cable provides a high quality connection between peripheral devices that feature a USB 3.2 Gen 1 type-B port, such as hard drive enclosures, card readers, docking stations and video capture devices and a USB-capable computer.

This cable is USB-IF certified to USB 3.2 Gen 1 specifications, guaranteeing a dependable, long-lasting connection to your USB 'B' devices and is backed by StarTech.com's Lifetime Warranty.

Certifications, Reports and Compatibility



Applications

• Connect a SuperSpeed USB 3.0 Type B peripheral (hard drive enclosure, card reader, docking station, video capture device, etc.) to a USB 3.0 capable desktop, laptop, or server

Features

- 1x USB 'A' male connector
- 1x USB 'B' male connector
- USB-IF Certified SuperSpeed USB 3.2 Gen1
- Data transfer rates up to 5Gbps





- Aluminum-Mylar Foil with Braided Shielding
- Molded connectors with strain relief
- Backward compatible with USB 2.0

Hardware		
	Warranty	Lifetime
	Connector Plating	Nickel
	Cable Jacket Material	PVC - Polyvinyl Chloride
	Cable Shield Material	Aluminum-Mylar Foil with Braid
Performance	Tupo and Poto	USB 3.0 - 5 Gbit/s
	Type and Rate	056 3.0 - 5 GDI/S
Connector(s)		
	Connector A	1 - USB Type-A (9 pin, 5 Gbps)
	Connector B	1 - USB 3.2 Type-B (9 pin, Gen 1, 5Gbps)
Environmental		
	Operating Temperature	-20C to 80C (-4F to 176F)
	Storage Temperature	-20C to 80C (-4F to 176F)
Physical Characteristics		
	Color	Black
	Connector Style	Straight
	Wire Gauge	24/28 AWG
	Cable Length	6.6 ft [2 m]
	Product Length	6.6 ft [2 m]
	Weight of Product	3.2 oz [90 g]
Packaging Information		
	Package Quantity	1



What's in the Box	Included in Package	1 - 2m USB 3.0 Certified A to B Cable - M/M
	Shipping (Package) Weight	3.5 oz [99 g]
	Package Height	0.6 in [16 mm]
	Package Width	7.9 in [20 cm]
	Package Length	8.7 in [22 cm]

*Product appearance and specifications are subject to change without notice.

