


BACK IN THE AIR, FASTER!



## Compact Pressurization System



FUEL FREE VERIFICATION | LEAK CHECK

# Compact Pressurization System (CPS)

The safest, most efficient method to complete fuel leak checks.

## Benefits

- Expedite fuel leak detection/repair
- Eliminates the need for intermediate soak checks
- Redundant protection against over-pressurization
- User friendly touch screen

## Applications

- Fuel Tank Repair Verification
- Bladder Repair Verification

## Technical Specifications

<b>Control Panel:</b>	
Dimensions:	21" x 17" x 8" (530 x 430 x 200mm)
Weight:	40 lbs (18 kg)
Accessory Cases:	Vary
Power source:	110/220 VAC, 50/60Hz
Accessory Cases:	Vary
<b>Operating Conditions:</b>	
Gas:	Helium, Industrial Grade
Helium pressure:	30 – 120 psi (2 to 8.5 bar)
Air pressure supply:	30 – 120 psi (2 to 8.5 bar)
Max. filling volume:	2300 gal (8700 l.)
Operating Temperature:	32° to 104° F (-0 to 40° C)
Storage:	0° to 122° F (-17 to 50° C)
Humidity:	0 - 90% relative w/o condensation
Pressure decay sensitivity:	0.01 psi (0.7 mbar)
Included accessories:	Hoses, one set of aircraft specific adapters

## Ordering Information

**Compact Pressurization Unit**

PN: TPS 800

### AEROWING

5217 Linbar Dr., Ste 303

Nashville, TN 37211

Tel: +1 (855) 325-3835

[aerowing.com](http://aerowing.com)

[support@aerowing.com](mailto:support@aerowing.com)