

HP Advanced Wireless Docking Station



Simple and secure wireless docking solution.

Expand your HP Elite x2 workspace with the HP Advanced Wireless Docking Station, which enables seamless connectivity through WiGig technology.¹

Clutter-free professional desktop

Enable flexible positioning and keep your workspace tidy with the elegant, cubic wireless design.

Instant desktop productivity

After a one-time onscreen set up through your HP Elite x2 1011 G1 or HP Elite x2 1012 G1 (Intel 18260 WLAN, sold separately, required), your connected devices are ready to go as soon as your tablet is in range.

Complete connectivity

Create a comprehensive, professional desktop solution and connect your tablet to dual displays, a wired network, and your everyday devices with DisplayPort, VGA, RJ-45, USB, and audio ports.

Enterprise-class security

Help keep your content safe during device pairing and data transfer with WiGig technology. Secure your dock to a table or other device with the integrated lock slot and a cable lock (sold separately).

Peace of mind

Get a one-year whole unit replacement limited warranty

1. Compatible with the HP Elite x2 1011 G1 with an optional installed Intel Tri Band Wireless AC with WiGig Combo card or HP Elite x2 1012 G1 with optional installed Intel 18260 WLAN card. Tablet must be positioned within 1.2 m (4 ft) and without obstruction in the line of sight of the wireless dock.

Specifications

HP Advanced Wireless Docking Station



Part number	F7M97AA
Unpackaged Dimensions (W x D x H)	3.35 x 3.35 x 3.43 in (8.5 x 8.5 x 8.7 cm)
Weight	0.92 lb (0.42 kg)
Stand-alone power requirements	
Normal Operating Voltage	18.5 V
Average Operating Power	18.5 W
Max Operating Power	< 45 W
Temperature	
Operating	32° to 95° F (0° to 35° C) (not writing optical)
Non-operating	4° to 140° F (-20° to 60° C)
Relative humidity	
Operating	10% to 90%, non-condensing
Non-operating	5% to 95%, 101.6° F (38.7° C) maximum wet bulb temperature
Altitude (unpressurized)	
Operating	-50 to 10,000 ft (-15.24 to 3,048 m)
Non-operating	-50 to 40,000 ft (-15.24 to 12,192 m)
Shock	
Operating	40 G, 2 ms, half-sine
Non-operating	240 G, 2 ms, half-sine
Random vibration	
Operating	0.251-1.043 g
Non-operating	3.50 g
Option kit contents	HP Wireless Dock, AC power adapter, documentation
Compatibility	HP Elite x2 1011 G1 with an optional installed Intel Tri Band Wireless AC with WiGig Combo card or HP Elite x2 1012 G1 with optional installed Intel 18260 WLAN card

Sign up for updates
hp.com/go/getupdated



Share with colleagues



Rate this document

