

# USB-C to HDMI Adapter Cable - 1m (3 ft.) - 4K at 30 Hz

Product ID: CDP2HDMM1MB



This USB- $C^{\text{TM}}$  to HDMI® adapter cable offers a convenient solution for directly connecting your DisplayPort over USB Type- $C^{\text{TM}}$  device to your HDMI monitor, television or projector. The adapter supports a connection distance of up to 1 m (3 ft.) and works with USB-C devices that support DP alt mode, such as the MacBook, ChromeBook Pixel<sup>TM</sup> and Dell<sup>TM</sup> XPS<sup>TM</sup> models 15 and 13. It's also compatible with Thunderbolt<sup>TM</sup> 3 ports.

### **Clutter-free installation**

At 1 m (3 ft.) in length, this adapter cable delivers a direct connection that eliminates excess adapters and cabling, ensuring a tidy, professional installation. For longer installations, we also offer a 2 m (6 ft.) USB-C to HDMI cable, enabling you to choose the right cable length for your custom installation needs.





### Hassle-free connection with USB Type-C

The adapter cable is easy to connect, through the versatility and convenience of the USB Type-C port on your device. USB-C is a reversible connector, so it doesn't matter which way you plug it in, the adapter will always connect. This saves you the frustration of trying to insert it correctly when you're docking your computer to your workstation or office hot desk.

### **Astonishing picture quality**

At four times the resolution of high-definition 1080p, you'll be amazed at the picture quality of a 4K monitor or television. This adapter cable lets you harness the video capabilities that are built into your USB Type-C connection to deliver the astonishing quality of Ultra HD to your 4K display.

The adapter is backward compatible with 1080p displays, ensuring the adapter will also work for HD applications at your home or office.

The CDP2HDMM1MB is backed by a 3-year StarTech.com warranty and free lifetime technical support.

Note:

Your USB-C equipped device must support video (DP alt mode) to work with this adapter.



### **Data Sheet**

# Certifications, Reports and Compatibility











### **Applications**

- Connect a USB Type-C computer to an HDMI projector or display in your classroom, auditorium or boardroom
- Install at your home workstation or office hot desk to make your USB-C computer compatible with your HDMI display

#### **Features**

- Reduce clutter with a compact 1 m (3 ft.) adapter cable
- Hassle-free connection with the reversible USB-C connector
- Astonishing video quality with support for video resolutions up to 4K at 30 Hz
- Plug-and-play installation
- No power adapter required
- Thunderbolt 3 port compatible



## **Data Sheet**

|                                 | Warranty                      | 3 Years  |
|---------------------------------|-------------------------------|--|
| Hardware                        | Adapter Style                 | Cable Adapters   |
|                                 | AV Input                      | USB Type-C   |
|                                 | AV Output                     | HDMI   |
|                                 | Chipset ID                    | Parade - PS171<br>NXP - PTN5100  |
|                                 | Ports                         | 1  |
| Performance                     | Audio Specifications          | 7.1 surround sound   |
|                                 | Maximum Analog Resolutions    | 1920x1200 or 1080p   |
|                                 | Maximum Digital Resolutions   | 3840x2160 @ 30 Hz  |
|                                 | Supported Resolutions         | 1024x768<br>1280x720 (High-definition 720p)<br>1920x1080 (High-definition 1080p)<br>1920x1200<br>2560x1440<br>2560x1600<br>3840x2160 (Ultra HD 4K) |
|                                 | Video Revision                | HDMI 1.4   |
|                                 | Wide Screen Supported         | Yes  |
| Connector(s)                    | Connector A                   | 1 - USB-C (24 pin) DisplayPort Alt Mode Male Input   |
|                                 | Connector B                   | 1 - HDMI (19 pin) Male Output  |
| Special Notes /<br>Requirements | Note                          | Your USB-C equipped device must support video (DP Alt Mode) to work with this adapter.   |
|                                 | System and Cable Requirements | Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter.  |
| Environmental                   | Humidity                      | 5%-90% RH (no condensation)  |
|                                 | Operating Temperature         | 0°C to 45°C (32°F to 113°F)  |
|                                 | Storage Temperature           | -10°C to 70°C (14°F to 158°F)  |
| Physical<br>Characteristics     | Accent Color                  | Black  |
|                                 | Cable Length                  | 3.3 ft [1 m]   |
|                                 | Color                         | Black  |
|                                 | Product Height                | 0.6 in [14 mm]   |
|                                 | Product Length                | 39.4 in [1000 mm]  |
|                                 | Product Weight                | 2.8 oz [79 g]  |
|                                 |                               |  |



## **Data Sheet**

|                          | Product Width             | 0.9 in [22 mm]                  |
|--------------------------|---------------------------|---------------------------------|
| Packaging<br>Information | Shipping (Package) Weight | 3 oz [84 g]                     |
| What's in the Box        | Included in Package       | 1 - USB-C to HDMI adapter cable |

Product appearance and specifications are subject to change without notice.