

Fujitsu recommends Windows 10 Pro.

Data Sheet

FUJITSU Desktop ESPRIMO Q958

Mini PC with excellent performance and integration capabilities

The FUJITSU ESPRIMO Q958 mini PC provides excellent performance, high energy efficiency and manageability. The 8th Gen Intel® Core™ processor and Intel® vPro™ technology combined with the DeskView manageability suite support professional computing and advanced manageability. With its innovative Low Power Active Mode feature and highly-efficient integrated power supply, this powerful mini PC ensures instant communication capabilities in your office while significantly reducing power bills. The optional Palm vein authentication combined with PalmSecure™ technology provides unrivaled security. With its halogen-free printed circuit board of mainboard and optional PVC-free power cord, it is an example of the Fujitsu commitment to environmental protection and sustainability. Experience a cleaner, quieter workplace with Zero Noise PC function and the small footprint of the FUJITSU ESPRIMO Q958.



An elegant mini PC for standard office applications

Eye-catching exclusive modern design

- Fully equipped PC with a volume of ~2.0 liters - based on standard desktop technology

Zero Noise PC

Pleasant working environment due to completely quiet system (solid state disk required)

- Fan stop in standard operations

Superb usability

Efficient working environment due to a tidy desk with easy access to front connectors

- Horizontal or vertical operations and an integrated VESA mount, easy upgrade of major components

Feature-rich, energy-efficient mini PC based on green technology

Be ready for instant communication and a significantly reduced energy bill

- Innovative Low Power Active Mode and energy-efficient integrated power supply
- Halogen-free printed circuit board of mainboard, optional PVC-free power cord

State-of-the-art security features

Keep your most valuable assets safe - your data

- Workplace Protect (secure authentication solution), Trusted Platform Module (TPM) 2.0, optional palm vein sensor for PalmSecure™ technology, SmartCard reader, EraseDisk



Components

Processor	<p>Intel® Core™ i7-8700T processor (6 Cores / 12 Threads, 2.40 GHz, up to 4.0 GHz, 12 MB, Intel® UHD Graphics 630) *</p> <p>Intel® Core™ i5-8500T processor (6 Cores / 6 Threads, 2.10 GHz, up to 3.5 GHz, 9 MB, Intel® UHD Graphics 630) *</p> <p>Intel® Core™ i3-8100T processor (4 Cores / 4 Threads, 3.10 GHz, 6 MB, Intel® UHD Graphics 630)</p> <p>Intel® Core™ i3-8100 processor (4 Cores / 4 Threads, 3.60 GHz, 6 MB, Intel® UHD Graphics 630)</p> <p>Intel® Pentium® Gold G5400 processor (2 Cores / 4 Threads, 3.70 GHz, 4 MB, Intel® UHD Graphics 610)</p> <p>Intel® vPro™ Logo with Intel® Core i5 and Core i7 processors *with Intel® Turbo Boost Technology (clock speed and performance will vary depending on workload and other variables)</p>
Operating systems	
Operating system pre-installed	Windows 10 Pro. Fujitsu recommends Windows 10 Pro. Windows 10 Home
Operating system notes	<p>Certified for SUSE Enterprise Desktop (pending)</p> <p>Windows 10 Support: After the end of the product life FUJITSU will continue to test and support all upcoming Windows 10 releases for a period of maximum 5 years – depending on the available extension of hardware services through FUJITSU Warranty top ups. For details please see “FUJITSU Service Statement for Windows 10 Semi-Annual-Channel Support” at http://support.ts.fujitsu.com.</p>
Memory modules	<p>4 GB (1 module(s) 4 GB) DDR4, non-ECC, 2,666 MHz, SO DIMM</p> <p>8 GB (1 module(s) 8 GB) DDR4, non-ECC, 2,666 MHz, SO DIMM</p> <p>16 GB (1 module(s) 16 GB) DDR4, non-ECC, 2,666 MHz, SO DIMM</p>
Hard disk drives (internal)	<p>SSD PCIe, 1024 GB M.2 NVMe Highend module</p> <p>SSD PCIe, 512 GB M.2 NVMe Highend module</p> <p>SSD PCIe, 256 GB M.2 NVMe Highend module</p> <p>SSD PCIe, 1024 GB M.2 NVMe module</p> <p>SSD PCIe, 512 GB M.2 NVMe module</p> <p>SSD PCIe, 256 GB M.2 NVMe module</p> <p>SSD PCIe, 1024 GB M.2 NVMe module, SED</p> <p>SSD PCIe, 512 GB M.2 NVMe module, SED</p> <p>SSD PCIe, 256 GB M.2 NVMe module, SED</p> <p>SSD SATA III, 1024 GB, 2.5-inch</p> <p>SSD SATA III, 512 GB, 2.5-inch</p> <p>SSD SATA III, 256 GB, 2.5-inch</p> <p>SSD SATA III, 128 GB, 2.5-inch</p> <p>HDD SATA III, 7,200 rpm, 500 GB, 2.5-inch</p> <p>HDD SATA II, 5,400 rpm, 1,000 GB, 2.5-inch*</p> <p>HDD SATA III, 5,400 rpm, 500 GB, 2.5-inch</p> <p>Intel Optane Memory (16 GB)</p>
Hard disk notes	<p>SSD (Solid State Disk)</p> <p>SED (Self-Encrypting Drive)</p>
Graphics	DP to DVI-D (single link) Adapter Cable
Drives (optional)	<p>BD Triple Writer SATA ultra slim (tray)</p> <p>DVD Super Multi ultra slim (tray)</p>
Interface add on cards/components (optional)	<p>Serial Port</p> <p>M.2 WLAN 802.11ac (2x2) and BT 5 (dedicated regions only)</p>

Base unit

Base unit	ESPRIMO Q958
Mainboard	
Mainboard type	D3613
Formfactor	proprietary
Chipset	Intel® Q370
Processor socket	LGA 1151
Processor quantity maximum	1
Supported capacity RAM (max.)	32 GB
Memory slots	2 DIMM (DDR4)
Memory frequency	2,666 MHz
Memory notes	Dual channel support For dual channel performance, 2 memory modules have to be ordered. Capacity per channel has to be the same. 2666 MHz may be clocked down to 2400 or 2133 depending on used processor
LAN	10/100/1,000 MBit/s Intel® I219LM
Integrated WLAN	1 (optional with Bluetooth together)
BIOS version	AMI Aptio V UEFI Specification 2.6
BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI) Support for Compatibility Support Module (CSM) is no longer possible on systems with 8th Generation Intel® Core™ i technology
Audio type	On board
Audio codec	Realtek ALC671
Audio features	Internal speaker supports audio playback (optional), High Definition audio
I/O controller on board	
Serial ATA total	2
thereof SATA III	2
Controller functions	Serial ATA III (6 Gbit) NCQ AHCI
Interfaces	
Audio: line-out	1
Front audio: microphone	1
Front audio: headphone	1
USB 2.0 total	2
USB 3.1 Gen1 (USB 3.0) total	2
USB 3.1 Gen2 total	5
USB front	2x USB 3.1 (Gen2); 1x USB 3.1 Type-C (Gen2)
USB rear	2x USB 2.0; 2x USB 3.1 (Gen1); 2x USB 3.1 (Gen2)
VGA	optional: via external active adapter cable
DisplayPort	2
DVI	1 (DVI-D)
Serial (RS-232)	optional: serial port (9pin, 16 byte FIFO, 16550 compatible)
Mouse / Keyboard (PS/2)	0/1 optional (with PC on/off function on Pin6)
Ethernet (RJ-45)	1
Interface Module notes	Anytime USB charge functionality, USB Typ C connector supports up to 15W

Input device / components

Input devices (optional)	Keyboard Mouse KBPC PX ECO Mouse M440 ECO
--------------------------	--

Drive bays

Drive bays total	3
2.5-inch internal bays	1
5.25-inch external bays	1
M.2-2280	1 x on mainboard for SSD NVMe (PCIe 3.0 x4; up to 32Gbit/s; supports Intel® Optane™ technology)

Mini PCI slots

M.2-2230	on mainboard for WLAN module
----------	------------------------------

Graphics on board

Graphics brand name	Intel® UHD Graphics 610, Intel® UHD Graphics 630
---------------------	--

Shared video memory	Up to half size of total system memory
---------------------	--

TFT resolution (DVI)	1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel
----------------------	---

TFT resolution (DisplayPort)	1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel 2,560 x 1,440 pixel 2,560 x 1,600 pixel 3,440 x 1,440 pixel 3,840 x 2,160 pixel 4,096 x 2,304 pixel
------------------------------	--

Graphics features	Support for up to three independent displays DirectX® 12 HDCP support OpenCL™ 2.0 (requires Intel® Core™ i3, i5 or i7 processors) OpenGL® 4.4 DisplayPort interface supports Ver. 1.2 incl. Multi-Stream DVI-D interface supports audio output if connected to the HDMI interface of a display via suitable adapter cables (not included)
-------------------	---

Graphics notes	up to 1 GB dedicated video memory (main memory owned and locked for graphics use) Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size and operating system Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz
----------------	--

Electrical values

Power efficiency note	power supply efficiency (at 230V; 2 Watt/ 10% / 20% / 50% / 100% load) : > 85%/ 90% / 90% / 92% / 92%
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Operating voltage range	90 V - 264 V
Operating line frequency range	47 Hz - 63 Hz
Max. output of single power supply	65 W (integrated in system)
Power factor correction/active power	No (meets input harmonic current according EN61000-3-2)

Power consumption

Power consumption note	See white paper Energy Consumption
Link to Energy White Paper	http://docs.ts.fujitsu.com/dl.aspx?id=938eb419-360e-4ba2-9b7f-86fdded0d7a4

Heat dissipation

Heat dissipation notes	See white paper Energy Consumption
------------------------	------------------------------------

Noise emission

Related Processors for noise	Intel® Core™ i7 8700T
Standard noise emission	2x4 GB, SSD, ODD, Windows According to ISO 7779:2010, ECMA-74
Standard noise notes / description	A-weighted sound power level Lw _d (in B) / Workplace related A-weighted sound pressure level Lp _{Am} (in dB(A))
Standard noise operation mode: CPU 50% load	3.2 B / 18 dB(A) Bystander; 20 dB(A) Operator position
Standard noise operation mode: HDD load	3.0 B / 17 dB(A) Bystander; 16 dB(A) Operator position
Standard noise operation mode: Idle mode	3.0 B / 16 dB(A) Bystander; 16 dB(A) Operator position
Standard noise operation mode: ODD load	4.4 B / 30 dB(A) Bystander; 34 dB(A) Operator position
Standard noise operation mode: Office applications 2.0	3.0 B / 16 dB(A) Bystander; 16 dB(A) Operator position

Dimensions / Weight / Environmental

Dimensions (W x D x H)	185 x 190 x 54 mm; with VESA cover: 185 x 190 x 56.2 mm 7.29 x 7.49 x 2.13 inch
Operating position	Vertical / horizontal (no feet needed)
VESA mount	optional VESA cover required
Weight	1.6 kg
Weight (lbs)	3.53 lbs
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	10 - 35 °C (50 - 95 °F)
Operating relative humidity	5 - 85 % (relative humidity)

Compliance

Product	ESPRIMO Q958
Model	MPC3
Germany	TÜV GS
Europe	CE
USA/Canada	FCC Class B cTUVus
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® 7.0 EPEAT® Gold (dedicated regions)
China	CCC (planned) CCC (depending on configuration) CEL (Chinese energy label) TPM 2.0 for China (optional)
Compliance notes	This product is free of polyvinyl chloride (PVC) when ordered with the optional PVC free power cord
Compliance link	https://sp.ts.fujitsu.com/sites/certificates

Additional Software

Additional software (preinstalled)	Adobe® Reader® (pdf reader) McAfee® LiveSafe™ (provides award-winning antivirus protection for your PC and much more. 30 days trial pre-installed) Microsoft Office (1 month trial for new Microsoft® Office 365 customers. Buy Microsoft Office.)
------------------------------------	--

Additional Software

Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink PowerDVD BD (playback software for Blu-ray Disc™) CyberLink PowerDVD DVD (playback software for DVD) Nero Essentials XL Microsoft® Office Professional 2019 Microsoft® Office Home and Business 2019 (A Microsoft Account is required to activate each copy of these products. For purchase and activation only in the region in which it was acquired.)
---------------------------------------	---

Manageability

Manageability technology	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) Intrusion switch (optional) WoL (Wake on LAN) iAMT 12.0 (depending on processor)
Manageability software	DeskView Client DeskView Instant BIOS Management
DeskView components	BIOS Management incl. Security Inventory Management Driver Management Alarm Management
Supported standards	DMI (Desktop Management Interface) SMBIOS (System Management BIOS) PXE (Preboot Execution Environment) WMI (Windows Management Instrumentation) WBEM (Web Based Enterprise Management) CIM (Common Information Model)
Manageability link	http://www.fujitsu.com/fts/manageability

Security

Physical Security	Kensington Lock support Eye for padlock Housing Lock Spring (to use with Kensington lock), (optional)
System and BIOS Security	Embedded security (TPM 2.0) EraseDisk (optional) Credential Guard Ready and Device Guard Capable (Windows 10, v. 1709) Boot sector virus protection Write protect option for the Flash EPROM Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces
User Security	User and supervisor BIOS password Hard disk password Access protection via internal SmartCard reader (optional) Access protection via external SmartCard reader (optional) Embedded PalmSecure® sensor (optional) Workplace Protect (secure authentication solution)
Workplace Embedded Tools	Auto BIOS Update via Fujitsu Server Auto BIOS Update via customer server Easy PC Protection
Security notes	Choose people over passwords. Protect your business with PalmSecure technology. http://choosepeopleoverpasswords.global.fujitsu.com/ #High accuracy: PalmSecure™ has a proven false rejection rate of 0.01 percent and a false acceptance rate of less than 0.00001 percent. No other system in the world can match this performance.#Hygienic and non-invasive: Contactless scanner#Easy to use: Scanning is intuitive and people feel no mental resistance to it.

Miscellaneous

Keyboard on (Special Fujitsu keyboard required)
 Keyboard on with one key (KBPX Eco, KB521)
 Keyboard on with 2 keys (CTRL+CTRL) with PS2 or special USB keyboards
 Keyboard on with any key (USB)
 Thermal management
 Low Power Active Mode
 Extended lifetime

Serviceability

EasyChange for HDD
 EasyChange for optical drives

Packaging information

Packaging dimension (mm)	395 x 198 x 284 mm
Packaging dimension (inch)	15.55 x 7.8 x 11.18 inch
Max. quantity / pallet	84
Material - Weight (g) Carton	670 g
Material - Weight (lbs) Carton	1.48 lbs
Material - Weight (g) EPS / PS	10 g
Material - Weight (lbs) EPS / PS	0.02 lbs
Material - Weight (g) PE	125 g
Material - Weight (lbs) PE	0.28 lbs
Packaging notes	If keyboard is included in packaging: 1.) packaging dimension is increasing to: 500 x 208 x 290mm / (19.69 x 8.19 x 11.42 inch); 2.) material weight of carton will increase to 880g; 3.) max. quantity/pallet = 56; printed user documentation is bleached in chlorin free process;

Warranty

Warranty period	3 years (depending on country)
Warranty type	Bring-In / Onsite Service (for countries within region EMEA, for all other countries depending on local regulations)
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty
Product Related Services - the perfect extension	
Recommended Service	9x5, Onsite Response Time: Next Business Day
Spare Parts availability	5 years after end of product life 5 years
Service Weblink	http://www.fujitsu.com/fts/services/support

Recommended Accessories

Display P27-8 TS UHD

The FUJITSU Display P27-8 TS UHD has a 3840 x 2160 Ultra HD resolution ships with a thin bezel housing ideal for multi-monitor use scenarios. The monitor has a 178°/178° wide viewing angle that delivers consistent picture quality, a 100% sRGB color space, ECO function, DisplayView™ IT Suite manageability software and a range of connectivity options ideal for medium- and large-sized businesses.

Order Code:
S26361-K1610-V160

Display B34-9 UE

The FUJITSU Display B34-9 UE is an ultrawide curved display with 3440 x 1440 resolution with a thin bezel housing. The monitor has a 1900R curvature and a wide viewing angle that delivers consistent picture quality, DisplayView™ Click manageability software and a range of connectivity options ideal for medium- and large-sized businesses.

Order Code:
S26361-K1642-V140

Display P24-8 WS Neo

The FUJITSU Display P24-8 WS Neo is a 16:10 IPS panel monitor that has DisplayView™ IT Suite that helps you activate features such Presence Sensor, Workplace Lighting Guide that promote the overall ergonomics and security of your workplace. The monitor has a 178°/178° wide viewing angle delivering a consistent picture quality and is ideal for CAD and Document Management applications.

Order Code:
S26361-K1647-V160

Wireless Mouse Touch WI910

The Fujitsu Wireless Mouse Touch WI910 has a special touch sensitive surface that recognizes when your hand touches the mouse even before you move it. This provides nearly instantaneous wake-up from the intelligent energy saving sleep mode. Unbeatable responsiveness combines with features like switchable resolution, and three programmable buttons for a unique user experience.

Order Code:
S26381-K465-L100

Keyboard KB950 Phone

The KB950 Phone is a modern and slim line USB keyboard with integrated Skype for business features. This extremely reliable, high-speed input device is the perfect way to manage incoming and outgoing calls, even when the system is locked. Three additional keys make it easy to accept and end calls and mute your microphone during a call. Easy number dialing is assured with the numpad. The integrated 61 x 12 mm display shows the time and date, the user status and shows incoming call data in the form of the calling number and caller ID.

S26381-F950-L4** (**:
Country specific variation)

More information

Fujitsu products, solutions & services

In addition to FUJITSU Desktop ESPRIMO Q958, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Desktop ESPRIMO Q958, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/fts/ESPRIMO

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright 2018 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions GmbH
Website: www.fujitsu.com/fts
2018-11-23 EM-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright 2018 Fujitsu Technology Solutions GmbH