Fujitsu recommends Windows 11 Pro.



Data Sheet

Fujitsu Tablet LIFEBOOK U9311X

World's Lightest Convertible With A Pen

Available in red and black, the FUJITSU Tablet LIFEBOOK U9311X is a lightweight 360-degree foldable device. All-day battery runtime and global LTE ensure highest productivity in any place, while security features such as the integrated PalmSecure™ sensor keep your business data protected. Powerful performance and full connectivity with Intel® Thunderbolt™ 4 offer you best-in-class user experience.

Ultra-slim and lightweight Convertible

The very slim and light housing make it very comfortable to carry the device. Thanks to its 360° foldability, it can be immediately turned from a Notebook to a Tablet – and back.

- Available in red or black
- Weighing from 1 kg with a robust magnesium housing
- Durability is MIL-STD-810H tested
- Intel® Iris® Xe Graphics

Security at its best

No compromises in security and data protection – the integrated PalmSecure™ sensor turns your unique palm vein pattern into your personal key.

- PalmSecure™
- Fingerprint & Full HD IR Camera supporting Windows Hello
- SmartCard reader
- Kensington Lock support

Excellent connectivity and usability

Newest interfaces and convenient features. All ports are full-sized – even the LAN port. No adapters, that can be lost and cause additional costs, needed.

- Complete set of full-sized interfaces: HDMI, LAN and USB Type-C with Intel® Thunderbolt™ 4
- 13.3 inch FHD anti-glare touch display with pen input
- Pen garage with inductive charging function
- 5 MP rear camera

Convenient mobility supporting usage on the go

Highest productivity on business trips without empty batteries or waste of time

- All-day battery runtime offers you the exceptional mobility that you need when on the move
- Anytime USB charging functionality for your peripheral devices, even when system is turned off
- Always connected and instantly ready

















Components

Base unit	LIFEBOOK U9311X black	LIFEBOOK U9311X red
Operating systems		
Operating system notes	Windows 11 Home edition requires interaccount)	net connectivity and a Microsoft account (https://account.microsoft.com/
	For all Windows 11 editions, internet acc some features. A Microsoft account is re	ess is required to perform updates and to download and take advantage of quired for some features.
	Window 10 releases for a period of maxi	e product life FUJITSU will continue to test and support all upcoming mum 5 years – depending on the available extension of hardware services letails please see "FUJITSU Service Statement for Windows 10 Semi-Annual-
Dun angang		
Processor	Intel® Core™ i7-1185G7 processor (4 Cores / 8 Threads)	
	Intel® Core™ i5-1145G7 processor (4 Core	·
	Intel® Core™ i5-1135G7 processor (4 Core	
	*Processor only for retail, SMB, education	n and government
Hard disk drives (internal)	SSD PCle, Teton Glacier (32GB Optane +	512GB SSD), SED
	SSD PCIe, SSD 512GB Value PCIe G3 M.2	FDE, SED
	SSD PCIe, SSD 512GB MS PCIe G3 M.2 FD	E, SED
	SSD PCIe, SSD 256GB Value PCIe G3 M.2	FDE, SED
	SSD PCIe, SSD 2TB MS PCIe G3 M.2 FDE,	SED
	SSD PCIe, SSD 1TB Value PCIe G3 M.2 FD	E, SED
	SSD PCIe, SSD 1TB MS PCIe G3 M.2 FDE,	SED
Hard disk notes	Accessible capacity may vary, also deper	nding on used software.
Interface add on cards/components (optional)		
4G/ LTE (optional)	LTE Sierra Wireless EM7421 (Cat. 7)	
	LTE module Fibocom L850-GL(Cat.9)	
Display	33.8 cm (13.3-inch), IPS, FHD, 1,920 x 1,0	30 pixel, Anti-glare touchscreen, 400 cd/m², 1000:1
Multimedia		
Camera	Front: IR Cam (2 MP) with LED, supportin Out camera: 5 MP with autofocus on top	

Base unit

Base unit	LIFEBOOK U9311X black	LIFEBOOK U9311X red	
General system information			
Chipset	Integrated in CPU		
Supported capacity RAM (min.)	8 GB		
Supported capacity RAM (max.)	32 GB		
Memory slots	LPDDR4 (4266 MHz)		
Memory notes	8 GB / 16 GB / 32 GB onboard LPDDR4 (3,200 MHz) Dual channel support		
LAN	10/100/1,000 MBit/s Intel® I219LM		
LAN notes	Intel vPro support		
Integrated WLAN	Intel WiFi 6 AX201 - WLAN, BT, SRD cat. 1		

General system information	HEFT Consideration 2.7		
BIOS version	UEFI Specification 2.7		
BIOS features	InsydeH2O BIOS On board		
Audio type	Realtek ALC255		
Audio codec Audio features			
MIL-STD tested	2x digital array microphones, 2x built-in speakers (stere	90)	
IMIL-31D tested	Yes, selected MIL-STD-810H tests passed. MIL-STD-810H test results are not a guarantee of future performance under identified test conditions. Accidental damage is not covered under standard international limited warranty.		
Color	Black	Red	
Material	Magnesium	Magnesium	
Display			
Diagonal Size	33.8 cm (13.3-inch)		
Display Technology	IPS		
Display type	Anti-glare touchscreen		
Display Resolution type	FHD		
Resolution (native)	1,920 x 1,080 pixel		
Aspect ratio	16:9		
Brightness - typical	400 cd/m ²		
Contrast - typical	1000:1		
Viewing angle (h/v) - typical	178°/178°		
Display notes	Wide-view high-bright LED display (for enhanced outdo	oor viewing). With magnesium display lid.	
Sensors	3-axis Accelerometer Gyroscope Magnetic Field Sensor Compass		
Digitizer / Touch Technology	Wacom Digitizer for pen (AES) input plus capacitive 10	finger multi-touch screen	
Pen	AES 4k pressure level Pen garage inductive charging		
Graphics			
Base unit	LIFEBOOK U9311X black	LIFEBOOK U9311X red	
TFT resolution (HDMI)	up to 4,096 x 2,160 @ 60 Hz	up to 4,096 x 2,160 @ 60 Hz	
Graphics brand name	Intel® Iris® Xe Graphics (with Dual channel memory)	Intel® Iris® Xe Graphics (with Dual channel memory)	
Graphics features	4 Display Support (3 external, 1 internal) HDCP support DirectX® 12 OpenGL® 4.5	4 Display Support (3 external, 1 internal) HDCP support DirectX® 12 OpenGL® 4.5	
Graphics notes	Shared memory depending on main memory size and of 3D accelerator	operating system	
Interfaces			
DC-in	1		
Audio: line-out / headphone	1 (combo port with Audio line-in)		
Audio: line-in / microphone	1 (combo port with Audio line-out)		
Internal microphones	2x digital array microphones		
USB 3.2 Gen1 (5 Gbps) total	2x Type-A (1 with Anytime USB charge functionality)		
USB 4.0 Gen3 (20 Gbps) total	2x Type-C Intel® Thunderbolt™ 4 (with Power Delivery functionality)		
USB Type-C	2 USB 4 Gen3 Thunderbolt™4, Power Delivery (15W), DP 1.4		
HDMI	1 v2.0		
Ethernet (RJ-45)	1		

 Interfaces			
Memory card slots	1 (USH-II) SD 4.0 standard		
memory cara siecs	SD/microSD card: 2GB		
	SDHC/microSDHC card: 32GB		
	SDXC/microSDXC card: 2TB		
	Speed Class: up to UHS-II (156MB/s)		
SmartCard slot	1		
SIM card slot	1 (Nano-SIM, only for models with integrated 4G/LTE mo	odule)	
Docking connector for Port Replicator	USB Type-C		
Kensington Lock support	1		
Port Replicator interfaces (optional)			
	Thunderbolt™ 4 PR	USB Type-C PR	
DC-in	1 (20V/170W required)	1 (19V/90W required)	
Power on switch	1	1	
Audio: comments	1 Combo jack for headset usage	1 Combo jack for headset usage	
DisplayPort	2x V1.4++	1x V1.2	
VGA		1	
HDMI text	V 2.0b	1	
Interface Notes	2x Type-A - 5V/0.9A, 4.5W	3x Type-A - 5V/0.9A, 4.5W	
	1x Type-A - 5V/2.4A, 12W	1xType-C - 15W $1x$ Type-C - Up to 60 W (PD v2.0-1.1) power output to	
	2x Type-C - 5V, 1.5A/4.5W charging port 1x Type-C - TBT4 up to 60 W (PD v2.0-1.1), 5-20V/3.0A	client or 4.5W input	
	upstream (PC), Intel AMT support (vPRO)	Chefit of 4.5W input	
	1x Type-C - TBT4 up to 15 W (PD v2.0-1.1), 5V/3.0A		
	downstream, power output to client		
Kensington Lock support	1	no	
Ethernet (RJ-45)	1 (10/100/1000 Mbit/s, 2,5 Gbps)	1	
Notes		resolutions and frequencies depend on mobile system an	
	display interface type.		
	Please consult always also the manual of the connected	client.	
Keyboard and pointing devices			
	Backlit keyboard w/o touchstick		
	Number of keyboard keys: 85, Keyboard pitch: 19 mm, K	Leyboard stroke: 1.5 mm	
	Multi gesture touchpad with integrated mouse button f	unctionality	
	Touchscreen		
	Tablet Pen (AES), stored in pen garage		
Wireless technologies			
Antennas	2x dual band for WLAN, 2x for LTE, Bluetooth shared with	h WLAN	
Bluetooth	v5.1		
Integrated WLAN	Intel WiFi 6 AX201 - WLAN, BT, SRD cat. 1		
WLAN encryption	WPA/WPA2/WPA3 (Wi-Fi Protected Access)		
WLAN notes	Import and usage according to country-specific regulations.		
Integrated WWAN	LTE Sierra Wireless EM7421 (Cat.7) - UMTS,LTE Fibocom L850-GL (Cat.9) - UMTS,LTE	LTE Sierra Wireless EM7421 (Cat.7) - UMTS,LTE Fibocom L850-GL (Cat.9) - UMTS,LTE	
WWAN notes	Including GPS functionality		
	Import and usage according to country-specific regulati	ions.	
GPS	LTE Connection Manager (if configured with 4G/LTE) Embedded in 4G module if configured with WWAN		
	Embedded in 40 module ii connguled with www.		
Power supply	201/2514/225 4) 4221/ 2421/ 251/ 251/ 251/ 251/ 251/ 251/ 251/ 2	201/ (55111/2 25 4) 4221/ 2421/ 251/ 251/ 251/ 251/ 251/ 251/ 251/ 2	
AC Adapter	20 V / 65 W (3.25 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin	20 V / 65 W (3.25 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) Type-C AC-Adapter standard	
ne naaptei	(grounded) Type-C AC-Adapter standard		
·	(grounded) Type-C AC-Adapter standard 19 V / 65 W (3.42 A), 100 V - 240 V, 50 Hz - 60 Hz		
AC Adapter AC Adapter	(grounded) Type-C AC-Adapter standard 19 V / 65 W (3.42 A), 100 V - 240 V, 50 Hz - 60 Hz 20 V / 65 W (3.25 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin	19 V / 65 W (3.42 A), 100 V - 240 V, 50 Hz - 60 Hz 20 V / 65 W (3.25 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin	

Power supply			
AC adapter	19 V / 65 W (3.42 A)	19 V / 65 W (3.42 A)	
	20 V / 65 W (3.25 A) Type C	20 V / 65 W (3.25 A) Type C	
Notes	65W AC adapter for usage with system/ min. 90W AC Adapter for usage with Port Replicator	65W AC adapter for usage with system/ min. 90W AC Adapter for usage with Port Replicator	
Rated voltage range	100 V - 240 V (AC Input)	100 V - 240 V (AC Input)	
Rated frequency range	50 Hz - 60 Hz	50 Hz - 60 Hz	
1st battery options	Lithium polymer battery 4-cell, 50 Wh	Lithium polymer battery 4-cell, 50 Wh	
1st battery	Lithium polymer battery 4-cell, 50 Wh	Lithium polymer battery 4-cell, 50 Wh	
Battery features	Quick Charge: 80% in 1h	Quick Charge: 80% in 1h	
Runtime 1st battery	11 h	11 h	
Battery notes	Battery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2018. Refer to www.bapco com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime.		
Noise emission			
Noise emission	Please refer to the Eco Declaration		
Dimensions / Weight / Environmental			
Dimensions (W x D x H)	309 x 214.8 x 16.9 mm		
	12.18 x 8.41 x 0.62 inch		
Weight	1,015 kg		
Weight (lbs)	2,23 lbs		
Weight notes	Weight may vary depending on actual configuration		
Operating ambient temperature	5 - 35 °C (41 - 95 °F); Packed -10 - 60 °C (14 - 140 °F)		
Operating relative humidity	Running: 20 - 80% (relative humidity); Packed: 20 - 80%	(relative humidity)	
Compliance			
Product	LIFEBOOK U9311X		
Germany	GS		
Europe	CE CB		
USA/Canada	FCC (depending on configuration)		
Global	TCO Certified 8.0 (depending on configuration) EPEAT® Silver (dedicated regions), depending on configuration WEEE (Waste electrical and electronic equipment) RoHS (Restriction of hazardous substances) MIL-STD-810H tested Microsoft Operating Systems (HCT / HCL entry / WHQL)		
India	BIS		
Russia	EAC		
China	CCC		
Compliance link	https://sp.ts.fujitsu.com/sites/certificates		
Additional Software			
Additional software (preinstalled)	Adobe® Reader® (pdf reader) CyberLink YouCam (webcam software) Fujitsu Display Manager Fujitsu DeskUpdate (driver and utility tool) ShockSensor Utility Power Saving Utility Fujitsu Plugfree Network (network management utility) EasyGuide online user documentation Microsoft Office (1 month trial for new Microsoft® Office		

Additional Software	
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) optional CyberLink PowerDVD BD (playback software for Blu-ray Disc™) CyberLink PowerDVD DVD (playback software for DVD) CyberLink YouCam (webcam software)
	Nero (backup and burning software)
Additional software (notes)	Use of accopanying and/or additional Software is subject to proactive acceptance of the respective License Agreements /EULAs/ Subscription and support terms of the Software manufacturer as applicable for the relevant Software whether preinstalled or optional. The software may only be available bundled with a software support subscription which – depending on the Software - may be subject to separate remuneration.
Manageability	
Manageability technology	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) WoL (Wake on LAN) Intel® vPro™ technology iAMT 14.0 (depending on processor)
Manageability software	DeskView Client DeskView Instant BIOS Management
DeskView components	Inventory Management BIOS Management Driver Management Security Management Alarm Management
Supported standards	WMI (Windows Management Instrumentation) PXE (Preboot Execution Environment) DMI (Desktop Management Interface) SMBIOS (System Management BIOS) WBEM (Web Based Enterprise Management) CIM (Common Information Model) BootP (made4you)
Manageability link	http://www.fujitsu.com/fts/manageability
Security	
Physical Security	Kensington Lock support
System and BIOS Security	Absolute Persistence® technology capable BIOS Optional: Trusted Platform Module (TPM 2.0) EraseDisk
User Security	Hard disk password User and supervisor BIOS password Embedded fingerprint sensor (optional) Embedded PalmSecure™ sensor (optional) Smartcard reader (integrated) AuthConductor Client Basic (secure authentication solution)
Security Notes	The properties of the product provide a baseline for product security and therefore end-customer IT security. However, these properties are not sufficient on their own to protect the product from all existing threats, such as intrusion attempts, data exfiltration and other forms of cyberattacks. To customize security settings, please use the configuration options as available for the respective product. During operation, the IT security of this product is within the responsibility of the respective administrator/end-user of the product. Please note, that Fujitsu as a manufacturer does not make any policy prescriptions or advocacy statements regarding IT security best practices and/or general product operation.
Packaging information	
Warranty	
Warranty period	2 years (for countries within EMEIA)
Warranty type	Bring-in Service / Collect & Return Service (depending on country)
W . T . O. C . I'''	

http://www.fujitsu.com/warranty

Warranty Terms & Conditions

Warranty	
Digital bug fixes	Subject to availability and following their generic release for the product, bug fixes and function-preserving patches for product-related software (firmware) can be downloaded from the technical support at: https://support.ts.fujitsu.com/ free of charge by entering the respective product serial number. For application software supplied together with the product, please directly refer to the support websites of the respective software manufacturer.
Product Support Services - the p	perfect extension
Recommended Service	9x5, Onsite Response Time: Next Business Day
Spare Parts availability	at least 5 years after shipment, for details see https://support.ts.fujitsu.com/
Service Weblink	http://www.fujitsu.com/emeia/products/product-support-services/

Recommended Accessories

Car Adapter USB-C-QC	One Car Adapter fits all.	Order Code:
AES Pen with replacement stylus tips	Take your creativity to the next level, with the most natural pen experience with the AES Pen with replacement stylus tips. With pen nibs that are very thin, you can experience the writing and signing behavior of an ink pen.	
USB Type-C AC Adapter	Recharge your notebook or tablet at work, at home or on the road with this USB Type-C power source easily.	Order Code: S26391-F3326-L502
Thunderbolt™ 3 Port Replicator	With Thunderbolt™ 3 you can connect almost everything with only on cable. Enhance your USB connection options, connect your displays via Thunderbolt™ 3, HDMI or DisplayPort while charging your device.	Order Code: S26391-F3357-L100
USB Type-C Port Replicator 2	Connect to your peripherals. Adapt to the task on demand. The universal USB Type-C interface supports you to get your peripheral devices connected easily. Multiply your USB ports to connect your peripherals as well as your external display via HDMI, DisplayPort or VGA. You also can charge your external USB devices without the need of any additional charger.	Order Code: \$26391-F3327-L100
Thunderbolt™ 4 Port Replicator	First Thunderbolt™ Port Replicator on the market providing enhanced security and full support of Intel® AMT (vPro®). The universal port can easily connect almost everything with a single cable and high speed-data transfer. This smart workspace solution keeps your desk clean and tidy.	Order Code: FPCPR401BP

charge.

Independent of your mobile device charging method this car adapter will \$26391-F2613-L630

fulfill all major requirements and standards for fast charging vendorbrand-independent notebooks and all mobile devices. The Car Adapter USB-C-QC supports USB PD with PPS, Quick Charge (QC), Apple- and Samsung

More information

Fujitsu products, solutions & services

In addition to Fujitsu Tablet LIFEBOOK U9311X, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products www.fujitsu.com/global/products/computing/

Software www.fujitsu.com/software/

More information

Learn more about Fujitsu Tablet LIFEBOOK U9311X, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

www.fujitsu.com/emeia/products/computing/pc/tablets

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT

Please find further information at http://www.fujitsu.com/global/about/environment



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html

Copyright 2022 Fujitsu Technology Solutions GmbH

Disclaimer

Please note that the data sheet reflects the technical specification with the maximum selection of components for the named system and not the detailed scope of delivery. The scope of delivery is defined by the selection of components at the time of ordering.

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

The overall product has been designed and manufactured for general office use, regular personal use and ordinary industrial use.

Contact

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com 2022-07-01 EM-EN All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html
Copyright 2022 Fujitsu Technology Solutions GmbH