




HD CHAINS, CABLES, & ATD SOCKS

Visit www.peerlesschain.com for a complete list of tire sizes and traction options.



QUIK GRIP ❄️



Highway Service - (Round Twist Link CAM Style)

SINGLE PAIR	DUAL PAIR	TIRE FITMENTS (If tire size not shown, check vendor website)
QG2239CAM	QG4239CAM	8.25-20, 9-22.5, 245/75-22.5, 255/70-22.5, 265/70-22.5, 275/70-22.5
QG2241CAM	QG4241CAM	9.00-20, 10-22.5
QG2243CAM	QG4243CAM	275/75-22.5, 275/80-22.5, 285/75-22.5, 295/70-22.5, 295/75-22.5
QG2245CAM	QG4245CAM	10.00-20, 10.00/90-20, 11-22.5, 13/80-20, 285/70-24.5
QG2247CAM	QG4247CAM	275/80-24.5, 285/75-24.5
QG2249CAM	QG4249CAM	10.00-22, 11-24.5
QG2251CAM	*QG4251	11.00-20, 12-22.5, 285/80-22.5, 285/80-24.5, 295/80-22.5, 305/80-22.5
QG2255CAM	*QG4255	11.00-22, 12.00-20, 12.75-22.5, 14/80-20, 305/75-24.5, 305/85-22.5, 315/80-22.5
*QG3255		15-22.5, 16.5-19.5, 365/85-20, 385/65-22.5, 445/55-22.5
*QG3261		19-22.5, 19.5-19.5, 395/85-20, 445/65-22.5
QG3269CAM		445/50-22.5, 455/50-22.5
QG3271CAM		16.5-22.5, 425/55-22.5, 425/65-22.5, 425/70-22.5, 445/65-19.5, 455/55-22.5

*CAM style is not available for these part numbers

QUIK GRIP ❄️



Highway Service V-Bar - (Round Twist Link CAM Style)

SINGLE PAIR	DUAL PAIR	TIRE FITMENTS (If tire size not shown, check vendor website)
QG2839CAM	QG4839CAM	8.25-20, 9-22.5, 245/75-22.5, 255/70-22.5, 265/70-22.5, 275/70-22.5
QG2841CAM	*QG4841	9.00-20, 10-22.5
QG2843CAM	QG4843CAM	275/75-22.5, 275/80-22.5, 285/75-22.5, 295/70-22.5, 295/75-22.5
QG2845CAM	QG4845CAM	10.00-20, 10.00/90-20, 11-22.5, 13/80-20, 285/70-24.5
QG2847CAM	QG4847CAM	275/80-24.5, 285/75-24.5
QG2849CAM	QG4849CAM	10.00-22, 11-24.5
QG2851CAM	*QG4851	11.00-20, 12-22.5, 285/80-22.5, 285/80-24.5, 295/80-22.5, 305/80-22.5
QG2855CAM	*QG4855	11.00-22, 12.00-20, 12.75-22.5, 14/80-20, 305/75-24.5, 305/85-22.5, 315/80-22.5

*CAM style is not available for these part numbers. Larger diameter V-BAR is also available.

QUIK GRIP ❄️

7mm Cross-Chain



Heavy Duty V-Bar/CTO Canadian Spec - (Also Available in Non-CAM Style)

SINGLE PAIR	DUAL TRIPLE	TIRE FITMENTS (If tire size not shown, check vendor website)
QGV343HD	QGV43HD	10.00-20, 11-22.5, 275/75-22.5, 275/80-22.5, 295/70-22.5
QGV344HD	QGV44HD	10.00-22, 11-24.5, 275/80-24.5, 285/75-24.5, 295/75-24.5
*QGV355	*QGV755	11.00-20, 12-22.5, 305/85-22.5, 320/75-24
*QGV356	*QGV756	11.00-22, 12.00-20, 12-24.5

*CAM style is not available for these part numbers.

QUIK GRIP ❄️

8mm Cross-Chain



Quik Grip Studded Chain - (Also Available in Non-CAM Style)

SINGLE PAIR	DUAL TRIPLE	TIRE FITMENTS (If tire size not shown, check vendor website)
QGS2945C	QGS4945C	11-22.5
QGS2949C	QGS4949C	10.00-22, 11-24.5, 295/75-24.5
QGS2951C	QGS4951C	11.00-20, 12-22.5, 295/80-22.5
QGS2955C	QGS4955C	12.00-20, 11-22, 12-24.5

QUIK GRIP ❄️

Highway Service Square Rod Alloy - (Non-Twist Link CAM Style)

SINGLE PAIR	DUAL PAIR	TIRE FITMENTS (If tire size not shown, check vendor website)
QG2143	QG4143	275/75-22.5, 275/80-22.5, 285/75-22.5, 295/70-22.5, 295/75-22.5
QG2145	QG4145	10.00-20, 10.00/90-20, 11-22.5, 285/70-24.5, 305/70-22.5, 315/70-22.5
QG2147	QG4147	275/80-24.5, 285/75-24.5
QG2149	QG4149	10.00-22, 11-24.5
QG2151		11.00-20, 12-22.5, 285/80-22.5, 285/80-24.5, 295/80-22.5, 305/80-22.5
QG2155		11.00-22, 12.00-20, 12.75-22.5, 14/80-20, 305/75-24.5, 305/85-22.5, 315/80-22.5

QUIK GRIP ❄️

Mud Off-Road



Mud Service - (8mm Square Alloy Non-Twist or .375" Round Twist)

SINGLE PAIR	DUAL TRIPLE	TIRE FITMENTS (If tire size not shown, check vendor website)
TC82145NC	TC84145NC	10.00-20, 10.00/90-20, 11-22.5, 285/70-24.5, 305/70-22.5, 315/70-22.5
TC82149NC	TC84149NC	10.00-22, 11-24.5
QG2448	QG4448	10.00-20, 11-22.5
QG2452	QG4461	10.00-22, 11.00-20, 11-24.5, 12-22.5, 305/85-22.5

SEE OTHER SIDE >

QUICK GRIP HD



Highway Service HD - (Round Twist Link, .312" Wire, CAM Style)

SINGLE PAIR	DUAL TRIPLE	TIRE FITMENTS (If tire size not shown, check vendor website)
QG2236HD	QG4236HD	275/80-24.5, 285/75-24.5
QG2244HD	QG4244HD	10.00-20, 11-22.5, 275/80-22.5, 275/80-24.5, 295/70-22.5, 295/75-22.5
QG2250HD	QG4250HD	10.00-22, 11-24.5

ALLOY RADIAL CHAIN

.525" OD COILS!



Highway Service Cable - (Alloy Traction Coils with Over-Center Latch)

SINGLE PAIR	DUAL PAIR	TIRE FITMENTS (If tire size not shown, check vendor website)
TA1939	TA3939	8.25-20, 9-22.5, 235/80-22.5, 245/80-22.5, 255/70-22.5, 255/75-22.5
TA1941	TA3941	9.00-20, 10-22.5
TA1943	TA3943	275/75-22.5, 275/80-22.5, 285/70-24.5, 285/75-22.5, 295/70-22.5, 295/75-22.5
TA1945	TA3945	10.00-20, 11-22.5, 13/80-20, 305/70-22.5, 315/70-22.5
TA1947	TA3947	11.5-22.5, 275/80-24.5, 285/75-24.5, 295/75-24.5, 305/80-22.5
TA1949	TA3949	10.00-22, 11-24.5, 12.75-22.5, 315/80-22.5
TA1951		11.00-20, 12-22.5, 285/80-22.5, 285/80-24.5, 295/80-22.5, 320/75-24
TA2069		445/50-22.5, 455/50-22.5, 455/55-22.5

*Economy class cables available: EC1943, EC1945, EC1947, EC1949

SUPER Z

.685" OD COILS!



Highway Service Super Z Cable - (Alloy Traction Coils - Diagonal Pattern)

SINGLE PAIR	DUAL PAIR	TIRE FITMENTS (If tire size not shown, check vendor website)
ZT881	Inquire for PN	10.00-20, 11-22.5, 275/80-22.5, 285/75-24.5, 285/80-22.5, 295/75-22.5, 305/70-22.5
ZT887	Inquire for PN	10.00-22, 11.00-20, 11-24.5, 11.50-2, 12-22.5, 315/80-22.5, 320/75-24
ZT891	Inquire for PN	11.00-22, 11.00-24, 12.00-20, 12.5-24.5, 12.75-22.5, 13.22.5
ZT892		14/80-20, 305/85-22.5, 365/70-22.5, 365/80-20, 385/65-22.5, 400/70-20
ZT896		16.5-22.5, 425/55-22.5, 425/65-22.5, 445/65-19.5
ZT897		445/50-22.5, 455/50-22.5
ZT898		395/85-20, 425/70-22.5
ZT899		455/55-22.5

SUPER SOX

Advanced Traction Technology



Highway Service - Super Sox ATD

SPIKE PADS	JACQUARD	TIRE FITMENTS (If tire size not shown, check vendor website)
S100	S200	275/70-22.5, 275/75-22.5, 275/80-22.5, 295/75-22.5
S120	S220	11-22.5, 305/70-22.5
S140	S240	11-24.5, 285/75-24.5, 295/80-22.5, 315/80-22.5



Optional for CAM chains

HD Multi-Arm Tire Chain Tensioner

STOCK NUMBER	DESCRIPTION	USED ON
QG20009	Free Moving Arms on Center Ring	18" - 24.5" Wheels

10 Pairs/Box



Optional for CAM chains

HD Spring Tire Chain Tensioner

STOCK NUMBER	DESCRIPTION	USED ON
QG20073	Chain with 6 Springs	20" - 24.5" Wheels

12 Pairs/Box

FOR MAXIMUM CHAIN LIFE:

- Keep chains tight.
- Avoid bare pavement and speeds over 30 mph. Chain links on cross members will be damaged and cause cross members to break. Damage could occur to chains, tires and vehicles.
- Avoid spinning tires: start slowly, even in uphill conditions.
- Avoid locking brakes.
- If a cross member should break, stop & remove or replace it immediately.

Installation Instructions and videos are available at: www.peerlesschain.com

Speeds over 30 mph, improper fit or improper installation voids this warranty.

#27.58-8/22 Printed in the U.S.A. © Peerless Chain Company All rights reserved.

One Year Limited Warranty

This product is warranted free from defect in workmanship and material for one year from the date of delivery to the user. Defective product may be returned to the manufacturer, freight prepaid, within 10 days of alleged defect. Inspection will be made to determine causes of failure. Chain determined to be defective will be repaired or replaced. Buyer shall not be entitled to recover any incidental or consequential damages. No compensation will be made for any labor claim, delays or damages incurred by using this product. Although this warranty gives you specific rights, you may have other legal rights which differ from state to state.



SEE OTHER SIDE >