Components Overview


HP Engage Go Convertible System





Components Overview

HP Engage Go Mobile



Front View

- 1. Front-facing camera LED
- 2. Front-facing camera
- 3. Power button

Components Overview




- 1. Rear-facing camera
- 2. Volume up/down
- 3. Fingerprint reader
- 4. Pogo pin connector to convertible dock

Rear View

- 5. Audio jack
- 6. Power button
- 7. 2 USB-C[™] 3.1 ports
- 8. Barcode scanner trigger buttons*
- 9. SIM Module

^{*}Only available on select SKUs

HP Engage Go Convertible System Basic I/O Connectivity Base (Rear/Side View)




Basic I/O Connectivity Base components

- 1. Cash drawer jack
- 2. Power connector
- 3. USB Type-C[™] power port
- 4. Powered serial ports (3)
- 5. USB 2.0 ports (4)
- USB 3.0 ports (2)

- 7. USB Type-C[™] port
- 8. RJ-45 network jack
- 9. Security cable slot
- 10. MicroSD card reader
- 11. Headset jack

IMPORTANT: To avoid damage to the computer, DO NOT plug a telephone cable into the cash drawer jack.

Advanced I/O Connectivity Base (Rear/Side View)



Advanced I/O Connectivity Base components

- 1. Cash drawer jack
- 2. Powered USB 12 V ports (2)
- 3. Powered USB 24 V port
- 4. Power connector
- 5. USB Type-C[™] power port
- 6. Powered serial ports (2)

- 7. USB 3.0 ports (4)
- 8. USB Type-C[™] port
- 9. RJ-45 network jack
- 10. Security cable slot
- 11. MicroSD card reader
- 12. Headset jack

IMPORTANT: To avoid damage to the computer, DO NOT plug a telephone cable into the cash drawer jack.

HP Engage Go Mobile Retail Case



Model

Engage Go Mobile Retail Case Engage Go Mobile Retail Case w/ MSR 3VM86AA 3VM87AA

Increase HP Engage Go Mobile drop specification from 3 feet (1m) to 4 feet (1.2m)*,** (2) attach points for shoulder strap (strap included with Case)
Pen loop
Optional MSR attachment

*MIL-STD 810G testing is passed and is not intended to demonstrate fitness for U.S. Department of Defense contract requirements or for military use. Test results are not a guarantee of future performance under these test conditions. Damage under the MIL STD test conditions or any accidental damage requires an optional HP Accidental Damage Protection Care Pack.

**HP Total Test Process results are not a guarantee of future performance under these test conditions. Damage under the test conditions or any accidental damage requires an optional HP Accidental Damage Protection Care Pack.



HP Engage Go Dock



- 10 degree tilt adjustability (angle is set between 50 and 60 degrees)
- 180 degree swivel in either direction
- Choice of standard or printer column
- HP Smart Dock (locking, unlocking)
- Push release button with LED (Amber, White, Green) for unlocking
- Pogo pin interface (power, USB, video), magnet-assisted connection with tablet
- Stability plate (attaches to HP Advanced and Basic Connectivity Base)
- Optional countertop mounting bracket
- Configurable with connectivity base
- Ebony Black or Ceramic White color

Dimensions (W X D X H)

Convertible Dock (standard column)



Overview

28.39 x 16.17 cm x 24.53 cm (283.9 x 161.7 mm x 245.3 mm) 11.18 x 6.37 in x 9.66 in 9.60 cm diameter (96 mm) 3.78 in diameter

Convertible Dock (printer column) 28.39 x 16.17 cm x 28.52 cm (283.9 x 161.7 mm x 285.2 mm) 11.18 x 6.37 in x 11.23 in 9.60 cm diameter (96 mm) 3.78 in diameter

Weight (Grams, lbs.)

Convertible Dock (standard column) 2480g (5.49lbs)

Convertible Dock (printer column) 3050g (6.74lbs)

HP Engage Go Jacket

Models

HP Engage Go Jacket iSMP4	5LX96AA
HP Engage Go Jacket iSMP4 B	5LX97AA
HP Engage Go Jacket MSR+SCR+OCR+BCS	5LY00AA
HP Engage Go Jacket MSR+SCR	5LY01AA
HP Engage Go Jacket MSR+SCR+BCS	5LY02AA
HP Engage Go Jacket (Base Jacket)	5PR24AA

Dimensions (W X D X H)	5LX96AA 30.17 x 22.14 x 2.13 cm (301.7 x 221.4 x 21.3 mm) 11.88 x 8.72 x 0.84 in ¹	5LX97AA 30.17 x 22.14 x 2.13 cm (301.7 x 221.4 x 21.3 mm) 11.88 x 8.72 x 0.84 in	5LY00AA 34.89 x 22.14 x 3.12 cm (348.9 x 221.4 x 31.2 mm) 13.74 x 8.72 x 1.23 in	5LY01AA 34.89 x 22.14 x 2.13 cm (348.9 x 221.4 x 21.3 mm) 13.74 x 8.72 x 0.84 in	5LY02AA 34.89 x 22.14 x 2.13 cm (348.9 x 221.4 x 21.3 mm) 13.74 x 8.72 x 0.84 in	5PR24AA 30.17 x 22.14 x 2.13 cm (301.7 x 221.4 x 21.3 mm) 11.88 x 8.72 x 0.84 in
Weight (Grams, lbs.)	690g (1.52lb)	690g (1.52lb)	780g (1.71lb)	710g (1.56lb)	720g (1.58lb)	570g (1.25lb)
Optional integrated Smart Card Reader			√	√	√	
Optional integrated Barcode Scanner			√		√	
Optional integrated OCR			√			
Optional integrated MSR			√	√	√	
PED Caddy	√	√				
Fingerprint reader access	√	√	√	√	√	√



Overview						
Rear camera and LED access	✓	√	√	√	√	√
Side USB-C ports access	√	√				
USB-C 3.1 Charging Port			✓	√	√	
Audio jack	√	√	√	√	√	√
Barcode scanner access	√			√		
Docking connector access (HP Engage Go Dock pogo pin)	✓	√	√	√	√	√
Input / Output Side barcode scanner buttons			√		√	
Rear barcode scanner buttons			√		√	
Volume and power buttons	√	√	✓	√	√	√
Hand Strap			Hingeable ar	ating nd detachable se latch		
Shoulder Strap		Sho	oulder strap include		unit	

Two attach points on jacket

PED Caddy for Ingenico iSMP4 **Power**

Pogo pin interface with Ingenico PEDs for single-charging and USB data transfer capability Requirements

Release button for detaching PED from caddy Ability to lock PED into caddy via security screw * PED Caddy only available for 5LX96AA and 5LX97AA

Black color only **Industrial Design** Pen loop

NOTE* Sold separately

NOTE 1: measurements without PED caddy

HP Engage Go Mobile

- Windows® 10 Pro 64, Windows® 10 IoT Enterprise 2016 LTSB 64-Value, Windows® 10 IoT Enterprise 2019 LTSC 64-bit, **FreeDOS**
- Intel® Kaby Lake Core™ and Pentium® processors
- Integrated Kaby Lake Premium PCH integrated with CPU
- 12.3" diagonal capacitive multi-touch, WUXGA+ display
- M.2 2280 solid state drives
- Soldered down LPDDR3 1866 memory
- 4-cell long life polymer battery with HP Fast Charging
- 802.11ac Wi-Fi (2x2)
- Bluetooth® 4.2 connectivity (combo card with Wi-Fi)
- LTE/HSPA+ WWAN options available (not available with barcode scanner)
- Optional integrated NFC, FPR and barcode scanner
- **Ebony Black or Ceramic White color**



DIMENSIONS AND WEIGHT

Dimensions (W X D X H)

Base Height 15.5 cm (155 mm) 6.10 in

Height from base to top of HP Engage Go Mobile System 28.32 cm (283.2 mm) (When tilted down) 11.15 in (When tilted down) 27.56 cm (275.6 mm) (When tilted up) 10.85 in (When tilted up)

32.81 x 23.36 x 2.13 cm (328.1 x 233.6 x 21.3 mm) 12.91 x 9.19 x .83 in (landscape orientation, case not included)

Retail Tablet 28.77 x 20.77 x 1.29 cm (287.7 x 207.7 x 12.9 mm) 11.33 x 8.18 x 0.51 in

(landscape orientation, case included)
Retail Tablet
30.20 x 22.17 x 1.82 cm (302 x 221.7 x 18.2 mm)
11.89 x 8.73 x 0.72 in w/o MSR

MSR

10.18 x 2.08 x 1.37 cm (101.8 x 20.8 x 13.7 mm) 4.01 x 0.82 x 0.54 in

Weight (Grams, lbs.)

Retail Tablet (case not included) 1098g (2.42lbs)

Retail Tablet (case included) 1257g (2.77lbs) w/o MSR 1306g (2.87lbs) w/ MSR

PORTS

(2) USB-C[™] 3.1 supports PD 2.0 and DP1.2 Alt mode (1) pogo pin connector to convertible dock

SERVICE AND SUPPORT

3-year standard parts, labor and onsite limited warranty. Online technical support is available seven days a week, 24 hours a day. Certain restrictions and exclusions apply. Depending on country; 3-year limited warranty on primary battery. Optional HP Care Pack Services are extended service contracts which go beyond your standard warranties. Service levels and response times for HP



Overview

Care Packs may vary depending on your geographic location. Restrictions and limitations apply. Service starts at date of hardware purchase. For details, visit http://www.hp.com/go/cpc.

NOTE: Certain restrictions and exclusions apply. Consult the HP Customer Support Center for details. http://h20000.www2.hp.com/bizsupport/TechSupport/ProductRoot.jsp



OPERATIVE SYSTEM

Preinstalled

Windows 10 Professional (64-bit)*
Windows 10 IoT Enterprise 2016 LTSB 64-Value¹
Windows 10 IoT Enterprise 2019 LTSC 64-bit
FreeDOS

Available for download

Android 8.1

Certified: SUSE Linux Enterprise Desktop YES Certified

https://www.suse.com/nbswebapp/yesBulletin.jsp?bulletinNumber=147394 https://www.suse.com/nbswebapp/yesBulletin.jsp?bulletinNumber=147325

* Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows 10 is automatically updated, which is always enabled. ISP fees may apply and additional requirements may apply over time for updates. See http://www.windows.com.

PROCESSOR

Intel® 7th generation Core™ and Pentium® processors

- Intel® Pentium® 4410Y
- Intel[®] Core[™] M3-7Y30
- Intel® Core™ i5-7Y57 vPro™**



^{*} Chipset is integrated with processor.

^{*} Multi-Core is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Intel's numbering is not a measurement of higher performance.

^{**}vPRO[™] is only supported on the HP Engage Go Mobile (Intel[®] Core[™] i5-7Y57 processor) in wireless mode when configured with the Intel WLAN 8265 with vPRO[™] Card. Some functionality of this technology, such as Intel Active management technology and Intel Virtualization technology, requires additional 3rd party software in order to run. Availability of future "virtual appliances" applications for Intel vPro technology is dependent on 3rd party software providers. Compatibility with future "virtual appliances" is yet to be determined.

MEMORY

Memory Soldered Down LPDDR3 1866 253 ball Supports Dual Channel Memory Supports up to 8GB

LPDDR3 1886: 4096 MB Total System Memory 8192 MB Total System Memory

* Onboard memory not customer accessible/upgradeable

STORAGE

Internal Storage Device

Supports M.2 SSD SS 2280

M.2 128GB SATA-3 SS TLC M.2 256GB PCle Gen3x4 NVMe SS TLC

* GB = 1 billion bytes. Actual formatted capacity is less.

DISPLAY

Internal

12.3" diagonal capacitive multi-touch, WUXGA+ BV WLED UWVA 72% 400 nits eDP 1.4 +PSR Ultraslim (1920x1280), featuring Corning® Gorilla® Glass 4

Display response time: 25ms

Contrast Ratio: 800:1 Refresh Rate: 60Hz

Features:

- 1920x1280 High Definition (FHD)* resolution**
- 3:2 aspect ratio
- Brightness (typical) 400nits (cd/m²)***
- 10-point capacitive touch solution, direct bonding
- Anti-smudge with Corning® Gorilla® Glass 4



^{*}High definition (HD) content is required to view high-definition images

^{**}Resolutions are dependent upon monitor capability, and resolution and color depth settings.

^{***} All specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.

GRAPHICS

Intel UMA Graphics (GT2) - with shared video memory*

*Shared video memory (UMA) uses part of the total system memory for video performance. System memory dedicated to video performance is not available for other use by other programs.

NETWORKING/COMMUNICATIONS

Integrated Wi-Fi*

Intel Wireless-AC 8265 802.11ac 2x2 WiFi + BT4.2 Combo Adaptor (non-vPro¹) Intel Wireless-AC 8265 802.11ac 2x2 WiFi + BT4.2 Combo Adaptor (vPro¹)

WLAN Antennas (2) (configured with panel on all units)

Bluetooth® Disabled IOPT

Support for Miracast

Supports WLAN/LAN/WWAN switching

Support HP Connection Optimizer with WiFi Load balancing

Support S3/S4 Wake on Wireless LAN

Support for DYNAMIC WiFi SAR in BIOS

Disclaimer required to document that Dynamic Regulatory Solution, will auto-change AC WLAN to abgn by passive scan when entering Indonesia.

NOTE: In Android 8.1 product release WWAN is not supported

WWAN**

LTE CAT4: Huawei HP lt4132, LTE/HSPA+ w/GPS M.2 LTE CAT9: Qualcomm® Snapdragon X12 LTE-Advanced

SIM Module: (user-accessible on side of slate) (4FF/nano SIM). (SIM module installed in factory when Service Provider is configured)

WWAN Antennas (2)

WWAN cards are compatible with a programmable removable eSIM

WWAN and BCS configurations are mutually exclusive

GPS

U-Blox GPS EVA-M8M M.2/USB

GPS and WWAN configurations are mutually exclusive

NFC

NXP NPC300 Near Field Communication Module

*Wireless cards are optional or add-on features and requires separately purchased wireless access point and internet service. Availability of public wireless access points limited. The specifications for the 802.11ac WLAN are draft specifications and are not final. If the final specifications differ from the draft specifications, it may affect the ability of the system to communicate with other 802.11ac WLAN devices.

**WWAN is an optional feature and requires factory configuration? WWAN use requires separately purchased service contract. Check with service provider for coverage and availability in your area. Connection speeds will vary due to location, environment, network conditions, and other factors. 4G LTE not available on all products, and in all regions.

¹vPRO™ is only supported on the HP Engage Go Mobile (Intel® Core™ i5-7Y57 processor) in wireless mode when configured with the Intel WLAN 8265 with vPRO™ Card

NOTE: In Android 8.1 product release vPro is not supported



AUDIO/MULTIMEDIA

Audio

HD Audio Audio Solution Codec CX7750 Stereo Speakers (2)

Cameras

RGB Camera:

Front facing camera 5MP with webcam LED indicator

Back Camera: 8MP

NOTE: In Android 8.1 product release Video recording is not supported

Sensors

Accelerometer Gyroscope Ambient light sensor Magnetometer

POWER

Power Supply

HP 65W USB Type-C™ AC Adapter non-PFC, Length: DC = 1.8m - Supports HP Fast Charging

Battery*

4-cell Long Life Polymer 47Whr (3.055Ahr) - Supports HP Fast Charging Battery life: Up to 12 hours

*Windows 10 MM14 Battery life will vary depending on various factors including product model, configuration, loaded applications, features, use, wireless functionality, and power management settings. The maximum capacity of the battery will naturally decrease with time and usage. See http://www.bapco.com/ for additional details.

MTBF: Red laser aimer: 378,000 hours

MOTION TOLERANCE up to 584 cm [230 in] per second in total darkness with 100% UPC at 10 cm [4 in] distance

FIELD OF VIEW Standard Range (SR): 42.4° (H) x 33° C (V)

Extended Range (ER): 35.6° (H) x 27.5° C (V)

SCAN ANGLES 360° , pitch: $\pm 45^{\circ}$, skew: $\pm 60^{\circ}$

SYMBOL CONTRAST 20% minimum reflectance

Supported Symbologies

Linear: UPC/EAN/JAN, GS1 DataBar, Code 39, Code 128, Code 32, Code 93, Codabar/NW7, Interleaved 2 of 5, Code 2 of 5, Matrix 2 of 5, MSI, Telepen, Trioptic, China Post

2D Stacked: PDF417, MicroPDF417, GS1 Composite

2D Matrix: Aztec Code, Data Matrix, QR Code, Micro QR Code, MaxiCode, Han Xin Cod

Postal: Intelligent Mail Barcode, Postal-4i, Australian Post, British Post, Canadian Post, Japanese Post, Netherlands (KIX) Post,

Postnet, Planet Code



Features

OCR Option: OCR-A, OCR-B, E13B (MICR)



Features

READ RANGES 1				
Symbology	Standard Rai	nge (Typical)	Extended Ra	nge (Typical)
	Start (mm/[in])	Stop (mm/[in])	Start (mm/[in])	Stop (mm/[in])
C39 5mil	64 [2.5]	163 [6.4]	96,5 [3.8]	283 [11.1]
C39 10mil	28 [1.1]	338 [13.3]	72 [2.8]	551 [21.7]
UPC-A 13mil	46 [1.8]	419 [16.5]	51 [2.0]	559 [22.0]
C39 20mil	_	-	56 [2.2]	819 [32.2]
PDF 417 6.7mil	46 [1.8]	185 [7.3]	127 [5.0]	232 [9.1]
QR 20mil	-	-	45 [1.8]	516 [20.3]
DM 10mil	53 [2.1]	203 [8.0]	120 [4.7]	282 [11.1]

¹ Barcode quality and environmental conditions may affect performance.



Technical Specifications

SOFTWARE AND SECURITY

BIOS

HP BIOSphere Gen49

Secure Erase

Absolute Persistence Module¹

Allow BIOS Rollback

HP DriveLock & Automatic DriveLock

Hardware Root or Trust

HP BIOS Protection (NIST 800-147)

HP SpareKey

Hybrid Boot

Master Record Security

Measured Boot

Power On Authentication

Pre-Boot Security

Connectivity

HP MAC Address Manager

HP Connection Optimizer v2

iPass

Platform Enabling Apps & Support

HP 3D DriveGuard *

HP Hotkey Support

HP JumpStart

HP Notifications

HP Recovery Manager

HP Support Assistant⁴

HP LAN/WLAN/WWAN switching

HP Power Manager * (w/ thermals support)

Microsoft Products

Buy Office

Bing Search

Skype²

Client Security Software

HP Client security Gen36

Intel Authenticate v2.5

HP Sure Click⁷

HP Sure Start Gen48

Manageability



Technical Specifications

Intel vPro (Core i5 SKU only)

HP Smart Dock

HP Client Security

HP MAC Address Manager

HP PC Hardware Diagnostics

HP Windows Hardware Diagnostics

HP Support Assistant

HP Softpag Download Manager

Discover HP Touchpoint Manager

HP Driver Packs (quarterly)3

HP System Software Manager (SSM)3

HP BIOS Config Utility (BCU)3

HP Client Catalog³

HP Client Integration Kit (CIK)

HP Client Security & Intel Authenticate

Microsoft Device Guard¹⁰

Credential Guard¹⁰

TPM config management

HP Audio Control

HP Power Manager

HPIA Integration & Recipes

Recipes

HP MIK for Microsoft SCCM Gen 2.55

HP Image Assistant Gen3

For more information on HP Client Management Solutions refer to: http://www.hp.com/go/clientmanagement.

Standard

TPM 2.0 SLB9670 (Infineon; soldered down)
Drive encryption pre-boot (Password)

Optional

HP Fingerprint Reader - Crossmatch

- 1. BIOS Absolute Persistence module is shipped turned off, and will be activated when customers purchase and activate a subscription. Service may be limited. Check with Absolute for availability outside the U.S. The optional subscription service of Absolute Recovery Guarantee is a limited warranty. Certain conditions apply. For full details visit: http://www.absolute.com/company/legal/agreements/computrace-agreement. If Data Delete is utilized, the Recovery Guarantee payment is null and void. In order to use the Data Delete service, customers must first sign a Pre-Authorization Agreement and either create a PIN or purchase one or more RSA SecurID tokens from Absolute Software. 2. Skype is not offered in China.
- 3. Not preinstalled, however available for download at http://www.hp.com/go/clientmanagement
- 4. Requires Windows and Internet Access
- 5. HP Manageability Integration Kit can be downloaded from

http://www8.hp.com/us/en/ads/clientmanagement/overview.html

- 6. Requires Windows and Intel®.
- 7. HP Sure Click is available on select HP platforms and supports Microsoft® Internet Explorer, Google Chrome, and Chromium™. Supported attachments include Microsoft Office (Word, Excel, PowerPoint) and PDF files in read only mode. Check http://h20195.www2.hp.com/v2/GetDocument.aspx?docname=4AA7-0922ENW for all compatible platforms as they become available.
- 8. HP Sure Start Gen4 is available on the HP Engage Go Mobile equipped with 7th generation Intel® processors.
- 9. HP BIOSphere Gen4 is available on the HP Engage Go Mobile equipped with 7th generation Intel® processors.
- 10. Microsoft Device Guard and Credential Guard are available with Windows 10 IoT Enterprise delivered from HP or to customers with a volume license to use Windows 10 Enterprise. Microsoft Device Guard and Credential Guard are not



Technical Specifications

available with Windows 10 Pro. The installation of Windows 10 Enterprise and Microsoft Device Guard and Credential Guard are available through HP Configuration & Deployment Services.

TEMPERATURE, HUMIDITY, ALTITUDE

Temperature Operating 41° to 95° F (5 to 35° C)

Non-operating -4° to 140° F (-20° to 60° C)

Relative humidity Operating 10 to 90%

(noncondensing)

Altitude Operating -50 to 10,000 ft (-15 to 3,048 m)
(unpressurized) Non-operating -50 to 40,000 ft (-15 to 12,192 m)

ENVIRONMENTAL DATA

Eco-Label Certifications & declarations	This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks: • IT ECO declaration • US ENERGY STAR® • EPEAT® Gold registered in the United States. See http://www.epeat.net for registration status in your country. See HP's 3rd party option store for solar energy accessory at http://www.hp.com/go/options .			
System Configuration	The configuration used for the En Notebook model is based on a "Ty			se Emissions data for the
Energy Consumption (in accordance with US ENERGY STAR® test method)	115VAC, 60Hz	230VAC,		100VAC, 60Hz
Normal Operation (Short idle)	5.62 W	5.87	W	5.76 W
Normal Operation (Long idle)	3.48 W	3.18	W	3.10 W
Sleep	0.49 W	0.61 W		0.57 W
Off	0.46 W	0.42	W	0.46 W
Heat Dissipation*	NOTE: Energy efficiency data listed is family. HP computers marked with th Environmental Protection Agency (EP offer ENERGY STAR® compliant configeaturing a hard disk drive, a high effi	e ENERGY STAR® Logo A) ENERGY STAR® spe Jurations, then energy	o are compliant wi cifications for con refficiency data lis and a Microsoft W	th the applicable U.S. nputers. If a model family does not sted is for a typically configured PC
Normal Operation (Short idle)	19 BTU/hr	20 BTU		20 BTU/hr
Normal Operation (Long idle)	12 BTU/hr	11 BTU/hr		11 BTU/hr
Sleep	2 BTU/hr	2 BTU,		2 BTU/hr
Off	BTU/hr	1 BTU,		1 BTU/hr
	NOTE: Heat dissipation is calculated to one hour.	ased on the measure	d watts, assuming	the service level is attained for
Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)	Sound Power (L _{WAd} , bels)			Sound Pressure (L _{pAm} , decibels)
Typically Configured – Idle	2.5		15	



Technical Specifications

Fixed Disk – Random writes		2.6	15
Longevity and Upgrading	This product can be upgraded, possibly extending its useful life by several years. Upgradeable features and/or components contained in the product may include: • 3 USB ports • 1 PC card slot (type I/II) • 1 ExpressCard/54 slot • 1 IEEE 1394 Port • 2 SODIMM memory slots • Optional expansion base docking station • 1 multi-bay II storage port • Interchangeable HDD Spare parts are available throughout the warranty period and or for up to "5" years after the end of		
Batteries	production. This battery(s) in this product comply with EU Directi	ive 2006/66/EC
	Mercury great Cadmium great Battery size: Battery type		
Additional Information	 Battery life: Up to 12 hours This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2011/65/EC. This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive – 2002/96/EC. This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986). This product is in compliance with the IEEE 1680 (EPEAT) standard at the <gold> level, see http://www.epeat.net</gold> Plastics parts weighing over 25 grams used in the product are marked per ISO11469 and ISO1043. This product contains 8.4% post-consumer recycled plastic (by wt.) This product is 95.9% recycle-able when properly disposed of at end of life. 		
Packaging Materials	External:	PAPER/Corrugated	310 g
	Internal:	PAPER/Paperboard PLASTIC/Polyethylene Expanded - EP PLASTIC/Polyethylene low density - L	
Material Usage	to the HP Geinttp://www.l Asbestos Certain Azo Certain Bro Cadmium Chlorinated Formaldeh Halogenate Lead carbo Lead and Lo Mercuric Ox	neral Specification for the Environment of hp.com/hpinfo/globalcitizenship/environ Colorants Colorants Minated Flame Retardants — may not be a Hydrocarbons Minated Flame Retardants — may not be a Hydrocarbons Minated Flame Retardants — may not be a Hydrocarbons Minated Flame Retardants — may not be a Hydrocarbons Minated Flame Retardants — may not be a Library Minated Fl	nment/pdf/gse.pdf) :



Technical Specifications

	Ozone Depleting Substances
	Polybrominated Biphenyls (PBBs)
	Polybrominated Biphenyl Ethers (PBBEs)
	Polybrominated Biphenyl Oxides (PBBOs)
	Polychlorinated Biphenyl (PCB)
	Polychlorinated Terphenyls (PCT)
	Polyvinyl Chloride (PVC) — except for wires and cables, and certain retail packaging has been
	voluntarily removed from most applications.
	• Radioactive Substances
Darlanda Harris	• Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)
Packaging Usage	HP follows these guidelines to decrease the environmental impact of product packaging:
	• Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.
	Eliminate the use of ozone-depleting substances (ODS) in packaging materials.
	Design packaging materials for ease of disassembly.
	Maximize the use of post-consumer recycled content materials in packaging materials.
	Use readily recyclable packaging materials such as paper and corrugated materials.
	Reduce size and weight of packages to improve transportation fuel efficiency. Reduce size and weight of packages to improve transportation fuel efficiency.
	Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.
End-of-life Management	HP Inc. offers end-of-life HP product return and recycling programs in many geographic areas. To
and Recycling	recycle your product, please go to: http://www.hp.com/go/reuse-recycle or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.
	The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: http://www.hp.com/go/recyclers. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM
HP Inc. Corporate	customers who integrate and re-sell HP equipment. For more information about HP's commitment to the environment:
Environmental	ו או הוסוב ווויסוחומנוטוו מטטענ דור 5 נטוווווונווופוונ נט נוופ פוועווטוווופוונ.
Information	Global Citizenship Report
yı mutivii	http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html
	Eco-label certifications
	http://www8.hp.com/us/en/hp-information/environment/ecolabels.html
	ISO 14001 certificates:
	http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/PC_GBU_Product_Design_ISO_14K_
	Certificate.pdf
	and
	http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf

EPEAT® Gold1

ENERGY STAR® certified**

Low halogen*

508 compliance

Mercury-free display backlights and arsenic-free display glass

All HP computing products are delivered by SmartWay carriers***

Recycled Packaging



Technical Specifications

The plastic recycled content is equal to, or greater than 90%.

The main cushions for the HP Engage Go Mobile unit and HP Engage Go Dock stand are made from 100% recycled expanded polyethylene.

Eligible for free recycling or cash back through HP's Planet Partners Recycling and Consumer Buyback programs (http://www.hp.com/go/easybuyback)****

HP Corporate Environmental Information

For more information about HP's commitment to the environment:

Global Citizenship Report

http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html

Environment website: http://www.hp.com/environment

- 1. EPEAT® registered where applicable. EPEAT registration varies by country. See www.epeat.net for registration status by country. See HP's 3rd party option store for solar energy accessory at www.hp.com/go/options.
- * External power supplies, power cords, cables and peripherals are not Low Halogen. Service parts obtained after purchase may not be Low Halogen.
- ** ENERGY STAR® is a registered trademark of the U.S. Environmental Protection Agency.
- *** Designation based on actions to reduce transportation-related emissions. SmartWay: US only. (14e) Free recycling in select countries.
- **** Program may not be available in your area. Check http://www.hp.com/go/recycling to see if HP offers free recycling in your area

HP ENGAGE GO CONVERTIBLE SANITIZATION TESTING RESULTS

You can use the following chemical compositions * to clean all exposed surfaces of the HP Engage Go Convertible (tablet only).

- Turn off your device
- Disconnect any external devices
- Dust the device by wiping with a soft, clean antistatic cloth

IMPORTANT: The cloth should be moist, but not wet. Water dripping into the ventilation or other points of entry can cause damage to your device. Allow the unit to air-dry before use.

- Benzyl-C12-18-alkyldimethyl ammonium chlorides: <0.1%
- Quaternary ammonium compounds, C12-14-alky[(ethylphenyl)methyl]di methyl, chlorides: <0.1%
- Isopropanol: 10-20%
- 2-Butoxyethanol: <5%
- Quaternary ammonium compounds, C12-14-alky[(ethylphenyl)methyl]di methyl, chlorides: <0.5%
- Benzyl-C12-18-alkyldimethyl ammonium chlorides: <0.5%
- Quaternary ammonium compounds, C12-14-alky[(ethylphenyl)methyl]di methyl, chlorides: <0.5%
- Benzyl-C12-18-alkyldimethyl ammonium chlorides: <0.5%
- Isopropyl alcohol: 55.0%
- Alkyl dimethyl benzyl ammonium chlorides: 0.25%
- Alkyl (68% C12, 32% C14) dimethyl ethylbenzyl ammonium chloride: 0.25%
- Isopropyl alcohol: 10-20%
- Ethylene Glycol Monobutyl Ether (2-Butoxyethanol): 1-5%
- Diisobutylphenoxyethoxyethyl dimethyl benzyl ammonium chloride: 0.1-0.5%
- Sodium hypochlorite: 0.1%-1.0%
- Cellulose: 10-30%



Technical Specifications

- Ethyl alcohol: 0.10-1%
- Isopropyl alcohol: 30-40%
- Water: 60-70%

Please do not use cleaners that contain any petroleum-based materials such as benzene, thinner, or any volatile substance to clean the display screen. These chemicals may damage the display

*Compounds tested as of August 19, 2018. Repeated use of these cleaning compounds may cause some cosmetic changes to the product

COUNTRY OF ORIGIN

China



Options and Accessories (sold separately and availability may vary by country)

<u>Type</u>	Description	Part #
Case	HP Engage Go Mobile Retail Case	3VM86AA
	HP Engage Go Mobile Retail Case w/ MSR	3VM87AA
Jacket	HP Engage Go Jacket iSMP4	5LX96AA
	HP Engage Go Jacket iSMP4 B	5LX97AA
	HP Engage Go Jacket MSR+SCR+OCR+BCS	5LY00AA
	HP Engage Go Jacket MSR+SCR	5LY01AA
	HP Engage Go Jacket MSR+SCR+BCS	5LY02AA
	HP Engage Go Jacket (Base Jacket)	5PR24AA
Docking	HP Engage Go Dock Black	5JG51AA
-	HP Engage Go Dock White	5JG52AA
	5.5	
Input/Output	HP Engage Go Advanced I/O Connectivity Base	5LT84AA
	HP Engage Go Basic I/O Connectivity Base	5LT86AA
	HP Engage Go Advanced I/O Connectivity Base White	5LT85AA
	HP Engage Go Basic I/O Connectivity Base White	5LT87AA
Printer	HP Engage One Serial USB Thermal Printer	1RL96AA
	HP Ethernet Network Receipt Printer	M2D54AA
	HP Value Serial/USB Receipt Printer II	X3B46AA
	HP PUSB Thermal Receipt Printer	FK224AA
	Epson TMT88V Serial USB Thermal Receipt Printer	D9Z52AA
California Carrata and alama	UD Forman One Defented USD a Dear Adents	1PM02AA
Cable kits for standalone printer	HP Engage One Printer USB + Pwr Adpter	1RM02AA
princei	HP Engage One Printer Serial + Pwr Adptr	1RM03AA
	HP Engage One Printer PUSB Y Cable	BM477AA
	HP Engage One Printer Serial + PUSB Pw only	1RM05AA
Barcode Scanners	HP Engage One 2D Barcode Scanner	1RL97AA
	HP Linear Barcode Scanner II	Z1Z36AA
	HP Imaging Barcode Scanner	BW868AA
	HP Presentation Barcode Scanner	QY439AA
	HP Wireless Barcode Scanner	E6P34AA
Cash Drawers	HP Flip Top Cash Drawer	BW867AA
	HP Heavy Duty Cash Drawer	FK182AA
	HP Standard Duty Cash Drawer	QT457AA
	HP USB Standard Duty Cash Drawer	E8E45AA
	HP Standard Duty Till Insert w/ Lockable Lid	QT458AA
	HP Cable Pack for Dual HP Cash Drawers	QT538AA
	THE CUBIC FUCKTOR DUUCTII CUBII DIGWEIS	אטכנוץ



Options and Accessories (sold separately and availability may vary by country)

Hub Covers	HP Engage One Hub Cover Black	5DS16AA
	HP Engage One Hub Cover White	5DS17AA
Mount Kits	HP Engage One Undercounter Mount Kit	5DS15AA
I/O Devices, I/O Adapters	HP USB Business Slim Keyboard	N3R87AA
	HP USB 1000dpi Laser Mouse	QY778AA
	HP Engage One Fingerprint Reader	1RL98AA
Pen	HP Active Pen with App Launch	T4Z24AA
	HP Rechargeable Active Pen	4KL69AA
	HP Active Pen	T5E12AA
Graphics Video Adapters &	HP Type-C™ to VGA Adapter	N9K76AA
Cables	HP Engage USB-C™ to HDMI Adapter	6FV70AA
	HP USB-C™ to RJ45/USB 3/USB-C™	N2Z64AA
	HP USB-C™ to USB 3.0 Adapter	N2Z63AA
Display	HP Engage One 10.1in Touch Display	1XD81AA
	HP Engage One 10.1in Non-Touch Display	1XD80AA
Power	HP 65W USB-C™ AC Adapter	TBD



Summary of Changes

Date of change:	Version History:		Description of change:
August 20, 2018	From v1 to v2	Changed	Format
August 30, 2018	From v2 to v3	Added	Footnotes for Power and Software sections
November 19, 2018	From v3 to v4	Added	HP Engage Go Advanced I/O Connectivity Base White and HP Engage Go Basic I/O Connectivity Base White
February 11, 2019	From v4 to v5	Added	HP Engage Go Jacket & HP Engage USB-C to HDMI Adapter
March 6, 2019	From v5 to v6	Added	Batery life, Metric values & Accessories updated
April 4, 2019 From v6 to v7		Added	Supported Symbologies section
		Changed	Memory section, Metric values
April 12, 2019 From v7 to v8		Added	TEMPERATURE, HUMIDITY, ALTITUDE & Connectivity bases sections
		Changed	Software, DIMENSIONS AND WEIGHT sections
June 13, 2019	From v8 to v9	Added	HP Engage Go Convertible Sanitization Testing Results section
		Changed	OPERATIVE SYSTEM and DISPLAY sections
July 31, 2019	From v9 to v10	Added	Android support
August 5, 2019	From v10 to v11	Changed	OPERATIVE SYSTEM section, SUSE Linux Enterprise Desktop YES Certified
August 22, 2019	From v11 to v12	Changed	Format page 14 and 15



Copyright © 2019 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Intel, Pentium and Core m3 are registered trademarks or trademarks of Intel Corporation in the U.S. and/or other countries. Bluetooth is a trademark of its proprietor and used by HP Inc. under license. Microsoft and Windows are U.S. registered trademarks of the Microsoft group of companies. ENERGY STAR® is a registered mark owned by the U.S. Environmental Protection Agency. USB Type-C™ and USB-C™ are trademarks of USB Implementers Forum.SD, SDXC, and MicroSD, are trademarks or registered trademarks of SD-3C in the United States, other countries or both.

