

HBB FUEL TRAIN

HBB is our classic design, offering on/off control as well as a safe, soft start. Double-block, inline gas-rated 6.5 C/I approved solenoids and a slow-opening control valve equip your appliance with safe ignition, soft start, and emergency shutdown. This fuel train is designed for applications between 0 to 3.5 MMBTU where simple on/off operation is desired.

HIGHLIGHTS & FEATURES


- Completely pre-assembled
- Double-block main shutdown
- Slow-opening TCV for soft start-up
- Z21.21, 6.5 C/I approved solenoids
- Main and pilot regulators

- 2000 WOG stainless ball valves
- 316 stainless dual ferrule tubing fittings
- Stainless, liquid-filled pressure gauges
- 2000 PSI SA105 fittings
- Low power draw

PROFIRE INLINE FUEL TRAIN SERIES (IFTS)

As the industry leader in burner management solutions, we offer the inline fuel train series, providing end users:

- True 'plug and play' solutions
- Streamlined and standardized options
- More efficient ordering and procurement
- More efficient installation



HBB FUEL TRAIN OPTIONS

KEY • STANDARD O OPTIONAL	n/a NOT AVAILABLE
SOLENOIDS	
ASCO	•
Peter Paul	0
ELECTRICAL ASSEMBLY	
Standard	•
Quick Disconnect	0
POWER SUPPLY	
12VDC	0
24VDC	0
SOLAR PACKAGE	0
PRESSURE TRANSMITTER	0
ASSEMBLY OPTIONS	
Double Skid Stand	0
Single Skid Stand	0
Quick Stand	n/a
Without Stand	•

HBB ASSEMBLY OPTIONS



HBB COMPATIBLE (BMS) CONTROLLERS



KEY • STANE	DARD O OPTIC	DNAL n/a NOT AVAILABLE
PF3100		0
PF2100		0
PF1800		0