

SuperChassis 835TQ-R800B

[Products](#) > [Chassis](#) > [3U](#) > [[SC835TQ-R800B](#)]



Note: Image above may show a varied configuration or optional parts. Please refer to parts list for standard parts included.

Key Features

Versatile Storage Chassis with High Efficiency Power

1. 800W Redundant Power Supply
2. 8x 3.5" Hot-swap SAS / SATA & 2x 5.25" Drive Bays
3. 1x Slim DVD-ROM Drive
4. 7x Full-height, Full-length Expansion Slots
5. 100% Cooling Redundancy
6. Adjustable Air Shroud

Please Note: Full SES2 Support is only available on SAS motherboards

Downloads

Chassis Manual



Specifications

Product SKUs

CSE-835TQ-R800B ■ SuperChassis 835TQ-R800B (Black)

Form Factor

3U chassis support for max. motherboard size - 13.68" x 13"

Processor Support

Supports dual, single Intel® / AMD processors

Dimensions

Height 5.2" (132mm)
Width 17.2" (437mm)
Depth 25.5" (648mm)
Gross Weight 75 lb (34.02 kg)
Available Colors Black

Expansion Slots

• 7x full-height full-length expansion slots

Drive Bays

Hot-swap 8x 3.5" SAS / SATA Hot-swap drive trays
 SAS or enterprise SATA HDD only recommended

SAS / SATA Backplane

1x 2U SAS / SATA Backplane with Enclosure Management

Peripheral Drives

DVD-ROM Slim DVD-ROM Drive

Front Panel

Buttons

- Power On/Off button
- System Reset button

LEDs

- Power LED
- Hard drive activity LED
- 2x Network activity LEDs

System Cooling

Fans

- 3x 80mm Hot-swap PWM Fans
- 2x 80mm Rear-exhaust PWM Fans

System Monitoring

Chassis intrusion switch

Operating Environment (System)

Operating Temperature Range ■ 5°C ~ 35°C (41°F ~ 95°F)
Non-Operating Temperature Range ■ -40°C ~ 60°C (-40°F ~ 140°F)
Operating Relative Humidity Range ■ 8% ~ 90% (non-condensing)
Non-Operating Relative Humidity Range ■ 5% - 95% (non-condensing)

Power Supply and Distributor

800W (1 + 1) Redundant AC-DC high-efficiency power supply w/ PFC

AC Voltage ■ 100 - 240V, 50-60Hz, 10-4 Amp
+5V standby ■ 4 Amp
+12V ■ 66 Amp
With Power Distributor

- +5V: 30 Amp
- +3.3V: 24 Amp
- -12V: 0.6 Amp

Regulatory (Power Supply)

Power Supply Safety / EMC

- USA - UL listed
- Canada - CUL listed
- Germany - TUV Certified
- EN 60950/IEC 60950-Compliant
- CB Report
- CCC Certification


- System Overheat LED
- Power fail LED

Components

Standard Parts List

	Part Number	Qty	Description
Chassis	CSE-835TQ-R800B	1	3U Chassis (Black)
Backplane	CSE-SAS-833TQ-O-P	1	SAS833 BACK PANEL WITH AMI MG9072
Cable 1	CBL-0044L	4	SATA CABLE 61CM FLAT S-S PBF. 26AWG flat
Power Supply	PWS-801-1R	2	800W,1U,12V OUTPUT POWER SUPPLY
Power Distributor	PDB-PT825-8824	1	SC825 24PIN REDUNDANT POWER DISTRIBUTOR
Air Shroud	MCP-310-39001-0N	1	SC835/836/936 Intel DP X9, X8 PC air shroud 1368x13/12x13MB
Accessory	ACC835-01-2B	1	Accessory Box for SC835 with two power cord and FDD acc.
Cable 2	CBL-0071L	1	ROUND 16 pin TO 16 PIN RIBBON FP CABLE 30
Cable 3	CBL-0216L	5	4 PIN TO 4 PIN MIDDLE FAN POWER EXTENSION, 20cm. 24AWG (PWM)
Peripheral Drive 1	DVM-PNSC-DVD-SBT3	1	BLACK PANASONIC SLIM DVD ROM SATA DRIVE,HF,RoHS/REACH
Fan 1	FAN-0126L4	3	80x80x38 mm 7K RPM Chassis Middle Fan w/ Housing
Fan 2	FAN-0125L4	2	80x32 mm 6.7K RPM SC836 Rear Exhaust Fan w/ Housing
Drive Tray(s)	MCP-220-00009-01	2	Black 5.25
Drive Tray(s)	MCP-220-00075-0B	8	Black gen 5.5 hot-swap 3.5" HDD tray
Mounting Rails	MCP-290-00053-0N	1	Rail set, quick/quick, default for 2,3U 17.2" W

Optional Parts List

	Part Number	Qty	Description
Heatsink / Retention	-	-	Please refer to our Thermal Components Matrix
Mounting Rails	MCP-290-00058-0N	-	19" to 26.6" rail set, Quick Release, Tool-less
Cable Management Arm	MCP-290-00073-0N	-	Supermicro Cable Management Arm for 2U, 3U and 4U chassis (Extendable Length: 70mm to 830mm)
Peripheral Drives	FPD-TEAC-SB	-	TEAC 3.5" 1.44MB Slim Floppy Drive (Black)
	MCP-220-82503-0B	-	Slim floppy accessory kit
	MCP-290-83301-0B	-	DVD Dummy Cover (Black)
	CSE-PT40L-B0	-	Black USB/COM port tray (MCP-220-82503-0B required)
Peripheral Drives	DVM-TEAC-DVD-SBT3	-	Black slim SATA DVD (8x DVD, 24x CDR), TEAC
	MCP-220-81502-0N	-	Slim SATA DVD kit (include backplane, cable)
Front Bezel (Compatibility Table)	MCP-210-83501-0B	-	 Front Bezel Cover, Black (optional)
Adaptor HDD carrier	MCP-220-00043-0N	-	Adaptor HDD carrier to install 2.5" HDD in 3.5" HDD tray

[Terms & Conditions](#) | [Privacy](#) | [Investor Relations](#) | [Jobs](#) | [Site Map](#)
[SuperServer®](#) | [Motherboard](#) | [Chassis](#) | [Rack Cabinet](#) | [SuperBlade®](#) | [Embedded](#) | [Networking](#) | [Storage](#) | [Accessories](#) | [AMD Solution](#) | [Power Supplies](#)

Copyright © 2014 Super Micro Computer, Inc.

Information in this document is subject to change without notice.
 Other products and companies referred to herein are trademarks or registered trademarks of their respective companies or mark holders.