

IN1142

LightPro™ Mobile LED Projector

Part#: IN1142

InFocus
Collaboration That Works

Touchboards

205 Westwood Ave, Long Branch, NJ 07740
Phone: 866-94 BOARDS (26273) / (732)-222-1511
Fax: (732)-222-7088 | E-mail: sales@touchboards.com

Easy, from the word “Go!”

If you're going mobile, take the InFocus LightPro™ IN1142 with you. Our smallest, lightest and most affordable LED projector also features the longest-lasting light source we've ever offered. At about the size of a paperback book and less than two pounds, the IN1142 is easy to pack in your bag and carry on.

Better still, this lampless model makes maintenance easy—or nonexistent—with a light-emitting diode (LED) that lasts up to 30,000 hours. So you can go from place to place, presentation to presentation, without ever giving your projector a thought.



Connectivity

HDMI w/audio and MHL 1.2
USB Type A (for service only)
3.5mm audio out

Why choose the LightPro IN1142?

- Incredible value
- 30,000-hour LED light source
- Only 1.76 pounds (0.8 kg)
- 700 lumens of brightness
- WXGA (1280 x 800) widescreen resolution
- HDMI input with audio and MHL 1.2 compatibility
- Striking image quality and contrast
- Auto keystone correction

Long-lived lampless light

How long will the light source of IN1142 LED projector really last? The LED is rated for up to 30,000 hours—so if you use it 4 hours a day, 5 days a week, 50 weeks a year, it'll last about 12 years. Until then, it's maintenance-free—not even a filter to clean or replace. And LED projectors even use less power than their conventional cousins, so you can feel more “green” too.



Striking color and contrast

LED projectors are known for their image stability and saturated colors. But the IN1142 features a high contrast of 10,000:1, so it's even better at vividly rendering fine detail and subtle color differences. Even ho-hum business graphics and content pop on the screen.



10,000:1

Present from laptop, tablet or smartphone

Quickly connect and present your content from your notebook, tablet or smartphone via the projector's HDMI port. Plus, the native widescreen resolution of the IN1142 means it's ready to display your HD content with incredible detail, contrast and color depth.



Ultra-simple operation

When giving a presentation, you don't want to focus on your projector too. The IN1142 is ready when you are. You don't even have to wait for it to warm up: it's on when you flip the switch. And auto keystone correction keeps your image square and true wherever you're projecting.



Auto Keystone
Correction

Specifications*

IN1142

| | |
|---------------------------------|---|
| Native Resolution | WXGA (1280 × 800) |
| Technology | DLP with LED light source |
| LED Life | 30,000 hours |
| Brightness | 700 lumens |
| Contrast Ratio | 10,000:1 |
| Aspect Ratio | 16:10 native, 16:9 and 4:3 compatible |
| Input Connections | HDMI 1.3 with audio and MHL 1.2 |
| Output Connections | 3.5mm audio out |
| Throw Distance | 35.4 - 94.5 in (0.9 - 2.4 m) |
| Throw Ratio | 1.4:1 |
| Image Width | 20 - 180 in (native 16:10) |
| Digital Zoom Ratio | 1.8:1 |
| Keystone Correction | ± 40° vertical |
| Video Compatibility | SDTV (NTSC, NTSC 4.43, PAL / M / N, SECAM, PAL60", 480i/p, 576i/p), HD (720p, 1080i) |
| H~Synch Range | 30.5 - 91.1 KHz |
| V~Synch Range | 50 - 85 Hz |
| Product Weight | 1.76 lbs (0.8 Kg) |
| Product Dimensions - W × D × H | 6.7 × 5.4 × 1.7 in (170 × 138 × 42.5 mm) |
| Shipping Weight | 4.4 lbs (2 kg) |
| Shipping Dimensions - W × D × H | 13 × 8.7 × 4.3 in (330 × 220 × 110 mm) |
| Speaker | 1 W × 1 |
| Power Consumption | 65 W (typical), < 0.5 W (standby) |
| Audible Noise | 32 dBA typical, 34 dBA maximum |
| Power Supply Range | 100V - 240V @ 50-60 Hz (65W) |
| Operating Temperature | 32 - 104° F (0 - 40° C) max |
| Operating Altitude | 0-7,500 feet @ 104° F / 7,500-10,000 feet @ 95° F |
| Operating Humidity | 10~85% RH without condensation |
| Standard Accessories | HDMI cable, carrying case, AC power adaptor, Remote control (no batteries), Documentation |
| Safety Certifications | FCC (US/Canada), CE (Europe), CB |
| OSD Languages | English, French, German, Spanish, Italian, Portuguese, Russian, Swedish, Dutch, Traditional Chinese, Simplified Chinese |

* Product specifications, terms, and offerings are subject to change at any time without notice.

Optional Accessories

- Presenter RF Remote with USB Receiver (HW-PRESENTER-2)
- Security Lock (SEC-LOCK-01)
- Cables and adapters
- Projection screens
- Extended warranties (PROJ-EW1YR-MC, PROJ-EW2YR-MC)

Warranty

The IN1142 projector comes standard with a 1-year factory warranty and a 90-day accessories warranty. Extended product warranty programs are available.



IN1142 Remote Control



Touchboards

205 Westwood Ave, Long Branch, NJ 07740
 Phone: 866-94 BOARDS (26273) / (732)-222-1511
 Fax: (732)-222-7088 | E-mail: sales@touchboards.com