

# EZ-CS-CV310-A0-1B2WFR

Ezviz 2 MP Wifi Camera  
Compression H.264  
2.8 mm lens / IR 30  
Bidirectional audio  
Siren and strobe light  
Suitable for exterior IP65



EZVIZ  
WiFi IP camera  
2Mpx (1920x1080) at 25 FPS  
Compression H.264  
2.8 mm Lens  
IR LED Range 30 m  
High quality bi-directional audio  
Integrated speaker and microphone  
MicroSD card slot up to 128 GB  
Active defense with siren and white light flash in the camera  
TCP/IP (RJ45) or WiFi 802.11b/g/n  
Large wifi coverage with outdoor antennas  
Suitable for exterior IP66  
EZVIZ CloudPlay Cloud Storage Service  
Ezviz app and EZ studio software

# Specifications

|                             |   |
|-----------------------------|---|
| <b>Brand</b>                | Ezviz   |
| <b>Model</b>                | CS-CV310-A0-1B2WFR  |
| <b>Image sensor</b>         | 1/2.7" Progressive Scan CMOS  |
| <b>Main stream encoding</b> | 1920x1080 at 25 FPS (default set to 720p)                               |
| <b>Lens</b>                 | 2.8 mm (Diagonal viewing angle 118°)                                    |
| <b>Minimum illumination</b> | 0.02Lux @ F2.0  |
| <b>Infrared lighting</b>    | 0 Lux / EXIR LEDs IR (30 m)   |
| <b>Audio</b>                | High quality bidirectional audio (microphone and speaker)               |
| <b>Network interface</b>    | Ethernet 10/100 BaseT and Wifi IEEE 802.11 b/g/n                        |
| <b>Internal memory</b>      | Supports microSD card (max. 128GB)                                      |
| <b>External storage</b>     | Ezviz NVR / CloudPlay cloud storage subscription option                 |
| <b>Remote access</b>        | EZVIZ App for Smartphone & Tablet and EZ Studio software                |
| <b>Deterrent alarm</b>      | Siren and white strobe light integrated in the camera (manual or event) |
| <b>Basic functions</b>      | OSD menu (remote), Day/Night with IR-CUT (ICR)                          |
| <b>Image improvements</b>   | DWDR, 3DNR, BLC, AGC  |
| <b>Power</b>                | DC 12 V / 500 mA  |
| <b>Degree of protection</b> | Weatherproof IP66   |
| <b>Temp. operation</b>      | -30° C ~ +60° C   |
| <b>Dimensions</b>           | 150.44 (D) x 71.64 (Ø) mm   |
| <b>Weight</b>               | 326 g   |