

IN5148HD

InFocus

Powerful, High-Performance Projector for Large Venues

Part #: IN5148HD

Captivate your audience with the high brightness, HD resolution and installation flexibility of the IN5148HD.

Key Features

- ◆ Crisp 1080p HD resolution for detailed presentations
- ◆ 5,000 lumens display bright, clear images in any light
- ◆ Large 1.49-3.02 throw ratio for flexibility to install at a variety of distances and adjust image size
- ◆ Motorized zoom, focus and horizontal and vertical lens shift
- ◆ Add the [LightCast Key](#) to wirelessly cast from any device or view documents
- ◆ HDBaseT Certified for greater interoperability



Install Where You Need It

The IN5148HD projector fits roughly 90% of pre-existing large-venue install applications, thanks to its flexible 1.49-3.02 throw ratio and 2:1 zoom ratio. Deliver outstanding high-resolution images in the size you need, with no more lenses to switch – plus shifting, focusing, and zooming have all been motorized.

LightCast Wireless Collaboration

Use the [LightCast Key](#) (sold separately) to easily connect and share content from your Apple, Windows, Android, or Chrome devices. Access the document viewer for PC-less presentation, and then browse the internet or use a digital whiteboard, all without connecting a device.*

* Wireless keyboard and mouse are recommended for digital whiteboard and internet browser usage.

High Brightness HD

Detailed, clear images make presentations better. The IN5148HD doesn't disappoint with a very bright 5,000 lumens and 1080p high-definition resolution. Your presentations will look as good on screen as they do on your computer display, even with the lights on.



Well Connected

HDBaseT Certification adds even more installation flexibility. With one LAN cable your projector can get HD digital video

and audio, 100BaseT Ethernet, USB 2.0, and various control signals from an HDBaseT device.



Specifications*

Projector	IN5148HD
Resolution – Native	Full HD (1920 x 1080)
Display Technology	DLP
Resolution – Compatibility	VGA, WVGA, SVGA, WSVGA, XGA, WXGA, SXGA, WSXGA+, WUXGA, WXGA+
Video Standard Compatibility	NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM, 480i, 480p, 576i, 720p, 1080i, 1080p
Speakers	Stereo 10W x 2
Lamp Brightness	5,000 lumens
Lamp Brightness – Low Power	4,000 lumens
Lamp Life	3,000 hours
Lamp Life – Low Power	4,500 hours
Lamp Power	365W
Lamp Power – Eco Mode	110W
Replacement Lamp	SP-LAMP-096
Contrast Ratio	12,000:1
Color Wheel	6 segment, 2x speed
Number of Colors	1.07 billion
Aspect Ratio	16:9
Aspect Ratio Compatibility	4:3, 16:10
Lens Type	Fully motorized
Lens Shift – Vertical (max)	+35% / -130%
Lens Shift – Horizontal (max)	+/-35%
Keystone Correction	+/- 40 degrees vertical
Connectors – Inputs	3.5mm stereo audio x2, HDMI 1.4 (rear), RJ45 (Ethernet) x2, Composite video, S-video, VGA x2, 3.5mm audio input x2
Connectors – Outputs	3.5mm audio output, Monitor out (VGA)
Audible Noise	< 32 dBA at 0°F / -17.8°C
Audible Noise – Eco Mode	< 30 dBA at 0°F / -17.8°C
Included Accessories	Power cord, Remote, VGA cable, Documentation
3D Support	720p @ 120Hz, 1080p @ 60Hz, All HDMI 1.4a 3D formats from Blu-Ray, DLP Link 3D glasses required
Product Warranty	2 years
Lamp Warranty	6 months
Accessories Warranty	90 days
Storage	4 GB
PC-less Compatibility	USB 2.0 Type-A x2, LightCast Key ready
Video Player Compatibility	AVI, 3GP, MP4, MPEG-1 (MPG, MPEG), QuickTime (MOV, QT), RealMedia (RM, RMVB)
Photo Viewer Compatibility	JPEG and JPG, PNG, Bitmap (BMP)
Music Player Compatibility	MP3, WMA, AAC, WAV
Power Standard	AC 100 to 240V, 50/60

Projector	IN5148HD
Operating Conditions	32 to 104°F at 0 to 10000 ft / 0 to 40°C at 0 to 3048 m
Menu Languages	English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Swedish, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Persian, Portuguese, Vietnamese, Czech, Romanian, Hungarian
Security Features	User PIN, Security bar, Security lock slot
Approvals	UL and c-UL, FCC, CE, CCC+CECP, KCC, NOM, PCT/CU/EAC, PSB, SABS, SASO, CB, Nemco/GS, KC
Throw and Zoom	
Throw Ratio – Minimum	1.49:1
Throw Ratio – Maximum	3.02:1
Zoom Ratio	2.0:1
Shipping	
Product Dimensions	6.6 x 19.3 x 12.4 in / 167.6 x 490.2 x 315 mm
Product Weight	19.5 lbs / 8.8 kg
Shipping Dimensions	9.5 x 22 x 18 in / 241.3 x 558.8 x 457.2 mm
Shipping Weight	23 lbs / 10.4 kg

* Product specifications, terms, and offerings are subject to change at any time without notice.

Accessories

- Universal Projector Ceiling Mount (PRJ-MNT-UNIV)
- Manual Pull Down Projector Screen: 106 in., 16:9 (SC-PDHD-106)
- Projector Lamp for IN5148HD (SP-LAMP-096)
- LightCast Key (INA-LCKEY1)
- LightCast Key (Europe) (INA-LCKEY2)
- LightCast Key (Asia-Pacific) (INA-LCKEY3)
- LiteShow 4 DB+ Dual Band Wireless Adapter (INLITESHOW4DB+)
- Replacement Remote for Meeting Room Projectors (HW-NAVIGATOR-4)
- Presenter 4 RF Remote with Laser Pointer (HW-PRESENTER-4)
- DLP Link 3D Glasses by XPAND (X103-EDUX3-R1)
- Projector Ceiling Mount System (Black) (PRJ-MNTKIT-UNIVB)
- Projector Ceiling Mount System (White) (PRJ-MNTKIT-UNIVW)
- VGA Cable (36 ft / 11 m) (SP-VGA-11M)
- Projector Lock by PC Guardian (SEC-LOCK-01)
- Manual Pull Up Projector Screen: 73 in., 16:9 (SC-PUW-73)
- 1 Year Extended Warranty for IN51XX, IN53XX Projectors (EPW-PJ1)
- 2 Year Extended Warranty for IN51XX, IN53XX Projectors (EPW-PJ2)