Overview


To remain competitive, IT organizations must keep pace with ever-increasing workloads without a similar increase in their budgets or resources. While virtualization has provided some relief by enabling the benefits of faster deployment and consolidation, it also tends to put additional stress on data center networks. In addition, the move toward cloud computing, which promises greater efficiency and a more service-oriented business model, means that these networks will face even greater demands.

The HP SN6000B Fibre Channel Switch meets the demands of hyper-scale, private cloud storage environments by delivering marketleading 16 Gb Fibre Channel technology and capabilities that support highly virtualized environments. Designed to enable maximum flexibility and investment protection, the SN6000B Switch is configurable in 24, 36, or 48 ports and supports 4, 8, 10, or 16 Gbps speeds in an efficiently designed 1U package. It also provides a simplified deployment process and a point-and-click user interfacemaking it both powerful and easy to use. The SN6000B Switch offers low-cost access to industry-leading Storage Area Network (SAN) technology while providing "pay-as-you-grow" scalability to meet the needs of an evolving storage environment.

The SN6000B is available in five models:

- HP SN6000B 16Gb 48-port/48-port Active Power Pack+ Fibre Channel Switch
- HP SN6000B 16Gb 48-port/24-port Active Power Pack+ Fibre Channel Switch
- HP SN6000B 16Gb 48-port/48-port Active Fibre Channel Switch
- HP SN6000B 16Gb 48-port/24-port Active Fibre Channel Switch
- HP StoreFabric SN6000B 16Gb Bundled Fibre Channel switch

Power Pack+ includes additional software: Adaptive Networking, Fabric Watch, ISL Trunking, Extended Fabric, Performance Monitor, and Server Application Optimization. Power Pack+ software provides the SAN administrator with the necessary tools to monitor the health and performance of the network, while also ensuring the highest levels of security, scalability and manageability.



What's New

- HP StoreFabric SN6000B 16Gb Bundled Fibre Channel switch
- New RoHS compliant HP SAN switches

NOTE: Restriction of Hazardous Substances Directive or RoHS is a directive adopted by the European Union that restricts the use of certain hazardous materials in the manufacture of various types of electronic and electrical equipment. The RoHS compliant products with new part numbers listed in this document are functionally equivalent to the corresponding products with old part numbers and are fully interchangeable.



Features and Benefits

Key Features and Benefits

- Delivers 16 Gbps performance with up to 48 ports in an energy-efficient, 1U form factor, providing maximum flexibility for diverse deployment and cooling strategies
- Features Ports on Demand (PoD) capabilities for fast, easy, and cost-effective scaling from 24 to 48 ports in 12-port increments
- Provides a flexible, simple, and easy-to-use SAN solution with industry-leading technology
- Supports highly virtualized, private cloud storage with multi-tenancy and non-stop operations
- Offers best-in-class port density and scalability for midrange enterprise SAN switches, along with redundant, hot-pluggable components and non-disruptive software upgrades
- Metro cloud connectivity features including integrated DWDM and dark fiber support (optional license)
- In-flight compression and encryption included providing efficient link utilization and security.
- Yields exceptional price/performance value, exceeding comparable Ethernet storage-based alternatives
- Unique Bundle model: The HP StoreFabric SN6000B 16Gb Bundled Fibre Channel switch model facilitates ease of ordering by offering the HP SN6000B 48/24 Fibre channel switch along with twenty-four 16Gb optical transceivers in one package. The HP StoreFabric SN6000B 16Gb Bundled Fibre Channel switch model is offered at a lower price than the sum of the list prices of the HP SN6000B 48/24 Fibre Channel switch and the 16Gb optical transceivers



Models

HP SN6000B 16Gb
FC Switch Models

HP SN6000B 16Gb 48-port/48-port Active Power Pack+ Fibre Channel Switch	QR481B
HP SN6000B 16Gb 48-port/24-port Active Power Pack+ Fibre Channel Switch	QK754B
HP SN6000B 16Gb 48-port/48-port Active Fibre Channel Switch	QR480B
HP SN6000B 16Gb 48-port/24-port Active Fibre Channel Switch	QK753B
HP StoreFabric SN6000B 16Gb Bundled Fibre Channel switch	C8R08A



Product Highlights

SN6000B 16Gb FC Switch	 Simplifies enterprise SAN deployment by combining higher edge switch port density with exceptional scalability, performance and reliability Delivers 24, 36, or 48-ports in a 1U enclosure Provides 4 Gb/s, 8 Gb/s, 10 Gb/s, 16 Gb/s* performance Employs optional Inter-Switch Link (ISL) Trunking to provide a high-speed data path between switches which enables a high speed data path between 16 Gb/s switches up to 128 Gb/s * 16 Gb/s ISL performance can be obtained between two 16 Gb/s switches.
Configuration Support	http://h18000.www1.hp.com/products/storageworks/san/documentation.html
High-availability features	 Two integrated redundant, hot swappable power supplies with integrated cooling fans Enhanced Fault Detection Logic Parity protection on all data paths and system memory
Advanced Fabric Services	 Hardware Enforced Zoning Frame Filtering Built-in Web browser management tools Enhanced Group Management (EGM) HP B-series SAN Network Advisor software (optional)
Cabinet Support	 HP (22U, 36U and 42U) 9000 and 10000 G1 Series, (25U, 33U and 41U) HP System/e, and the 22U, 36U, and 42U HP 10000 G2 Series NOTE: To order factory integration, add 0D1 after the part number on your sales order.
Software Compone Frame Filtering	ents, Standard, Base Models An ASIC based capability that enables new applications and features. The switch has the ability to "view"
	the first 64 bytes of the Fibre Channel frame. At this time, Frame Filtering enables advanced capabilities such as Advanced Zoning and Advanced Performance Monitoring.

Advanced ZoningWWN Zoning and Access Control are enforced by hardware that provides the same simple administration
previously enforced only with software. Administrators can organize a physical fabric into logical groups
and prevent unauthorized access by devices outside the Zone.

Web Tools	Web Tools is an intuitive and easy-to-use graphical interface that enables organizations to monitor and manage SAN fabrics. Tasks can be performed through a Java-capable Web browser from a standard
	laptop, desktop PC or workstation from any location within the enterprise.



Product Highlights

EGM

Enhanced Group Management (EGM) is a FOS license that is included with all B-Series switches and enables multi-switch operations. It helps automate operations across multiple switches to save time and streamline repetitive operations, which are typically prone to error. EGM drives consistency across fabrics, while minimizing the risk associated with potential downtime due to configuration mismatches. EGM provides streamlined troubleshooting for more effective fabric monitoring and diagnosis.

HP SAN Network Advisor Professional, Professional Plus, and Enterprise enable EGM functionality. Customers have EGM functionality enabled within the hardware product and need only to make the decision around which management application is right for them.

In-flight Compression andIn-flight compression optimizes network performance within the data center and over long-distance links.EncryptionData is compressed at the source and uncompressed at the destination. Performance varies by data type,
but generally achieve 2:1 compression with minimal impact on performance. Compression can be used in
conjunction with in-flight encryption.

In-flight encryption minimizes the risk of unauthorized access for traffic within the data center and over long-distance links. It is switch-to-switch encryption, not device or data-at-rest encryption. Data is encrypted at the source and decrypted at the destination. Encryption and decryption are performed in hardware using the AES-GCM-256 algorithm, minimizing any impact on performance. Encryption can be used in conjunction with in-flight compression. This is complementary to data-at-rest encryption provided by the Encryption SAN Switch and the Encryption Blade for B-series SAN Directors.

Software Components, Optional

SN6000B 16Gb Switch Power Pack+ Software Bundle The Power Pack+ Software Bundle comes with the SN6000B16Gb 48/48 Power Pack+ Switch and SN6000B 16Gb 48/24 Power Pack+ Switch or as an optional software bundle for the SN6000B 16Gb 48/48 FC Switch, the SN6000B 48/24 FC Switch and the SN6000B Bundled Fibre Channel switch. It includes the following:

- Adaptive Networking
- Fabric Watch
- Advanced Performance Monitor
- Extended Fabric
- ISL Trunking
- Server Application Optimization



Product Highlights

Adaptive Networking	Adaptive Networking (AN) is an optional family of technologies which allow flexible control of traffic
	movement within the fabric which deliver application aware management of fabric resources. Applications may be used with multiple protocols and multiple classes of service. It includes the following features:
	Ingress Rate Limiting:
	Allows the ingress bandwidth of a port to be throttled to a rate lower than negotiated with the SAN node. This could be very useful for enterprises offering stepped levels of service and enforcing SLAs.
	Quality of Service (QoS):
	Enables zones with high, medium, and low priorities within a fabric on a zone by zone basis. This can be very useful for prioritizing array replication over MANs and WANs over less critical traffic.
	Traffic Isolation Zones:
	Defines paths through a fabric for some or all nodes. Failover allows a non-preferred path to be used if the preferred fails. TIZs use failover by default but it can be disabled if traffic should stop if a preferred path fails. TIZ can be used to manually map out traffic flows within a fabric based on application, priority, and topology.
Fabric Watch	Fabric Watch is an optional license which enables each switch to monitor the SAN for potential faults and automatically alert network managers to problems before they become failures. Fabric Watch tracks a variety of SAN fabric elements, events, and counters. Monitoring fabric-wide events, ports, SFPs, and environmental parameters permits early fault detection and isolation as well as performance measurement. Each switch in the SAN needs its own Fabric Watch license.
Advanced Performance Monitor	This optional enabling technology helps administrators monitor and watch specific fabric metrics from a SID (Source ID) to a DID (Destination ID) so they can fine-tune and scale the fabric more efficiently. Plus, Advanced Performance Monitoring includes the ability for early warning detection of hot spots within the fabric, a powerful tool for maintaining overall balanced performance.
	Top Talkers is a component of Advanced Performance Monitoring and tracks the top traffic flows for hosts and targets for a switch port or a switch. Top Talkers can help identify the ports that need certain Quality of Service (QoS) attributes or it can help determine portions of the physical topology that need reconfiguration.
Extended Fabric	Optional license which extends all of the scalability, reliability, and performance benefits of Fibre Channel Storage Area Networks (SANs) beyond the native 10 km distance specified by the Fibre Channel standard.
ISL Trunking	For high performance enhanced Trunking, this optional license logically groups up to eight E-ports to provide a high bandwidth trunk between two switches. Each 16Gb switch needs its own license. The switch operating system views the trunk as a single, high bandwidth resource (up to 128Gb) when routing connections between 16Gb switches. Connections are load-balanced across the individual links, which comprise the logical trunk group.



Product Highlights

Server Application Optimization	Server Application Optimization (SAO) license improves overall application performance for physical servers and virtual machines. SAO, when deployed with B-Series Fibre Channel HBAs, extends B-Series Adaptive Networking from the B-series SAN fabric to the server infrastructure. This delivers application-level, fine-grain Quality of Service (QoS) management to the HBAs and related server applications.				
	Solution Requirements:				
	 SAO license must be installed on the edge (server connected) switch Adaptive Networking (AN) license must be installed on the edge (server connected) switch SAO requires B-series HBA installed in the server 				
Integrated Fibre Channel Extension	Integrated SAN extension over native Fibre Channel provide metro connections up to 100 km including support for 10 Gbps Fibre Channel over Dense Wavelength Division Multiplexing (DWDM) and dark fiber. This license enables support on the first eight (8) ports of the switch.				
SAN Network Advisor Professional	HP SAN Network Advisor Professional is a server based management application available at no-charge that comes with B-series SAN Switches and includes the following features:				
	 Allows management of a single Fabric OS (FOS) fabric (up to a 1,000 B-Series switch ports) Performs group switch management beyond the scope of Web Tools Does not offer management for the DC SAN Backbone Director, the SN8000B Director, or FICON 				
	It is targeted for SMB customers that use FOS based SAN fabrics and require a management solution for smaller SANs based on a single fabric.				
	SMB customers that initially start off with SAN Network Advisor Professional and have a small SAN environment may over time feel the need for an enterprise-class product (SAN Network Advisor Enterprise) as their environments start to grow in size and complexity, and as they start to uptake more enterprise-class functionality (such as Fibre Channel Routing, FCIP, etc.). A non-disruptive upgrade path is available from SAN Network Advisor Professional to SAN Network Advisor Enterprise.				
SAN Network Advisor Enterprise and Professional+	HP SAN Network Advisor Enterprise and Professional+ are the enterprise-class products that support FOS products. SAN Network Advisor Enterprise provides complete B-series Directors Management including enterprise-class features/environments such as FICON, Fibre Channel Routing, FCIP, adaptive networking, etc while SAN Network Advisor Professional+ provides the same feature set except for support for the DC SAN Backbone Director, SN8000B 8-Slot Director, and FICON.				
_	SAN Network Advisor Enterprise delivers unprecedented scalability, up to 24 fabrics and 9,000 switch ports, while SAN Network Advisor Professional+ scales to 4 SAN Fabrics and 2560 switch ports. There is an upgrade available from SAN Network Advisor Professional Plus to SAN Network Advisor Enterprise.				
Integrated Routing	Integrated Routing is an optional license which provides native Fibre Channel Routing (FCR) on a per-port basis, rather than limiting routing ports to those on a dedicated routing switch or blade. Just like traditional FCR, Integrated Routing uses EX_Ports to import/export devices between fabrics, enabling selective device sharing while maintaining remote fabric isolation. Integrated Routing provides architecture flexibility to route on a port-by-port basis, enabling increased scalability and fault isolation.				



Service and Support

Warranty	(1-1-1) Hardware Warranty; 1-year parts; 1-year on-site (standard business hours, next business day response) and 1-year labor.			
	NOTE: The hardware warranty covers firmware and embedded non-saleable software. For extended hardware installation and maintenance information, click the link below: http://www.hp.com/hps/carepack/services/.			
	NOTE: Certain restrictions and exclusions apply. Consult the Customer Support Center for details. Hardware or Software product installation is not included in the warranty, but is available and highly recommended.			
Service and Support	Technology Services for increased uptime, productivity and ROI TRUST HP storage technology experts for every level of service and support. Our integrated portfolio of Services for storage help customers reduce costs, optimize data, streamline storage management, and improve backup and recovery. Capitalizing on HP Storage Systems' capabilities requires a service partner who understands your increasingly complex environment. Team with the people who know HP infrastructure hardware and software best-the experienced professionals at HP Services.			
	Protect your business beyond warranty Warranty protects against manufacturer defects, however warranty uplifts, such as HP Care Pack Services protect the business-by reducing downtime risks and providing operational consistency for mission- critical and standard business computing.			
	What HP Storage Technology Services can do for you HP Storage Technology Services can help you design, deploy, test, integrate, support, and manage IT and infrastructure solutions. HP storage lifecycle support services offers a full spectrum of customer care- from technology support to complex migrations to complete managed services.			
	Choose the right level of support, deployment and integration services HP support recommendations are designed to help you enhance technology operations and lower risk-and make it easier for you to seek the right balance between affordability and service-level commitments. Depending on your individual support needs, choose from three levels of care that cover the entire lifecycle to better address your needs-Optimized Care, Standard Care, and Basic Care. If none of our support recommendations meet your needs, we can tailor a service solution for your unique support requirements. Only HP brings together deep expertise, proactive and business critical support and a strong			

partner network-plus, a full set of infrastructure services designed to power a Converged Infrastructure.



Service and Support

Optimized Care - delivers best performance and stability through deployment and proactive management practices

Choose either:

HP Critical Advantage Level 3 Service - Choose this service when you need an end-to-end infrastructure support solution that encompasses server, operating system, hypervisor, storage, and network. It's the level of support well suited for business-critical applications running on virtualized and x86 infrastructures. (Includes 60 Critical Advantage flexible credits.) http://h20195.www2.hp.com/V2/GetPDF.aspx/4AA3-1772ENW.pdf

Or:

3-Year HP Critical Service - Designed for environments where downtime cannot be tolerated, HP monitors your environment around-the-clock, 365 days a year. We implement improvement projects to mitigate risks and reduce incidents. If outages do occur, they are addressed immediately with access to our dedicated critical support escalation resources.

http://h20195.www2.hp.com/V2/GetPDF.aspx/4AA0-1613ENW.pdf

Standard Care - maintains Choose either:

high level of uptime, along with expert help to cut the cost and complexity of implementation and support	HP Critical Advantage Level 2 Service - Opt for end-to-end infrastructure support including server, operating system, hypervisor, storage, and network in an environment running business critical applications on virtualized and x86 infrastructures. (Includes 30 Critical Advantage flexible credits.) http://h20195.www2.hp.com/V2/GetPDF.aspx/4AA3-1772ENW.pdf		
	Or:		
	3-Year HP Proactive 24 Service - This is the right choice for environments where some downtime is acceptable. HP helps manage your IT environment for improved performance, stability, and availability. Your incidents are addressed 24x7, with a maximum 4-hour onsite response 365 days a year. http://h20195.www2.hp.com/V2/GetPDF.aspx/5981-9842EN.pdf		
	Plus:		
	HP Proactive Select - Choose from an extensive menu of consultancy and technical services, such as onsite firmware upgrades, health checks, assessments, and education. (Includes 30 Proactive Select flexible credits.) http://h20195.www2.hp.com/V2/GetPDF.aspx/4AA2-3842ENW.pdf		
Basic Care - Minimum recommended support	3-Year HP Proactive 24 Service - This is the right choice for environments where some downtime is acceptable. HP helps manage your IT environment for improved performance, stability, and availability. Your incidents are addressed 24x7, with a maximum 4-hour onsite response 365 days a year. http://h20195.www2.hp.com/V2/GetPDF.aspx/5981-9842EN.pdf		
Implement right from the start	Whichever level of care you select, it includes: HP Enhanced Implementation Service for SANs-HP delivers complete design and implementation services for Fibre Channel, FCoE, FCIP, SAS, and iSCSI SAN connectivity components. http://h20195.www2.hp.com/V2/GetPDF.aspx/5981-8527EN.pdf		



Service and Support

Remote	HP Insight Remote Support - Count on proven technology to deliver secure, reliable 24x7 remote monitoring, diagnosis, and problem resolution, all available at no extra charge if you have an existing warranty, service agreement, or HP Care Pack Service with HP.			
Support Tools	http://h20195.www2.hp.com/V2/GetPDF.aspx/4AA2-4676ENW.pdf			
Additional service to	HP Assessment Service for SANs - We offer customized technical and operational guidance to customers employing HP storage subsystems and the interconnecting storage area network (SAN), with recommendations to help improve availability levels and ongoing environment management.			
meet your needs	http://h20195.www2.hp.com/V2/GetPDF.aspx/4AA1-2941ENW.pdf			
For more information	 www.hp.com/services/storage To learn more on HP Storage Services, please contact your HP sales representative or HP Authorized Channel Partner HP Care Pack Services are sold by HP and HP Authorized Service Partners: Services for customers purchasing from HP or an enterprise reseller are quoted using HP order configuration tools. Customers purchasing from a commercial reseller can find HP Care Pack Services at www.hp.com/go/lookuptool 			



Features	8/8 SAN Switch Base and 8/8 SAN Switch	8/24 SAN Switch Base	8/40 SAN Switch and 8/40 SAN Switch Power Pack+	8/80 SAN Switch and 8/80 SAN Switch Power Pack+	SN6000B 16Gb FC Switch and SN6000B 16Gb FC Power Pack+
Targeted Environment	Workgroups, Departments	Workgroups, Departments	Workgroups, Departments	Workgroups, Departments	Workgroups, Departments
Fibre Channel Port Bandwidth	8Gbit/sec	8Gbit/sec	8Gbit/sec	8Gbit/sec	16Gbit/sec
Aggregate device bandwidth	128 - 384 Gbit/sec end-to-end	256 - 384 Gbit/sec end-to-end	384 - 640 Gbit/sec end-to-end	768 - 1280 Gbit/sec end-to-end	768 - 1536 Gbit/sec end-to-end
OS Support	http:		lease Refer to SAN Desindesign or http://www.	-	juide
Storage system support		P9000/XF	P, 3PAR, P6000/EVA, P2	2000/MSA	
FC Ports	8 Enabled 24 Max	16 Enabled 24 Max	24 Enabled 40 Max	48 Enabled 80 Max	24 or 48 Enabled 48 Max
SFP	B-series	B-series	B-series	B-series	B-series
Advanced Trunking	Optional Upgrade	Included with Power Pack+ or Optional Upgrade	Included with Power Pack+ or Optional Upgrade	Included with Power Pack+ or Optional Upgrade	Included with Power Pack+ or Optional Upgrade
Adaptive Networking	Optional Upgrade	Included with Power Pack+ or Optional Upgrade	Included with Power Pack+ or Optional Upgrade	Included with Power Pack+ or Optional Upgrade	Included with Power Pack+ or Optional Upgrade
Form factor	10	10	10	20	1U
Zoning Software	Yes (Included)	Yes (Included)	Yes (Included)	Yes (Included)	Yes (Included)
Hot plug, redundant power supplies	No	No	Yes	Yes	Yes
Hot plug fans	No	No	Yes	Yes	Yes (integrated with power supply)



Features	2408 FCoE CN Switch and 2408 FCoE CN Switch Power Pack+	1606 Extension SAN Switch	Encryption SAN Switch		
Targeted Environment	Workgroups, Departments	Workgroups, Departments Data Centers			
Fibre Channel Port Bandwidth	8Gbit/sec	8Gbit/sec	8Gbit/sec		
Ethernet	10Gbit/sec Converged Enhanced Ethernet	1Gbit/sec Ethernet	N/A		
Aggregate device bandwidth			512 Gbit/sec end-to-end		
OS Support		NOTE: Please Refer to SAN Design Guide http://www.hp.com/go/sandesign or http://www.hp.com/go/sandesignguide			
Storage system support	P9000/XP, 3PAR, P6000/EVA, P2000/MSA				
FC Ports	8 Enabled 4 or 16 Enabled 8 Max 16 Max		32 Enabled 32 Max		
Ethernet Ports	24 Enabled 24 Max	2 or 6 Enabled 6 Max	N/A		
SFP	B-series B-series		B-series		
Advanced Trunking	Included with Power Pack+ or Optional Upgrade	Included with Power Pack+ or Optional Upgrade	Optional Upgrade		
Adaptive Networking	No	Included with Power Pack+ or Optional Upgrade	Optional Upgrade		
Form factor	r 1U 1U		2U		
Zoning Software	Yes (Included)	Yes (Included) Yes (Included) Yes			
Hot plug, redundant power supplies	Yes	Yes	Yes		
Hot plug fans	Yes	Yes			



Features	SN8000B 8-Slot SAN Director Power Pack+	SN8000B 4-Slot SAN Director and 4-Slot SAN Director Power Pack+	DC SAN Backbone Director Power Pack+	DCO4 SAN Director and DCO4 SAN Director Power Pack+	
Targeted Environment	Cloud Optimized Data Centers	Cloud Optimized Data Centers	Traditional Data Centers	Traditional Data Centers	
Port Bandwidth	Up to 16Gbit/sec	Up to 16Gbit/sec	8Gbit/sec	8Gbit/sec	
Aggregate device bandwidth	8.2 Tbit/sec end-to-end	4.1 Tbit/sec end-to-end	4.1 Tbit/sec end-to-end	2 Tbit/sec end-to-end	
OS Support	http://ww		to SAN Design Guide http://www.hp.com/go/sande	esignguide	
Storage system support	P9000/XP, 3PAR, P6000/EVA, P2000/MSA				
Ports	Up to 512 SFP	Up to 256 SFP	Up to 512	Up to 256	
SFP	B-series	B-series	B-series	B-series	
Advanced Trunking	Included with Power Pack	Included with Power Pack or Optional Upgrade	Included with Power Pack+	Included with Power Pack+ or Optional	
Adaptive Networking	Included with Power Pack	Included with Power Pack or Optional Upgrade	Included with Power Pack+	Included with Power Pack+ or Optional	
Form factor	14U	90 140		90	
Zoning Software	Yes (included)	Yes (included)	Yes (Included)	Yes (Included)	
Hot plug, redundant power supplies	Yes	Yes	Yes	Yes	
Hot plug fans	Yes	Yes	Yes	Yes	

Features	Embedded SAN Switch for EVA4400	Brocade 8Gb SAN Switch for HP c-Class BladeSystem	B-Series Multi-protocol Router Blade	B-Series Multi-protocol Extension Blade
Targeted Environment	Workgroups, Departments	Workgroups, Departments	Data Centers	Data Centers
Port Bandwidth	8Gbit/sec	8Gbit/sec	4 Gbit/sec FC Ethernet: 1 Gbit/sec	8 Gbit/sec FC Ethernet: 1 or 10 Gbit/sec
Aggregate device bandwidth	320 Gbit/sec end-to-end	384 Gbit/sec end-to-end	N/A	N/A
OS Support	NOTE: Please Refer to SAN Design Guide http://www.hp.com/go/sandesign or http://www.hp.com/go/sandesignguide			
Storage system Support	P9000/XP, 3PAR, P6000/EVA, P2000/MSA			
Ports	20 external per EVA Controller Pair	4 or 8 external / 8 or 16 internal	18 ports: 16 FC and 2 Gigabit Ethernet	16 8Gb FC and 10 1GbE or 2 10GbE
SFP	B-series	B-series	HP	B-series
Advanced Trunking	Included with Power Pack+ or Optional Upgrade	Included with Power Pack+ or Optional Upgrade	Optional Upgrade to chassis	Optional Upgrade to chassis



HP SN6000B Fibre Channel Switch

Adaptive Networking	Included with Power Pack+ or Optional Upgrade	Included with Power Pack+ or Optional Upgrade	Optional Upgrade to chassis	Optional Upgrade to chassis
Form factor	Embedded	Embedded	Blade in 4/256, DC SAN Back, or DC04 SAN Dir	Blade in SN8000B and DC SAN Directors
Zoning Software	Embedded	Yes (Included)	Yes (Included)	Yes (Included)
Hot plug, redundant power supplies	Yes, in EVA 4400 Enclosure	Yes, in BladeSystem Enclosure	Yes, in director chassis	Yes, in director chassis
Hot plug fans	Yes, in EVA 4400 Enclosure	Yes, in BladeSystem Enclosure	Yes, in director chassis	Yes, in director chassis



Configuration Information

Step 1 - Base Configuration

Select one:

Selectione.		
Model	Model Description	Part Number
SN6000B 16Gb 48/48 P	ower Pack+ FC Switch	QR481B
	16Gb 48/48 FC Switch with 48 active ports; rackmount kit; accessory kit (enterprise safety and regulatory information, installation guide, rack-mounting instructions), power cords, serial cable, base software of Advanced Fabric OS, Advanced Web Tools, Advanced Zoning, SAN Network Advisor Professional, Brocade EZ Switch, and Power Pack+ software of Adaptive Networking, ISL Trunking, Extended Fabric, Advanced Performance Monitoring, Server Application Optimization, and Fabric Watch. NOTE: Requires optical transceivers listed below.	
SN6000B 16Gb 48/24 P	ower Pack+ FC Switch	QK754B
	16Gb 48/48 FC Switch with 24 active ports; rackmount kit; accessory kit (enterprise safety and regulatory information, installation guide, rack-mounting instructions), power cords, serial cable, base software of Advanced Fabric OS, Advanced Web Tools, Advanced Zoning, SAN Network Advisor Professional, Brocade EZ Switch, and Power Pack+ software of Adaptive Networking, ISL Trunking, Extended Fabric, Advanced Performance Monitoring, Server Application Optimization, and Fabric Watch. NOTE: Requires optical transceivers listed below.	
SN6000B 16Gb 48/48 F	C Switch	QR480B
	16Gb 48/48 FC Switch with 48 active ports; rackmount kit; accessory kit (enterprise safety and regulatory information, installation guide, rack-mounting instructions), power cords, serial cable, base software of Advanced Fabric OS, Advanced Web Tools, Brocade EZ Switch, Advanced Zoning and SAN Network Advisor Professional. NOTE: Requires optical transceivers listed below.	
SN6000B 16Gb 48/24 F	C Switch	QK753B
	16Gb 48/48 FC Switch with 24 active ports; rackmount kit; accessory kit (enterprise safety and regulatory information, installation guide, rack-mounting instructions), power cords, serial cable, base software of Advanced Fabric OS, Advanced Web Tools, Brocade EZ Switch, Advanced Zoning, and SAN Network Advisor Professional. NOTE: Requires optical transceivers listed below.	
SN6000B 16Gb Bundled	I Fibre Channel Switch	C8R08A
	16Gb 48/48 FC Switch with 24 active ports; rackmount kit; twenty-four 16Gb optical transceivers, accessory kit (enterprise safety and regulatory information, installation guide, rack-mounting instructions), power cords, serial cable, base software of Advanced Fabric OS, Advanced Web Tools, Brocade EZ Switch, Advanced Zoning, and SAN Network Advisor Professional. NOTE: Twenty-four 16Gb optical transceivers (QK724A) are included in the package with this switch model.	
SN6000B 16Gb 24-48 1	2-port FC Upgrade LTU	TC356A
	12 port upgrade license for SN6000B 16Gb 48/24 Power Pack FC Switch (QK754B), SN6000B 16Gb 48/24 FC Switch (QK753B) and the SN6000B 16Gb Bundled Fibre Channel Switch (C8R08A)	

Step 2 - Options



Configuration Information

	Model Descri	ption				Part Number
Fibre Channel	HP B-series 16	5Gb SFP+ Short V	Vave Transceiver			QK724A
Transceivers	HP 8Gb Short Wave B-series FC SFP+ 1 Pack					AJ716B*
	* NOTE: AJ716	A is not supporte	ed with the SN600	0B 16Gb FC Switch		
	Distance -	HP Standard	HP Standard	HP PremierFlex	HP PremierFlex	
	Maximum	OM2 Cable	OM3 Cable	OM3+ Cable	OM4 Cable	
	16Gb performance:	35 meters	100 meters	100 meters	125 meters	
	8Gb performance:	50 meters	150 meters	150 meters	190 meters	
	4Gb performance:	150 meters	380 meters	380 meters	400 meters	
	HP B-series 16	5Gb SFP+ Long W	/ave 10km Transce	eiver	<u>^</u>	QK725A
		-		1 Pack SFP+ Transce	eiver	AJ717A
	-			SFP Transceiver 1 Pa		AW538A
	HP B-series 10) Gb SFP+ Short F	Range Transceiver			QK726A
	HP B-series 10)Gb SFP+ Long R	ange Transceiver			QK727A
USB	2Gb USB Devi	ce				AK864B
Optical Cables	HP PremierFlex OM4+ Fiber Optic Cables					
	HP Premier Flex LC/LC Multi-mode OM4 2 fiber 1m Cable					QK732A
	HP Premier Flex LC/LC Multi-mode OM4 2 fiber 2m Cable					QK733A
	HP Premier Flex LC/LC Multi-mode OM4 5 fiber 5m Cable					QK734A
	HP Premier Flex LC/LC Multi-mode OM4 2 fiber 15m Cable					QK735A
	HP Premier Flex LC/LC Multi-mode OM4 2 fiber 30m Cable					QK736A
	HP Premier Flex LC/LC Multi-mode OM4 2 fiber 50m Cable					QK737A
	HP PremierFlex OM3+ Optical Cables					
	HP .5m Premier Flex LC/LC 1 Pack Optical Cable					BK837A
	HP 1m Premier Flex LC/LC 1 Pack Optical Cable					BK838A
	HP 2m Premier Flex LC/LC 1 Pack Optical Cable					BK839A
	HP 5m Premier Flex LC/LC 1 Pack Optical Cable					BK840A
	HP 15m Premier Flex LC/LC 1 Pack Optical Cable					BK841A
	HP 30m Premier Flex LC/LC 1 Pack Optical Cable					BK842A
	HP 50m Premier Flex LC/LC 1 Pack Optical Cable					BK843A
	HP OM3 LC-LC Optical Cables					
	HP LC to LC Multi-mode OM3 2-Fiber 0.5m 1-Pack Fiber Optic Cable				AJ833A	
	HP LC to LC Multi-mode OM3 2-Fiber 1.0m 1-Pack Fiber Optic Cable				AJ834A	
	HP LC to LC Multi-mode OM3 2-Fiber 2.0m 1-Pack Fiber Optic Cable			AJ835A		



Configuration Information

HP LC to LC Multi-mode OM3 2-Fiber 5.0m 1-Pack Fiber Optic Cable	AJ836A
HP LC to LC Multi-mode OM3 2-Fiber 15.0m 1-Pack Fiber Optic Cable	AJ837A
HP LC to LC Multi-mode OM3 2-Fiber 30.0m 1-Pack Fiber Optic Cable	AJ838A
HP LC to LC Multi-mode OM3 2-Fiber 50.0m 1-Pack Fiber Optic Cable	AJ839A

Step 3 - Optional Software*

mum requirements, please refer to: http://spock.corp.hp.com/	
HP B-series SAN Network Advisor Enterprise LTU	TC352A
HP B-series SAN Network Advisor Professional Plus LTU	TC353A
HP B-series SAN Network Advisor Professional Plus Upgrade LTU	TC354A
HP B-series 24-40 Port SAN Switch Power Pack+ Upgrade LTU NOTE: The Power Pack+ Software Bundle kit includes Adaptive Networking, Fabric Watch, ISL Trunking, Extended Fabric, Server Application Optimization, and Advanced Performance Monitor.	T5522A
Extended Fabric SAN Switch 2/32	313458-B21
Fabric Watch SAN Switch 2/32	313454-B21
Advanced Performance Monitor SAN Switch 2/32	313450-B21
ISL Trunking SAN Switch 2/32	313452-B21
HP SN6000B 10Gb 24-48 Port Integrated Fibre Channel Extension LTU (enables 10Gb FC for first eight ports)	TC358A
HP B-series 24-40 Port SAN Switch Integrated Routing LTU	T5528A
HP Intelligent Infrastructure Analyzer Software LTU	TC400A
HP Intelligent Infrastructure Analyzer Software E-LTU	TC400AAE
	 HP B-series SAN Network Advisor Enterprise LTU HP B-series SAN Network Advisor Professional Plus LTU HP B-series SAN Network Advisor Professional Plus Upgrade LTU HP B-series 24-40 Port SAN Switch Power Pack+ Upgrade LTU NOTE: The Power Pack+ Software Bundle kit includes Adaptive Networking, Fabric Watch, ISL Trunking, Extended Fabric, Server Application Optimization, and Advanced Performance Monitor. Extended Fabric SAN Switch 2/32 Fabric Watch SAN Switch 2/32 Advanced Performance Monitor SAN Switch 2/32 ISL Trunking SAN Switch 2/32 HP SN6000B 10Gb 24-48 Port Integrated Fibre Channel Extension LTU (enables 10Gb FC for first eight ports) HP B-series 24-40 Port SAN Switch Integrated Routing LTU HP Intelligent Infrastructure Analyzer Software LTU



Technical Specifications

System Architecture	Fibre Channel ports	Switch mode (default): 24-, 36-, and 48-port configurations (12-port increments through Ports on Demand [PoD] licenses); universal (E, F, M, D, EX) ports
	Scalability	Full fabric architecture: http://h18006.www1.hp.com/products/storageworks/san/ documentation.html
	Certified maximum	Refer to SAN Design Guide for current configuration information: http://h18006.www1.hp.com/products/storageworks/san/ documentation.html
	Interoperability	 4/256 SAN Director 4/64 SAN Switch 4/32 SAN Switch 4/32B SAN Switch 4/32B SAN Switch 4/16 SAN Switch 4/16 SAN Switch 8/8 SAN Switch 8/24 SAN Switch 8/24 SAN Switch 8/40 SAN Switch 8/80 SAN Switch 8/80 SAN Switch 2408 FCoE Converged Network Switch 1606 Extension SAN Switch DC04 SAN Director DC SAN Backbone Director SN8000B 8-Slot SAN Backbone Director SN8000B 4-Slot SAN Director Brocade 4Gb SAN Switch for HP c-Class BladeSystem Brocade 8Gb SAN Switch for HP BladeSystem c-Class HP 400 MP-Router
	Performance	Auto-sensing of 4, 8, and 16 Gbps port speeds; 10 Gbps and optionally programmable to fixed port speed.
	ISL Trunking	Frame-based trunking with up to eight 16 Gbps ports per ISL trunk; up to 128 Gbps per ISL trunk. Exchange-based load balancing across ISLs with DPS included in Fabric OS. There is no limit to how many trunk groups can be configured in the switch.
	Aggregate bandwidth	1536 Gbit/sec full duplex
	Fabric latency	Latency for locally switched ports is 700 ns; encryption/compression is 5.5 sec per node; Forward Error Correction (FEC) adds 400 ns between E_Ports (enabled by default).
	Maximum frame size	2112-byte payload
	Classes of service	Class 2, Class 3, Class F (inter-switch frames)
	Port types	D_Port (Diagnostic Port), E_Port, EX_Port, F_Port, M_Port (Mirror Port); self- discovery based on switch type (U_Port); optional port type control Access Gateway mode: F_Port and NPIV-enabled N_Port
	Data traffic types	Fabric switches supporting unicast



Technical Specifications

	Media types	Hot-pluggable, B-Series Branded Small Form Factor Pluggable (SFP), LC connector; Short-Wave Laser (SWL), Long-Wave Laser (LWL); distance depends on fiber-optic cable and port speed. Supports SFP+ (16/10/8 Gbit/sec) optical transceivers.
	USB	One USB port for system log file downloads or firmware upgrades
	Fabric services	Advanced Performance Monitoring (APM) (including Top Talkers for E_Ports, F_Ports, and Fabric mode); Adaptive Networking (Ingress Rate Limiting, Traffic Isolation, QoS); Bottleneck Detection; Advanced Zoning (default zoning, port/WWN zoning, broadcast zoning); Dynamic Fabric Provisioning (DFP); Dynamic Path Selection (DPS); Extended Fabrics; Enhanced BB credit recovery; Brocade Fabric Watch; FDMI; Frame Redirection; Frame-based Trunking; FSPF; Integrated Routing; IPoFC; ISL Trunking; Management Server; NPIV; NTP v3; Port Fencing; Registered State Change Notification (RSCN); Reliable Commit Service (RCS); Server Application Optimization (SAO); Simple Name Server (SNS); Virtual Fabrics (Logical Switch, Logical Fabric)
	Extension	Fibre Channel, in-flight compression (Brocade LZO) and encryption (AES-GCM- 256); integrated 10 Gbps Fibre Channel for DWDM MAN connectivity
	Options	SFP media, USB Device
Management	Management software supported	HTTP, SNMP v1/v3 (FE MIB, FC Management MIB), SSH; Auditing, Syslog; Brocade Advanced Web Tools, APM, Fabric Watch; SAN Network Advisor Enterprise or SAN Network Advisor Professional/Professional Plus; Command Line Interface (CLI); SMI-S compliant; Administrative Domains; trial licenses for add-on capabilities
	Management access	10/100 Mbps Ethernet (RJ-45), in-band over Fibre Channel, serial port (RJ-45), and one USB port
	Diagnostics	D_Port offline diagnostics, including electrical/ optical loopback, link traffic/latency/distance; POST and embedded online/offline diagnostics, including environmental monitoring, FCping and Pathinfo (FC traceroute), frame viewer, non-disruptive daemon restart port mirroring (SPAN port), optics health monitoring, power monitoring, RAStrace logging, and Rolling Reboot Detection (RRD)
Mechanicals	Enclosure	Back-to-front airflow; power from back; 1U
	Size	Width: 438 mm (17.23 in.) Height: 43 mm (1.7 in.) Depth: 443 mm (17.45 in.)
	System Weight	9.16 kg (20.20 lb) with two power supply FRUs, without transceivers
Environment	Temperature	Operating: 0° to 40° C (32° to 104° F) Non-operating: -25° to 70° C (-13° to 158° F)
	Humidity	Operating: 10 to 85 percent non-condensing
	Altitude	Operating: Up to 3000 meters (9,842 feet) Storage: Up to 12 kilometers (39,370 feet)
	Shock	Operating: 20 g, 6 ms half-sine Non-operating: Half sine, 33G 11ms. 3/eg Axis
	Vibration	Operating: 0.5 g sine, 0.4 grms random, 5 to 500 Hz Non-operating: 2.0 g sine, 1.1 grms random, 5 to 500 Hz
Power	Power Supply	Dual, hot-swappable redundant power supplies with integrated system cooling fans



Technical Specifications

AC input	85 V to 264 V ~5 A to 2.5 A	
Input line frequency	47 Hz to 63 Hz	
Power Consumption	110 watts with all 48 ports populated with 16 Gbps SWL optics 72 watts for empty chassis with no optics	

© Copyright 2012 Hewlett-Packard Development Company, L.P.

The information contained herein is subject to change without notice.

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

