



| | |
|---|--|
| Angle Measurement | |
| Horizontal Accuracy (Standard deviation based on ISO 17123-3) | 1" (0.3 mgon) |
| Vertical Accuracy (Standard deviation based on ISO 17123-3) | 1" (0.3 mgon) |
| Angle Reading (least count) | |
| Standard | 1" (0.3 mgon) |
| Tracking | 2" (0.6 mgon) |
| Automatic Level Compensator | |
| | Dual-axis compensator +/- 5.4' (+/- 100 mgon) |
| Distance Measurement Accuracy (Standard Deviation), Prism Mode | |
| Standard | $\pm(2 \text{ mm} + 2 \text{ ppm}) \pm(0.0065 \text{ ft} + 2 \text{ ppm})$ |
| Tested standard deviation according to ISO17123-4 | $\pm(1 \text{ mm} + 1 \text{ ppm}) \pm(0.003 \text{ ft} + 1 \text{ ppm})$ |
| Tracking | $\pm(4 \text{ mm} + 2 \text{ ppm}) \pm(0.013 \text{ ft} + 2 \text{ ppm})$ |
| Dynamic Measurement Capability (Standard Deviation) | |
| Synchronized Angle and Distance Measurements | Yes |
| Maximized Position Update Rate | 20 Hz |
| DR Mode | |
| Standard Measurement | $\pm(2 \text{ mm} + 2 \text{ ppm}) \pm(0.0065 \text{ ft} + 2 \text{ ppm})$ |
| Tracking | $\pm(4 \text{ mm} + 2 \text{ ppm}) \pm(0.013 \text{ ft} + 2 \text{ ppm})$ |
| Measuring Time, Prism Mode | |
| Standard | 1.2 seconds |
| Tracking | 0.4 seconds |
| Measuring Time, DR Mode | |
| Standard | 1 to 5 seconds |
| Tracking | 0.4 seconds |
| Range (under clear conditions), Prism Mode | |
| 1 prism | 2,500 m (8,202 ft) |
| 1 prism Long Range mode | 5,500 m (18,044 ft) max range |
| 3 prism | 3500 m (11,482 ft) |
| Shortest possible range | 0.2 m (0.65 ft) |
| Range (under clear conditions), DR Mode | |
| Kodak Gray Card (18% reflective) | >600 m (1969 ft) |
| Kodak Gray Card (90% reflective) | >1300 m (4265 ft) |
| Range (under difficult conditions), DR Mode | |
| Kodak Gray Card (18% reflective) | >550 m (1804 ft) |
| Kodak Gray Card (90% reflective) | >1200 m (3937 ft) |
| Typical ranges, DR Mode | |
| Concrete | 600 – 800 m (1968 – 2624 ft) |
| Wood construction | 400 – 800 m (1312 – 2624 ft) |
| Metal construction | 400 – 500 m (1312 – 1640 ft) |
| Light rock | 400 – 600 m (1312 – 1968 ft) |
| Dark rock | 300 – 400 m (984 – 1312 ft) |
| Reflective foil 20 mm x 20 mm (0.7 in x .07 in) | 1000 m (3280 ft) |
| Reflective foil 60 mm x 60 mm (2.3 in x 2.3 in) | 1600 m (5,249 ft) |
| Shortest possible range | 1m (6.56 ft) |
| DR Extended Range Mode | |
| Kodak Gray Card (18% reflective) | 900-1000 m (2952 - 3280 ft) |
| Kodak Gray Card (90% reflective) | 2000 - 2200 m (6560 - 7216 ft) |
| Accuracy | $\pm(10 \text{ mm} + 2 \text{ ppm}) \pm(0.033 \text{ ft} + 2 \text{ ppm})$ |

Specifications

SPS930 DR+ Total Station

| | |
|--|---|
| DR surface scan and surface profile speed | 3 Hz / 1.3 points per second - turn and measure |
| Light Source | Pulsed laser diode 905 nm, Laser class 1 |
| Laser pointer coaxial (standard) | Laser class 2 |
| Beam Divergence in Prism Mode | |
| Horizontal | 4 cm/100 m (0.13 ft/328 ft) |
| Vertical | 8 cm/100 m (0.26 ft/328 ft) |
| Beam Divergence in DR Mode | |
| Horizontal | |
| Vertical | |
| Atmospheric Correction | -130 ppm to 160 ppm continuous |
| Leveling | |
| Circular level in Tribrach | 8/2 mm (8/0.007 ft) |
| Electronic 2-axis level in the LCD | 0.3" (0.1 mgon) |
| Servo system | MagDrive servo technology, integrated servo/angle sensor electromagnetic direct drive |
| Rotation speed | 115 degrees/sec (128 gon/sec) |
| Positioning speed 360/180 degrees (400/200 gon) | 3.2 sec / 2.6 sec |
| Positioning speed - Change Face I to Face II | 2.6 sec |
| Clamps and slow motions | Servo-driven, endless fine adjustment |
| Centering | |
| Centering system | Trimble 3-pin |
| Optical plummet | Alidade optical plummet |
| Magnification/shortest focusing distance | 2.3x/0.5 m – infinity (1.6 ft – infinity) |
| Telescope | |
| Magnification | 30x |
| Aperture | 40 mm (1.57 inches) |
| Field of view at 100 m (328 ft) | 2.6 m at 100 m (8.5 ft at 328 ft) |
| Shortest focusing distance | 1.5 m (4.92 ft)–infinity |
| Illuminated crosshair | Variable (10 steps) |
| Built-in tracklight | Standard |
| Operating temperature | -20 °C to +50 °C (-4 °F to +122 °F) |
| Dust and water proofing | IP65 |
| Focus type | Servo assisted on side cover and autofocus |
| Power Supply | |
| Internal battery | Rechargeable Li-Ion battery 11.1 V, 4.4 Ah |
| Operating Time | |
| One internal battery | Approximately 6 hours |
| Three internal batteries in multi-battery adaptor | Approximately 18 hours |
| Robotic holder with one internal battery | Approximately 12 hours |
| Weight | |
| Instrument (Servo/Autolock) | 5.15 kg (11.35 lb) |
| Instrument (Robotic) | 5.25 kg (11.57 lb) |
| Trimble CU Controller | 0.4 kg (0.88 lb) |
| Tribrach | 0.7 kg (1.54 lb) |
| Internal battery | 0.35 kg (0.77 lb) |
| 196 mm (7.71 in) | |
| Trunnion axis Height | |
| Handle | Detachable and eccentric for unrestricted sighting |
| Range | |
| Robotic | 500–700 m (1,640–2,297 ft) |
| Autolock | 500–700 m (1,640–2,297 ft) |
| Autolock to Trimble AT360 Target | 500 m (1,640 ft) |
| Autolock to Trimble MT1000 Target | 800 m (2625 ft) |
| Shortest search distance | 0.2 m (.65 ft) |
| Autolock pointing precision at 200 m (656 ft) (Standard deviation) | <2 mm (0.007 ft) |
| Angle Reading | |
| Standard | 1" (0.3 mgon) |
| Tracking | 2" (0.6 mgon) |
| Averaged observations | 0.1" (0.03 mgon) |
| Type of radio | 2.4 GHz frequency-hopping, spread-spectrum radios |
| Search time | 2 – 10 s |
| Search area | 360 degrees (400 gon) or defined horizontal and vertical search window |

Specifications

SPS930 DR+ Total Station

| | |
|---|---|
| Communication | USB, Serial, Bluetooth® |
| Machine Control Specifications | |
| Machine Control Capable | Optional |
| Range to target (MT900) | 5m – 500-700 m, from 2m with reduced performance |
| Search time | 2 to 10 seconds |
| Search area | 360 degrees (400 gon) or defined horizontal and vertical search window |
| Maximum acceleration of target at short distance 2 m (6.5 ft) radial acceleration | 148°/sec |
| Maximum velocity of target | |
| Radial speed | 114°/sec |
| Axial speed | 6m/s |
| Data Output | |
| Rate | 20 Hz |
| Data Timing | +/- 1 ms |
| Data Latency | 40 ms over Cirronet radio, 23 ms over USB connection |
| Synchronized measurement data | <1 ms |
| Accuracy to a target moving at 1 m/s (Standard deviation) | |
| Horizontal | ± (2 mm + 14 ppm) ± (0.007 ft + 14 ppm) |
| Vertical | ± (2 mm + 14 ppm) ± (0.007 ft + 14 ppm) |
| Slope Distance | ± (2 mm + 14 ppm) ± (0.007 ft + 14 ppm) |
| Models Available | Servo, Autolock, Robotic, UTS |
| Upgradable | Yes |
| <i>Specifications subject to change without notice.</i> | <i>© 2018, Trimble Inc. All rights reserved. Trimble, the Globe & Triangle logo, are trademarks of Trimble Inc, registered in the United States and in other countries. All other trademarks are the property of their respective owners.</i> |

Trimble Heavy Civil Construction Division

10368 Westmoor Drive
Westminster, Colorado 80021
USA
800-361-1249 (Toll Free)
+1-937-245-5154 Phone
+1-937-233-9441 Fax
www.trimble.com

Trimble Authorized Distribution Partner