

Data Sheet Fujitsu Display B24-8 TE Pro

Advanced display: 60.5 cm (23.8-inch) widescreen
Best ergonomic and energy saving solutions for office applications

The FUJITSU Display B24-8 TE Pro is made for intensive office work. With visual and mechanical ergonomics this marble-grey display enables fatigue-free working for hours in front of the screen. The large 60.5 cm (23.8-inch) screen allows you to keep always track of all open applications. This high-quality display works unfailingly around the clock. Easy connectivity, manageability and usability help you increase your productivity.

The display provides an excellent visual performance with In-Plane Switching (IPS) technology.

The display had an optimized and relaxed position and provides an ergonomic stand featuring height adjust, swivel, tilt and 90° rotation.

The DisplayView software enables you to configure your monitor for adjusting screen brightness, pivot function and much more.

The display allows for flexible connectivity with DisplayPort, DVI, Analog and USB.

The smart design with space saving front frame and smart details like discretely integrated speakers and cable guide allow for a clean desk.

The environment-friendly LED technology provides unique, high efficient energy saving solutions like ECO operation mode and ECO standby.













Technical details

| Special features | |
|------------------------------------|---|
| | In-Plane Switching (IPS) technology, Eco button for Eco mode and 3-coloured Eco status LED, 5-in-1 Stand, Cable guide, Pivot, Always available USB (in operating and standby mode), DisplayView™ Software, 24/7 usage, Headset connector, Integrated speakers |
| Ergonomic stand | connector, integrated speakers |
| Stand | 5-in-1 Stand |
| Height adjust range | 150 mm |
| Picture height over desk (min) | 40 mm |
| Rotation to portrait | 90° |
| Filt angle | -5° / +35° |
| Swivel angle | 345° |
| Picture performance | 3.5 |
| Panel and backlit | In-Plane Switching (IPS) technology/LED |
| Screen Surface Treatment | Anti-glare, 3H hard coating |
| Contrast - typical | 1,000:1 |
| Contrast - advanced | 20,000,000:1 |
| Response time gray to gray typical | 5 ms (in video mode) |
| Viewing angle (h/v) - typical | 178°/178° CR10:1 |
| Color performance | 16.7 million colors |
| Brightness - typical | 250 cd/m2 |
| Size and resolution | 230 CQ/III2 |
| | 16:9 |
| Aspect ratio Diagonal Size | 60.5 cm (23.8-inch) |
| Resolution (native) | 1,920 x 1,080 pixel |
| · · · · · · | |
| Resolution (interpolated) | 1,680 x 1,050 pixel, 1,440 x 900 pixel, 1,280 x 1,024 pixel, 1,280 x 720 pixel, 1,024 x 768 pixel, 800 x 600 pixel, 640 x 480 pixel |
| Picture size | 527 x 296 mm |
| Pixel Pitch | 0.2745 mm |
| Frequencies | |
| Horizontal | 30 - 82 kHz |
| Vertical | 56 - 76 Hz |
| Connectivity | |
| DisplayPort | 1 x DisplayPort |
| DVI | 1 x DVI-D (HDCP) |
| VGA/D-SUB | 1 x D-SUB |
| Audio signal output | 3.5 mm stereo phone jack for head phone |
| Audio signal input | 3.5 mm stereo phone jack |
| Audio sound output | 2 x 2 W |
| JSB downstream | 2x USB 2.0 |
| JSB upstream | 1 x USB |
| Ease-of-use menu | |
| Languages | Arabic, Czech, Danish, Dutch, English, Finnish, French, German, Italian, Norwegian, Polish, Portuguese, Russian, |
| 0.1. /6 | Spanish, Swedish, Turkish, Japanese, Chinese simply, Chinese traditional |
| Brightness / Contrast | Brightness, Contrast, Black level, Auto level |
| Mode | sRGB, Office, Photo, Video, Low Blue Light |
| Color | sRGB, 5000K, 6500K, 7500K, Native, Custom Color (R,G,B) |
| mage adjust | Clock, Phase, H-Position, V-Position, Expansion |
| Audio | Mute, Volume, Input for HDMI and DP interface |
| | Model name, Serial number, Resolution/mode, Signal input |

Page 2 / 5 http://ts.fujitsu.com

| Power consumption (typical, w/o sound | |
|---------------------------------------|--|
| Soft switch off | 0.14 W |
| Power save mode | 0.17 W |
| Operating with EPA settings | 11.95 W |
| Total Energy Consumption (ETEC) | 43.6 kWh/year |
| Operating maximum brightness | 22 W |
| Power supply | integrated |
| Power notes | Speakers off, USB not connected ETEC and EPA refer to ENERGY STAR® 8.0 |
| Electrical values | |
| Rated voltage range | 100 V - 240 V |
| Rated frequency range | 50 Hz - 60 Hz |
| Protection class | 1 |
| Compliance | |
| Europe | EN 62368-1, CE certification according to EC Directive 2004/108/EEC, RoHS, WEEE, IT-Eco-Declaration |
| Model | B24-8T |
| Germany | TÜV GS |
| Russia | EAC |
| USA/Canada | FCC Class B, cTUVus |
| Australia/New Zealand | RCM |
| | |
| South Korea | KC |
| Singapore | S-Mark |
| Taiwan | BSMI |
| China | CCC |
| Global | ENERGY STAR® 8.0, EPEAT® Bronze (dedicated regions), TÜV Low Blue Light Certified, TÜV Flicker Free Certified, Zero bright and dark pixel faults, Subpixel faults according to ISO9241-307 (Pixel fault class I), TCO Certified |
| Compliance link | https://sp.ts.fujitsu.com/sites/certificates |
| Dimensions / Weight / Environmental | |
| Dimension without stand (W x D x H) | 553 x 63.5 x 330.2 mm |
| | 21.77 x 2.5 x 13.00 inch |
| Dimension with stand (W x D x H) | 553 x 229.4 x 347 mm |
| | 21.77 x 9.03 x 13.65 inch |
| Weight (packed) | 7.4 kg |
| reight (packed) | 16.20 lbs |
| Weight (unpacked) | 5.6 kg |
| | 12.35 lbs |
| Weight (Monitor only) | 3.5 kg |
| weight (Monitor only) | 7.74 lbs |
| | |
| Operating ambient temperature | 5 - 35 °C (41 - 95 °F) |
| Operating relative humidity | 10 - 85 % (non condensing) |
| Miscellaneous | VEGA DDG (GLEL D) LA MARIA LA CAMPANA MARIA MARI |
| Miscellaneous | VESA DDC/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared |
| Color | Marble grey |
| Package content | |
| Display delivered accessories | DisplayPort data cable 1.8 m DVI-D Data cable 1.8 m Audio cable 1.8 m USB-cable 1.8 m USB-cable 1.8 m (USB-A to USB-B) Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8 m Quickstart flyer Safety notes |
| Display delivered accessories notes | Power cable with IEC-60320-C13, 3-pin connector on display side Data cables and USB cable detachable on display User manual and DisplayView Software is available via download |

Page 3 / 5 http://ts.fujitsu.com

| Packaging dimension (mm) | |
|--------------------------|--|
| Weight (packed) | 7.4 kg |
| Weight (packed) (lbs) | 16.20 lbs |
| Warranty | |
| Warranty period | 3 years (depending on country) |
| Spare Parts availability | at least 7 years after shipment, for details see https://support.ts.fujitsu.com/ |
| | 5 years |

Page 4 / 5 http://ts.fujitsu.com

More information

In addition to Fujitsu Display B24-8 TE Pro, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures
With the Fujitsu Dynamic Infrastructures
approach, Fujitsu offers a full portfolio of IT
products, solutions and services, ranging
from clients to datacenter solutions, Managed
Infrastructure and Infrastructure as-aService. How much you benefit from Fujitsu
technologies and services depends on the
level of cooperation you choose. This takes IT
flexibility and efficiency to the next level.

Computing Products www.fujitsu.com/global/products/ computing/

Software www.fujitsu.com/software/

More information

Learn more about Fujitsu Display B24-8 TE Pro, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. http://ts.fujitsu.com All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see http://ts.fujitsu. com/terms_of_use.html Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

Contact

Address: x-xx-x, street, city, state, ZIP code, country Phone: xx-xxxx-xxxx
Fax : xx-xxxx-xxxx
Email: xxx.xxxxx(fujitsu.com
Website: www.fujitsu.com/[country]
2024-04-06 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see http://ts.fujitsu.com/terms_of_use.html Copyright © Fujitsu Technology Solutions