

Overview

HPE StoreEver MSL3040 Tape Library

The highly scalable HPE StoreEver MSL3040 Tape Library provides small to mid-sized organizations with flexibility for long-term data protection and retention of data storage assets. With its modular design and ability to reuse existing HPE MSL LTO upgrade drive kits, you can cost-effectively store up to 8.4 PB compressed with LTO-8 media. The HPE StoreEver MSL3040 Tape Library offers exceptional enterprise features and functionality as standard providing advanced security features and reliability. It delivers a tape storage solution that addresses backup and long-term data management challenges such as storing medical records, video surveillance files or for business compliance.



HPE StoreEver MSL3040 Tape Library

Industry leading scalability - from 40-slot Base Library Module to 280 slots in a 21U Rack with 6 Expansion Modules

What's New

- MSL3040 base module now supports 40 slots

Standard Features

Key Features

- **High scalability** - Pay as you grow with the fast, non-disruptive addition of Expansion Modules for expansion of tape slots.
 - Start with 40-slot 3U form-factor Base Library Module, and add up to 6 Expansion Library Modules for a total of 280 slots in a 21U rack form factor
 - 8.4PB of total maximum capacity with 280 slots and LTO-8 drives
 - Performance scaling from 1 to 21 LTO HH Tape Drives and transfer rates of up to 300 MB/s per LTO-8 Tape Drive native.
- **Cost Effective tape solution**
 - Existing customers of MSL2024, 4048, and 6480 Tape Libraries can repurpose their existing LTO-8, LTO-7 and LTO-6 drives in the new MSL3040 to leverage their investment
 - Industry leading storage density to save rack space, floor space, power, cooling and management costs –13 cartridge slots (390 TB) per 1U of rack space
 - Great flexibility with up to 21 logical library partitions
 - Customer installable, scalable and serviceable
- **Enterprise-class manageability and reliability**
 - Manage multiple HPE Tape Libraries from a single pane of glass with HPE StoreEver Command View Tape Library software. Download for free at: https://support.hpe.com/hpsc/doc/public/display?docId=emr_na-a00037719en_us&docLocale=en_US
 - Intelligent, proactive and predictive reporting with HPE StoreEver TapeAssure Advanced
- **Advanced security features**
 - Using the HPE Encryption Kit get the simplest, lowest cost encryption and key management solution available - no additional software required
 - HPE Secure Manager License provides an additional level of security that lets you control access to the tape library by authorizing specific servers
 - Achieve higher levels of availability with data path failover and control path failover.

MSL3040	
Drive Technology Supported	LTO-8 Ultrium 30750 LTO-7 Ultrium 15000 LTO-6 Ultrium 6250
Maximum Number of Drives	21 HH
Maximum Capacity (2.5:1 compression)	1.2 PB (LTO-8, 40 slots) 8.4 PB (LTO-8, 280 slots)
Maximum Data Transfer (Native)	22.5 TB/hr (21 LTO-8 drives)
Drive Interface	8 Gb/sec Fibre Channel 6 Gb/sec SAS
Mail Slots	5 slots per module



Standard Features

High Scalability

Keep pace with data growth across the lifecycle with the MSL3040's scalability.

Effortlessly address both short-term and long-term storage capacity and performance needs and respond to unpredictable data growth, variance in service, or changes to backup window and retention period. Scale-out architecture allows you to pay as you grow - simply add in new modules to boost capacity and performance without investing in a whole new library.

The modular design of the MSL3040 includes a continuous robotics feature to provide in-box scaling for higher performance, greater scalability, and higher reliability. Upgrades are fast and non-disruptive. Scale vertically from 40 to 280 cartridge slots to store up to 8.4PB* in a single 19-inch rack. Several drive options are available

- Add between 1 and 21 HPE StoreEver LTO-8 Ultrium 30750, LTO-7 Ultrium 15000, LTO-6 Ultrium 6250 FC or SAS tape drives
- Scaling up with the MSL3040 couldn't be easier:
- Start with an empty Base Library
- Add a redundant power supply if required**
- Add between 1 and 3 LTO-8, LTO-7 or LTO-6 half-height tape drives and utilize up to 40 cartridge slots - a fully configured base unit with LTO-8 provides a max capacity of up to 1.2PB (assuming 2.5:1 compression)
- Then add between 1 and 6 empty expansion modules to the Base Library - each 3U expansion module might require a power supply if further drives are to be installed in the expansion. Redundant power supply needs to be added if required**.
- Expansion modules can be flexibly installed above or below the base library module
- You can then configure each expansion module with up to 3x LTO-8, LTO-7, or LTO-6 FC or SAS tape drives and utilize up to 40 cartridge slots per expansion module

Notes:

- *Assumes fully loaded with LTO-8 media cartridges at a 2.5:1 data compression ratio
- **Extra power supplies need to be factory integrated in order to be TAA compliant

Cost Effective Tape Solution

Existing customers of MSL2024, 4048, and 6480 Tape Libraries can repurpose their existing LTO-8, LTO-7 and LTO-6 drives in the new MSL3040 to leverage their investment.

Expansion modules are customer-installable; easy to configure and remove.

The MSL Tape Libraries are shipped as a rack-ready unit. The rack mount hardware included with the library allows installation in a variety of HPE racks. For more information on the HPE rack offerings, please see the following URL:

<http://www.hpe.com/info/rackandpower>

Save rack space, floor space, and power and cooling costs with industry leading storage density. The MSL3040 offers 13 cartridge slots per 1U of rack space providing up to 390 TBs per 1U of rack space using LTO-8 drives.

Partitioning

The MSL3040 Tape Library supports up to 21 logical partitions for greater flexibility and higher asset utilization.

Partitioning allows each partitioned library to be presented to the host as an independent library, separate from other partitions in the library. Hosts for each partition own independent sets of media and can use ISV software that is different from the other partitions allowing maximum flexibility and utilization of the MSL library.



Standard Features

Management Console

The HPE StoreEver MSL3040 comes with web-based remote manageability so it can be easily monitored and managed from across the room or across the globe. Functions included in the management tool include:

- Status information on the drive and system
- System configuration operations and reporting
- System error and status logs
- Library and drive firmware upgrade capabilities
- Diagnostic tests and information
- Cartridge movement for maintenance and management purposes
- Cleaning cartridge support
- Security and access control
- SNMP support for IP communication
- Partitioning and Encryption management
- HTTPS capable
- IPv6 and IPv4 network protocol support

HPE StoreEver Management Software

HPE StoreEver Management Software provides an easy to use interface for efficiently managing, monitoring and configuring an entire tape library environment. The HPE StoreEver Management Software solution is made up of HPE Command View for Tape Libraries (CVTL), HPE StoreEver TapeAssure Advanced and HPE StoreEver Data Verification. CVTL provides the centralized platform for TapeAssure Advanced reporting and Data Verification analysis, alongside remote management, diagnostics and configuration for all MSL Tape Libraries from across the room or across the globe. HPE StoreEver TapeAssure Advanced provides the analytics element that implements and presents automated and predictive health, performance and utilization related monitoring of all tape drives and cartridges. HPE StoreEver Data Verification Software proactively validates and scans, non-disruptively, the quality of data stored on LTO tape cartridges, which ensures a successful restore is possible when critical business data is needed.

HPE StoreEver TapeAssure Advanced and Data Verification Software can also be trialed for free once the CVTL Software has been installed. Simply download CVTL for free from <http://www.hpe.com/storage/cvtldownload> and get a 60 day instant-on period to experience TapeAssure Advanced features, and trial Data Verification for the MSL3040 & MSL6480 Tape Libraries with a 10 cartridge slot license.

For more information on HPE StoreEver Management Software, visit:

<http://http://www.hpe.com/storage/storeevermanagementsoftware>

HPE Library and Tape Tools

The MSL3040 Tape Library is supported with HPE Library and Tape Tools (L&TT). L&TT is a free diagnostic tool for all of HPE's tape storage products. This robust diagnostic tool is designed for both the experienced professional and the untrained administrator, and it allows customers to verify the installation, ensure product reliability, perform diagnostics and achieve faster resolution of tape device issues. L&TT performs firmware upgrades, verification of device operation, failure analysis and a range of utility functions. Performance tools assist in troubleshooting issues and system configuration checks warn of common host issues. It also provides seamless integration with HPE support by generating and e-mailing test results and support tickets. HPE Support will require the use of L&TT to troubleshoot most device issues, so it is recommended that a support ticket is pulled and the device assessment test is run before calling.

HPE Library & Tape Tools can be downloaded from the following location:

For more information on L&TT, please visit: <http://www.hpe.com/support/tapetools>.



Standard Features

Safeguarding data for Disaster Recovery

The HPE StoreEver MSL3040 Tape Library can provide the 'last line of defense' for your data.

- Tape is inherently 'offline to threats' - tape's removable media is off-line to the threats from viruses, hackers and cyber-attacks that online data on disk is susceptible to. It is also a logically clean copy that won't be accidentally overwritten by mirroring software.
- LTO-8, LTO-7 and LTO-6 Ultrium tape drives include hardware based data encryption to prevent unauthorized access to data at rest.
- LTO-8, LTO-7 and LTO-6 cartridges are available with write-once-read-many (WORM) capability to prevent accidental overwriting of data archived on the tape.

Both WORM and hardware-based data encryption features help organizations with compliance to increased data security regulations.

Data Encryption

The HPE MSL3040 Tape Library offers multiple options for data encryption, depending on the requirements for policy, regulation, compliance, and centralized key management.

- HPE 1/8 G2 & MSL Encryption Kit
- The HPE MSL Encryption Kit provides a library-enabled encryption solution that greatly enhances data privacy, confidentiality, and integrity of your critical business data while supporting compliance requirements. While there are a wide range of encryption solutions available, the HPE MSL Encryption Kit is intended to be an easy and affordable library-enabled solution for small businesses.
- The encryption kit includes two USB key server tokens, product documentation, and firmware support. One encryption kit is needed per library, which must be physically accessible so that the USB token can be inserted into the automation device. The second token will be used as a backup token, in case the first one is lost or damaged. The USB key server token will plug into the USB port in the library and will generate and maintain encryption keys for the LTO-4 and later generation drives. The USB key server token uses a hardware random number generator, password authentication, and digital envelopes for strong encryption keys and security operations. The encryption kit provides a self-contained solution for autoloaders and MSL libraries with no additional software, PCs, or servers required or involved.
- KMIP
- The HPE MSL3040 is capable of operation using the KMIP 1.2 protocol. One library encryption license will be needed based on the KMIP protocol.

For more information on all supported key management servers, please visit: <http://www.hpe.com/storage/DAPRcompatibility>

Secure Manager License

HPE MSL3040 Secure Manager License is an optional software feature that provides an additional level of security that lets you control access to the tape library by authorizing specific servers to access the library's drives and robotics. Secure Manager increases backup reliability by blocking disruptive traffic from unauthorized hosts to the library, which is one of the main causes of failed or incomplete backups.

- Easily configure device-level SAN access settings
- Allow only authorized servers to access tape drives and critical data
- Manage access control from a single pane of glass, through the library itself
- Paths to robotics can be separated between two independent SANs for isolation purposes

Secure Manager allows you to:

- Create host access groups
- Add and modify host information
- Map device access to specific hosts
- Allows a disable feature when switch zoning is desired



Standard Features

HPE Ultrium WORM

Critical to the success of data retention policies in highly regulated environments is the ability to store and manage data in an unalterable state. Following stringent guidelines set forth by regulatory agencies such as the SEC and HIPPA, IT organizations must now integrate new solutions and policies that can verify the integrity of stored data for periods that can extend well beyond seven years.

Every generation of LTO Ultrium since LTO-3 tape drives feature the ability to archive and store data in a read-only, non-rewriteable format that meets the most stringent regulatory guidelines. Using a combination of integrated fail-safe features in the drive firmware, cartridge memory, and tape formatting, LTO Ultrium provides the ability to archive large amounts of data for periods of up to 30 years in a secure, untampered state. Ultrium tape drives include support for both rewritable and WORM media providing for a secure, long-term archiving solution into any data protection strategy. LTO Ultrium WORM provides the following advantages:

- A single drive to support all backup and archiving needs
- Two distinctive tape cartridges to easily distinguish and manage both rewriteable and WORM data cartridges
- A specially designed WORM data cartridge with multiple integrated fail-safe features to prevent accidental or intentional overwriting of data
- Support from many backup and archiving software vendors, providing the most comprehensive and mainstream support in the industry
- The LTO open standard that offers greater choice and compatibility across all third-generation and later LTO Ultrium products

High Availability

To make the most of your library performance, the MSL3040 offers high availability failover capability utilizing LTO-8, LTO-7 and LTO-6 Tape Drives.

- **Driver-based Data Path Failover (supports LTO-6 drives)**
 - This feature requires the HPE StoreEver MSL3040 High Availability LTO-6 Data Path Failover License.
 - SAN wide failure protection
 - Both ports are connected and both are active but the driver selects between them and uses them one at a time.
 - If a link breaks anywhere between the host and the drive, the host side driver switches to another path and recovers outstanding commands.
 - Drivers handle errors before applications see them.
- **Driver-based Control Path Failover (supports LTO-6 drives)**
 - This feature requires the HPE StoreEver MSL3040 High Availability LTO-6 Control Path Failover License.
 - SAN wide failure protection
 - Both the Control Path (CP) drive and the Control Path Failover (CPF) drive are accessible from the same hosts.
 - If the Control Path drive is lost, the library activates the Control Path Failover drive and the host-based drivers find the robot on the new path.
 - Drivers will handle errors before applications see them.
- **LTO-7 + driver-based Data and Control Path Failover (supports LTO-7 and later FC drives):**
 - LTO-7+ Path Failover supports Data Path and Control Path failover, unlocking feature-sets with just one license enabled in the library.
 - Both Drive paths are active; both ports are green and up in the library and the switch.
 - The Driver-Based Failover technology has the failover intelligence in the driver that runs on the server. Drivers on the host perform path and command failover recovery.
 - Requires host driver support, in addition to minimal tape drive and library firmware features, to manage multiple paths across multiple SAN. Presents a single drive or library path to applications and automatically transfers commands to the new path if the original path is lost.
 - The transfer to the failover path is invisible to most applications, avoiding the need for user intervention.
 - The Driver-Based Failover will only present one library path and one drive path to the host for each library or drive that is attached to the host.
 - If an LTO-8 or LTO-7 drive is enabled for Driver-Based Failover, it can still be seen by hosts with a standard driver even though the Driver-Based Failover will not be functional.



Standard Features

HPE Storage Media

Hewlett Packard Enterprise branded Linear Tape Open (LTO) Ultrium cartridges are designed, manufactured and tested to provide outstanding reliability for backing up, archiving and restoring your data. We continuously monitor the quality of our branded tapes using what we believe is the industry's most comprehensive and forensic specification for quality and reliability. Using real life conditions and both Hewlett Packard Enterprise and non-HPE drives, we supplement extensive in-process QA parametric testing with ongoing drive based scrutiny, to make sure performance is excellent for any combination of device, duty cycle and environment.

Because Hewlett Packard Enterprise is a leading supplier of both LTO tape devices and media, we have the ability to re-create many different scenarios mirroring how customers use their cartridges. And many of HPE's protocols are either unique in nature or scale, such as the HPE 'Green Tape', and HPE 'Environmental Interchange' tests, or far surpass industry standards, for example, Hewlett Packard Enterprise 'Locate/Rewind/Append' test. Since the beginning of 2016, almost 700 million meters of media have been pulled and over 40 million gigabytes of data have been written in HPE's demanding GTT protocol. All of these ongoing tests are intended to ensure HPE LTO Ultrium media is the most reliable you can find. Your best choice for ease of support and maximum dependability is to use HPE-branded Ultrium cartridges at all times.

LTO-7 Type M media

The MSL3040 Tape Library supports LTO-7 Type M media. This is the ability of an LTO-8 drive to write 9 TB (native) on a brand new LTO-7 cartridge instead of 6 TB (native) as specified by the LTO-7 format. LTO-7 Type M cartridges will be designated by an automation barcode label ending with the last 2 characters "M8". A standard 6TB LTO-7 cartridge is indicated with an automation barcode label ending in "L7". An LTO-8 cartridge has a capacity of 12 TB (native), and is indicated with an automation barcode label ending in "L8".

Only unused LTO-7 cartridges may be initialized as LTO-7 Type M. Once a cartridge is initialized as Type M, it may not be changed back to a 6TB LTO-7 cartridge. Also, an LTO-7 Type M cartridge can only be written and read in an LTO-8 drive; LTO-7 drives are not capable of reading LTO-7 Type M cartridges.

- LTO-7 Type M media supports existing LTO format features including data compression, encryption and partitioning enabling LTFS.
- LTO-7 Type M media is not supported on WORM cartridges.
- LTO-9 drives will not be backward compatible with LTO-7 Type M media.

Proven Reliability

With a rating of 2,000,000 robot load/unload cycles, the MSL Tape Libraries provides necessary high reliability for today's demanding environment. To improve reliability and longevity, all HPE Ultrium products feature Data Rate Matching (DRM). This allows the tape drive to dynamically and continuously adjust the speed of the drive, to match the speed of the host or network. This increases performance, reduces mechanical wear on the tape drive and extends tape life.

HPE Tape Libraries include redundancy features for high availability. Dual power supplies are available for increased system reliability and uptime.

Data Rate Matching

Data Rate Matching combines sophisticated buffer management with variable tape drive motor speeds to match the tape drive transfer rate to the host output. This feature ensures that the tape drive continues to stream data regardless of the environment, and brings three big advantages:

- It optimizes performance and maximizes overall efficiency, allowing the drive to respond immediately to any data speed changes from the host.
- It minimizes rewinding and repositioning of the tape, significantly reducing physical wear and increasing reliability.
- It minimizes the power requirements for the drive by reducing the number of repositions needed.



Standard Features

LTO Ultrium Tape Drive	ATS data transfer rate range (native)
HPE LTO-8 Ultrium 30750	101 to 300 MB/s
HPE LTO-7 Ultrium 15000	101 to 300 MB/s
HPE LTO-6 Ultrium 6250	54 to 160 MB/s

Longevity

Organizations need to be confident that their data in archive is still there when they need it. LTO tape media is specified with a 30 year shelf life in normal ambient conditions. HPE TapeAssure Advanced also analyses the results of every tape use to ensure the availability of data placed in long-term storage, archive or DR.

LTO Ultrium Technology

HPE LTO (Linear Tape Open) Ultrium Tape Drives use best of breed technology. By taking the best features from other tape technologies and combining them into a single new technology, Ultrium tape drives are in a league of their own. The LTO Ultrium specification is an industry standard format; thus data written on HPE Ultrium Tape Drives can be interchanged directly with LTO Ultrium Tape Drives from other vendors.

HPE LTO tape drives and automation products are founded on the LTO open standard and adhere to the published twelve-generation LTO format roadmap.

The LTO standard for backward compatibility up to generation seven is to write back one generation and read back two generations. Eighth-generation LTO Ultrium drives read and write LTO -7 and LTO-8 media. As part of the LTO open standard, all HPE tape drives and media offer the same standards of compatibility with tape drives and media manufactured by other LTO vendors.

Micro Focus Data Protector software

Micro Focus Data Protector software automates high performance backup and recovery, from disk or tape, over unlimited distances, to enable 24x7x365 business continuity and improve IT resource utilization. Data Protector software responds to the pressure for lower IT costs and greater operational efficiency, extensive scalability and features for continuous backup and recovery operations enable growth with a single product. A superb solution, no other software can integrate better with the Hewlett Packard Enterprise market-leading line of disk and tape family of products, as well as with other heterogeneous storage infrastructures. Data Protector software fully integrates with the Hewlett Packard Enterprise management solutions, allowing managing data protection as an essential element of an overall IT service.

Data Protector software simplifies the use of complex backup and recovery procedures with the fastest installation, automated routine tasks, and easy-to-use features. The centralized multi-site management easily allows implementing multi-site changes, adapting in real time to changing business requirements. Appropriate for medium and large companies in any industry, Data Protector software is the ideal solution to reduce IT costs and complexity while remaining reliable and scalable to grow from single server environments to the largest distributed enterprise infrastructures.

For further information, please visit:

<https://software.microfocus.com/en-us/software/data-protector>

Compatibility

Hewlett Packard Enterprise's extensive compatibility testing program assures that your HPE MSL Tape Libraries work with leading servers, operating systems, and backup software applications - and not just those sold by Hewlett Packard Enterprise. The MSL libraries work seamlessly in many environments, making them especially suitable if you have a mixed system environment. For the complete and latest list of servers, workstations, operating systems, and backup software that support the MSL tape libraries, reference the HPE Data Agile DAPR Compatibility Matrix (Formerly EBS) at: <http://www.hpe.com/storage/DAPRcompatibility>.



Service and Support

Warranty and Services Include with the Product

Hewlett Packard Enterprise provides a 1-year, next business day onsite, part exchange, limited warranty for the MSL3040 tape library, plus 9x5 phone support for the duration of the warranty.

Service and Support

Protect your business beyond warranty with HPE Support Services

HPE Pointnext delivers confidence, reduces risk and helps customers realize agility and stability. Our integrated portfolio of Services for storage help customers reduce costs, optimize data, streamline storage management, and improve backup and recovery. HPE Support Services enable you to choose the right service level, length of coverage and response time as you purchase your new storage solution, giving you full entitlement for the support for need for your IT and business.

Connect your devices

Unlock all of the benefits of your technology investment by connecting your products to Hewlett Packard Enterprise. Achieve up to 77%¹ reduction in down time, near 100%² diagnostic accuracy and a single consolidated view of your environment. By connecting, you will receive 24x7 monitoring, pre-failure alerts, automatic call logging, and automatic parts dispatch. HPE Proactive Care Service and HPE Datacenter Care Service customers will also benefit from proactive activities to help prevent issues and increase optimization.

All of these benefits are already available to you with your server storage and networking products, securely connected to HPE support.

Notes:

- ¹IDC
 - ²HP CSC reports 2014 - 2015
-

Recommended Services

Optimized Care

HPE Proactive Care* with 24x7 coverage, three year Support Service + 20 Services credits

HPE Proactive Care gives customers an enhanced call experience plus helps preventing problems and maintains IT stability by utilizing personalized proactive reports with recommendations and advice when your products are connected to HPE. This Service combines three years' proactive reporting and advice with our 24x7 coverage, four hour hardware response time when there is a problem.

<https://www.hpe.com/h20195/v2/GetPDF.aspx/4AA3-8855ENW.pdf>

Standard Care

HPE Proactive Care* with 24x7 coverage, three year Support Service + 10 Services credits

HPE Proactive Care gives customers an enhanced call experience plus helps preventing problems and maintains IT stability by utilizing personalized proactive reports with recommendations and advice when your products are connected to HPE. This Service combines three years' proactive reporting and advice with our 24x7 coverage, four hour hardware response time when there is a problem.

<https://www.hpe.com/h20195/v2/GetPDF.aspx/4AA3-8855ENW.pdf>

Basic Care

HPE Foundation Care 24x7, three-year Support Service

HPE Foundation Care 24x7 gives you access to HPE 24 hours a day, seven days a week for assistance on resolving issues. This service includes need based Hardware onsite response within four hours. Simplify your support experience and make HPE your first call to help resolve hardware or software problems.

<https://www.hpe.com/h20195/V2/GetDocument.aspx?docname=4AA4-8876ENW&cc=us&lc=en>



Service and Support

HPE Support Services Credits

Services Credits offer flexible services and technical skills to meet your changing IT demands. With a menu of service that is tailored to suit your needs, you get additional resources and specialist skills to help you maintain peak performance of your IT. Offered as annual credits, you can plan your budgets while proactively responding to your dynamic business.

Notes:*HPE Proactive Care and HPE Proactive Care Advanced require that the customer connect their devices to make the most of these services and receive all the deliverables.

Related Services

HPE Backup Recovery Efficiency Analysis

Assessment of how efficiently backup components are being used as the amount of data to be backed up continues to grow exponentially via analysis intelligence and a snapshot of your current backup environment.

HPE Backup Recovery Impact Analysis

Focus placed on service requirements and design as the key to success for gaining a clear understanding of the role of increasingly diverse data protection strategies.

HPE Installation and Startup Service for HPE StoreEver Storage Systems

Installation and testing of your hardware and software onsite, including configuration of the storage deployment HPE Storage and Data Consultant Residency Services - Strategically augments current environment with Hewlett Packard Enterprise resources who become your trusted advisor to provide answers that are right for your storage and backup environment

HPE Storage Data Migration Service

End-to-end data migration service providing seamless discovery, assessment, planning, and design, completely customizable to your organization's storage area network (SAN) or network attached storage (NAS) environment and using innovative software to help you migrate to HPE storage quickly and efficiently

For more information

<http://www.hpe.com/services/storage>

HPE Support Service Services are sold by Hewlett Packard Enterprise and Hewlett Packard Enterprise Authorized Service Partners:

- Services for customers purchasing from Hewlett Packard Enterprise or an enterprise reseller are quoted using Hewlett Packard Enterprise order configuration tools.
-

Parts and Materials

Hewlett Packard Enterprise will provide HPE-supported replacement parts and materials necessary to maintain the covered hardware product in operating condition, including parts and materials for available and recommended engineering improvements.

Parts and components that have reached their maximum supported lifetime and/or the maximum usage limitations as set forth in the manufacturer's operating manual, product quick-specs, or the technical product data sheet will not be provided, repaired, or replaced as part of these services.

The defective media retention service feature option applies only to Disk or eligible SSD/Flash Drives replaced by Hewlett Packard Enterprise due to malfunction.



Configuration Information

Step 1 - Base Configuration

HPE StoreEver MSL3040

Base Module description

HPE StoreEver MSL3040 Scalable Library Base Module

SKU

Q6Q62B

Notes:

- This product is TAA (Trade Agreements Act) compliant.
- The base module is 3U rack mountable.
- Base module enables 40 slots
- Standard power supply is included with the base module. Redundant power supply is not included as standard, if required it needs to be added to the order. This needs to be factory integrated, #OD1, in order to be TAA compliant
- It does not contain any tape drives, up to 3 HH tape drives may be added to the base module
- MSL3040 rack-rail extends between approximately 683 and 900mm (between 68.3 and 90 cm).

Kit Contents

- 2.5M PDU Power Cord, C13/C14, 10A
- Rack-mount hardware
- Getting started poster
- Power Supply

HPE StoreEver MSL3040 Scalable Library Expansion Module

Q6Q63A

Notes:

- Expansion module activates 40 slots.
- This product is TAA (Trade Agreements Act) compliant.
- The expansion module is 3U rack mountable.
- It does not contain any tape drives, up to 3 HH tape drives may be added to the expansion module. If drives are added to the expansion module then a power supply is required. Standard or redundant power supplies are not included. If needed, these will have to be added to the order. If TAA compliance is required, power supplies need to be factory integrated, #OD1.

Kit Contents

- 2.5M PDU Power Cord, C13/C14, 10A
- Rack-mount hardware
- Getting started poster
- Module interconnect cable (expansion module only)

HPE StoreEver MSL3040 Upgrade Power Supply Kit

Q6Q64A

Notes:

- Redundant power supply is not included as standard with the base module, if required it needs to be added to the order. This needs to be factory integrated, #OD1, in order to be TAA compliant
- In EMEA, for the redundant power supply kit (Q6Q64A) to be integrated into the library base module (Q6Q62B), the library must be factory integrated (#OD1) into a rack.
- If the library, Q6Q62B (HPE MSL3040 Scalable Base Module) is racked (OD1), then the Power Supply kit, Q6Q64A (HPE MSL3040 Upgrade Power Supply Kit), or drives can be integrated (OD1) into the library.
- For the expansion module, neither the standard power supply nor the redundant are included. A power supply is only needed if tape drives need to be installed in the expansion module. If TAA compliance is required, power supplies need to be factory integrated, #OD1.
- In EMEA, for the power supply or redundant power supply kits (Q6Q64A) to be integrated into the expansion modules (Q6Q63A), the expansion module must be factory integrated (#OD1) into a rack. If the Expansion Module (Q6Q63A) is racked (OD1), then the Power Supply kit, Q6Q64A (HPE MSL3040 Upgrade Power Supply Kit), or drives can be integrated (OD1) into the Expansion Module

Factory Racking

Factory integrate MSL3040 Tape Library with other HPE products such as HPE ProLiant Servers

#OD1

Notes: #OD1 will appear after the Tape Library part number on the sales order if HPE factory integration is indicated



Configuration Information

Step 2 - Select Generation & Quantity of LTO Ultrium Tape Drives

Description	SKU
HPE StoreEver LTO-8 Ultrium 30750 FC Drive Kit HPE StoreEver MSL LTO-8 Ultrium 30750 FC Drive Upgrade Kit	Q6Q67A
Notes: <ul style="list-style-type: none"> – Half height LTO-8 FC tape drive. For use with the MSL2024, 4048, 3040 or 6480 libraries. Drive kit includes a tape drive and documentation. – #OD1 will appear after Q6Q67A on the sales order if HPE factory integration is indicated. – For tape drives to be integrated into the library, the library must be factory integrated (#OD1) into a rack – This product is TAA (Trade Agreements Act) compliant. 	
HPE StoreEver LTO-8 Ultrium 30750 SAS Drive Kit HPE StoreEver MSL LTO-8 Ultrium 30750 SAS Drive Upgrade Kit	Q6Q68A
Notes: <ul style="list-style-type: none"> – Half height LTO-8 SAS tape drive. For use with the MSL2024, 4048, 3040 or 6480 libraries. Drive kit includes a tape drive and documentation. – #OD1 will appear after Q6Q68A on the sales order if HPE factory integration is indicated. – For tape drives to be integrated into the library, the library must be factory integrated (#OD1) into a rack – This product is TAA (Trade Agreements Act) compliant 	
HPE StoreEver LTO-7 Ultrium 15000 FC Drive Kit HPE StoreEver MSL LTO-7 Ultrium 15000 FC Drive Upgrade Kit	N7P36A
Notes: <ul style="list-style-type: none"> – Half height LTO-7 FC tape drive. For use with the MSL2024, 4048, 3040 or 6480 libraries. Drive kit includes a tape drive and documentation. – #OD1 will appear after N7P36A on the sales order if HPE factory integration is indicated. – For tape drives to be integrated into the library, the library must be factory integrated (#OD1) into a rack – This product is TAA (Trade Agreements Act) compliant. 	
HPE StoreEver LTO-7 Ultrium 15000 SAS Drive Kit HPE StoreEver MSL LTO-7 Ultrium 15000 SAS Drive Upgrade Kit	N7P37A
Notes: <ul style="list-style-type: none"> – Half height LTO-7 SAS tape drive. For use with the MSL2024, 4048, 3040 or 6480 libraries. Drive kit includes a tape drive and documentation. – #OD1 will appear after N7P37A on the sales order if HPE factory integration is indicated. – For tape drives to be integrated into the library, the library must be factory integrated (#OD1) into a rack – This product is TAA (Trade Agreements Act) compliant. 	
HPE StoreEver LTO-6 Ultrium 6250 FC Drive Kit HPE StoreEver MSL LTO-6 Ultrium 6250 Fibre Channel Drive Upgrade Kit	COH28A
Notes: <ul style="list-style-type: none"> – Half height LTO-6 FC tape drive. For use with the MSL2024, 4048, 3040 or 6480 libraries. Drive kit includes a tape drive and documentation. – #OD1 will appear after COH28A on the sales order if HPE factory integration is indicated. – For tape drives to be integrated into the library, the library must be factory integrated (#OD1) into a rack – This product is TAA (Trade Agreements Act) compliant 	



Configuration Information

HPE StoreEver LTO-6 Ultrium 6250 SAS Drive Kit

HPE StoreEver MSL LTO-6 Ultrium 6250 SAS Drive Upgrade Kit

COH27A

Notes:

- Half height LTO-6 SAS tape drive. For use with the MSL2024, 4048, 3040 or 6480 libraries. Drive kit includes a tape drive and documentation.
- #OD1 will appear after COH27A on the sales order if HPE factory integration is indicated.
- For tape drives to be integrated into the library, the library must be factory integrated (#OD1) into a rack
- This product is TAA (Trade Agreements Act) compliant.

Step 3 - Select Software Licenses

Select each option as required with quantities specified.

Quantity	Description	SKU
----------	-------------	-----

HPE StoreEver MSL TapeAssure Advanced LTU

1 each	HPE StoreEver MSL TapeAssure Advanced LTU	TC406A
--------	---	--------

TC406A

Notes:

- Advanced analytics feature makes use of predictive analytics to predict the likelihood of failures, bottlenecks and load balancing issues in the tape infrastructure. It has unique capabilities of analytics around drive health and life as well as cartridge health and life.
- One license needed per library and Command View TL must be installed.
- This is a paper license that will be mailed.

HPE StoreEver MSL TapeAssure Advanced E-LTU

1 each	HPE StoreEver MSL TapeAssure Advanced E-LTU	TC406AAE
--------	---	----------

TC406AAE

Notes:

- One license needed per library and Command View TL must be installed.
- This is an electronically delivered License.

HPE StoreEver MSL3040 KMIP Key Manager LTU

1 each	HPE StoreEver MSL3040 KMIP Key Manager LTU	Q8K98A
--------	--	--------

Q8K98A

Notes: This is a paper license that will be mailed.

HPE StoreEver MSL3040 KMIP Key Manager E-LTU

1 each	HPE StoreEver MSL3040 KMIP Key Manager E-LTU	Q8K98AAE
--------	--	----------

Q8K98AAE

Notes: This is an electronically delivered License.

HPE StoreEver MSL3040 Secure Manager LTU

1 each	HPE StoreEver MSL3040 Secure Manager LTU	Q8K99A
--------	--	--------

Q8K99A

Notes: This is a paper license that will be mailed.

HPE StoreEver MSL3040 Secure Manager E-LTU

1 each	HPE StoreEver MSL3040 Secure Manager E-LTU	Q8K99AAE
--------	--	----------

Q8K99AAE

Notes: This is an electronically delivered License.

HPE StoreEver MSL3040 LTO-7+ Path Failover LTU

1 each	HPE StoreEver MSL3040 LTO-7+ Path Failover LTU	Q8L00A
--------	--	--------

Q8L00A

Notes: This is an electronically delivered License.

HPE StoreEver MSL3040 LTO-7+ Path Failover E-LTU

1 each	HPE StoreEver MSL3040 LTO-7+ Path Failover E-LTU	Q8L00AAE
--------	--	----------

Q8L00AAE

Notes: This is an electronically delivered License.



Configuration Information

Quantity	Description	SKU
	HPE StoreEver High Availability MSL3040 LTO-6 Control Path Failover LTU	
1 each	HPE StoreEver MSL3040 High Availability LTO-6 Control Path Failover LTU	Q8K96A
	Notes: This is an electronically delivered License.	
	HPE StoreEver High Availability MSL3040 LTO-6 Control Path Failover E-LTU	
1 each	HPE StoreEver MSL3040 High Availability LTO-6 Control Path Failover E-LTU	Q8K96AAE
	Notes: This is an electronically delivered License.	
	HPE StoreEver High Availability MSL3040 LTO-6 Data Path Failover LTU	
1 each	HPE StoreEver MSL3040 High Availability LTO-6 Data Path Failover LTU	Q8K97A
	Notes: This is an electronically delivered License.	
	HPE StoreEver High Availability MSL3040 LTO-6 Data Path Failover E-LTU	
1 each	HPE StoreEver MSL3040 High Availability LTO-6 Data Path Failover E-LTU	Q8K97AAE
	Notes: This is an electronically delivered License.	

Step 4 - Select Additional Accessories

Power Cords

Quantity	Description	SKU
1 each	HPE C13 - C14 WW 250V 10Amp 2.5m Jumper Cord	142257-002

Notes: This cord ships standard with each MSL3040 Base Tape Library and Power Supply Upgrade Kit. It can be used to connect the rack-mounted device to PDUs with IEC-320 receptacles.

Regional Power Cord Options

Notes: One PDU cord is shipped with each base module (above). If regional power cords are preferred, order qty (1) for the base module and one with each upgrade power supply purchased. Please select the correct power cord for your geographical location.

Quantity to order: 1 per base module and upgrade power supply

HPE C13 - Nema 5-15P US/CA 110V 10Amp 1.83m Power Cord	AF556A
HPE C13 - CEE-VII EU 250V 10Amp 1.83m Power Cord	AF568A
HPE C13 - BS-1363A UK/HK/SG 250V 10Amp 1.83m Power Cord	AF570A
HPE C13 - DK-2.5A DK 250V 10Amp 1.83m Power Cord	AF566A
HPE C13 - SEV 1011 CH 250V 10Amp 1.83m Power Cord	AF565A
HPE C13 - SABS-164 ZA 250V 10Amp 2.5m Power Cord	AF567A
HPE C13 - CNS-690 TW 110V 13Amp 1.83m Power Cord	AF561A
HPE C13 - GB-1002 CN 250V 10Amp 1.83m Power Cord	AF557A
HPE C13 - JIS C8303 JP 100V 12Amp 2.0m Power Cord	AF572A
HPE C13 - AS3112-3 AU 250V 10Amp 2.5m Power Cord	AF569A
HPE C13 - IRAM -2073 AR 250V 10A 2.5m Power Cord	AF558A
HPE C13 - Nema 5-15P TH/PH 250V 10Amp 1.83m Power Cord	AF559A
HPE C13 - KSC- 8305 KR 250V 10Amp 1.83m Power Cord	AF560A
HPE C13 - SI-32 IL 250V 10Amp 1.83m Power Cord	AF564A
HPE C13 - IS-1293 IN 240V 6Amp LV 2.0m Power Cord	AF562A
HPE C13 - IS-1293 IN 240V 6Amp LV 2.0m Power Cord	AF562A

Configuration Information

Notes: This product can ONLY be used with an HPE approved power cord for your specific geographic region. Use of a non-HPE approved power cord may result in:

- Not meeting individual country specific safety requirements;
 - Insufficient conductor capacity that could result in overheating with potential personal injury and/or property damage
 - An unapproved power cord could fracture resulting in the internal contacts being exposed, which potentially could subject the user to a shock hazard. Hewlett Packard Enterprise disclaims all liability in the event a non-HPE approved power cord is used.
-



Related Options

Redundant Power Supply Upgrade Kit

Description

HPE StoreEver MSL3040 Upgrade Power Supply Kit

SKU

Q6Q64A

Notes:

- Redundant power supply is not included as standard with the base module, if required it needs to be added to the order. This needs to be factory integrated, #OD1, in order to be TAA compliant.
- For the expansion module, neither the standard power supply nor the redundant are included. A power supply is only needed if tape drives need to be installed in the expansion module. If TAA compliance is required, power supplies need to be factory integrated, #OD1.

Factory Racking

#OD1

Factory integrate the MSL Tape Libraries with other Hewlett Packard Enterprise products such as HPE ProLiant Servers

Notes: #OD1 will appear after the Tape Library part number on the sales order if HPE factory integration is indicated. One Base Module and up to 6 Expansion Modules can be factory integrated up to 21U in a single rack.

Encryption

HPE StoreEver 1/8 G2 Tape Autoloader and MSL Tape Library Encryption Kit

AM495A

Notes: The Encryption Kit key server token will generate and retain encryption keys for HPE LTO Ultrium tape drives in the library. Works independent of application or backup software; doesn't require ISV support.

HPE StoreEver MSL3040 KMIP Key Manager LTU

Q8K98A

Notes: This is a paper license that will be mailed.

HPE StoreEver MSL3040 KMIP Key Manager E-LTU

Q8K98AAE

Notes: This is an electronically delivered License.

FC Host Bus Adapters

The MSL Libraries are certified with a number of Fibre Channel Host Bus Adapters. For the most current list of supported FC HBAs, please reference the HPE Data Agile DAPR Compatibility Matrix (Formerly EBS) and Design Guide located at:

<http://www.hpe.com/storage/DAPRcompatibility>.

For more information on FC HBAs, see HPE StoreFabric Adapters at:

<http://www.hpe.com/storage/san/>

SAS Host Bus Adapters

The MSL Libraries are certified with a number of SAS Host Bus Adapters and ProLiant Smart Array Controllers. For the most current list of supported devices, please reference the HPE Data Agile DAPR Compatibility Matrix (Formerly EBS) and Design Guide located at: <http://www.hpe.com/storage/DAPRcompatibility>.

For more information on HPE Smart Array RAID controllers, see Fibre HPE P-class RAID controllers at:

<http://www.hpe.com/servers/smartarray/>

For more information on HPE ProLiant (SAS) host bus adapters, see H-class HBA controllers at:

<http://www.hpe.com/servers/smartarray/>



Related Options

HBAs and SAS Controllers

Description	SKU
HPE Smart Array P408e-p SR Gen10 (8 External Lanes/4GB Cache) 12G SAS PCIe Plug-in Controller	804405-B21
Notes: Recommended for ProLiant Gen10 SAS tape automation connect.	
HPE Smart Array E208e-p SR Gen10 (8 External Lanes/No Cache) 12G SAS PCIe Plug-in Controller	804398-B21
Notes: Recommended for ProLiant Gen10 SAS tape automation connect.	
Microsemi Adaptec HBA 1100-8e	A1100-8E
Notes: Recommended SAS HBA for DL & ML Gen9 servers only. HPE does not provide official support for this adapter, however the configuration is supported.	

Optical cables

OM4 LC-LC type cables

HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 1m Cable	QK732A
HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 2m Cable	QK733A
HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 5m Cable	QK734A
HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 15m Cable	QK735A
HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 30m Cable	QK736A
HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 50m Cable	QK737A

Allowed cable lengths

External Cable type	Drive type	2Gb	4Gb	8Gb
OM2	All drive types	0.5m - 300m	0.5m - 150m	NA
OM3/OM4	All drive tapes	0.5m - 500m	0.5m - 380m	0.5m - 150m

Notes: The lowest OM rating in a path from the drive to the switch or HBA will dictate the maximum length of the connection path.

Cable Kits (SAS)

HPE StoreEver Mini-SAS High Density to 4-lane Mini-SAS External Fanout 2m Cable	K2R09A
Notes: One cable can connect up to four tape drives. Use this cable to connect HPE MSL SAS Tape Libraries to the ProLiant Gen9 and Gen 10 Smart Host Bus Adapter and the HPE H241 Smart Host Bus Adapter.	
HPE StoreEver Mini-SAS High Density to 4-lane Mini-SAS External Fanout 4m Cable	K2R10A
Notes: One cable can connect up to four tape drives. Use this cable to connect HPE MSL SAS Tape Libraries to the ProLiant Gen9 and Gen 10 Smart Host Bus Adapter and the HPE H241 Smart Host Bus Adapter.	
HPE 2.0m External Mini SAS High Density to Mini SAS Cable	716191-B21
Notes: One cable is required for every tape drive. Use this cable to connect HPE MSL SAS Tape Libraries to the HPE H241 Smart Host Bus Adapter.	
HPE 4.0m External Mini SAS High Density to Mini SAS Cable	716193-B21
Notes: One cable is required for every tape drive. Use this cable to connect HPE MSL SAS Tape Libraries to the HPE H241 Smart Host Bus Adapter.	

Rack Cabinets

The MSL3040 libraries are supported in a variety of HPE Rack offerings, including the HPE Intelligent Series Racks and the HPE 10000 G2 Series Racks.

Notes: If ordering the #0D1 Factory Integration option, the MSL3040 Tape Libraries are certified to ship with one base module and up to 6 expansion modules (up to 21U) installed in the HPE Intelligent Series rack.



Related Options

Description	SKU
Media	
HPE LTO-8 Ultrium 30TB RW Data Cartridge	Q2078A
HPE LTO-8 Ultrium 30TB WORM Data Cartridge	Q2078W
HPE LTO-7 Ultrium 15TB RW Data Cartridge	C7977A
HPE LTO-7 Ultrium No Case 960 Tape Pallet	C7977AB
HPE LTO-7 Ultrium RW 960 Tape Pallet	C7977AD
HPE LTO-7 Ultrium 15TB Eco Case Data Cartridge 20 Pack	C7977AH
HPE LTO-7 Ultrium WORM Data Cartridge	C7977W
HPE LTO-6 Ultrium 6.25TB MP RW Data Cartridge	C7976A
HPE LTO-6 Ultrium 6.25TB MP WORM Data Cartridge	C7976W
HPE LTO-6 Ultrium 6.25TB BaFe RW Data Cartridge	C7976B
HPE LTO-6 Ultrium 6.25TB BaFe WORM Data Cartridge	C7976BW
HPE LTO-5 Ultrium 3TB RW Data Cartridge	C7975A
HPE LTO-5 Ultrium 3TB WORM Data Cartridge	C7975W
Bar Code Labels	
HPE LTO-8 Ultrium RW Bar Code Label Pack	Q2015A
HPE LTO-7 Ultrium Type M RW Bar Code Label Pack	Q2016A
HPE LTO-7 Ultrium RW Bar Code Label Pack	Q2014A
HPE LTO-6 Ultrium RW Bar Code Label Pack	Q2013A
HPE LTO-5 Ultrium RW Bar Code Label Pack	Q2011A
HPE LTO-5 Ultrium WORM Bar Code Label Pack	Q2012A
Non-Custom Labeled Data Cartridges	
Notes: Non-Custom labels will come pre-labeled with a pre-determined number sequence.	
HPE LTO-8 Ultrium 30TB RW Non Custom Labeled Library Pack 20 Data Cartridges with Cases	Q2078AN
HPE LTO-7 Ultrium Type M 22.5TB RW 20 Data Cartridges Non Custom Labeled with Cases	Q2078MN
HPE LTO-7 Ultrium RW No Case Custom Labeled Data Cartridge 20 Pack	C7977AC
HPE LTO-7 Ultrium Non Custom Labeled Data Cartridge 20 Pack	C7977AN
HPE LTO-6 Ultrium 6.25TB MP RW Non Custom Labeled Data Cartridge 20 Pack	C7976AN
HPE LTO-6 Ultrium 6.25TB BaFe RW Non Custom Labeled Data Cartridges 20 Pack	C7976BN
HPE LTO-5 Ultrium Non-custom Labeled Data Cartridge 20 Pack	C7975AN
Custom Labeled Data Cartridges	
Notes: Custom labeled products allow customers to customize a specific sequence printed on each label.	
HPE LTO-8 Ultrium 30TB RW Custom Labeled Library Pack 20 Data Cartridges with Cases	Q2078AL
HPE LTO-8 Ultrium 30TB WORM Custom Labeled Library Pack 20 Data Cartridges with Cases	Q2078WL
HPE LTO-8 Ultrium 30TB RW Custom Labeled Library Pack 20 Data Cartridges without Cases	Q2078AC
HPE LTO-7 Ultrium Type M 22.5TB RW 20 Data Cartridges Custom Labeled with Cases	Q2078ML
HPE LTO-7 Ultrium Type M 22.5TB RW 20 Data Cartridges Custom Labeled Library Pack without Cases	Q2078MC
HPE LTO-7 Ultrium 15 TB RW RFID Custom Labeled Data Cartridge (20 pack)	7977AF
HPE LTO-7 Ultrium RW Custom Labeled Data Cartridge 20 Pack	C7977AL
HPE LTO-7 Ultrium WORM Custom Labeled Data Cartridge 20 Pack	C7977WL
HPE LTO-6 Ultrium 6.25TB MP RW Custom Labeled Data Cartridge 20 Pack	C7976AL
HPE LTO-6 Ultrium 6.25TB MP RW Custom Labeled Data Cartridge No Case 20 Pack	C7976AC

Related Options

Description

	SKU
HPE LTO-5 RW Custom Labeled Data Cartridge 20 Pack	C7975AL
HPE LTO-5 RW Custom Labeled No Case Data Cartridge 20 Pack	C7975AC
HPE LTO-5 WORM Custom Labeled Cartridge 20 Pack	C7975WL

Notes: For more information on LTO media, see:

<https://www.hpe.com/us/en/product-catalog/storage/storage-media.hits-12.html>

HPE Support Service Options

HPE 3 Year Foundation Care Next Business Day MSL 3040 Base Module Service	H9XW8E
HPE 3 Year Foundation Care Same Business Day MSL 3040 Base Module Service	H9XX0E
HPE 3 Year Foundation Care 24x7 MSL 3040 Base Module Service	H9XX5E
HPE 3 Year Foundation Care Call-To-Repair MSL 3040 Base Module Service	H9XY1E
HPE 4 Year Foundation Care 24x7 MSL 3040 Base Module Service	H9XZ4E
HPE 4 Year Foundation Care Call-To-Repair MSL 3040 Base Module Service	H9YA0E
HPE 5 Year Foundation Care 24x7 MSL 3040 Base Module Service	HA0R0E
HPE 5 Year Foundation Care Call-To-Repair MSL 3040 Base Module Service	HA0R6E
HPE 1 Year Post Warranty Foundation Care Next Business Day MSL 3040 Base Module Service	HA0S2PE
HPE 1 Year Post Warranty Foundation Care Same Business Day MSL 3040 Base Module Service	HA0S4PE
HPE 1 Year Post Warranty Foundation Care 24x7 MSL 3040 Base Module Service	HA0S7PE
HPE 1 Year Post Warranty Foundation Care Call-To-Repair MSL 3040 Base Module Service	HA0T1PE
HPE Installation Storage Service	U4823E
HPE StoreEver MSL2024/4048/3040 Startup Service	UA871E



Technical Specifications

MSL3040		
Drive Technology	LTO-8 Ultrium 30750 LTO-7 Ultrium 15000 LTO-6 Ultrium 6250	
Maximum Number of Drives - Per Module	3 HH (per Module)	
- Per fully expanded Library	21 HH (per Library)	
Number of Slots - Per Module	40 (Base Module)/40 (Expansion Module)	
- Per fully expanded Library	280 (per Library)	
Drive Interface	8 Gb Native Fibre Channel 6 Gb/sec SAS	
Maximum Capacity	Native - Per Base Module	480 TB (LTO-8, 40 slots) 240 TB (LTO-7, 40 slots) 100 TB (LTO-6, 40 slots)
	- Per Full Library	3.36PB (LTO-8, 280 slots) 1.68 PB (LTO-7, 280 slots) 700 TB (LTO-6, 280 slots)
	Compressed (2.5:1) - Per Module	1.2 PB (LTO-8, 40 slots) 600 TB (LTO-7, 40 slots) 250 TB (LTO-6, 40 slots)
	- Per Library	8.4 PB (LTO-8, 280 slots) 4.2 PB (LTO-7, 280 slots) 1.75 PB (LTO-6, 280 slots)
Maximum Transfer Rate	Native - Per Module	3.24 TB/hour (with 3 LTO-8 drives) 3.24 TB/hour (with 3 LTO-7 drives) 1.73 TB/hour (with 3 LTO-6 drives)
	- Per Library	22.5 TB/hr (with 21 LTO-8 drives) 22.5 TB/hr (with 21 LTO-7 drives) 14 TB/hr (with 21 LTO-6 drives)
	Compressed (2.5:1) - 3 HH drives Per Module	Up to 8.1TB/hr (with 3 LTO-8 drives) Up to 8.1TB/hr (with 3 LTO-7 drives) 4.3 TB/hr (with 3 LTO-6 drives) Up to 72.45 TB/hr (with 21 LTO-8 drives)
	- 21 HH drives Per Library	Up to 72.45 TB/hr (with 21 LTO-7 drives) 30.2 TB/hr (with 21 LTO-6 drives)
MSL3040		
Dimensions	Out-of-Box (HxWxD)	5.24 X 18.98 X 34.27 in (13.3 x 48.2 x 87.3 cm)
	Shipping (HxWxD)	12.6 X 27.09 X 45.59 in (61.5 x 80.0 x 120.0 cm)
Weight	Out of box	55.34 lbs (25.1 kg)
	Shipping	68.34 lbs (31 kg)
Notes: The weight of each library varies somewhat based on the type and number of LTO tape drives contained in the configuration. Configurations with different numbers of tape drives can be calculated by adding or subtracting the weight of a tape drive.		

Technical Specifications

Reliability	MTBF (mean time between failures)	125,000 hours (based on 1M MSBF)
	MSBF (Mean swaps before failure)	1,000,000
Average Cartridge Swap Time (drive to slot, slot to drive)	N/A	26 seconds (Base Unit)
Initialization Time	N/A	77 to 204 seconds
Inventory Time	N/A	50 seconds (average) Base unit
Connectors	Mini-SAS (MSL SAS model only) LC Optical Fibre (MSL FC models only) (1)RJ-45 Ethernet	
Color Control Panel information (on front panel)	Monochrome graphic display, 4 inch diagonal, 240 by 128 black dots, 4/3 aspect ratio	
Management Interface	10/100/1000 Mbits/second, auto-configuring interface. RJ-45 connection. Https configurable.	
Power	230 Watts (max)	
Input Requirements	100-240 VAC, 3.7A Max., 50/60Hz	
Relative Humidity (non-condensing)	Operating	20% to 80%
	Shipping	20% to 90%
Temperature Range (wet bulb)	Operating	50° to 95° F (10° to 35° C)
	Shipping	-22° to 140° F (-30° to 60° C)
Altitude	Notes: Library operating temperature limits are based on the industry standard tape limit.	
	Operating	13,000 ft (4000 m)
	Shipping	35,000 ft (10,675 m)



Summary of Changes

Date	Version History	Action	Description of Change
01-Feb-2021	Version 14	Changed	Related Options section was updated.
07-Dec-2020	Version 13	Changed	Technical Specifications section was updated
05-Oct-2020	Version 12	Changed	Configuration Information section was updated
08-Sep-2020	Version 11	Changed	Configuration Information section was updated
17-Aug-2020	Version 10	Changed	QuickSpecs layout was updated and Branding Refresh was applied.
09-Dec-2019	Version 9	Changed	Related Options section was updated
07-Oct-2019	Version 8	Changed	Related Options section was updated
03-Jun-2019	Version 7	Changed	Overview section was updated.
15-Apr-2019	Version 6	Changed	Overview and Configuration Information sections were updated.
04-Mar-2019	Version 5	Changed	Related Options section was updated.
01-Oct-2018	Version 4	Changed	Overview, Product Highlights, Service and Support, Configuration Information, Related Options and Technical Specification sections were updated. SKU descriptions were updated. Obsolete SKUs were removed.
05-Mar-2018	Version 3	Changed	Product Highlights and Related Options were revised.
05-Feb-2018	Version 2	Changed	Product Highlights and Related Options were revised.
04-Dec-2017	Version 1	New	New QuickSpecs



Copyright

Make the right purchase decision.
Contact our presales specialists.



Chat



Email



Call



Get updates



© Copyright 2021 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for HPE products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HPE shall not be liable for technical or editorial errors or omissions contained herein.

For tape drives and media, 1 GB = 1 billion bytes. Actual formatted capacity is less.

a00026511enw - 16082 - Worldwide - V14 - 01-February-2021