


### Overview

#### HP 290 G2 Microtower Business PC



#### **Front**


1. Slim-height Bay - supporting an optical disk drive (optional)
2. Power Button
3. Combo jack, Headphone/ Microphone
4. SD Card Reader
5. (2) USB 3.1 Gen1 Port
6. HDD LED Light

#### **Not Shown**

- Slots
- (1) PCI Express x16
  - (1) PCI Express x1
  - (1) Legacy PCI (Optional)
  - (1) M.2 for WLAN
  - (1) M.2 2242/2280 storage
- Bays
- (1) 3.5" internal HDD bay
  - (1) 3.5" or 2.5" internal HDD bay (share bay)
  - (1) 9.5mm internal optical drive bay

### Overview

#### HP 290 G2 Microtower Business PC



#### **Back**

- |   |   |
|---|---|
| 1. Audio Mic in   | 7. Standard lock slot   |
| 2. Audio Line out   | 8. (2) USB 2.0 port   |
| 3. Audio Link in  | 9. RJ-45 Network Connector                                    |
| 4. HDMI Port <sup>1</sup>                                   | 10. (2) USB 3.1 Gen1 Port (left) and (2) USB 2.0 port (right) |
| 5. VGA Port <sup>1</sup>                                    | 11. Power Cord Connector                                      |
| 6. Serial Port (optional, and available on legacy PCA only) | 12. Padlock Loop  |

#### **Not Shown**

- (1) PS/2 Port (optional, and available on legacy PCA only)
- (2) Parallel Port (Optional via PCIe slot)
- (3) 4 Serial Port (Optional via PCIe slot)

1. Port will be covered up when discrete graphic card is configured on shipped machine

### Standard Features and Configurable Modules

#### AT A GLANCE

- Windows 10 Pro, Windows 10 Home or FreeDOS 2.0
- Intel® H370 chipset supporting Intel® 8<sup>th</sup> and 9<sup>th</sup> processors featuring Intel® UHD Graphics
- Supports an optional discrete graphics card
- Integrated 10/100/1000 Ethernet Controller or 802.11ac (1x1) WiFi and Bluetooth® 4.2 Combo
- Up to 32GB DDR4-2666 Unbuffered Memory (UDIMM)
- Independent monitor support via VGA and HDMI interfaces
- TPM 2.0 support (either dTPM or fTPM)<sup>1</sup>
- Supports both Hard Disk Drives and SATA TLC / M.2 PCIe NVMe Solid State Drives
- Audio in, Audio out and Mic in support 5.1 channel
- 8 USB Ports (including 4 USB 3.1 Gen1 ports)
- 180W/310W 90% HE power supply
- Security cable lock supported (sold separately)
- Protected by HP Services; terms and conditions vary by country; certain restrictions and exclusions apply
- Dust filter available

TPM feature will not be supported on machine pre-configured with FreeDOS  
In cases, machines pre-configured with Windows OS might ship with TPM turned off

**NOTE: See important legal disclosures for all listed specs in their respective features sections.**

### Standard Features and Configurable Modules

#### PRODUCT NAME

HP 290 G2 Microtower Business PC

#### OPERATING SYSTEM

<b>Preinstalled</b>	Windows 10 Pro 64* Windows 10 Home 64*
<b>Pre-installed (other)</b>	FreeDOS 2.0

1. Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows 10 is automatically updated, which is always enabled. ISP fees may apply and additional requirements may apply over time for updates. See <http://www.windows.com/>

#### PROCESSORS

##### Intel® Celeron® Processors<sup>2,3</sup>

CPU Intel Celeron G4900 Dual Core 3.1GHz 2400MHz 54W (3.1 GHz, 2 MB cache, 2 cores)

CPU Intel Celeron G4930 Dual Core 3.2GHz 2400MHz 54W (3.2GHz, 2 MB cache, 2 cores)

##### Intel® Pentium® Processors<sup>2,3</sup>

CPU Intel Pentium G5400 Dual Core 3.7GHz 2400MHz 54W (3.7 GHz, 4 MB cache, 2 cores)

CPU Intel Pentium G5500 Dual Core 3.8GHz 2400MHz 54W (3.8 GHz, 4 MB cache, 2 cores)

##### Intel® Pentium Gold®<sup>2,3</sup>

CPU Intel Pentium G5420 Dual Core 3.8GHz 2400MHz 54W (3.8GHz, 4 MB cache, 2 cores)

CPU Intel Pentium G5600 Dual Core 3.9GHz 2400MHz 54W (3.9 GHz, 4 MB cache, 2 cores)

CPU Intel Pentium G5620 Dual Core 3.8GHz 2400MHz 54W (3.8GHz, 4 MB cache, 2 cores)

##### Intel 8<sup>th</sup> Processors

###### Intel® Core™ i3<sup>2,3</sup>

CPU Intel Core i3-8100 Quad Core 3.6GHz 2400MHz 65W (3.6 GHz, 6 MB cache, 4 cores)

###### Intel® Core™ i5<sup>2,3</sup>

CPU Intel Core i5-8400 6C 2.8GHz 2666MHz 65W (2.8GHz, turbo up to 4GHz, 9 MB cache, 6 cores)

CPU Intel Core i5+ (Core i5 and Intel® Optane™ Memory<sup>4</sup>)

i5-8400 6C 2.8GHz 2666MHz 65W (2.8GHz, turbo up to 4GHz, 9 MB cache, 6 cores)

###### Intel® Core™ i5<sup>2,3</sup>

CPU Intel Core i5-8500 6C 3.0GHz 2666MHz 65W (3GHz, turbo up to 4.1GHz, 9 MB cache, 6 cores)

CPU Intel Core i5+ (Core i5 and Intel® Optane™ Memory<sup>4</sup>)

i5-8500 6C 3.0GHz 2666MHz 65W (3GHz, turbo up to 4.1GHz, 9 MB cache, 6 cores)

###### Intel® Core™ i7<sup>2,3</sup>

CPU Intel Core i7-8700 6C 3.2GHz 2666MHz 65W (3.2GHz, turbo up to 4.6GHz, 12 MB cache, 6 cores)

CPU Intel Core i7+ (Core i7 and Intel® Optane™ Memory<sup>4</sup>)

i7-8700 6C 3.2GHz 2666MHz 65W (Coffee Lake-S) (3.2GHz, turbo up to 4.6GHz, 12 MB cache, 6 cores)

##### Intel 9<sup>th</sup> Processors

###### Intel® Core™ i3<sup>2,3</sup>

CPU Intel Core i3-9100 4C 3.6GHz 2400MHz 65W (3.6GHz, turbo up to 4.2GHz, 6 MB cache, 4 cores)

CPU Intel Core i3-9300 4C 3.7GHz 2400MHz 62W (3.7GHz, turbo up to 4.3GHz, 8 MB cache, 4 cores)

###### Intel® Core™ i5<sup>2,3</sup>

CPU Intel Core i5-9400 6C 2.9GHz 2666MHz 65W (2.9GHz, turbo up to 4.7GHz, 9 MB cache, 6 cores)\*

### Standard Features and Configurable Modules

CPU Intel Core i5-9400F 6C 2.9GHz 2666MHz 65W (2.9GHz, turbo up to 4.1GHz, 9 MB cache, 6 cores)

CPU Intel Core i5-9500 6C 3GHz 2666MHz 65W (3GHz, turbo up to 4.4GHz, 9 MB cache, 6 cores)

CPU Intel Core i5-9500F 6C 3GHz 2666MHz 65W (3GHz, turbo up to 4.4GHz, 9 MB cache, 6 cores)

CPU Intel Core i5-9600 6C 3.1GHz 2666MHz 65W (3.1GHz, turbo up to 4.6GHz, 9 MB cache, 6 cores)

#### Intel® Core™ i7<sup>2,3</sup>

CPU Intel Core i7-9700 8C 3GHz 2666MHz 65W (3GHz, turbo up to 4.7GHz, 12 MB cache, 8 cores)

2. Your product does not support Windows 8 or Windows 7. In accordance with Microsoft's support policy, HP does not support the Windows® 8 or Windows 7 operating system on products configured with Intel 8<sup>th</sup> or 9<sup>th</sup> generation and forward processors or provide any Windows® 8 or Windows 7 drivers on <http://www.support.hp.com>

3. Multi-Core is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. 64-bit computing system required. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. Intel's numbering is not a measurement of higher performance.

4 Intel® Optane™ memory (cache) is sold separately. Intel® Optane™ memory system acceleration does not replace or increase the DRAM in your system. Available for HP commercial desktops and notebooks and for select HP workstations (HP Z240 Tower/SFF, Z2 Mini, ZBook Studio, 15 and 17 G5) and requires a SATA HDD, 7th Gen or higher Intel® Core™ processor or Intel® Xeon® processor E3-1200 V6 product family or higher, BIOS version with Intel® Optane™ supported, Windows 10 version 1703 or higher, M.2 type 2280-S1-B-M connector on a PCH Remapped PCIe Controller and Lanes in a x2 or x4 configuration with B-M keys that meet NVMe™ Spec 1.1, and an Intel® Rapid Storage Technology (Intel® RST) 15.5 driver.

**\*NOTE:** Only available on selected region

## CHIPSET

Intel® H370 Chipset

## GRAPHICS

### Integrated<sup>5,6</sup>

Intel® UHD

Graphics 630 (integrated on 8<sup>th</sup> Core i7/i5/i3 processors and 9<sup>th</sup> i5 processors)

Intel® UHD

Graphics 610 (integrated on 8<sup>th</sup> and 9<sup>th</sup> Pentium and Celeron)

### Discrete Graphics

AMD Radeon™ R7 430 2GB PCIe x16 GFX

AMD Radeon™ 520 1GB GFX

NVIDIA® GeForce® GT730 1GB GFX

NVIDIA® GeForce® GT730 2GB GFX

NVIDIA® GeForce® GT1060 3GB GFX\*

NVIDIA® GeForce® GT1060 6GB GFX\*

NVIDIA® GeForce® GTX 1650 4GB\*

5. HD content required to view HD images.

6. Integrated Intel software is available on select models only and requires separately purchased projector, tv or computer monitor with an integrated or external receiver. External receivers connect to the projector, tv or computer monitor via a standard VGA, HDMI cable, also sold separately.

**NOTE\*:** Available for specific region.

### Standard Features and Configurable Modules

#### MEMORY<sup>7</sup>

Form Factor	Type	Maximum	# of Slots
Microtower	DDR4 2666 (Transfer rates up to 2666 MT/s)	32 GB capacity	2 DIMM
	4GB DDR4-2666 UDIMM NECC (1x4GB)		
	8GB DDR4-2666 UDIMM NECC (1x8GB)		
	8GB DDR4-2666 UDIMM NECC (2x4GB)		
	16GB DDR4-2666 UDIMM NECC (1x16GB)		
	16GB DDR4-2666 UDIMM NECC (2x8GB)		

7. Memory modules support data transfer rates up to 2666 MT/s; actual data rate is determined by the system's configured processor. See processor specifications for supported memory data rate.

### Standard Features and Configurable Modules

#### STORAGE<sup>8</sup>

##### SATA3 - 3.5" or 2.5" 6Gb/s HDDs

2TB 7200 RPM SATA Hard Disk Drive

1TB 7200 RPM SATA Hard Disk Drive

500GB 7200 RPM SATA Hard Disk Drive

128GB 2.5" TLC SSD

256GB 2.5" TLC SSD

##### Solid State Drives

128GB M.2 NVMe

256GB M.2 NVMe

512GB M.2 NVMe

##### SD Card Reader<sup>9</sup>

SD/SDHC/SDXC SD Card Reader

##### Intel Optane Memory<sup>10</sup>

SSD Intel 16GB 2280 Optane Memory

8. For hard drives and solid state drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36 GB (for Windows 10) of system disk is reserved for the system recovery software.

9. Card sold separately

10. Optional per configuration

---

#### OPTICAL DISC DRIVES<sup>11</sup>

DVD-ROM 9.5mm

DVD-Writer 9.5mm\*

11. Optical drives are optional or add on features. Duplication of copyrighted material is strictly prohibited. Actual speeds may vary. Double Layer media compatibility will widely vary with some home DVD players and DVD-ROM drives.

---

#### NETWORKING<sup>12</sup>

##### Ethernet (RJ-45)

Integrated 10/100/1000M GbE LAN

##### Wi-Fi and Bluetooth<sup>®</sup>

802.11ac (1x1) WiFi and Bluetooth<sup>®</sup> 4.2 Combo

12. Wireless cards are optional or add-on features and requires separately purchased wireless access point and internet service. Availability of public wireless access points limited.

### Standard Features and Configurable Modules

#### AUDIO / MULTIMEDIA

Integrated Hi-Definition Audio  
Combo Jack, Headphone / Microphone  
Line-in / Line-out / Mic-in jacks (3.5mm)

---

#### KEYBOARDS AND POINTING DEVICES<sup>13</sup>

##### Keyboard

USB Business Slim Wired Keyboard  
HP USB Keyboard  
Business Slim USB Antimicrobial Wired Keyboard (China)  
Business Slim PS/2 Wired Keyboard  
No KB Option

##### Mouse

Antimicrobial USB Mouse (China)  
HP Optical USB Mouse  
Universal Wired Mouse USB  
USB Hardened Mouse (India)  
HP PS/2 Mouse (for machine configured with PS/2 port)  
No Mouse Option

[13. Keyboards and mouse are optional or add-on features.](#)

---

#### PORTS

##### Front

Slim-height Bay - supporting an optical disk drive (optional)  
Power Button  
Combo jack, Headphone / Microphone  
SD Card Reader  
(2) USB 3.1 Gen1 Port  
HDD LED Light

##### Not Shown

(1) PCI Express x16  
(1) PCI Express x1 Accessory slot  
(1) Full-height PCI (Optional)  
(1) M.2 for WLAN  
(1) M.2 2242/2280 storage



### Standard Features and Configurable Modules

#### Rear

- Audio Mic in
- Audio Line out
- Audio Link in
- HDMI Port<sup>1</sup>
- VGA Port<sup>1</sup>
- Serial Port (optional, and available on legacy PCA only)
- Standard lock slot
- (2) USB 2.0 port
- RJ-45 Network Connector
- (2) USB 3.1 Gen1 Port and (2) USB 2.0 Port
- Power Cord Connector
- Padlock loop

#### Not Shown

- (2) PS/2 Port (optional, and available on legacy PCA only)
- (1) Parallel Port (Optional via PCIe1 slot)

<sup>1</sup>: Port will be covered up when discrete graphic card is configured on shipped machine

### BAYS

- (1) 9.5mm external slimline ODD bay (optional)
- (1) 3.5" internal HDD bay
- (1) 3.5 or 2.5" internal HDD bay (share bay)

### ENVIRONMENTAL AND INDUSTRY

<b>Environmental Data</b>	<b>Eco-Label Certifications &amp; declarations</b>	This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks: <ul style="list-style-type: none"> <li>• IT ECO declaration</li> <li>• US ENERGY STAR®</li> <li>• EPEAT® registered in the United States.*</li> </ul> See <a href="http://www.epeat.net">http://www.epeat.net</a> for registration status in your country.		
	<b>System Configuration</b>	The configuration used for the Energy Consumption and Declared Noise Emissions data for the Desktop model is based on a “Typically Configured Desktop”.		
	<b>Energy Consumption (in accordance with US ENERGY STAR® test method)</b>	<b>115VAC, 60Hz</b>	<b>230VAC, 50Hz</b>	<b>100VAC, 60Hz</b>
	Normal Operation (Short idle)	12.97	13.03	13.39
	Normal Operation (Long idle)	10.64	10.72	10.46
Sleep	0.78	0.76	0.77	

### Standard Features and Configurable Modules

Off	0.42	0.41	0.42
<p>Note: Energy efficiency data listed is for an ENERGY STAR® compliant product if offered within the model family. HP computers marked with the ENERGY STAR® Logo are compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is for a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.</p>			
<b>Heat Dissipation*</b>	<b>115VAC, 60Hz</b>	<b>230VAC, 50Hz</b>	<b>100VAC, 60Hz</b>
Normal Operation (Short idle)	44.23	44.43	45.66
Normal Operation (Long idle)	36.28	36.56	35.67
Sleep	2.66	2.59	2.63
Off	1.43	1.4	1.43
<p>*NOTE: Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.</p>			
<b>Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)</b>	Sound Power (L <sub>WAd</sub> , bels)		Sound Pressure (L <sub>pAm</sub> , decibels)
Typically Configured – Idle	3.6		26.5
Fixed Disk – Random writes	3.6		26.5
<b>Longevity and Upgrading</b>	<p>"This product can be upgraded, possibly extending its useful life by several years. Upgradeable features and/or components contained in the product may include:</p> <p>Spare parts are available throughout the warranty period and or for up to "5" years after the end of production.</p>		
<b>Batteries</b>	<p>"This battery(s) in this product comply with EU Directive 2006/66/EC</p> <p>Batteries used in the product do not contain:            Mercury greater the 1ppm by weight            Cadmium greater than 20ppm by weight</p> <p>Battery size: CR2032 (coin cell)            Battery type: Lithium</p>		
<b>Additional Information</b>	<ul style="list-style-type: none"> <li>• "• This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2011/65/EC.</li> <li>• • This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive – 2002/96/EC.</li> <li>• • This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).</li> <li>• • This product is in compliance with the IEEE 1680 (EPEAT) standard, see <a href="http://www.epeat.net">www.epeat.net</a> *</li> <li>• • Plastics parts weighing over 25 grams used in the product are marked per ISO11469 and ISO1043.</li> <li>• • This product contains 0% post-consumer recycled plastic (by wt.)</li> <li>• • This product is 94.4% recycle-able when properly disposed of at end of life."</li> </ul>		

### Standard Features and Configurable Modules

	<b>Packaging Materials</b>	<b>External:</b>	PAPER/Corrugated	
		<b>Internal:</b>	PLASTIC/EPE (Expanded Polyethylene)	
			PLASTIC/Polyethylene low density - LDPE	
		The plastic packaging material contains at least 50% recycled content.		
		The corrugated paper packaging materials contains at least 75% recycled content.		
	<b>Material Usage</b>	<p>This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at <a href="http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/gse.pdf">http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/gse.pdf</a>):</p> <ul style="list-style-type: none"> <li>• Asbestos</li> <li>• Certain Azo Colorants</li> <li>• Certain Brominated Flame Retardants – may not be used as flame retardants in plastics</li> <li>• Cadmium</li> <li>• Chlorinated Hydrocarbons</li> <li>• Chlorinated Paraffins</li> <li>• Formaldehyde</li> <li>• Halogenated Diphenyl Methanes</li> <li>• Lead carbonates and sulfates</li> <li>• Lead and Lead compounds</li> <li>• Mercuric Oxide Batteries</li> <li>• Nickel – finishes must not be used on the external surface designed to be frequently handled or carried by the user.</li> <li>• Ozone Depleting Substances</li> <li>• Polybrominated Biphenyls (PBBs)</li> <li>• Polybrominated Biphenyl Ethers (PBBEs)</li> <li>• Polybrominated Biphenyl Oxides (PBBOs)</li> <li>• Polychlorinated Biphenyl (PCB)</li> <li>• Polychlorinated Terphenyls (PCT)</li> <li>• Polyvinyl Chloride (PVC) – except for wires and cables, has been voluntarily removed from most applications.</li> <li>• Radioactive Substances</li> <li>• Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)</li> </ul>		
	<b>Packaging Usage</b>	<p>HP follows these guidelines to decrease the environmental impact of product packaging:</p> <ul style="list-style-type: none"> <li>• Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.</li> <li>• Eliminate the use of ozone-depleting substances (ODS) in packaging materials.</li> <li>• Design packaging materials for ease of disassembly.</li> <li>• Maximize the use of post-consumer recycled content materials in packaging materials.</li> <li>• Use readily recyclable packaging materials such as paper and corrugated materials.</li> <li>• Reduce size and weight of packages to improve transportation fuel efficiency.</li> <li>• Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.</li> </ul>		

### Standard Features and Configurable Modules

	<p><b>End-of-life Management and Recycling</b></p>	<p>Hewlett-Packard offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: <a href="http://www.hp.com/go/reuse-recycle">http://www.hp.com/go/reuse-recycle</a> or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.</p> <p>The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: <a href="http://www.hp.com/go/recyclers">http://www.hp.com/go/recyclers</a>. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.</p>
	<p><b>HP, Inc. Corporate Environmental Information</b></p>	<p>For more information about HP's commitment to the environment:</p> <p>Global Citizenship Report  <a href="http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html">http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html</a></p> <p>Eco-label certifications  <a href="http://www8.hp.com/us/en/hp-information/environment/ecolabels.html">http://www8.hp.com/us/en/hp-information/environment/ecolabels.html</a></p> <p>ISO 14001 certificates:  <a href="http://h20195.www2.hp.com/V2/GetDocument.aspx?docname=c04755842">http://h20195.www2.hp.com/V2/GetDocument.aspx?docname=c04755842</a>  <a href="http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf">http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf</a></p>

\*EPEAT® registered where applicable. EPEAT registration varies by country. See [www.epeat.net](http://www.epeat.net) for registration status by country

### Standard Features and Configurable Modules

#### SOFTWARE COMPONENTS AND APPLICATIONS WITH WINDOWS

##### Security and Protection

McAfee\* LiveSafe™ 11

##### Productivity

Buy Office (sold separately)

Dropbox<sup>12</sup>

##### ODD Playback and TV Tuners

Power Media Player 14 for HP with DVD (ODD SKU only)<sup>13</sup>

##### Movies

Netflix<sup>14</sup>

##### App Stores and Content Purchasing

Amazon<sup>14</sup>

##### HP Utilities and Support

HP Documentation

HP JumpStart

HP Audio Switch

HP Support Assistant<sup>15</sup>

##### BTB

HP Setup Integrated OOBE

##### Hardware Enabling Drivers or software utility

HP System Event Utility

**\*NOTE:** Available for LA region only.

11. Free 1-year subscription of McAfee LiveSafe service included. Internet access required and not included. Subscription required after expiration

12. New Dropbox users are eligible to get 25 GB of Dropbox space free for 12 months from date of registration. For complete details and terms of use, including cancellation policies, visit the Dropbox website at <https://www.dropbox.com/help/space/hp-promotion>.

Internet service required and not included.

13. Actual speeds may vary. Don't copy copyright-protected materials

14. Internet access required and not included.

15. Easily switch between speaker and microphone sources with intuitive controls and a consistent app experience

17. HP ePrint Driver requires an Internet connection to HP web-enabled printer and HP ePrint account registration (for a list of eligible printers, supported documents and image types and other HP ePrint details, see [www.hp.com/go/eprintcenter](http://www.hp.com/go/eprintcenter)). Print times and connection speeds may vary.

---

#### POWER SUPPLY<sup>16</sup>

180 W

ENERGY® STAR® Libra2 EPA90 (Gold) Full range 115V/230V

310 W

SFF ENTL EPA90 (Gold) Full range 115V/230V

16. All power supplies are not available in every region.

#### DIMENSIONS AND WEIGHT

### Standard Features and Configurable Modules

#### Dimensions

6.69 x 13.3 x 10.79 in  
(170 x 338 x 274 mm)

#### Weight

11.9 lbs / 5.4 kg

---

## UNIT ENVIRONMENT AND OPERATING CONDITIONS

### General Unit Operating Guidelines

- Keep the computer away from excessive moisture, direct moisture and the extremes of heat and cold, to ensure that unit is operated within the specified operating range.
- Leave a 10.2 cm (4 in) clearance on all vented sides of the computer to permit the required airflow.
- Never restrict airflow into the computer by blocking any vents or air intakes.
- Do not stack computers on top of each other or place computers so near each other that they are subject to each other's re-circulated or preheated air.
- Occasionally clean the air vents on the front, back, and any other vented side of the computer. Lint, dust and other foreign matter can block the vents and limit the airflow.
- If the computer is to be operated within a separate enclosure, intake and exhaust ventilation must be provided on the enclosure, and the same operating guidelines listed above will still apply.

Temperature Range	Operating: 32° to 104° F (0° to 40° C) <sup>17</sup> Non-operating: -22° to 140° F (-30° to 60° C)
Relative Humidity	Operating: 10% to 90% (non-condensing at ambient) Non-operating: 0% to 95% (non-condensing at ambient)
Maximum Altitude (unpressurized)	Operating: 10,000 ft (3048 m) Non-operating: 30,000 ft (9144 m)

<sup>17</sup> Operating temperature is de-rated 1.0 deg C per 300 m (1000 ft) to 3000 m (10,000 ft) above sea level, no direct sustained sunlight. Maximum rate of change is 10 deg C/Hr. The upper limit may be limited by the type and number of options installed.

### Standard Features and Configurable Modules

#### SERVICE AND SUPPORT

On-site Warranty 1: Available three-year (3-3-3) or one-year (1-1-1) limited warranty (varies by country) delivers on-site, next business day 2 service for parts and labor and complimentary limited technical support.<sup>3</sup> Three-year onsite and labor are not available in all countries. Service offers terms up to 5 years by choosing an optional HP Care Pack.<sup>4</sup> To choose the right level of service for your HP product, visit HP Care Pack Central: <http://www.hp.com/go/cpc>.

**NOTE 1:** Terms and conditions may vary by country. Certain restrictions and exclusions apply. Other warranty variations may be offered in your region.

**NOTE 2:** On-site service may be provided pursuant to a service contract between HP and an authorized HP third-party provider, and is not available in certain countries. Global service response times are based on commercially reasonable best effort and may vary by country.

**NOTE 3:** Technical support applies only to HP-configured and third-party HP qualified hardware and software.

**NOTE 4:** Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. For details, visit <http://www.hp.com/go/cpc>. HP services are governed by the applicable HP terms and conditions of service provided or indicated to Customer at the time of purchase. Customer may have additional statutory rights according to applicable local laws, and such rights are not in any way affected by the HP terms and conditions of service or the HP Limited Warranty provided with your HP Product.

### Technical Specifications - Graphics

#### GRAPHICS

<b>Intel® UHD Graphics 630 (integrated on Core i7/i5/i3 processors)</b> <b>Intel® UHD Graphics 610 (integrated on Pentium and Celeron)</b>	
DisplayPort™	Multimode capable; supports HDCP, DisplayPort™ Audio (2 streams), HBR2 link rates and Multi-Stream Technology for a maximum of 3 displays (including the integrated panel)
Memory	Additional memory is allocated for graphics as needed using Intel's Dynamic Video Memory Technology (DVMT), to provide an optimal balance between graphics and system memory use.
Maximum Graphics Memory	Windows 10: >4 GB
Maximum Color Depth	32 bits/pixel
Graphics/Video API Support	8 <sup>th</sup> and 9 <sup>th</sup> Generation Intel® Core Processors With Intel® UHD Graphics 630 8 <sup>th</sup> and 9 <sup>th</sup> Generation Pentium® G5400 and Celeron® G4900, With Intel® UHD Graphics 610
<b>Supported Display Resolutions and Refresh Rates</b>	
Resolution/ Refresh Rates	800x600 @ 60 Hz 1024x768 @ 60 Hz 1152x864 @ 60 Hz 1280x600 @ 60 Hz 1280x720 @ 60 Hz 1280x800 @ 60 Hz 1280x960 @ 60 Hz 1280x1024 @ 60 Hz 1360x768 @ 60 Hz 1366x768 @ 60 Hz 1400x1050 @ 60 Hz 1440x900 @ 60 Hz 1600x900 @ 60 Hz 1600x1200[1] @ 60 Hz 1680x1050 @ 60 Hz 1920x1080 @ 60 Hz
<b>Note:</b> The actual amount of maximum graphics memory can be less than the amounts listed above depending upon your computer's configuration. <b>Note:</b> other resolutions may be available but are not recommended as they may not have been tested and qualified by HP Only supported on displays connected to the external DisplayPort™ connector.	



### Technical Specifications - Graphics

#### **NVIDIA® GeForce® GTX 1060 3GB Graphics Card**

<b>Engine Clock</b>	1506 MHz
<b>Memory Clock</b>	4004 MHz
<b>Memory Size(width)</b>	3GB(192-bit)
<b>Memory Type</b>	128M x 32 GDDR5 @6pcs
<b>Max. Resolution(DVI)</b>	2560x1600@60Hz
<b>Max. Resolution(HDMI)</b>	4096x2160@60Hz
<b>Max. Resolution(DP)</b>	5120x3200@60Hz
<b>Multi Display Support</b>	4 displays
<b>HDCP Compliance</b>	Yes
<b>Rear I/O connectors(bracket)</b>	DVI-D+HDMI+DPx3
<b>Cooling(active/passive)</b>	Active fan-sink (Active cooling with dynamic speed)
<b>Total power consumption(W)</b>	<120W
<b>PCB form-factor with bracket</b>	ATX (Full height) PCB with ATX dual slot bracket

---

#### **NVIDIA® GeForce® GTX 1060 6GB Graphics Card**

<b>Engine Clock</b>	1506 MHz
<b>Memory Clock</b>	4004 MHz
<b>Memory Size(width)</b>	6GB(192-bit)
<b>Memory Type</b>	256M x 32 GDDR5 @6pcs
<b>Max. Resolution(DVI)</b>	2560x1600@60Hz
<b>Max. Resolution(HDMI)</b>	4096x2160@60Hz
<b>Max. Resolution(DP)</b>	5120x3200@60Hz
<b>Multi Display Support</b>	4 displays
<b>HDCP Compliance</b>	Yes
<b>Rear I/O connectors(bracket)</b>	DVI-D+HDMI+DPx3
<b>Cooling(active/passive)</b>	Active fan-sink (Active cooling with dynamic speed)
<b>Total power consumption(W)</b>	<120W
<b>PCB form-factor with bracket</b>	ATX (Full height) PCB with ATX dual slot bracket

---

#### **NVIDIA® GeForce® GTX 1650 4GB Graphics Card**

<b>Engine Clock</b>	1665 MHz
<b>Memory Clock</b>	4000 MHz
<b>Memory Size(width)</b>	4GB(128-bit)
<b>Memory Type</b>	256M x 32 GDDR5 @4pcs
<b>Max. Resolution(HDMI)</b>	4096 x 2160 x 24bpp @ 60 Hz
<b>Max. Resolution(DVI)</b>	2560 x 1600 x 24bpp @ 60 Hz
<b>Multi Display Support</b>	2 displays
<b>HDCP Compliance</b>	yes
<b>Rear I/O connectors(bracket)</b>	HDMI + DVI

### Technical Specifications - Graphics

<b>Cooling(active/passive)</b>	Active fan-sink
<b>Total power consumption(W)</b>	<75W
<b>PCB form-factor with bracket</b>	ATX (Full height) PCB with ATX dual slot bracket

---

#### **NVIDIA® GeForce® GT730 1GB Graphics Card**

<b>Engine Clock</b>	902 MHz
<b>Memory Clock</b>	1250 MHz
<b>Memory Size(width)</b>	1GB(64-bit)
<b>Memory Type</b>	128M x 32 GDDR5 @2pcs
<b>Max. Resolution(DVI)</b>	2560x1600@60Hz
<b>Max. Resolution(HDMI)</b>	4096x2160@24Hz
<b>Multi Display Support</b>	2 displays
<b>HDCP Compliance</b>	yes
<b>Rear I/O connectors(bracket)</b>	DVI+HDMI
<b>Cooling(active/passive)</b>	Active fan-sink (Active cooling with dynamic speed)
<b>Total power consumption(W)</b>	<35W
<b>PCB form-factor with bracket</b>	LP PCB with FH/LP bracket

---

#### **NVIDIA® GeForce® GT 730 2GB Graphics Card**

<b>Engine Clock</b>	902 MHz
<b>Memory Clock</b>	1250 MHz
<b>Memory Size(width)</b>	2GB(64-bit)
<b>Memory Type</b>	256M x 32 GDDR5 @2pcs
<b>Max. Resolution(DVI)</b>	2560x1600@60Hz
<b>Max. Resolution(DP)</b>	4096x2160@60Hz
<b>Multi Display Support</b>	2 displays
<b>HDCP Compliance</b>	yes
<b>Rear I/O connectors(bracket)</b>	DVI+DP
<b>Cooling(active/passive)</b>	Active fan-sink(Active cooling with dynamic speed)
<b>Total power consumption(W)</b>	<35W
<b>PCB form-factor with bracket</b>	LP PCB with FH/LP bracket

---

#### **AMD Radeon™ R7 430 2GB Graphics Card**

<b>Engine Clock</b>	780 MHz
<b>Memory Clock</b>	1100 MHz
<b>Memory Size(width)</b>	2GB(128-bit)
<b>Memory Type</b>	128M x 32 GDDR5 @4pcs
<b>Max. Resolution(VGA)</b>	2048x1536

### Technical Specifications - Graphics

<b>Max. Resolution(DP)</b>	4096x2160@60Hz
<b>Multi Display Support</b>	2 displays
<b>HDCP Compliance</b>	yes
<b>Rear I/O connectors(bracket)</b>	VGA+DP
<b>Cooling(active/passive)</b>	Active fan-sink (Active cooling with dynamic speed)
<b>Total power consumption(W)</b>	<50W
<b>PCB form-factor with bracket</b>	LP PCB with FH/LP bracket

---

### AMD Radeon™ 520 1GB Graphics Card

<b>Engine Clock</b>	780 MHz
<b>Memory Clock</b>	1100 MHz
<b>Memory Size(width)</b>	1GB(32-bit)
<b>Memory Type</b>	256M x 32 GDDR5
<b>Max. Resolution(VGA)</b>	2048x1536
<b>Max. Resolution(DP)</b>	4096x2160@60Hz
<b>Multi Display Support</b>	2 displays
<b>HDCP Compliance</b>	yes
<b>Rear I/O connectors(bracket)</b>	VGA+DP
<b>Cooling(active/passive)</b>	Active fan-sink (Active cooling with dynamic speed)
<b>Total power consumption(W)</b>	<50W
<b>PCB form-factor with bracket</b>	LP PCB with FH/LP bracket

---

### Technical Specifications -Storage

#### STORAGE

##### HP 2 TB 7.2K rpm SATA 6.0Gb/s 3.5" Hard Disk Drive

<b>Capacity</b>	2 TB
<b>Rotational Speed</b>	7,200 rpm
<b>Interface</b>	SATA 6Gb/s NCQ
<b>Buffer Size</b>	64 MB
<b>Logical Blocks</b>	3,907,029,168
<b>Seek Time</b>	Read: <8.5 ms Write: <9.5 ms
<b>Height</b>	1.028 in/26.11 mm
<b>Width</b>	4.0 in/101.6 mm
<b>Operating Temperature</b>	32° to 140° F (0° to 60° C)

**NOTE:** For hard drives and solid state drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36 GB (for Windows 10) of system disk is reserved for the system recovery software.

##### 1 TB 7.2K rpm SATA 6.0Gb/s 3.5" Hard Disk Drive

<b>Capacity</b>	1 TB
<b>Rotational Speed</b>	7,200 rpm
<b>Interface</b>	Serial ATA 3.0 (6.0 Gb/s)
<b>Buffer Size</b>	32 MB
<b>Logical Blocks</b>	1,953,525,168
<b>Seek Time</b>	Single Track: 2.0 ms Average: 11 ms Full-Stroke: 21 ms
<b>Height</b>	1 in/2.54 cm
<b>Width</b>	Media diameter: 3.5 in/8.89 cm Physical size: 4 in/10.2 cm
<b>Operating Temperature</b>	41° to 131° F (5° to 55° C)

**NOTE:** For hard drives and solid state drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36 GB (for Windows 10) of system disk is reserved for the system recovery software.

##### 500 GB 7.2K rpm SATA 6.0Gb/s 3.5" Hard Disk Drive

<b>Capacity</b>	500 GB
<b>Rotational Speed</b>	7,200 rpm
<b>Interface</b>	Serial ATA 3.0 (6.0 Gb/s)
<b>Buffer Size</b>	32 MB
<b>Logical Blocks</b>	1,953,525,168
<b>Seek Time</b>	Single Track: 2.0 ms

### Technical Specifications -Storage

	Average: 11 ms Full-Stroke: 21 ms
<b>Height</b>	1 in/2.54 cm
<b>Width</b>	Media diameter: 3.5 in/8.89 cm Physical size: 4 in/10.2 cm
<b>Operating Temperature</b>	41° to 131° F (5° to 55° C)

**NOTE:** For hard drives and solid state drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36 GB (for Windows 10) of system disk is reserved for the system recovery software.

### HP 9.5mm Desktop G2 Slim DVD Writer Drive

<b>Height</b>	9.5 mm height																												
<b>Orientation</b>	Either horizontal or vertical																												
<b>Interface type</b>	SATA/ATAPI																												
<b>Disc recording capacity</b>	Up to 8.5 GB DL or 4.7 GB standard																												
<b>Dimensions (W x H x D)</b>	5.04 x 0.37 x 5.0 in (128 x 9.5 x 127 mm) without bezel																												
<b>Weight (max)</b>	0.31 lb (140 g)																												
<b>Read Speeds</b>	<table> <tr> <td>DVD-R DL</td> <td>Up to 6X</td> </tr> <tr> <td>DVD+R</td> <td>Up to 8X</td> </tr> <tr> <td>DVD+RW</td> <td>Up to 8X</td> </tr> <tr> <td>DVD-R DL</td> <td>Up to 6X</td> </tr> <tr> <td>DVD-R</td> <td>Up to 8X</td> </tr> <tr> <td>DVD-RW</td> <td>Up to 6X</td> </tr> <tr> <td>CD-R</td> <td>Up to 24X</td> </tr> <tr> <td>CD-RW</td> <td>Up to 10X</td> </tr> <tr> <td>DVD-RW, DVD+RW</td> <td>Up to 8X</td> </tr> <tr> <td>DVD-R DL, DVD+R DL</td> <td>Up to 8X</td> </tr> <tr> <td>DVD+R, DVD-R</td> <td>Up to 8X</td> </tr> <tr> <td>DVD-ROM DL, DVD-ROM</td> <td>Up to 8X</td> </tr> <tr> <td>CD-ROM, CD-R</td> <td>Up to 24X</td> </tr> <tr> <td>CD-RW</td> <td>Up to 24X</td> </tr> </table>	DVD-R DL	Up to 6X	DVD+R	Up to 8X	DVD+RW	Up to 8X	DVD-R DL	Up to 6X	DVD-R	Up to 8X	DVD-RW	Up to 6X	CD-R	Up to 24X	CD-RW	Up to 10X	DVD-RW, DVD+RW	Up to 8X	DVD-R DL, DVD+R DL	Up to 8X	DVD+R, DVD-R	Up to 8X	DVD-ROM DL, DVD-ROM	Up to 8X	CD-ROM, CD-R	Up to 24X	CD-RW	Up to 24X
DVD-R DL	Up to 6X																												
DVD+R	Up to 8X																												
DVD+RW	Up to 8X																												
DVD-R DL	Up to 6X																												
DVD-R	Up to 8X																												
DVD-RW	Up to 6X																												
CD-R	Up to 24X																												
CD-RW	Up to 10X																												
DVD-RW, DVD+RW	Up to 8X																												
DVD-R DL, DVD+R DL	Up to 8X																												
DVD+R, DVD-R	Up to 8X																												
DVD-ROM DL, DVD-ROM	Up to 8X																												
CD-ROM, CD-R	Up to 24X																												
CD-RW	Up to 24X																												
<b>Access time (typical reads, including settling)</b>	Random DVD-ROM: 170 ms (typical), CD-ROM: 170 ms (typical) Full Stroke DVD-ROM: 320 ms (typical), CD-ROM: 320 ms (typical) Stop Time 6 seconds (typical)																												
<b>Power</b>	Source Slimline SATA DC power receptacle DC Power Requirement 5 VDC ± 5%-100 mV ripple p-p DC Current 5 VDC (< 1000 mA typical, 1600 mA maximum)																												
<b>Environmental conditions (operating - non-condensing)</b>	Temperature 41° to 122° F (5° to 50° C) Relative Humidity 10% to 80% Maximum Wet Bulb Temperature 84° F (29° C)																												

### HP 9.5mm Desktop G2 Slim DVD-ROM Drive

<b>Height</b>	9.5 mm height
<b>Orientation</b>	Either horizontal or vertical
<b>Interface type</b>	SATA/ATAPI
<b>Disc recording capacity</b>	Up to 8.5 GB DL or 4.7 GB standard

### Technical Specifications -Storage

<b>Dimensions (W x H x D)</b>	5.04 x 0.37 x 5.0 in (128 x 9.5 x 127 mm) without bezel	
<b>Weight (max)</b>	0.31 lb (140 g)	
<b>Read Speeds</b>	DVD-R DL	Up to 6X
	DVD+R	Up to 8X
	DVD+RW	Up to 8X
	DVD+R DL	Up to 6X
	DVD-R	Up to 8X
	DVD-RW	Up to 6X
	CD-R	Up to 24X
	CD-RW	Up to 10X
	DVD-RW, DVD+RW	Up to 8X
	DVD-R DL, DVD+R DL	Up to 8X
	DVD+R, DVD-R	Up to 8X
	DVD-ROM DL, DVD-ROM	Up to 8X
	CD-ROM, CD-R	Up to 24X
	CD-RW	Up to 24X
<b>Access time (typical reads, including settling)</b>	Random DVD-ROM: 170 ms (typical), CD-ROM: 170 ms (typical) Full Stroke DVD-ROM: 320 ms (typical), CD-ROM: 320 ms (typical) Stop Time 6 seconds (typical)	
<b>Power</b>	Source Slimline SATA DC power receptacle DC Power Requirement 5 VDC $\pm$ 5%-100 mV ripple p-p DC Current 5 VDC (< 1000 mA typical, 1600 mA maximum)	
<b>Environmental conditions (operating - non-condensing)</b>	Temperature 41° to 122° F (5° to 50° C) Relative Humidity 10% to 80% Maximum Wet Bulb Temperature 84° F (29° C)	

### 128 GB M.2 2280 PCIe NVMe SSD

<b>Drive Weight</b>	< 10g
<b>Capacity</b>	128GB
<b>Height</b>	2.38mm
<b>Length</b>	80mm
<b>Width</b>	22mm
<b>Interface</b>	PCIe Gen3
<b>Maximum Sequential Read</b>	Up to 1400MB/s
<b>Maximum Sequential Write</b>	Up to 395MB/s
<b>Logical Blocks</b>	250,069,680
<b>Operating Temperature</b>	0° to 70°C (32° to 158°F) [ambient temp]
<b>Features</b>	APST; ASPM L1.2; NVME spec 1.2

**NOTE:** For hard drives and solid state drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36 GB (for Windows 10) of system disk is reserved for the system recovery software.

### Technical Specifications -Storage

#### 256 GB M.2 2280 PCIe NVMe SSD

<b>Drive Weight</b>	< 10g
<b>Capacity</b>	256 GB
<b>Height</b>	2.38mm
<b>Length</b>	80mm
<b>Width</b>	22mm
<b>Interface</b>	PCIe Gen3
<b>Maximum Sequential Read</b>	Up to 1600MB/s
<b>Maximum Sequential Write</b>	Up to 780MB/s
<b>Logical Blocks</b>	500,118,192
<b>Operating Temperature</b>	0° to 70°C (32° to 158°F) [ambient temp]
<b>Features</b>	APST; ASPM L1.2; NVME spec 1.2

**NOTE:** For hard drives and solid state drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36 GB (for Windows 10) of system disk is reserved for the system recovery software.

#### 512 GB M.2 2280 PCIe NVMe SSD

<b>Drive Weight</b>	< 10g
<b>Capacity</b>	512 GB
<b>Height</b>	2.38mm
<b>Length</b>	80mm
<b>Width</b>	22mm
<b>Interface</b>	PCIe Gen3
<b>Maximum Sequential Read</b>	Up to 1600MB/s
<b>Maximum Sequential Write</b>	Up to 860MB/s
<b>Logical Blocks</b>	1,000,215,216
<b>Operating Temperature</b>	0° to 70°C (32° to 158°F) [ambient temp]
<b>Features</b>	APST; ASPM L1.2; NVME spec 1.2

**NOTE:** For hard drives and solid state drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36 GB (for Windows 10) of system disk is reserved for the system recovery software.

#### 128GB 2.5in SATA Three Layer Cell SSD

<b>Drive Weight</b>	<50g
<b>Capacity</b>	128GB
<b>Height</b>	7mm
<b>Length</b>	100.45mm
<b>Width</b>	69.85mm
<b>Interface</b>	SATA 3.0 (6Gb/s)
<b>Performance</b>	Up to Random Read/Write = 70K/40K IOPS

### Technical Specifications -Storage

<b>Maximum Sequential Read</b>	Up to 530MB/s
<b>Maximum Sequential Write</b>	Up to 380MB/s
<b>Logical Blocks</b>	250,069,680
<b>Operating Temperature</b>	0° to 70°C (32° to 158°F) [ambient temp]
<b>Features</b>	DIPM; TRIM

**NOTE:** For hard drives and solid state drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36 GB (for Windows 10) of system disk is reserved for the system recovery software.

---

### 256GB 2.5in SATA Three Layer Cell SSD

<b>Drive Weight</b>	<62g
<b>Capacity</b>	256GB
<b>Height</b>	7mm
<b>Length</b>	100.45mm
<b>Width</b>	69.85mm
<b>Interface</b>	SATA 3.0 (6Gb/s)
<b>Performance</b>	Up to Random Read/Write = 55K/68K IOPS
<b>Maximum Sequential Read</b>	Up to 530MB/s
<b>Maximum Sequential Write</b>	Up to 450MB/s
<b>Logical Blocks</b>	500,118,192
<b>Operating Temperature</b>	0° to 70°C (32° to 158°F) [ambient temp]
<b>Features</b>	DIPM; TRIM

**NOTE:** For hard drives and solid state drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 36 GB (for Windows 10) of system disk is reserved for the system recovery software.

---



### Technical Specifications - Audio

#### HIGH DEFINITION AUDIO

<b>Type</b>	Integrated
<b>HD Stereo Codec</b>	Realtek ALC3601
<b>Audio I/O Ports</b>	Front side Combo jack for supporting CTIA, Rear side Line-in/ Line-out/ Mic-in jacks
<b>Internal Speaker Amplifier</b>	2W class D mono amplifier for the internal speaker only. External speakers must be powered externally.
<b>Multi-streaming Capable</b>	Playback multi-streaming can be enabled in the audio control panel to allow independent audio streams to be sent to/from the front and rear jacks or integrated speaker.
<b>HD Audio Codec</b>	Realtek ALC3601
<b>Sampling</b>	Independent sampling rates for DAC's and ADC's; supports resolutions from 16 to 24-bit; 44.1K/ 48 K/96K / 192K Hz for DAC and 44.1K/ 48K/ 96K/ 192K Hz Hz for ADC
<b>Wavetable Syntheses</b>	Yes
<b>Analog Audio</b>	Yes
<b># of Channels on Line-Out</b>	Stereo
<b>Internal Speaker</b>	Yes
<b>External Speaker Jack</b>	2W class D mono amplifier for the internal speaker only. External speakers must be powered externally.

---

### Technical Specifications - Power

#### POWER SUPPLY

<b>Operating Voltage Range</b>	90 – 264 VAC
<b>Rated Voltage Range</b>	100-240V AC
<b>Rated Line Frequency</b>	50/60 HZ
<b>Operating Line Frequency</b>	47 – 63 Hz
<b>Rated Input Current</b>	180W : <2.3A; 310W: <4A
<b>Rated Input Current with Energy Efficient* Power Supply</b>	180W active PFC 87/90/87% efficient at 20/50/100% load (115V) 88/91/88% efficient at 20/50/100% load (230V); 310W active PFC 87/90/87% efficient at 20/50/100% load (115V) 88/91/88% efficient at 20/50/100% load (230V)
<b>DC Output</b>	+12.1V
<b>Current Leakage (NFPA 99: 2102)</b>	Less than 500 microamps of leakage current at 120 Vac with the ground wire disconnected, as required for Non-patient Electrical Appliances and Equipment used in a patient care facility or that contact patients in normal use. Per section 10.3.5.1. Less than 100 microamps of leakage current at 120 Vac with the ground wire intact with normal polarity, as required for Non-patient Electrical Appliances and Equipment used in a patient care facility or that contact patients in normal use. Per section 10.3.5.1.
<b>Power Supply Fan</b>	70*25mm (linear type)

---

### Technical Specifications – Weights and Dimensions

#### WEIGHT AND DIMENSIONS

<b>Chassis (W x H x D)</b>	6.69 x 13.3 x 10.79 in (170 x 338 x 274 mm)
<b>System Volume</b>	960.06cu in 15.76L
<b>System Weight*</b>	11.9 lbs / 5.4 kg
<b>Max Supported Weight (desktop orientation)</b>	N/A
<b>Tower Stand (H x W x D)</b>	13.42 x 6.69 x 10.92 in (340.8 x 170 x 277.5 mm)
<b>Packaged (H x W x D)</b>	11.46 x 15.35 x 19.65 in 291 x 390 x 499 mm
<b>Shipping Weight</b>	17.64lb / 8 kg
<b>Palletization Profile</b>	6 units per layer 7layer max 42 per pallet Footprint -85.31x39.37x47.24 in ( 2167 x 1000 x1200 mm)

### Technical Specifications–Miscellaneous Features

#### ADDITIONAL FEATURES

**SMART Technology (Self-Monitoring, Analysis and Reporting Technology)**

**Description**

Allows hard drives to monitor their own health and to raise flags if imminent failures were predicted

### Technical Specifications- Networking

#### NETWORKING

<b>10/100/1000 NIC</b>	<b>Ethernet Features</b>	10 Mbit/s operation (10BASE-T; IEEE 802.3i; IEEE 802.3 clauses 13-14) 100 Mbit/s operation (100BASE-TX; IEEE 802.3u; IEEE 802.3 clauses 21-30) 1000 Mbit/s operation (1000BASE-T; IEEE 802.3ab; IEEE 8023 clauses 40) Auto-Negotiation (Automatic Speed Selection) Full Duplex Operation at all Speeds, Half Duplex operation at 10 and 100 Mbit/s
	<b>Power Management</b>	ACPI compliant – multiple power modes Situation-sensitive features reduce power consumption Advanced link down power saving for reducing link down power consumption
	<b>Performance Features</b>	TCP/IP/UDP Checksum Offload (configurable) Protocol Offload (ARP & NS) Large send offload and Giant send offload Receiving Side Scaling Jumbo Frame 9K
	<b>Manageability</b>	Wake-on-LAN from standby and hibernation (Magic Packet and Microsoft Wake-Up Frame); Wake-on-LAN from off (Magic Packet only) PXE 2.1 Remote Boot Statistics Gathering (SNMP MIB II, Ethernet-like MIB, Ethernet MIB (802.3x, clause 30)) Comprehensive diagnostic and configuration software suite Virtual Cable Doctor for Ethernet cable status
	<b>Interface</b>	PCIe + SMBus
	<b>NIC Device Driver Name</b>	PCIe GBE Ethernet Family Controller

#### Realtek 802.11ac (1x1) WiFi and Bluetooth® 4.2 Combo \*

<b>Wireless LAN Standards</b>	IEEE 802.11a IEEE 802.11b IEEE 802.11g IEEE 802.11n IEEE 802.11ac	
<b>Interoperability</b>	Wi-Fi certification	
<b>Frequency Bands</b>	802.11b/g/n	<ul style="list-style-type: none"> <li>2.402 – 2.482 GHz</li> </ul>
	802.11a/n	<ul style="list-style-type: none"> <li>4.9 – 4.95 GHz (Japan)</li> <li>5.15 – 5.25 GHz</li> <li>5.25 – 5.35 GHz</li> <li>5.47 – 5.725 GHz</li> </ul>

### Technical Specifications- Networking

	<ul style="list-style-type: none"> <li>• 5.825 – 5.850 GHz</li> </ul>
<b>Data Rates</b>	<ul style="list-style-type: none"> <li>• 802.11b: 1, 2, 5.5, 11 Mbps</li> <li>• 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps</li> <li>• 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps</li> <li>• 802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz)</li> <li>• 802.11ac : MCS0 ~ MCS9, (1SS, and 2SS) (20MHz, 40MHz, and 80MHz)</li> </ul>
<b>Modulation</b>	<p>Direct Sequence Spread Spectrum</p> <p>BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM</p>
<b>Security<sup>1</sup></b>	<ul style="list-style-type: none"> <li>• IEEE and WiFi compliant 64 / 128 bit WEP encryption for a/b/g mode only</li> <li>• AES-CCMP: 128 bit in hardware</li> <li>• 802.1x authentication</li> <li>• WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES.</li> <li>• WPA2 certification</li> <li>• IEEE 802.11i</li> <li>• Cisco Certified Extensions, all versions through CCX4 and CCX Lite</li> <li>• WAPI</li> </ul>
<b>Network Architecture Models</b>	<p>Ad-hoc (Peer to Peer)</p> <p>Infrastructure (Access Point Required)</p>
<b>Roaming</b>	IEEE 802.11 compliant roaming between access points
<b>Output Power<sup>2</sup></b>	<ul style="list-style-type: none"> <li>• 802.11b : +14dBm minimum</li> <li>• 802.11g : +12dBm minimum</li> <li>• 802.11a : +12dBm minimum</li> <li>• 802.11n HT20(2.4GHz) : +12dBm minimum</li> <li>• 802.11n HT40(2.4GHz) : +12dBm minimum</li> <li>• 802.11n HT20(5GHz) : +10dBm minimum</li> <li>• 802.11n HT40(5GHz) : +10dBm minimum</li> <li>• 802.11ac VHT80(5GHz) : +10dBm minimum</li> </ul>
<b>Power Consumption</b>	<ul style="list-style-type: none"> <li>• Transmit mode 2.0 W</li> <li>• Receive mode 1.6 W</li> <li>• Idle mode (PSP) 180 mW (WLAN Associated)</li> <li>• Idle mode 50 mW (WLAN unassociated)</li> <li>• Connected Standby 10mW</li> <li>• Radio disabled 8 mW</li> </ul>
<b>Power Management</b>	<p>ACPI and PCI Express compliant power management</p> <p>802.11 compliant power saving mode</p>

### Technical Specifications- Networking

<b>Receiver Sensitivity<sup>3</sup></b>	<ul style="list-style-type: none"> <li>802.11b, 1Mbps : -93.5dBm maximum</li> <li>802.11b, 11Mbps : -84dBm maximum</li> <li>802.11a/g, 6Mbps : -86dBm maximum</li> <li>802.11a/g, 54Mbps : -72dBm maximum</li> <li>802.11n, MCS07 : -67dBm maximum</li> <li>802.11n, MCS15 : -64dBm maximum</li> <li>802.11ac, MCS0 : -84dBm maximum</li> <li>802.11ac, MCS9 : -59dBm maximum</li> </ul>	
<b>Antenna type</b>	High efficiency antenna with spatial diversity, mounted in the display enclosure Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth® communications	
<b>Form Factors</b>	PCI-Express M.2 MiniCard	
<b>Dimensions</b>	Type 2230 : 2.3 x 22.0 x 30.0 mm	
<b>Weight</b>	Type 2230 : 2.8g	
<b>Operating Voltage</b>	3.3v +/- 9%	
<b>Temperature</b>	<b>Operating:</b>	14° to 158° F (-10° to 70° C)
	<b>Non-operating:</b>	-40° to 176° F (-40° to 80° C)
<b>Humidity</b>	<b>Operating:</b>	10% to 90% (non-condensing)
	<b>Non-operating:</b>	5% to 95% (non-condensing)
<b>Altitude</b>	<b>Operating:</b>	0 to 10,000 ft (3,048 m)
	<b>Non-operating:</b>	0 to 50,000 ft (15,240 m)
<b>LED Activity</b>	LED Amber – Radio OFF; LED White – Radio ON	
<b>HP Integrated Module with Bluetooth 4.0/4.1/4.2 Wireless Technology</b>		
<b>Bluetooth® Specification</b>	4.0/4.1/4.2 Compliant	
<b>Frequency Band</b>	2402 to 2480 MHz	
<b>Number of Available Channels</b>	Legacy : 0~79 (1 MHz/CH) BLE : 0~39 (2 MHz/CH)	
<b>Data Rates and Throughput</b>	Legacy : 3 Mbps data rate; throughput up to 2.17 Mbps	
	BLE : 1 Mbps data rate; throughput up to 0.2 Mbps Legacy : Synchronous Connection Oriented links up to 3, 64 kbps, voice channels	

### Technical Specifications- Networking

	Legacy : Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)
<b>Transmit Power</b>	The Bluetooth® component shall operate as a Class II Bluetooth® device with a maximum transmit power of + 4 dBm for BR and EDR.
<b>Receiver Sensitivity Legacy</b>	
<b>Power Consumption</b>	Peak (Tx) 330 mW Peak (Rx) 230 mW Selective Suspend 17 mW
<b>Range</b>	Legacy : 0~79 (1 MHz/CH) BLE : 0~39 (2 MHz/CH)
<b>Electrical Interface</b>	USB 2.0 compliant
<b>Bluetooth® Software Supported Link Topology</b>	Microsoft Windows Bluetooth® Software
<b>Power Management Certifications</b>	ETS 300 328, ETS 300 826 Low Voltage Directive IEC950 UL, CSA, and CE Mark
<b>Certifications Bluetooth® Profiles Supported</b>	FCC (47 CFR) Part 15C, Section 15.247 & 15.249
<b>Power Management Certifications</b>	Microsoft Windows ACPI, and USB Bus Support
<b>Certifications Bluetooth® Profiles Supported</b>	BT4.1-ESR 5/6/7 Compliance LE Link Layer Ping LE Dual Mode LE Link Layer LE Low Duty Cycle Directed Advertising LE L2CAP Connection Oriented Channels Train Nudging & Interlaced Scan BT4.2 ESR08 Compliance LE Secure Connection- Basic/Full LE Privacy 1.2 –Link Layer Privacy LE Privacy 1.2 –Extended Scanner Filter Policies LE Data Packet Length Extension FAX Profile (FAX) Basic Imaging Profile (BIP)2 Headset Profile (HSP) Hands Free Profile (HFP) Advanced Audio Distribution Profile (A2DP)

1. Mobile Broadband is an optional feature. Connection requires wireless data service contract, network support, and is not available in all areas. Contact service provider to determine the coverage area and availability. Connection speeds will vary due to location, environment, network conditions, and other factors. 4G LTE not available on all products or in all countries.

2. The FCC has declared products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 & 15.249 or otherwise disable those channels.



### Technical Specifications- Networking

3. Check latest software/driver release for updates on supported security features.
4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).
5. Wireless access point and Internet service required and not included. Availability of public wireless access points limited.

After-Market Options (availability may vary by region)

### AFTER MARKET OPTIONS

Type	Description	Part #
<b>Memory</b>	HP 4GB DDR4-2666 DIMM	3TK85AA
	HP 8GB DDR4-2666 DIMM	3TK87AA
	HP 16GB DDR4-2666 DIMM	3TK83AA
<b>Storage</b>	HP 500GB SATA 6.0Gb/s Hard Drive	QK554AA
	HP 1TB 7200rpm SATA 6Gbps Hard Drive	QK555AA
	HP Turbo Drive Gen2 256GB M.2 SSD Drive	1CA51AA
	Intel Optane Memory 16GB (cache) ****	1WV97AA
	HP 256GB SATA TLC Non-SED Solid State Drive	P1N68AA
	HP 9.5mm G3 8/6/4 SFF G4 400 SFF/MT DVD Writer	1CA53AA
<b>Graphics</b>	NVIDIA® GT 730 2GB DP Card	Z9H51AA
	AMD Radeon™ R7 430 Card	1MX32AA
<b>Security</b>	HP Business PC Security Lock V2 Kit	N3R93AA
	HP Keyed Cable Lock 10mm kit	T1A62AA
<b>Adapters</b>	HP USB to Serial Adapter	J7B60AA
	HP HDMI Standard Cable Kit	T6F94AA
	HP USB to Serial Port Adapter	J7B60AA
<b>Networking</b>	Intel Ethernet I210-T1 GbE NIC Card	E0X95AA
<b>Input</b>	HP USB Mouse	QY777AA
	HP USB Hardened Mouse	P1N77AA
	HP USB Keyboard	QY776AA
	HP PS/2 Business Slim Keyboard	N3R86AA
	HP USB Business Slim Keyboard	N3R87AA
	HP Conferencing Keyboard	K8P74AA
	HP USB Antimicrobial Slim Keyboard and Mouse	Z9H50AA
<b>Others</b>	HP Business Headset v2	T4E61AA
	HP USB Business Speakers v2	N3R89AA

### Change Log

© Copyright 2020 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. Microsoft and Windows are registered trademarks or trademarks of Microsoft Corporation in the U.S. and/or other countries. Intel, Celeron®, Core, Pentium are registered trademarks or trademarks of Intel Corporation in the U.S. and/or other countries. Bluetooth is a trademark of its proprietor, used by HP Inc. under license. NVIDIA, GeForce, Kepler and NVS are trademarks and/or registered trademarks of NVIDIA Corporation in the U.S. and other countries. AMD and Radeon are trademarks of Advanced Micro Devices, Inc. ENERGY STAR is a registered trademark owned by the U.S. Environmental Protection Agency.

<b>Date of change:</b>	<b>Version History:</b>	<b>Change</b>	<b>Description of change:</b>
March 18, 2019	From v1 to v2	Update	Processor i5-9400 removed
March 21, 2019	From v2 to v3	Update	Processor i5-9400 put back on
April 23, 2019	From v3 to v4	Refresh	Processors under embargo added to official QS refresh
May 14, 2019	From v4 to v5	Update	i7-9700/i5-9400F/i5-9500F processors added
July 2, 2019	From v5 to v6	Update	CPU Intel Core i3-9300, i5-9600 and Pentium Gold G5620 added and Intel® Core™ i7-9700 removed to/from processors section
August 1, 2019	From v6 to v7	Update	GTX1650 added to graphics Pentium G5600 added to processors.
August 16, 2019	From V7 to V8	Update	PCIe x1 (2.0) corrected AMD Radeon 520 1GB added Standard security lock slot upgrade @ call outs
August 21, 2019	From V8 to V9	Update	Intel® Core™ i7-9700 put back in to processors section
October 3, 2019	From V9 to V10	Update	Miscellaneous Features section added
November 27, 2019	From V10 to V11	Update	NVIDIA® GeForce® GT1060 6GB GFX reference added to footnote
December 2, 2019	From V11 to V12	Update	NVIDIA® GeForce® GT1060 3GB GFX reference added to footnote
February 27, 2020	From V12 to V13	Update	Processor i7-9700 Turbo boost tech spec corrected