

# CLAM GRAPPLE



The WBM Clam (Powerclam) Grapple is a very versatile tool. With many options to choose from, this grapple can be configured to handle tree length, cut-to-length, shortwood, as well as brush piling and blow down with the cut-off saw arrangement. Bucket configurations are also available for road building and other bulk material handling applications.

## FEATURES & BENEFITS

- Performs loading, piling and digging operations, depending on jaw type
- Pin-on or Quick Coupler lugging
- 360° continuous rotation with single or dual high torque drive motors for optimum rotation and holding torque
- Hardened pins & bushings and replaceable wear parts for optimum service life
- Configuration versatility to handle a variety of applications
- Large diameter rotation bearing allows power tilting (heeling) logs
- Interchangeable jaws to suit application
- High pressure cylinders

## OPTIONAL EQUIPMENT

- Hydraulic outrigger
- Fixed outrigger
- Shortwood jaws (cut-to-Length)
- Clamshell buckets
- Sorting jaws
- Cut-off saw
- Control valve in head (2,3 or 4 Section)
- Heavy duty tilt cylinder
- Rotate float
- Single or dual jaw timing link (10' or 24' jaws)



Continued on next page »

MACHINE SIZE	MODEL	CAPACITY	JAW TYPE	BEARING SIZE	WIDTH (IN.)	OPENING (IN.)	CLOSED (IN.)	WEIGHT (LBS.)
EX200	EX200-CG-L5*	5.25 sq. ft.	Loader jaws	M	42	75-5/16	7-1/16	4,500
EX200	EX200-CG-S10*	10 sq. ft.	Shortwood jaws	M	42	89-5/8	12-1/2	5,300
EX200	EX250-CB-L6*	6 sq. ft.	Loader jaws	M	42	79-1/4	8-9/16	4,700
EX250	EX250-CB-L8*	8 sq. ft.	Loader jaws	M	42	78-5/8	5-7/8	4,900
EX250	EX250-CB-S10*	10 sq. ft.	Shortwood jaws	M	42	89 5/8	12-1/2	5,300
EX250	EX250-CB-S12*	12.25 sq. ft.	Shortwood jaws	M	42	92-3/4	12-1/2	5,500
EX300	EX300-CG-L8*	8 sq. ft.	Loader jaws	M	42	78-5/8	5-7/8	4,900
EX300	EX300-CG-S12*	12 sq. ft.	Shortwood jaws	M	42	92-3/4	12-1/2	5,500
EX300	EX300-CG-S14TL*	14.5 sq. ft.	Shortwood jaws	M	42	106	22	5,800
EX300	EX300-CG-L6HD**	6 sq. ft.	Loader jaws	L	42	79-1/4	8-9/16	6,000
EX300	EX300-CG-S14.5HD**	14.5 sq. ft.	Shortwood jaws	L	42	106	22	7,500
EX400	EX400-CG-L8**	8 sq. ft.	Loader jaws	L	42	78-5/8	5-7/8	7,500
EX400	EX400-CG-S14.5TL**	14.5 sq. ft.	Shortwood c/w single timing link	L	42	106	22	7,500
EX400	EX400-CG-S24DTL**	24 sq. ft.	Shortwood jaws c/w dual timing link	L	42	134	28	8,500

\* Previously XPC-500

\*\* Previously XPC-600

Cord Capacity = Capacity (Sq.Ft.) X Wood Length (Ft.) X .8 Fill Factor X .0078

Cubic Meter Capacity = Capacity (Sq. Ft.) X Wood Length (Ft.) X .8 Fill Factor X .0283

WBM Part #148-527-xxxx

