

Data Sheet

FUJITSU Storage CELVIN® NAS Q805 Storage

Powerful 4-Drive NAS

The FUJITSU CELVIN® NAS Server Q805 is the ideal product for file sharing, end to end backup options and SAN (Storage Area Network) integration for SMB customers - enabling centralized data management at a reasonable price. It is a balanced multipurpose device with up to 32 TB storage and can be set up for anything from surveillance operations to NAS plus iSCSI storage.

Business Server Feature

- 4 hot swappable drives
- Integrated backup server with diverse replication modes
- VMWare®/Citrix®/HyperV™ Capable
- Enabling private cloud

Reliability

- Service-friendly cabinet
- 3-years spare part supply
- Country-specific warranty
- Top-up services are available



CELVIN® NAS Q805

Technical specifications

	Linux embedded system (2.6 kernel) Firmware based on 4.3.3 Processor: Intel® Celeron® J1900 1.99GHz (up to 2,41GHz) Memory: 2 GB DDR3L RAM, one free slot, max up to 8GB 512 MB Flash on DOM FAN: 1x quiet cooling fan (12cm) Intel® Ethernet Controller I210-AT Formfactor: Tower
Hard disk capacity	Up to 4 x 2.5-inch or 3.5-inch SATA I/II/SATA 6Gb/s HDD or SSD up to 32TB raw capacity, consult HDD compatibility list NAS HDD: ready for 24x7 use; Business Critical HDD: tailored for 24x7 reliability
LED	USB Status HDD 1 -4 LAN Power
System controls	Power button, One-touch copy button, Alarm Buzzer (System Warning), Reset Button, Display mode button
Color	Black housing, copper colored trays

Interfaces

USB 3.1 Gen1 (USB 3.0) total	Rear side: x2, front: x1 USB2.0: x2
HDMI	Rear side: x1
LAN / Ethernet	Rear side: x4 Gigabit RJ-45 Ethernet port (always on)

Software specification

Networking	<p>TCP/IP (IPv4 /IPv6 dual stack), multi IP setting, LACP, Port trunking /NIC teaming: Balance-rr (Round-Robin), Active Backup, Balance XOR, Broadcast, IEEE 802.3ad, Balance-tlb (Adaptive, Transmit Load Balancing), Balance-alb (Adaptive Load Balancing) DHCP client, DHCP server including PXE boot CIFS/SMB(1.0,2.0,2.1,3.0 selectable), SAMBA 4, AFP/Netatalk3.3, NFS v3, HTTP, HTTPS, FTP,SFTP(admin), DDNS, NTP, Telnet, SSH, iSCSI, SNMP, WebDAV, SMC Gigabit NICs w/ Jumbo Frame, Bonjour</p> <p>iSCSI target (with multi-LUNs per target), Up to 256 LUNs/targets combined iSCSI LUN online expansion LUN mapping / LUN masking Online LUN capacity expansion SCSI Primary Commands -3 (SPC-3) support / persistent reservation MC/S (multiple TCP connections / session) support to reach iSCSI target MPIO (multipath input output) for load balancing and failover iSCSI LUN Backup, One-time-Snapshot and Restore iSCSI initiator for virtual disks (max 8 disks); stack chaining master Virtual disk support for EXT3/ EXT4/ NTFS/ FAT32/ HFS+ iSCSI Connection and Management by Fujitsu Finder (Windows)</p> <p>Support for VMware VSphere (ESXi 5.x) via NFS and iSCSI (VMware VAAI for iSCSI and VAAI for NAS) Windows Server 2008 support (Hyper-V & failover clustering) Windows Server 2012 R2 Hyper-V; ODX support Citrix XenServer (6.2)</p> <p>VLAN 802.1Q USB WiFi-Adapter support IEEE 802.11b/g/n/ac WEP, WPA-personal (AES/TKIP), WPA2-personal (AES) Connection to wireless network or Ad Hoc network</p>
-------------------	---

Software specification

Backup Management	<ul style="list-style-type: none"> Client backup software Time machine backup (OS X Lion support) 3rd party backup software support Encrypted block-level remote replication (instant, scheduled backup management); synchronization mode/Rsync Real-time remote replication (RTRR protocol) for real-time backup of server & client, 3 sync modes, filter, policy definition, SSL protected Backup to Cloud Backup to (encryptable) USB storage devices LUN backup and restore LUN point-in-time snapshot (1x)
File System Management	<ul style="list-style-type: none"> Network share management (max. 512 shares) Share folder level ACL support Unicode support Journaling file system Web File Manager <ul style="list-style-type: none"> File management by Web-browser File and folder search Direct file viewing via Google Docs support (pdf,tif/tiff,ppt,doc,xls,pptx,docx,xlsx,svg,odt) Create and send download links for public file sharing (time expiration, password protected)
Disk Management	<ul style="list-style-type: none"> Disk usage status management; HDD S.M.A.R.T.; Bad blocks scan RAID 0/1/5/5+HS/10/6, JBOD, single disk Online RAID capacity expansion; online RAID-level migration RAID recovery, Bitmap support ISO mounting (max 256) via Web File Manager
User Management	<ul style="list-style-type: none"> User quota management Windows Active Directory support, max. 10k users LDAP directory service supports Open LDAP, max. 10k domain users User account management (max. 4096users) User group management (max. 512 groups) Shared folders (max. 512) Concurrent connections (max. 256) Support batch creating users User Import/ Export for Multiple CELVIN NAS Deployment Subfolder Permission (File/Directory ACL) Microsoft Networking (Samba) Host Access Control (Domain/IP)
RADIUS Server	<ul style="list-style-type: none"> Support for 802.1x security authentication: PAP, EAP-TLS/PAP, EAP-TTLS/PAP (WPA-Enterprise, WPA2-Enterprise) max. 10 RADIUS clients, max. 4096 users
VPN Server	<ul style="list-style-type: none"> OpenVPN up to 256bit SSL/TLS, PPTP up to 128bit encryption; 15 clients each
System Tools	<ul style="list-style-type: none"> E-mail alert (SMTP authentication); SMS alert notification Disk usage alert HDD standby mode Automatic power on after power loss Schedule power on/ off (15 settings max) System firmware upgrade Wake-on-LAN Smart fan setting Back up, restore, reset system settings Configurable management port Remote login by Telnet connection USB, SNMP(v2, v3) UPS support Network recycle bin
Event Logs	<ul style="list-style-type: none"> Complete system logs (file level): system events management, connection logs, current connection of on-line users Centralized monitoring / syslog server (TCP / UDP) Manually and advanced log filtering via wizard
Multilingual (Online) Support	<ul style="list-style-type: none"> English, German, Czech, Danish, Spanish, French, Italian, Norwegian, Polish, Russian, Finish, Swedish, Dutch, Turkish, Greek, Hungarian, Portuguese (Brazil), Romanian, Japanese, Korean, Thai, Chinese (Traditional & Simplified)

Software specification

FTP Server	<p>FTP remote access (max. 256 concurrent connections) FTP with SSL/ TLS (explicit) mode FTP bandwidth control and connection control Passive FTP port range control FXP and Unicode support TFTP server (PXE boot) SFTP (admin only)</p>
Printer Server	<p>USB printer network sharing (Windows / Mac) Internet printing protocol, printer management, Apple Bonjour printing</p>
Web Server	<p>Built-in editable php.ini, SQLite and MySQL Web-based management via phpMyAdmin Max. 32 virtual hosts</p>
MySQL Server	<p>MySQL database server</p>
Security	<p>Network access protection with autoblocking (SSH, Telnet, HTTP(S), FTP, CIFS/SMB, AFP) Policy based automatic IP blocking and IP filter Encrypted access (HTTPS, FTP with SSL/TLS(explicit),SSH/SFTP, RSync over SSH, CIFS host access control for shared folders ClamAV antivirus protection FIPS 140-2 validated AES 256-bit volume based data encryption Importable SSL certificates OpenVPN up to 256bit SSL/TLS, PPTP up to 128bit encryption Radius Server Instant alert via E-mail, SMS, Instant Messaging, LCD</p>
Surveillance Station	<p>2 channel free, up to 16 channels possible (fee-based) IP camera finder software and configuration</p>
Multimedia	<p>UPnP Media Server Built-in TwonkyMedia Server Real-time & Background Photo Transcoding Supports UPnP Media Player Such as PlayStation 3 and Xbox 360 Supported format (The actual playback capabilities may vary depending on the UPnP client.) Audio: MP3, MP4, M4A, M4A (ALAC), M4B, 3GP, APL, AC3, M1V, M4V, MOV, AAC, AMR, AWB, WAV, PCM, LPCM, MP1, MP2, AIF, AIFF, AIFC, SND, WMA, OGG, FLAC Photo: JPG, JPE, JPEG, TIFF, TIF, GIF, PNG, BMP Video: WMV, ASF, VDR, AVI, XVID, DIVX, FLV, MPG, MPE, MTS, M2TS, M2T, MPEG, SPTS, M2P, M2V, MP2T, MP2P, MPG2, DVR-MS, VOB Playlist: M3U, M3U8, WPL, PLS</p> <p>DLNA Server Supports DLNA/UPnP TVs and Players such as PlayStation 3 and Xbox 360 Supported audio format: AIFF, APE, DSD (DSF, DFF), FLAC, M4A, M4A Apple Lossless (ALAC), MP3, Ogg Vorbis, WAV (PCM, LPCM), WMA, WMA PRO, WMA VBR DRM encryption format is not supported. Support CUE indexing file for APE, FLAC audio format. Video and Audio On-the-fly Transcoding</p> <p>Multimedia Device Supports Photo, Audio and Video Image Slideshow and Rotation Automatic & Schedule Thumbnail Generation for Easy Browsing Display Photo Details from EXIF: Date, Exposure Time, Aperture, etc. Display Audio Details from ID3 Tag: Album Cover, Title, Artist, Album, etc. Access Authority Management Multimedia (Video & Audio) Streaming Supports Cooliris Supports Web Publishing (Facebook, MySpace, MSN Live, Twitter, Plurk, Blogger) Share Photos by Email Supported Formats: Photo - JPG/JPEG, GIF, PNG Audio - MP3 Video Playback: FLV, MPEG-4 Video (H.264 + AAC) AVI, M4V, MPG/MPEG, RM/RMVB, WMV</p>

Software specification

Application center	Diverse applications downloadable via App center Fujitsu NAS Explorer, Fujitsu NAS Manager for Android / iOS Fujitsu Finder, Qsync, Qget, Netbak Replicator standard software
Download Station	BitTorrent (FTP/ HTTP scheduled download) Support of TCP/ UDP tracker protocol, distributed hash table/DHT Up to 500 BT download tasks Download configuration / download status list RSS download manager, subscription to RSS feeds, RSS download Multiple URLs in one task
Supported operating systems	Windows 10 Windows 8.1 Windows 8 Windows 7 Mac OS X Linux UNIX Windows® Server 2012 R2 Windows® Server 2012 Windows® Server 2008 R2 Windows® Server 2003
Browser Support	Internet Explorer 10+ / Edge / Mozilla Firefox 8, 9, 10 / Apple Safari 4, 5 / Google Chrome

Supported formats

Supported file system	EXT4 (internal/external HDD) EXT3 (external HDD) NTFS (external HDD) FAT32 (external HDD) HFS+ (external HDD)
------------------------------	---

Electrical values

Device Classification	Information according to ErP Regulation (EC) No. 1275/2008 – Standby/networked standby requirements: All CELVIN® NAS have a so called “EUP-mode” implemented. With activated “EuP-mode” the device has a maximum power consumption of 0.5 W in standby mode by limited functionality. (Details are described in the operating manual) The intended use of these type of networked infrastructure device is providing always available data access while operating (i.e. “always on”). The requirement of networked standby mode function as described in Regulation (EC) No. 1275/2008 Annex II, 3(b) (“Power management for networked equipment”) would be inappropriate for this intended use of the equipment. It could only be achieved by turning off vital components of the equipment that are essential for the maintenance of the intended use.
Power consumption	Off-mode (EuP-mode):>0.3W Off-mode (WoL-mode enabled):1.0W HDD-Sleep mode :20.7W Idle-mode:27.1W HDD R/W-mode: 33.1W
Power supply input	Internal power supply ATX 250W 50-60Hz Input: 100-240V AC

Compliance

Device Classification	EAC
Europe	CE
Russia	EAC
USA/Canada	FCC Class B
Japan	VCCI
Compliance link	https://sp.ts.fujitsu.com/sites/certificates

Dimensions / Weight / Environmental

Dimensions (W x D x H)	180 x 235 x 177 mm
Weight	Net weight: 3.65 kg, Gross weight: 4.65 kg;
Operating ambient temperature	0 - 40 °C
Operating relative humidity	5 - 95 % (relative humidity), wet bulb 27° C
Acoustic noise level	Sound level HDD sleep:14.1 dB(A) measured at frontal bystander position In operation: 20,3 dB(A) measured at frontal bystander position (4x 500GB HDD)

Package content

CELVIN NAS Server Q805; Power Cord, CD, LAN cable x4 ,
Key for tray lock x2, trays x4, Quick Start Guide, Service flyer

Order information

S26341-F105-L805	EAN: 4054681908502	w/o Hard Disk Drives, 4 trays included
S26341-F105-L812	EAN: 4054681908540	4 x 2 TB NAS Hard Disk Drives
S26341-F105-L813	EAN: 4054681908588	4 x 3 TB NAS HDD EU
S26341-F105-L814	EAN: 4054681908625	4 x 4 TB NAS Hard Disk Drives
S26341-F105-L816	EAN: 4054681908663	4 x 6 TB NAS Hard Disk Drives
S26341-F105-L820	EAN: 4054681909189	w/o Hard Disk Drives, 4 trays included INT
S26341-F105-L822	EAN: 4054681909196	4 x 2 TB NAS HDD INT
S26341-F105-L824	EAN: 4054681909608	4 x 4 TB NAS HDD INT
S26341-F105-L873	EAN: 4054681908700	4 x 3 TB BC HDD EU
S26341-F105-L874	EAN: 4054681908748	4 x 4 TB BC HDD EU
VFY:CQ805XX020E1	EAN: 4054681953977	4 x 2 TB NAS Hard Disk Drives EU
VFY:CQ805XX040E1	EAN: 4054681953984	4 x 4 TB NAS Hard Disk Drives EU
VFY:CQ805XX060E1	EAN: 4054681953991	4 x 6 TB NAS Hard Disk Drives EU

Warranty

Warranty period	2 years
Warranty type	Bring-In / Send-In Service
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty
Recommended Service	X - 2/3 years, 9x5, Onsite Response Time: Next Business Day or Second Business Day
Spare Parts availability	3 years
Service Weblink	http://www.fujitsu.com/fts/services/support

More information

Fujitsu products, solutions & services

In addition to FUJITSU Storage CELVIN® NAS Q805, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Storage CELVIN® NAS Q805, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/fts/accessories

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright 2018 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions GmbH
Website: www.fujitsu.com/fts
2018-05-01 EM-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright 2018 Fujitsu Technology Solutions GmbH