

Product	Primary Port	Uplink	Temp Range	PoE Power	Max PoE+ Ports (30W)	Max PoE Ports (15.4W)
CHASSIS-BASED SWITCHES — LAYER 3						
SwitchBlade® x8112	Up to 400 modular	-	0°C to 40°C	1200W or 2400W	80	155
SwitchBlade® x8106	Up to 200 modular	-	0°C to 40°C	1200W or 2400W	80	120
10/100/1000 MANAGED SWITCHES — STACKABLE LAYER 3						
AT-x930-52GPX	48 x Gigabit Ethernet	4 x 10 Gigabit Ethernet	0°C to 45°C	380W - 1440W or 380W - 740W Redundant	48	48
AT-x930-28GPX	24 x Gigabit Ethernet	4 x 10 Gigabit Ethernet	0°C to 45°C	380W - 1440W or 380W - 740W Redundant	24	24
AT-x610-48Ts/X-POE+	48 x Gigabit Ethernet	4 x 10 Gigabit Ethernet	0°C to 45°C	480W or 780W	48 ¹	48
AT-x610-48Ts-POE+	48 x Gigabit Ethernet	2 x 10 Gigabit Ethernet	0°C to 45°C	480W or 780W	48 ¹	48
AT-x610-24Ts/X-POE+	24 x Gigabit Ethernet	4 x 10 Gigabit Ethernet	0°C to 45°C	480W or 780W	24	24
AT-x610-24Ts-POE+	24 x Gigabit Ethernet	2 x 10 Gigabit Ethernet	0°C to 45°C	480W or 780W	24	24
AT-x510-52GPX	48 x Gigabit Ethernet	4 x 10 Gigabit Ethernet	0°C to 45°C	370W	12	24
AT-x510-28GPX	24 x Gigabit Ethernet	4 x 10 Gigabit Ethernet	0°C to 45°C	370W	12	24
AT-x510L-52GP	48 x Gigabit Ethernet	4 x 10 Gigabit Ethernet	0°C to 45°C	185W	6	12
AT-x510L-28GP	24 x Gigabit Ethernet	4 x 10 Gigabit Ethernet	0°C to 45°C	185W	6	12
10/100/1000 MANAGED SWITCHES — LAYER 3						
AT-IE300-12GP	8 x Gigabit Ethernet	4 x Gigabit Ethernet	-40°C to 75°C	240W	8	8
10/100 MANAGED SWITCHES — STACKABLE LAYER 3						
AT-x310-50FP	48 x Fast Ethernet	2 x Gigabit Ethernet	0°C to 50°C	370W	12	24
AT-x310-26FP	24 x Fast Ethernet	2 x Gigabit Ethernet	0°C to 50°C	370W	12	24
CHASSIS-BASED SWITCHES — LAYER 2						
SwitchBlade® x3112	Up to 400 modular	-	0°C to 40°C	1200W or 2400W	80	155
SwitchBlade® x3106	Up to 200 modular	-	0°C to 40°C	1200W or 2400W	80	120
10/100/1000 MANAGED SWITCHES — STACKABLE LAYER 2						
AT-IX5-28GPX	24 x Gigabit Ethernet	4 x 10 Gigabit Ethernet	0°C to 50°C	370W or 720W	24	24
AT-GS948MPX	48 x Gigabit Ethernet	2 x 10 Gigabit Ethernet	0°C to 50°C	370W	12	24
AT-GS924MPX	24 x Gigabit Ethernet	2 x 10 Gigabit Ethernet	0°C to 50°C	370W	12	24
10/100/1000 MANAGED SWITCHES — LAYER 2						
AT-x230-28GP	24 x Gigabit Ethernet	4 x Gigabit Ethernet	0°C to 50°C	370W	12	24
AT-x230-18GP	16 x Gigabit Ethernet	2 x Gigabit Ethernet	0°C to 50°C	247W	8	16
AT-x230-10GP	8 x Gigabit Ethernet	2 x Gigabit Ethernet	0°C to 50°C	124W	4	8
AT-IE200-6GP	4 x Gigabit Ethernet	2 x Gigabit Ethernet	-40°C to 75°C	120W	4	4
10/100 MANAGED SWITCHES — STACKABLE LAYER 2						
AT-8000S/48POE ²	48 x Fast Ethernet	2 x Gigabit Ethernet	0°C to 40°C	375W	-	24
10/100 MANAGED SWITCHES — LAYER 2						
AT-FS970M/48PS	48 x Fast Ethernet	2 x Gigabit Ethernet	0°C to 40°C	370W	12	24
AT-FS970M/24PS	24 x Fast Ethernet	2 x Gigabit Ethernet	0°C to 40°C	370W	12	24

¹ When using AT-RPS3000 for additional power. Stand-alone maximum = 26 ports² Not available in APAC

Product	Primary Port	Uplink	Temp Range	PoE Power	Max PoE+ Ports (30W)	Max PoE Ports (15.4W)
10/100 MANAGED SWITCHES — LAYER 2						
AT-FS970M/24LPS	24 x Fast Ethernet	2 x Gigabit Ethernet	0°C to 40°C	185W	6	12
AT-FS970M/8PS	8 x Fast Ethernet	2 x Gigabit Ethernet	0°C to 40°C	185W	6	8
AT-FS970M/8PS-E	8 x Fast Ethernet	2 x Gigabit Ethernet	0°C to 50°C	185W	6	8
AT-8000/8POE	8 x Fast Ethernet	1 x Gigabit Ethernet	0°C to 45°C	95W	-	6
AT-IE200-6FP	4 x Fast Ethernet	2 x Gigabit Ethernet	-40°C to 75°C	120W	4	4
AT-IFS802SP/POE(W)	8 x Fast Ethernet	2 x Gigabit Ethernet	-40°C to 75°C	123.2W	-	8
10/100/1000 UNMANAGED AND WEBSMART SWITCHES						
AT-GS950/48PS	48 x Gigabit Ethernet	4 x Gigabit Ethernet	0°C to 40°C	370W	12	24
AT-GS950/28PS ⁴	24 x Gigabit Ethernet	4 x Gigabit Ethernet	0°C to 40°C	185W	4	12
AT-GS950/16PS	14 x Gigabit Ethernet	2 x Gigabit Ethernet	0°C to 40°C	185W	6	12
AT-GS950/10PS	8 x Gigabit Ethernet	2 x Gigabit Ethernet	0°C to 40°C	75W	2	4
AT-GS900/8PS	8 x Gigabit Ethernet	1 x Gigabit Ethernet	0°C to 40°C	75W	2	4
10/100 UNMANAGED AND WEBSMART SWITCHES						
AT-FS750/28PS	24 x Fast Ethernet	4 x Gigabit Ethernet	0°C to 40°C	193W	4	12
AT-FS708/POE	8 x Fast Ethernet	1 x Gigabit Ethernet	0°C to 40°C	65W	-	4
AT-FS708LE/POE	8 x Fast Ethernet	-	0°C to 40°C	30W	-	2

NETWORK INTERFACE CARDS (PCIe)						
AT-2716POE/FXSC	Fast Ethernet	MMF SC	0°C to 40°C	15W	-	1
AT-2716POE/FXST	Fast Ethernet	MMF ST	0°C to 40°C	15W	-	1
AT-2911GP/LXLC	Gigabit Ethernet	SMF LC	0°C to 40°C	30W	1	1
AT-2911GP/LXSC	Gigabit Ethernet	SMF SC	0°C to 40°C	30W	1	1
AT-2911GP/SFP	Gigabit Ethernet	SFP	0°C to 40°C	30W	1	1
AT-2911GP/SXLC	Gigabit Ethernet	MMF LC	0°C to 40°C	30W	1	1
AT-2911GP/SXSC	Gigabit Ethernet	MMF SC	0°C to 40°C	30W	1	1
MEDIA CONVERTERS						
AT-PC232/POE	Fast Ethernet	100FX MMF	0°C to 40°C	15W	-	1
AT-PC2002POE	Gigabit Ethernet	SFP	0°C to 40°C	15W	-	1
AT-IMC1000TP/SFP	Gigabit Ethernet	SFP	0°C to 40°C	30W	1	1
INJECTOR/MIDSPAN						
AT-6101GP	Gigabit Ethernet	Gigabit Ethernet	0°C to 40°C	30W	1	1
AT-6112GP	12 x Gigabit Ethernet	12 x Gigabit Ethernet	0°C to 40°C	370W	12	12

² Not available in APAC

³ Not available in USA

⁴ Available Q3 2016



NETWORK SMARTER

North America Headquarters | 19800 North Creek Parkway | Suite 100 | Bothell | WA 98011 | USA | T: +1 800 424 4284 | F: +1 425 481 3895

Asia-Pacific Headquarters | 11 Tai Seng Link | Singapore | 534182 | T: +65 6383 3832 | F: +65 6383 3830

EMEA & CSA Operations | Incheonweg 7 | 1437 EK Rozenburg | The Netherlands | T: +31 20 7950020 | F: +31 20 7950021

alliedtelesis.com

© 2016 Allied Telesis, Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners.
C618-3410015 Rev1