Emerson Avocent® SV200 Series Desktop KVM Switches

Connect and control your entire desktop





SV240D

Benefits

- Access: Access from two to four computers using a single keyboard, monitor and mouse
- Enhanced Usability: Managed copy and paste of files and text between sources
- Seamless Integration: Mobile High-Definition Link (available on 4-port HDMI models) enables viewing of media from mobile devices on connected HDMI monitors
- Advanced Video Support: Support for DVI-I, HDMI 1.4 and DP1.2 in single and dual head models supporting high resolutions up to UHD 4K
- Zero Delay Switching: Mouse and keyboard switching via emulation assures zero delay in switching time between connected sources
- Independent Audio and USB Switching: Easily switch audio and USB 3.0 (select models) peripherals independently of KVM
- Streamlined, Flexible
 Connectivity: Three USB 3.0
 ports on the front of the 240
 KVMs enable easy connectivity to
 external USB devices, quick data
 transfer and high speed charging
 of mobile devices

Specifications

•							
	SV220	SV220D	SV220H	SV240	SV240D	SV240H	
System Connections	2				4		
Display Connections		1			1		
Display Support	DVI-I, HDMI and VGA with adapter	DP 1.2	HDMI 1.4	DVI-I, HDMI and VGA with adapter	DP 1.2	HDMI 1.4	
Max Resolution	UHD 4K - 3840X2160 @ 30 Hz (via DVI to HDMI cable) DVI dual-link - 2560X1600 @ 60 Hz (via DVI cable) VGA - 2048X1536	resolutio	ng UHD 4K ons up to 50 @ 30Hz	UHD 4K - 3840X2160 @ 30 Hz (via DVI to HDMI cable) DVI dual-link - 2560X1600 @ 60 Hz (via DVI cable) VGA - 2048X1536	resolutio	ng UHD 4K ons up to 50 @ 30Hz	
	EFFICIENCY FEATURES						
	Front panel USB 3.0 ports including high-power charging port (SV240 series) Copy-Paste (Text and File)						
	SUPPORTED HARDWARE						
Console Peripherals		USB Type-A			USB Type-A		
Computer Peripherals	USB Type-B			USB Type-B			
Dedicated Peripheral Port	N/A			3 x USB Super Speed			
Audio Input/Output	2 x 3.5mm stereo female 2 x 3.5mm stereo female						
	MECHANICAL						
Enclosure	Steel with Plastic Front Panel Steel with Plastic Front Panel						
Dimensions WxDxH	177 x 61 x 35 mm 342x125x42mm						
	7 x 2.4 x 1.4 inches 13.7x5x1.7 inches						
Weight	.5 kg (1 lbs) 1.5 kg (3 lbs)						
	POWER						
Power Requirements	12V DC, 1.5A (maximum) power adapter with center-pin-positive polarity			35W Max Internal			
AC Input Voltage	100 to 240V AC 100 to 240V AC						
	ENVIRONMENTAL						
Operating Temperature	32° to 104° F: 0° to 40° C						
Storage Temperature	-4° to 140° F; -20° to 60° C						
Humidity	0-80% RH, non-condensing						
Certifications	RCM. EU. FCC Class B. VCCI. c-UL						

Ordering Details

Warranty

EMERSON AVOCENT® DESKTOP KVM CABLES

EMERSON, WOLLING BESINGS IN MICHELES		
PART NUMBER	MODEL NUMBER	DETAILS
CBL0118	SV220/SV240	USB keyboard, mouse & DVI-I video cable with audio - 6 ft.
CBL0119	SV220/SV240	USB keyboard, mouse & DVI-I video cable with audio - 10 ft.
CBL0122	SV220D/SV240D	USB keyboard, mouse & DisplayPort video cable with audio - 6 ft.
CBL0123	SV220D/SV240D	USB keyboard, mouse & DisplayPort video cable with audio - 10 ft.
CBL0126	SV220H/SV240H	USB keyboard, mouse & HDMI video cable with audio - 6 ft.
CBL0127	SV220H/SV240H	USB keyboard, mouse & HDMI video cable with audio - 10 ft.



Emerson Network Power.com

Emerson, Emerson Network Power and the Emerson Network Power logo are service marks and trademarks of Emerson Electric Co. Avocent is a trademark of Avocent Corporation. ©2015 Emerson Electric Co. All rights reserved. AV-11410_R0615

2 years

Emerson Avocent® SV300 Series Desktop KVM Switches

Connect and control your entire desktop



SV340D

Benefits

- Access: Access up to four computers using a single keyboard, monitor and mouse
- Enhanced Usability: Managed copy and paste of files and text between sources
- Seamless Integration: Mobile
 High-Definition Link (available
 on 4-port HDMI models) enables
 viewing of media from mobile
 devices on connected
 HDMI monitors
- Advanced Video Support: Support for DVI-I, HDMI 1.4 and DP1.2 in single and dual head models supporting high resolutions up to UHD 4K
- Zero Delay Switching: Mouse and keyboard switching via emulation assures zero delay in switching time between connected sources
- Independent Audio and USB Switching: Easily switch audio and USB 3.0 (select models) peripherals independently of KVM
- Streamlined, Flexible
 Connectivity: Three USB
 3.0 ports on the front of the
 340 series KVMs enable easy
 connectivity to external USB
 devices, quick data transfer
 and high speed charging of
 mobile devices

Specifications

	SV340	SV340H	SV340D
System Connections	4	4	4
Console Connections	2	2	2
Display Support	HDMI & VGA with adapter	HDMI 1.4	DP1.2
Max Resolution	3840X2160 @ 30 Hz (via DVI to HDMI cable) DVI dual-link - 2560X1600 @ 60 Hz (via DVI cable) VGA - 2048X1536	Supporting UHD 4K resolutions up to 3840x2160 @ 30Hz	Supporting UHD 4K resolutions up to 3840x2160 @ 30Hz
	EFFICIENCY FEATURES		
	Front panel USB 3.0 ports including high-power charging port Copy-Paste (Text and File)		
	SUPPORTED HARDWARE		
Console Peripherals	USB Type-A		
Computer Peripherals	USB Type-B		
Dedicated Peripheral Port	3 x USB Super Speed		
Audio Input/Output	2 x 3.5mm stereo female		
	BAECHANICAL		

Computer Peripherals	USB Type-B
Dedicated Peripheral Port	3 x USB Super Speed
Audio Input/Output	2 x 3.5mm stereo female
	MECHANICAL
Enclosure	Steel with Plastic Front Panel
Dimensions WxDxH	342x125x56mm
	13.7x5x2.2 inches
Weight	1.85 kg (3.7 lbs)
	POWER
Power Requirements	35W Max Internal
AC Input Voltage	100 to 240V AC

AC Input Voltage ENVIRONMENTAL Operating Temperature Storage Temperature 4° to 140° F; -20° to 60° C Humidity 0-80% RH, non-condensing Certifications 100 to 240V AC ENVIRONMENTAL 32° to 104° F; 0° to 40° C 50° C 4° to 140° F; -20° to 60° C Humidity RCM, EU, FCC Class B, VCCI, c-UL	i owei kequirements	33W Max Internal
Operating Temperature 32° to 104° F; 0° to 40° C Storage Temperature -4° to 140° F; -20° to 60° C Humidity 0-80% RH, non-condensing Certifications RCM, EU, FCC Class B, VCCI, c-UL	AC Input Voltage	100 to 240V AC
Storage Temperature -4° to 140° F; -20° to 60° C Humidity 0-80% RH, non-condensing Certifications RCM, EU, FCC Class B, VCCI, c-UL		ENVIRONMENTAL
Humidity 0-80% RH, non-condensing Certifications RCM, EU, FCC Class B, VCCI, c-UL	Operating Temperature	32° to 104° F; 0° to 40° C
Certifications RCM, EU, FCC Class B, VCCI, c-UL	Storage Temperature	-4° to 140° F; -20° to 60° C
, -, -, -	Humidity	0-80% RH, non-condensing
	Certifications	RCM, EU, FCC Class B, VCCI, c-UL
Warranty 2 years	Warranty	2 years

Ordering Details

EMERSON AVOCENT® DESKTOP KVM CABLES

DADT NILIMDED	MODEL NUMBER	DETAILS
PART NOWBER	MODEL NOMBER	DETAILS
CBL0120	SV 340	USB keyboard, mouse & dual head DVI-I video cable with audio - 6 ft.
CBL0121	SV 340	USB keyboard, mouse & dual head DVI-I video cable with audio - 10 ft.
CBL0124	SV 340D	USB keyboard, mouse & dual head DisplayPort video cable with audio - 6 ft.
CBL0125	SV 340D	USB keyboard, mouse & dual head DisplayPort video cable with audio - 10 ft.
CBL0128	SV 340H	USB keyboard, mouse & dual head HDMI video cable with audio - 6 ft.
CBL0129	SV 340H	USB keyboard, mouse & dual head HDMI video cable with audio - 10 ft.



Emerson Network Power.com

Emerson, Emerson Network Power and the Emerson Network Power logo are service marks and trademarks of Emerson Electric Co. Avocent is a registered trademark of Avocent Corporation. ©2015 Emerson Electric Co. All rights reserved. AV-11410_R0615