



### Purchase

APC  
 AP7832

### Overview

Model Name	Rack PDU, Metered, Zero U, 30A, 120V, (24) 5-20
Includes	Rack Mounting brackets , Toolless Mounting Kit , User Manual
Standard Lead Time	Usually in Stock
Product Distribution	Antigua And Barbuda , Anguilla , Netherlands Antilles , Argentina , Aruba , Barbados , Bermuda , Bolivia , Brazil , Bahamas , Belize , Canada , Chile , Colombia , Costa Rica , Cuba , Dominica , Dominican Republic , Ecuador , Falkland Islands (Malvinas) , Grenada , Guadeloupe , Guatemala , Guyana , Honduras , Haiti , Jamaica , SAINT KITTS AND NEVIS , Martinique , Mexico , Nicaragua , Panama , Peru , Puerto Rico , Paraguay , El Salvador , Turks And Caicos Islands , Trinidad And Tobago , Taiwan , United States , Uruguay , SAINT VINCENT AND THE GRENADINES , Venezuela , VIRGIN ISLANDS (UNITED STATES)

### Output

Nominal Output Voltage	120V
Maximum Total Current Draw per Phase	24 A
Output Connections	(24) NEMA 5-20R (Battery Backup)
Overload Protection	Yes

### Input

Nominal Input Voltage	100V , 120V
Input Frequency	50/60 Hz
Regulatory Derated Input Current (North America)	24 A
Input Connections	NEMA L5-30P
Cord Length	3.05 meters
Number of Power Cords	1
Maximum Input Current per phase	30 A
Load Capacity	2880 VA

## Physical

Net Weight	5.68 kg
Maximum Height	1619 mm
Maximum Width	56 mm
Maximum Depth	44 mm
Shipping Weight	6.59 kg
Shipping Height	2134 mm
Shipping Width	152 mm
Shipping Depth	127 mm
Color	Black

## Environmental

Operating Environment	0 - 45 °C
Operating Relative Humidity	5 - 95 %
Operating Elevation	0-3000 meters
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	5 - 95 %
Storage Elevation	0-15000 meters

## Conformance

Approvals	CUL Listed , CSA C22.2 No. 60950-1-03 , FCC Part 15 Class A , ICES-003 , Industry Canada , UL 60950 , UL 60950-1
Standard warranty	2 years repair or replace

## Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs
Battery Directive	Compliant
Battery Notes	Battery Notes