Lexmark XS955de

Power up your office and increase productivity with the Lexmark XS955de, featuring high-performance A3 colour functionality, flexible features, easy-to-use workflow solutions, advanced security and 2GB RAM.

Part Number
3084911

Print Technology
Colour LED

Function
Colour Copying, Colour Faxing, Colour Printing, Color Scanning, Colour Network Scanning

Workgroup Size
Departmental Workgroup

Touch Screen Display
Yes

Display
Lexmark e-Task 10-inch (25 cm) class color touch screen

Print Speed (A4, Black)
Up to 55 ppm

Print Speed (A4, Colour)
Up to 50 ppm

Print Speed (A4, Black) Duplex
Up to 55 spm

Print Speed (A4, Colour) Duplex
Up to 50 spm

Time to First Page (Black)
As fast as 5.0 seconds

Time to First Page (Colour)
As fast as 7.2 seconds

Duplex (2-sided) Printing
Integrated Duplex

Print Resolution, Black
1200 x 1200 dpi, 2400 Image Quality

Print Resolution, Colour
1200 x 1200 dpi, 2400 Image Quality

Copy Speed (A4, Black)
Up to 55 cpm

Copy Speed (A4, Colour)
Up to 50 cpm

Copy Speed (A4, Black) Duplex
Up to 55 spm

Time to First Copy (Black)
As fast as 6.4 seconds

Time to First Copy (Colour)
As fast as 9.9 seconds

Reduce / Enlarge Range
25 - 400 %

A4/Ltr Simplex Scan Speed (Black)
Up to 68 / 70 Sides per minute

A4/Ltr Simplex Scan Speed (Colour)
Up to 52 / 52 Sides per minute

A4/Ltr Duplex Scan Speed (Black)
Up to 38 / 37 Sides per minute

A4/Ltr Duplex Scan Speed (Colour)
Up to 38 / 37 Sides per minute

Scan Area, Maximum (mm)
297 x 432 mm

ADF Scan
RADF (reversing Duplex)

Scanner Type
Flatbed scanner with ADF

Scan Technology
CCD

Optical Scanning Resolution
600 X 600 ppi

Scan File Formats (Send as)
JPEG, JPG, PDF, Secure PDF, TIFF, XPS, Archival PDF (A-1a, A-1b), Searchable PDF (optional OCR with 1GB RAM and hard disk required), Highly compressed PDF (1GB RAM and hard disk required)

Scan Destinations
e-mail, FTP, USB Flash drive, USB or Network connected computer, Lexmark Document Solutions Suite (LDSS)

Modem Speed
33.6 Kbps

Processor Speed
1.2 GHz

Memory, Standard
2048 MB

Memory, Maximum
2048 MB

Hard Disk
Included in configuration

Apple Operating Systems Supported
Apple OS X (10.5, 10.6, 10.7, 10.8, 10.9, 10.10)

Citrix MetaFrame
Microsoft Windows Server 2003 running Terminal Services with Citrix Presentation Server 3.0, 4.0, 4.5, Microsoft Windows Server 2003 and 2003 X64 Edition with Citrix XenApp 5.0, Microsoft Windows Server 2008 and 2008 X64 Edition with Citrix XenApp 5.0

Linux Operating Systems Supported
SUSE Linux Enterprise Server 10, 11, SUSE Linux Enterprise Desktop 10, 11, Red Hat Enterprise Linux WS 4.0, 5.0, Red Flag Linux Desktop 6.0, Linpus Linux Desktop 9.6, Ubuntu 9.04, 9.10, 10.04, 10.10, Debian GNU/Linux 5.0, 6.0, Ubuntu 11.04, 11.10, 12.04, 12.10, openSUSE 11.3, 11.4, 12.1, 12.2, Fedora 14, 15, 16, 17, Mint 10, 11, 12, 13

Microsoft Windows Operating Systems Supported
Windows XP, Windows Server 2003, Windows XP x64, Windows Server 2003 x64, Windows Vista, Windows Vista x64, Windows Server 2008, Windows Server 2008 x64, Windows 7, Windows 7 x64, Windows Server 2008 R2, Windows 8, Windows 8 x64, Windows Server 2012, Windows 8.1, Windows 8.1 x64, Windows Server 2012 R2, Windows RT, Windows RT 8.1

Novell Operating Systems Supported
Novell NetWare 6.5 Open Enterprise Server, Novell NetWare 5.1(SP 6+), 6.0(SP 3+) with Novell Distributed Print Services (NDPS), Novell Open Enterprise Server on SUSE Linux Enterprise Server

UNIX Operating Systems Supported
Sun Solaris SPARC 8, 9, 10, Sun Solaris x86 10, HP-UX 11.11, 11.23, 11.31, IBM AIX 5.3, 6.1, 7.1

Paper Handling Standard
500-Sheet Output Bin, Integrated Duplex, 100-Sheet Multipurpose Feeder, 520-Sheet Input Tray

Paper Handling Optional
Banner Media Tray, 2,000-Sheet High Capacity Feeder, 3,500-Sheet Finisher, 3 x 520-Sheet Drawer Stand, Booklet Finisher, 2,520-Sheet Tandem Tray Module, 520-Sheet Drawer Stand

Paper Input Capacity, Standard
Up to 620 pages 75 gsm bond

Paper Input Capacity, Maximum
Up to 5140 pages 75 gsm bond

Paper Output Capacity, Standard
Up to 500 pages 75 gsm bond

Paper Output Capacity, Maximum
Up to 3750 pages 75 gsm bond

Paper Weight Range Supported - Standard Tray (gsm)
60 - 256 gsm

A3
Yes

ADF
110-Sheet Automatic Document Feeder

ADF Paper Input Capacity
Up to 110 pages 75 gsm bond

ADF Paper Output Capacity
Up to 110 pages 75 gsm bond

Finishing Option
Yes

Number of Paper Inputs, Standard
2

Number of Paper Inputs, Maximum
6

Media Types Supported
Card Stock, Envelopes, Glossy paper, Labels, Plain Paper, Transparencies, Refer to the Card Stock & Label Guide.

Media Sizes Supported
10 Envelope, 7 3/4 Envelope, A3, A4, A5, C5 Envelope, DL Envelope, Executive, Folio, JIS-B4, JIS-B5, Ledger, Legal, Letter, Statement, Universal, Super Tabloid (305 x 457 mm), Oficio, A6

Lexmark

Standard Ports
USB 2.0 Specification Hi-Speed Certified
(Type B), Front USB 2.0 Specification Hi-
Speed Certified port (Type A), Rear USB 2.0
Specification Hi-Speed Certified port (Type A),
Ethernet 10/100/1000 BaseTX (RJ-45)

Optional Local Ports
Internal RS-232C serial, Internal 1284-B
Bidirectional Parallel

Optional Network Ports
Internal MarkNet™ N8130 Fiber Fast Ethernet,
Internal MarkNet™ N8250 802.11b/g/n Wireless

Direct USB
Yes

Ethernet Network
Yes

Network Protocol Support
TCP/IP IPv4, AppleTalk™, TCP/IP IPv6, TCP,
UDP

Network Printing Methods
LPR/LPD, Direct IP (Port 9100), HTTP, NDPS/
NEPS (Novell Distributed Print Services, Novell
Netware Enterprise Print Services), Enhanced
IP (Port 9400), FTP, TFTP, IPP 1.1 (Internet
Printing Protocol), ThinPrint .print integration

Network Management Protocols[2]
HTTP, HTTPs (SSL/TLS), SNMPv3, WINS,
IGMP, BOOTP, RARP, APIPA (AutoIP), DHCP,
ICMP, DNS, SNMPv2c, Bonjour, DDNS, mDNS,
ARP, NTP, Telnet, Finger,

Network Security
SNMPv3, 802.1x Authentication: MD5,
MSCHAPv2, LEAP, PEAP, TLS, TTLS, IPSec

Printable Area (metric)
4.2 mm of the top, bottom, right and left
edges (within)

Printer Languages (Standard)
PCL 5c Emulation, PCL 6 Emulation, Personal
Printer Data Stream (PPDS), PostScript
3 Emulation, xHTML, PDF 1.6 Emulation,
Direct Image, Microsoft XPS (XML Paper
Specification), AirPrint™

Fonts and Symbol Sets
3 of 9 scalable PCL 5e fonts in Narrow,
Regular and Wide, 158 scalable PostScript
fonts, 2 PCL bitmap fonts, 39 scalable PPDS
fonts, 5 PPDS bitmap fonts, 84 scalable PCL
fonts, OCR-A, OCR-B scalable PCL 5e fonts,
For more information, refer to the Technical
Reference.

Supplies Yield[1]
22,000-page Colour (CMY) Toner
Cartridges32,000-page Black Toner Cartridge

Photoconductor Estimated Yield
Up to 115000 pages, based on 3 average
letter/A4-size pages per print job and ~ 5%
coverage[5]

Cartridge(s) Shipping with Product
11,000-page Colour (CMY) Starter Toner
Cartridges, 16,000-page Black Starter Toner
Cartridge

Packaged Size (mm - H x W x D)
870 x 848 x 769 mm

Packaged Weight (kg)
125.0 kg

Size (mm - H x W x D)
762 x 640 x 685 mm

Weight (kg)
116.0 kg

Size, Trays Extended (mm - H x W x D)
1098 x 640 x 1108 mm

Noise Level, Idle
24 dBA

Noise Level (Print), Operating
53 dBA

Duplex Print Noise Level, Operating
55 dBA

Noise Level (Copy), Operating
55 dBA

Noise Level (Scan), Operating
54 dBA

ENERGY STAR
Yes

Average Power (Hibernate Mode)
1 watts

Average Power (Sleep Mode)
16.5 watts

Average Power (Printing)
750 watts

Average Power while Printing Duplex
725 watts

Average Power (Copying)
850 watts

Average Power (Scanning)
135 watts

**ENERGY STAR Typical Electricity
Consumption (TEC)**
6.6 kilowatt-hours per week

Product Guarantee
1-year Onsite Service + 3-years Parts Only
guarantee (Maintenance Kit included)

Product Certifications
ENERGY STAR, CAN/CSA-C22.2 60950-1-07,
ICES-003 Class A, BSMI Class A, CNS 13438
and 14336, VCCI Class A, FCC Class A,
UL 60950-1, EN/IEC 60320-1, NOM-019-
SCFI-1998, CB IEC 60950-1, EN 60950-1,
EN/IEC 61000-3, EN 55022 Class A, EN
55024, GS (TÜV), SAT, SABS, ZIK, KPSIM, Bel
GISS, GOST-R 'Cpt' Mark, N Mark, IRAM, CS,
TÜV Rh, ACMA A-tick mark Class A, AS/NZS
60950-1, CCC Class A, GB4943, CISPIR 22
Class A, MIC Mark, EK-K60950, PSB-SS 337

Maximum Monthly Duty Cycle
Up to 250000 pages per month[4]

Recommended Monthly Page Volume
5000 - 33000 pages[3]

Specified Operating Environment
Altitude: 0 - 2500 Meters (8,200 Feet),
Temperature: 10 to 32°C, Humidity: 15 to 85%
Relative Humidity

Country of Origin
China (PR)

UNSPSC Code
43212110

[1]Yield at approximately 5% coverage per colour

[2]This product includes software developed by the
OpenSSL Project for use in the OpenSSL Toolkit. (http://
www.openssl.org/)

[3]"Recommended Monthly Page Volume" is a range of pages
that helps customers evaluate Lexmark's product offerings
based on the average number of pages customers plan to
print on the device each month. Lexmark recommends that
the number of pages per month be within the stated range
for optimum device performance, based on factors including:
supplies replacement intervals, paper loading intervals,
speed, and typical customer usage.

[4]"Maximum Monthly Duty Cycle" is defined as the maximum
number of pages a device could deliver in a month using a
multishift operation. This metric provides a comparison of
robustness in relation to other Lexmark printers and MFPs.

[5]Actual Yield may vary based on other factors such as device
speed, paper size and feed orientation, toner coverage, tray
source, percentage of black-only printing and average print
job complexity.

Lexmark

- 3,500-Sheet Finisher
- 25 cm (10-inch) Class Touch Screen
- 500-Sheet Output Bin
- 100-Sheet Multipurpose Feeder
- 520-Sheet Input Tray
- 2,520-Sheet Tandem Tray Module
- 2,000-Sheet High Capacity Feeder
- Booklet Finisher
- 3 x 520-Sheet Drawer Stand
- 520-Sheet Drawer Stand

■ Standard
■ Optional

P/N	Toner Cartridges
25A0013	Staple Cartridges (3 pack)
21Z0357	Saddle Staple Cartridges (4 pack)
C950X71G	C950, X950/2/4 Photoconductor Unit 1-Pack
C950X76G	C950, X950/2/4 Waste Toner Bottle
C950X73G	C950, X950/2/4 Photoconductor Unit 3-Pack
22Z0008	XS955 Black Extra High Yield Toner Cartridge (32K)
22Z0009	XS955 Cyan Extra High Yield Toner Cartridge (22K)
22Z0010	XS955 Magenta Extra High Yield Toner Cartridge (22K)
22Z0011	XS955 Yellow Extra High Yield Toner Cartridge (22K)

P/N	Paper Handling
22Z0014	C950, X95x 2520-Sheet Tandem Tray Module
22Z0013	C950, X95x 3x520-Sheet Drawer Stand
22Z0012	C950, X95x 520-Sheet Drawer Stand
22Z0015	C950, X95x 2000-Sheet High Capacity Feeder
22Z0175	C950, X95x 3500-Sheet Finisher (4-Hole)
22Z0176	C950, X95x Booklet Finisher (4-Hole)
22Z0205	C950, X95x Banner Media Tray

P/N	Memory Options
14F0245	256MB Flash Card
30G0825	Korean Font Card
30G0828	Japanese Font Card
30G0827	Traditional Chinese Font Card
30G0826	Simplified Chinese Font Card
30G0287	Arabic Font Card
57X0070	Removable Hard Disk Enclosure Kit

P/N	Application Solutions
57X9000	Lexmark PrintCryption Card
22Z0186	X950, X952, X954 Card for IPDS
22Z0187	X950, X952, X954 Card for PRESCRIBE Emulation
22Z0185	X950, X952, X954 Forms and Bar Code Card

P/N	Connectivity
1021231	Parallel (10') Cable
1021294	USB (2 Meter) Cable
14F0100	RS-232C Serial Interface Card
14F0000	Parallel 1284-B Interface Card
14F0042	MarkNet N8130 Fiber Ethernet 100BaseFX, 10BaseFL Print Server
27X0225	MarkNet N8350 802.11b/g/n Wireless Print Server
SPD0002	Surge Protective Device, 220-240V

P/N	Extended Warranties
2359561	XS955 1-Year Renewal Parts Only Guarantee with Maintenance kit
2359902	XS955 Upgrade to Parts and Labour, Total 4 years (1+3)
2359904	XS955 1-Year Renewal Parts and Labour with Maintenance kit
2359420	XS955 Upgrade to Onsite Service, Total 4 years (1+3)
2359610	XS955 1-Year Renewal Onsite Service with Maintenance kit

P/N	User Replaceable Parts
40X7569	C950, X95x Fuser Maintenance Kit, 320K, 220-240V
40X7540	C950, X95x 160K Maintenance Kit
40X7530	X95x ADF Maintenance Kit
40X7560	C950, X95x 480K Maintenance Kit

P/N	Installation Service
2355255	Standard Installation Service

P/N	Service Parts
40X6824	X95x ADF feed /pick roller assembly