

HP LaserJet Enterprise 700 Printer M712n (CF235A) Active as of 11/1/2012

Detailed Specifications

Accessories

HP LaserJet 500-sheet Feeder and Tray CF239A, HP LaserJet 1x500-sheet Paper Feeder with Cabinet and Stand CF243A, HP LaserJet 3x500-sheet Feeder and Stand CF242A, HP LaserJet 3500-sheet HCI Feeder and Stand CF245A, HP LaserJet Duplex Printing Assembly CF240A, HP LaserJet 110V Maintenance/Fuser Kit CF249A, HP LaserJet 220V Maintenance/Fuser Kit CF254A, HP 512 MB 144-pin x32 DDR2 DIMM CE483A

Acoustic power emissions (active, printing)

6.8 B(A)

Acoustic power emissions (ready) Inaudible

Acoustic power footnote number

[4]

Acoustic power note

Acoustic values are subject to change. For current information see hp.com/support. Configuration tested: M712dn model, simplex printing, A4 paper at an average of 41 ppm.

Acoustic pressure emissions bystander (active, printing)

54 dB(A)

Acoustic pressure emissions bystander (ready) Inaudible

Automatic paper sensor

No

Bottom margin (A4)

2 mm

Cable included

No, please purchase USB cable separately

Code name

Annapurna

Compatible Operating Systems

Windows 10, Windows 8, Windows 7, Windows Vista, Windows XP (SP2+), Windows Server 2003 (SP1+), Windows Server 2008 (32 and 64-bit), Windows Server 2008 R2 (64-bit); Mac OS X v10.6, 10.7; For the latest operating system support see: Citrix and Windows Terminal Services (http://www.hp.com/go/upd); Novell (http://www.novell.com/iprint); Linux (http://www.hplip.net); UNIX (http://www.hp.com/go/unix, http://www.hp.com/go/unixmodelscripts, http://www.hp.com/go/jetdirectunix_software); SAP device types (http://www.hp.com/go/sap/drivers, http://www.hp.com/go/sap/print); HP ePrint Mobile Driver (http://www.hp.com/go/eprintmobiledriver)

Connectivity, optional

802.11b/g/n wireless LAN (station mode), other networking accessories, HP Jetdirect 2700w USB Wireless Print Server

Connectivity, standard

2 Hi-Speed USB 2.0; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000 Base-T; 1 Hi-Speed USB 2.0 Easy Access Walkup Port; 1 Hardware Integration Pocket (HIP)

Control panel

2-in, 4-line LCD (color text and graphics); job control buttons; LED status indicators; 10-button keypad, Hardware Integration Pocket; easy access USB

Count of cartons per pallet layer

1

Count of layers in pallet

2

Country of origin Made in China

Datasheet photo 1

Publication photos/IPG_HW_M712dn.jpg

Datasheet photo 4

Publication photos/LJ Ent 700 M712 wkp.jpg

Display

2-in, 4-line LCD (color text and graphics)

Driver updates

Current HP printer drivers and software for all supported operating systems can be obtained from HP Support Web site, hp.com/go/lj700M712_software

Duplex printing

Manual (driver support provided)

Duty cycle (monthly, A4)

Up to 100,000 pages

Duty cycle (monthly, letter)

Up to 100,000 pages

Duty cycle footnote number

[2]

Duty cycle note

Duty cycle is defined as the maximum number of pages per month of imaged output. This value provides a comparison of product robustness in relation to other HP LaserJet or HP Color LaserJet devices, and enables appropriate deployment of printers and MFPs to satisfy the demands of connected individuals or groups.

Eco label

ENERGY STAR® qualified

Electromagnetic compatibility

CISPR 22:2008 / EN 55022:2010 (Class A); EN 61000-3-2 :2006 +A1:2009 +A2:2009; EN 61000-3-3 :2008; EN 55024:1998 +A1 +A2; FCC Title 47 CFR, Part 15 Class A(USA); ICES-003, Issue 4 (Canada); other EMC approvals as required by individual countries

Energy efficiency

CECP, Taiwan Green Mark

Energy savings feature technology

HP Auto-On/Auto-Off Technology; Instant-on Technology

Envelope Feeder

No

FCC Class A emissions

FCC Class A emissions - for use in commercial environments, not residential environments

Finished output handling

Sheetfed

First page out black (A4, ready) As fast as 10.5 sec

First page out black (letter, ready)

As fast as 10.5 sec

First page out black (letter, sleep) As fast as 23.5 sec

Functions Print

HP ePrint capability Yes

Image legal disclaimer

Product image may differ from actual product

Input capacity

Up to 600 sheets

Internal Storage None

NULLE

Left margin (A4)

2 mm

Legal disclaimer

© Copyright 2012 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. ENERGY STAR and the ENERGY STAR logo are registered U.S. marks. Windows is a registered trademark of Microsoft Corporation. AirPrint, iPad, iPhone, and iPod touch are trademarks of Apple Inc., registered in the U.S. and other countries.

Mac compatible

Yes

Maximum dimensions (W x D x H)

33.8 x 38.9 x 15.4 in

Maximum dimensions (W x D x H)

858 x 989 x 392 mm

Maximum input capacity (sheets)

Up to 4600 sheets (CF239A (1x) and CF243A can be installed together; no other input accessories can be combined)

Maximum Memory

1 GB

Maximum metric depth 989

Maximum metric height

392

Maximum metric width 858

Maximum output capacity (sheets)

Up to 250 sheets

Media size, tray 1

A3; A4; A5; B4 (JIS); B5 (JIS); 76.2 x 127 to 312 x 469.9 mm

Media size, tray 2

A4; A5;, B4 (JIS); B5 (JIS); 148 x 210 to 297 x 363 mm

Media size, tray 3

A3; A4; A5; B4 (JIS); B5 (JIS); 148 x 210 to 297 x 431 mm

Media sizes supported

Tray 1, 2: A3; A4; A5; B4 (JIS); B5 (JIS); Tray 3: A3; A4; A5; B4 (JIS); B5 (JIS)

Media sizes supported

Tray 1: Letter, legal, executive, 8.5 x 13 in, 11 x 17 in; Tray 2: Letter, legal, executive, 8.5 x 13 in; Tray 3: letter, legal, executive, 8.5 x 13 in, 11 x 17 in

Media sizes supported, key

A4; A3

Media sizes supported, key Letter; Legal; 11 x 17 in

Media sizes, custom

Tray 1: 3 x 5 to 12.3 x 18.5 in; Tray 2: 5.8 x 8.3 to 11.7 to 14.3 in; Tray 3: 5.8 x 8.3 to 11.7 to 17 in

Media sizes, custom

Tray 1: 76.2 x 127 to 312 x 469.9 mm; Tray 2: 148 x 210 to 297 to 363 mm; Tray 3: 148 x 210 to 297 to 431 mm

Media type and capacity, tray 1

Sheets: 100; envelopes: 10; labels: 100; transparencies: 100; postcards: 10

Media type and capacity, tray 2 Sheets: 250

Media type and capacity, tray 3

sheets: 250

Media types

Paper (color, letterhead, light, plain, preprinted, prepunched, recycled, rough, tough paper), bond, cardstock, envelope, labels, transparency, vellum

Media weight (tray 1)

60 to 199 g/m²

Media weight (tray 2) 60 to 120 g/m²

00 t0 120 g/m-

Media weight (tray 3)

60 to 120 g/m²

Media weight, supported

Tray 1: 16 to 53 lb; Tray 2, 3: 16 to 32 lb

Media weight, supported

Tray 1: 60 to 199 g/m²; Tray 2, 3: 60 to 120 g/m²

Memory

512 MB

Memory Slots

One 144 pin DDR2 DIMM slot

Memory upgrade

Expandable to 1 GB through 1 industry-standard DIMM slot

Metric depth 585

Metric height 392

Metric width

Minimum dimensions (W x D x H) 22.4 x 23.4 x 15.4 in

22.4 X 23.4 X 13.4 III

Minimum dimensions (W x D x H)

568 x 585 x 392 mm

Minimum System Requirements

Windows 10, Windows 8, Windows 7, Windows Vista, Windows XP (SP2+), Windows Server 2003 (SP1+), Windows Server 2008, Windows Server 2008 R2; 200 MB available hard disk space; operating system compatible hardware system requirements, see http://www.microsoft.com

Minimum System Requirements for Macintosh

Mac OS X v10.6, 10.7; 200 MB available hard disk space; operating system compatible hardware system requirements, see apple.com

Mobile printing capability

HP ePrint; Apple AirPrint[™]; Mopria[™]-certified

Network capabilities

Yes, via HP Jetdirect Ethernet embedded print server (standard) supports: 10Base-T, 100Base-Tx, 1000Base-T; 802.3az (EEE) support on Fast Ethernet and Gigabit Ethernet; IPsec (standard); 802.11b/g/n wireless networking (optional)

Network protocols, supported

IPv4/IPv6: Apple Bonjour Compatible (Mac OS v10.2.4 or higher), SNMPv1/v2c/v3, HTTP, HTTPS, FTP, TFTP, Port 9100, LPD, WS Discovery, IPP, Secure-IPP, IPsec/Firewall; IPv6: DHCPv6, MLDv1, ICMPv6; IPv4: Auto-IP, SLP, Telnet, IGMPv2, BOOTP/DHCP, WINS, IP Direct Mode, WS Print

Network ready

Standard (built-in Gigabit Ethernet)

Non-Operating Humidity Range

10 to 90% RH

Number of print cartridges

1 (black)

Number of users

10-30 Users

Operating humidity range

20 to 80% RH

Operating system (supported note)

Windows Installer has the same Operating System support as the driver except the following: Windows XP[®] SP2+ (32-bit only); Windows[®] Server 2003 SP1+ (32-bit only); Windows Vista[®] Starter not supported in Driver nor Installer

Operating temperature range

10 to 32.5°C

Operating temperature range

50 to 91ºF

Output capacity

Up to 250 sheets

Package dimensions (W x D x H)

31.9 x 30.9 x 25.4 in

Package dimensions (W x D x H)

810 x 785 x 644 mm

Package weight 41.8 kg

Package weight

91.9 lb

Page yield footnote

Declared yield value for black cartridge in accordance with ISO/IEC 19752. Actual yields vary considerably based on images printed and other factors. For more information, visit hp.com/go/learnaboutsupplies

Pallet dimensions

32.5 x 31.5 x 82 in

Pallet dimensions (W x D x H)

825 x 800 x 2082 mm

Pallet weight

148.1 kg

Pallet weight

325.8 lb

Paper handling input, optional

Optional 500-sheet input tray, optional 1 x 500-sheet paper feeder with cabinet and stand, optional 3 x 500-sheet paper feeder with stand, optional 3500-sheet high capacity input tray with stand

Paper handling input, standard

100-sheet multipurpose tray, 2 x 250-sheet input trays

Paper handling output, standard

250-sheet output bin

Paper trays, maximum

6

Paper trays, standard

3

Ports

1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000 Base-T; 1 Hi-Speed USB 2.0 Easy Access USB; 1 Hardware Integration Pocket (HIP)

Power

Input voltage: 110 to 127 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz)

Power consumption

786 watts (Printing), 22.1 watts (Ready), 6.1 watts (Sleep), 0.21 watts (Off)

Power consumption Note

Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages; this will damage the printer and void the product warranty. Values subject to change, see hp.com/support for current information.

Power supply type

Built-in power supply

Print colors

No

Print languages

HP PCL 6, HP PCL 5, HP postscript 3 emulation, native PDF printing (v 1.4)

Print quality black (best)

Up to 1200 x 1200 dpi

Print quality black (normal) HP FastRes 1200 (1200 dpi effective quality), 600 dpi with HP Resolution Enhancement technology

Print Resolution Technologies

HP ProRes 1200, HP FastRes 1200, HP REt, 600 dpi, 300 dpi

Print speed

Print speed up to 41 ppm (black)

Print speed (A4/letter) footnote number

[1]

Print speed black (ISO, A4)

Up to 41 ppm

Print speed black (ISO, letter)

Up to 40 ppm

Print speed black (normal, A3) Up to 20 ppm

Print speed black (normal, tabloid)

Up to 20 ppm

Print speed duplex (A4)

Up to 26 ipm

Print speed duplex (letter) Up to 26 ipm

Print speed footnote

Measured using ISO/IEC 24734, excludes first set of test documents. For more information see hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.

Print technology

Laser

Print Technology

Laser

Printer Management

HP Web Jetadmin. HP Utility (Mac)

Printer smart software features

HP ePrint, Apple AirPrint[™], Mopria-certified, HP Auto On/Auto Off technology, FutureSmart Firmware, Hardware Integration Pocket, Easy Access USB

Processor speed

800 MHz

Product note

FCC Class A emissions device for use in commercial environments, not residential environments[11]

Quantity per pallet

Recommended monthly page volume

5000 to 20,000

Recommended monthly page volume footnote number

[3]

Recommended monthly page volume note

HP recommends that the number of printed pages per month be within the stated range for optimum device performance, based on factors including supplies replacement intervals and device life over an extended warranty period.

Recommended operating humidity range

30 to 70% RH

Recommended operating temperature range

10 to 32.5ºC

Recommended operating temperature range

50 to 91ºF

Replacement cartridges

HP 14A Black Laser Jet Toner Cartridge (~10,000 yield) CF214A; HP 14X Black Laser Jet Toner Cartridge (~17,500 yield) CF214X

Right margin (A4)

2 mm

RMN number

BOISB-1105-00

Safety

IEC 60950-1:2005 +A1; EN60950-1: 2006 +A11:2009 +A1:2010 +A12:2011; IEC 60825-1:2007 (Class 1 Laser/Led Product); EN 60825-1:2007 (Class 1 Laser/LED Product); UL/cUL Listed (USA/Canada); IEC 62479:2010; EN 62479:2010; other safety approvals as required by individual countries

Security management

Management security: SNMPv3, SSL/TLS, WPA2-Enterprise, 802.1X authentication (EAP- PEAP, EAP-TLS), IPP over TLS, IPsec/Firewall with Certificate, Pre-Shared Key Authentication, and Kerberos Authentication; Support for WJA-10 IPsec Configuration using IPsec Plug-in

Services

Assembly, network configuration, and basic administrator familiarization

Services

Onsite replacement of your printer's maintenance kit including parts, materials, and labor

Services

Onsite service the next business day after the service call is received

Services

Onsite support within four hours after a service call received within the coverage window

Services (Care Pack)

HP 2-year Next Business Day HW Support U6Y95E; HP 3-year Next Business Day HW Support U6Y96A; HP 3year Next Business Day HW Support U6Y96E; HP 4-year Next Business Day HW Support U6Y97E; HP 5-year Next Business Day HW Support U6Y98E; HP 3-year 4h 9x5 HW Support U6Y99E; HP 3-year 4h 13x5 HW Support U6Z00E; HP 4-year 4h 9x5 HW Support U6Z01E; HP 4-year 4h 13x5 HW Support U6Z02E; HP 5-year 4h 9x5 HW Support U6Z03E; HP 5-year 4h 13x5 HW Support U6Z04E; HP 3-year Next Business Day with DMR Support U6Z05E; HP 4-year Next Business Day with DMR Support U6Z06E; HP 5-year Next Business Day with DMR Support U6Z07E: HP 3-year Next Business Day Channel Remarket Printer Support U6Z11E: HP 4-year Next Business Day Channel Remarket Printer Support U6Z12E; HP 5-year Next Business Day Channel Remarket Printer Support U6Z13E; HP 3-year Next Business Day Call-to-Repair with DMR Support U6Z14E; HP 4-year Next Business Day Call-to-Repair with DMR Support U6Z15E; HP 5-yearr Next Business Day Callto-Repair with DMR Support U6Z16E; HP 3-year Second Business Day Call-to-Repair with DMR Support U6Z17E; HP 4-year Second Business Day Call-to-Repair with DMR Support U6Z18E; HP 5-year Second Business Day Call-to-Repair with DMR Support U6Z19E; HP 1-year Post Warranty Next Business Day HW Support U6Z20PA; HP 1-year Post Warranty Next Business Day HW Support U6Z20PE; HP 2-year Post Warranty Next Business Day HW Support U6Z21PE; HP 1-year Post Warranty 4h 9x5 Support U6Z22PE; HP 1-year Post Warranty 4h 13x5 Support U6Z23PE; HP 1-year Post Warranty Next Business Day with DMR Support U6Z24PE; HP 1-year Post Warranty Channel Remarket Printer Support U6Z26PE; HP 1-year Post Warranty Next Business Day Call-to-Repair with DMR HW Support U6Z27PE; HP 1-year Post Warranty Second Business Day Call-to-Repair with DMR HW Support U6Z28PE

Services description headline 01

Onsite Support:

Services description headline 02 Next Business Day Onsite Support:

Services description headline 03

Maintenance Kit Replacement Service:

Services description headline 04

Installation with Network Configuration Service:

Software included

Windows Installer, HP PCL 6 discrete driver, Mac Installer, HP Postscript emulation driver

Standard input capacity (envelopes) Up to 10 envelopes

Standard output capacity (envelopes)

Up to 50 envelopes

Standard output capacity (transparencies)

Up to 250 sheets

Storage device and direct print support

Front-facing USB/Flash drive

Storage temperature range

0 to 60ºC

Storage temperature range 32 to 140°F

SureSupply note

HP SureSupply alerts you when your print cartridge is running low and helps you purchase online or locally through HP or a participating retailer. For more information, visit hp.com/go/SureSupply; only available with Original HP supplies; Internet access required.

SureSupply supported

Yes

Target user and print volume

For teams over 25 users; Prints up to 20,000 pages/month

Tariff numbers

8443321010

Tech spec footnote

[1] Measured using ISO/IEC 24734, excludes first set of test documents. For more information see hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.

Tech spec footnote

[2] Duty cycle is defined as the maximum number of pages per month of imaged output. This value provides a comparison of product robustness in relation to other HP LaserJet or HP Color LaserJet devices, and enables appropriate deployment of printers and MFPs to satisfy the demands of connected individuals or groups.

Tech spec footnote

[3] HP recommends that the number of printed pages per month be within the stated range for optimum device performance, based on factors including supplies replacement intervals and device life over an extended warranty period.

Tech spec footnote

[4] Acoustic values are subject to change. For current information see hp.com/support. Configuration tested: M712dn model, simplex printing, A4 paper at an average of 41 ppm.

Tech spec footnote

[5] Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages; this will damage the printer and void the product warranty. Values subject to change, see hp.com/support for current information.

Top key features

Front-facing USB printing

Top margin (A4)

2 mm

Tray capacity 600

Typical electricity consumption (TEC) number

3.289 kWh/Week

UNSPSC code

43212105

UPC number

(AB0) 886112999445; (AB1) 886112999452; (AB2) 886112999469; (ABJ) 886112999476; (ABT) 886112999513; (ABY) 886112999520; (ACJ) 886112999483; (ACQ) 886112999537; (B19) 886112999544; (BAZ) 886112999551; (BBU) 886112999490; (BGJ) 886112999568; (BGM) 886112999506

Warranty

One-year, next-business day, onsite warranty. Warranty and support options vary by product, country and local legal requirements. Go to http://www.hp.com/support to learn about HP award winning service and support options in your region.

Weight

34.7 kg

Weight

76.5 lb

What's in the box

HP Laser Jet Enterprise 700 M712n Printer (includes built-in HP Jetdirect Gigabit Ethernet embedded print server); HP Black Laser Jet Toner Cartridge (~10,000 pages); Getting Started Guide; CD containing drivers and electronic documentation; Power cord

Wireless capability

Optional, enabled with purchase of a hardware accessory

© Copyright 2012 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing shall be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.