

HP LaserJet Pro M501dn (J8H61A)

Active as of 4/1/2016

Detailed Specifications

Accessories

F2A72A HP LaserJet 550-sheet Paper Tray

Acoustic power emissions (active, printing)

6.8 B(A)

Acoustic power emissions (ready)

4.0 B(A)

Acoustic power footnote number

[8]

Acoustic pressure emissions bystander (active, printing)

54 dB(A)

Acoustic pressure emissions bystander (ready)

25 dB(A)

Automatic paper sensor

No

Best technical electricity consumption (TEC)

1.569 kWh/Week

Best technical electricity consumption (TEC) footnote

[6]

Blue Angel (sleep mode)

1.18 W

Blue Angel compliant

Yes, Blue Angel DE-UZ 205—only ensured when using Original HP supplies

Bottom margin (A4)

5.0 mm

Cable included

No, please purchase USB cable separately

Code name

Bigeye

Compatible Network Operating Systems

Windows OS compatible with In-Box Driver; Windows Server 2003/2003 R2 32-bit (SP1/SP2) Standard/Enterprise (+ Cluster & Terminal Services), Windows Server 2008 32-/64-bit (SP2) Standard/Enterprise (+ Cluster & Terminal Services), Windows Server 2008 R2 64-bit (SP1) Standard/Enterprise (+ Cluster & Terminal Services; Windows OS compatible with Universal Print Driver (UPD) or Product-Specific drivers from HP.com; Windows Server 2003/2003 R2 32-/64-bit (SP1/SP2) Standard/Enterprise/Datacenter (+ Cluster & Terminal Services), Windows Server 2008/2008 R2 32-/64-bit (SP1/SP2) Standard/Enterprise/Datacenter (+ Cluster & Terminal Services), Windows Server 2012/2012 R2 64-bit Standard/Foundation/Essentials/Datacenter (+ Cluster & Terminal Services); Citrix (on Windows Server 2003/2003R2), Citrix MetaFrame Presentation Server, 3.0, Citrix MetaFrame XP Presentation Server (Feature Release 1, 2, and 3), Citrix Presentation Server 4.0/4.5, Citrix XenApp 5.0 (Plus Feature Pack 2 & 3), Citrix (on Windows Server 2008/2008R2, Citrix XenApp 5.0 (Plus Feature Pack 2 & 3), Citrix XenApp 6.0/6.5/7.5, Citrix XenDesktop 5.6/7.0/7.5, Citrix (on Windows Server 2012/2012R2, Citrix XenApp 7.5, Citrix XenDesktop 7.0/7.5; Novell Servers; www.novell.com/iprint), Novell iPrint Appliance v1.0, Novell Open Enterprise Server 11/SP1, Novell Open Enterprise Server 2 for Linux, NetWare 6.5/SP8, Novell Clients (www.novell.com/iprint; Windows 8 (32-bit / 64-bit) recommend v5.86+, 8.1 recommend v5.94+, Windows 7 (32-bit / 64-bit) recommend v5.82+, Windows Vista (32-bit / 64-bit) recommend v5.82+, Windows XP /

Compatible Operating Systems

Windows OS compatible with In-Box Driver; Windows XP SP3 all 32-bit editions (XP Home, XP Pro, etc.), Windows Vista all 32-bit editions (Home Basic, Premium, Professional, etc.), Windows 7 all 32- & 64-bit editions, Windows 8/8.1 all 32- & 64-bit editions (excluding RT OS for Tablets), Windows 10 all 32- & 64-bit editions (excluding RT OS for Tablets); Windows OS compatible with Universal Print Driver (From HP.com); Windows XP SP3 32- & 64-bit editions (XP Home, XP Pro, etc.), Windows Vista all 32- & 64-bit editions (Home Basic, Premium, Professional, etc.), Windows 7 all 32- & 64-bit editions, Windows 8/8.1 all 32- & 64-bit editions (excluding RT OS for Tablets); Windows 10 all 32- & 64-bit editions (excluding RT OS for Tablets); Mac OS (HP Print Drivers available from HP.com and Apple Store); OS X 10.9 Mavericks, OS X 10.10 Yosemite, OS X 10.11 El Capitan; Mobile OS (In-OS drivers); iOS, Android, Windows 8/8.1/10 RT; Linux OS (In-OS HPLIP; SUSE Linux (12.2, 12.3, 13.1), Fedora (17, 18, 19, 20), Linux Mint (13, 14, 15, 16, 17), Boss (3.0, 5.0), Ubuntu (10.04, 11.10, 12.04, 12.10, 13.04, 13.10, 14.04, 14.10), Debian (6.0.x, 7.x); Other OS; UNIX

Connectivity, standard

Hi-Speed USB 2.0 Host/Device Ports; Fast Ethernet 10Base-T/100Base-Tx, Gigabit Ethernet 1000Base-T

Control panel

2-line; backlit text display; 6 buttons (Cancel job, Up arrow, Down arrow, Select, Back, Settings) and 12 key numerical

Count of cartons per pallet layer

6

Count of layers in pallet

5

Country of origin

J8H61A#696 - Made in Brazil

Datasheet photo 1

Publication photos/M501dn.jpg

Datasheet photo 4

Publication photos/M501_walkaround.jpg

Datasheet publication number

4AA6-4221ENUC

Dimension(W x D x H) Footnote Number

[2]

Display

2-line LCD (text)

Display area (imperial)

 $1.8 \times 0.5 in$

Display area (metric)

46 x 12.5 mm

Downloadable software

From 123.hp.com; HP Easy Start (Guided Software Install for Windows OS and Mac); From HP.com for Windows OS; Full-solution software and drivers (Same solution as "Software Included"); HP PCL6 print driver only (No installer for "Add Printer" installs), HP PCL6 print driver with installer, Product Documentation and Support; From HP.com for Mac OS; Full-solution software and drivers; For Mobile OS; (See "HP Mobile Printing" http://www8.hp.com/us/en/ads/mobility/overview.html); From In-OS app stores; HP recommended printer drivers and software; http://www.HP.com for printer administrators, Printer Administrator Resource Kit (Driver Configuration Utility, Driver Deployment Utility, Managed Printing Administrator), HP Universal Print Drivers (PCL6 & PS for Windows), HP ePrint Software (ePrint Mobile Driver for Windows), Linux/Unix Print Drivers, SAP (PS Print Drivers), HP Web JetAdmin Software, HP Proxy Agent Software, HP JetAdvantage Security Manager, HP Imaging and Printing Security Center

Driver updates

From 123.hp.com: HP Easy Start (Guided Software Install for Windows and Mac); From HP.com for Windows OS: Full-solution software and drivers (Same solution as "Software Included"), HP PLC 6 print driver only (No installer; for "Add Printer" installs), HP PCL 6 print driver with installer, Product Documentation and Support; From HP.com for Mac OS: Full-solution software and drivers; For Mobile OS: See "HP Mobile Printing" (http://www8.hp.com/us/en/ads/mobility/overview.html); From In-OS app stores: HP recommended printer drivers and software; From HP.com for printer administrators: Printer Administrator Resource Kit (Driver Configuration Utility, Driver Deployment Utility, Managed Printing Administrator), HP Universal Print Drivers

(PCL6, PCL5 & PS for Windows), HP ePrint Software (ePrint Mobile Driver for Windows), Linux/Unix Print Drivers, SAP (PCL 5 and PS Print Drivers), HP Web JetAdmin Software, HP Proxy Agent Software, HP JetAdvantage Security Manager.

Duplex printing

Automatic

Duty cycle (monthly, A4)

Up to 100,000 pages

Duty cycle (monthly, letter)

Up to 100,000 pages

Duty cycle footnote number

[13]

Electromagnetic compatibility

CISPR 22:2008 (International) - Class A, EN 55022: 2010 (EU) - Class A, EN 61000-3-2: 2006 +A1: 2009 +A2: 2009, EN 61000-3-3: 2008, EN 55024: 2010, EMC Directive 2004/108/EC; FCC CFR 47 Part 15 Class A / ICES-003, Issue 5 Class A, Other EMC approvals as required by individual countries

Energy efficiency

ENERGY STAR® qualified; EPEAT® Silver; CECP; Taiwan Green Mark

Energy efficiency compliance footnote number

[1]

Energy savings feature technology

HP Auto-Off Technology; HP Auto-On/Auto-Off Technology; Instant-on Technology; Low-power sleep mode

Energy star certified

Yes

Envelope Feeder

No

Environmental

ENERGY STAR® certified; EPEAT® rated

FCC Class A emissions

FCC Class A emissions - for use in commercial environments, not residential environments

Finished output handling

Sheetfed

First page out black (A4, ready)

As fast as 5.8 sec

First page out black (A4, sleep)

As fast as 7.2 sec

First page out black (letter, ready)

As fast as 5.7 sec

First page out black (letter, sleep)

As fast as 7.3 sec

First page out footnote number

[12]

Fonts and typefaces

84 scalable TrueType fonts

Functions

Print

HP ePrint capability

Yes

Image legal disclaimer

Product image may differ from actual product

Input capacity

650

Left margin (A4)

5.0 mm

Legal disclaimer

© Copyright 2016 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. ENERGY STAR and the ENERGY STAR logo are registered U.S. marks. Windows is a registered trademark of Microsoft Corporation. AirPrint, iPad, iPhone, and iPod touch are trademarks of Apple Inc., registered in the U.S. and other countries.

Mac compatible

Yes

Maximum dimensions (W x D x H)

16.46 x 25.16 x 11.38 in

Maximum dimensions (W x D x H)

418 x 639 x 289 mm

Maximum input capacity (sheets)

1200

Maximum Memory

256 MB

Maximum output capacity (sheets)

Up to 250 sheets

Media size, tray 1

Tray 1: 10 x 15 cm, 16k (184 x 260 mm), 16k (195 x 270 mm), 16k (197 x 273 mm), A4, A5, A6, Envelope B5, Envelope C5, Custom, Envelope DL, B5 (JIS), B6 (JIS), Japanese Postcard, Double Japan Postcard Rotated, Oficio (216 x 340 mm)

Media size, tray 2

Tray 2: 16k (184 x 260 mm), 16k (195 x 270 mm), 16k (197 x 273 mm), A4, A5, A6, Custom, B5 (JIS), B6 (JIS), Double Japan Postcard Rotated, Oficio (216 x 340 mm)

Media size, tray 3

Tray 3: 16k (184 x 260 mm), 16k (195 x 270 mm), 16k (197 x 273 mm), A4, A5, A6, Custom, B5 (JIS), B6 (JIS), Double Japan Postcard Rotated, Oficio (216 x 340 mm)

Media sizes supported

Tray 1: 10×15 cm, 16k (184×260 mm), 16k (195×270 mm), 16k (197×273 mm), A4, A5, A6, Envelope B5, Envelope C5, Custom, Envelope DL, B5 (JIS), B6 (JIS), Japanese Postcard, Double Japan Postcard Rotated, Oficio (216×340 mm); Tray $2 \times 16k$ (184×260 mm), 16k (195×270 mm), 16k (197×273 mm), 197×273

Media sizes supported

Tray 1: 4×6 in, 5×8 in, Letter, Legal, Executive, Oficio 8.5 $\times 13$ in, Envelope No. 10, Monarch, Custom; Tray 2 & Tray 3: 5×8 in, Letter, Legal, Executive, Oficio 8.5 $\times 13$ in, Custom

Media sizes supported, key

10 x 15 cm; A4; Envelopes

Media sizes supported, key

4 x 6 in; Letter; Legal; Envelopes

Media sizes, custom

Tray 1: 3 x 5 to 8.5 x 14 in; Tray 2 & Tray 3: 4.14 x 5.83 to 8.5 x 14 in

Media sizes, custom

Tray 1: 76.2 x 127 mm to 215.9 x 355.6 mm; Tray 2 & Tray 3: 105 x 148 mm to 215.9 x 355.6 mm

Media type and capacity, tray 1

100 sheets of 20-lb cut sheet paper, 10 envelopes

Media type and capacity, tray 2

550 sheets of 20-lb cut sheet paper

Media type and capacity, tray 3

550 sheets of 20-lb cut sheet paper

Media types

Paper (plain, EcoFFICIENT, light, midweight, intermediate, heavy, extra heavy, bond, cardstock, colored, letterhead, preprinted, prepunched, recycled, rough, ecofficient); envelopes; labels; transparencies

Media weight (tray 1)

60 to 200 g/m²

Media weight (tray 2)

60 to 120 g/m²

Media weight, supported

Tray 1: 16 to 58 lb bond; Tray 2 & Tray 3: 16 to 32 lb bond

Media weight, supported

Tray 1: 60 to 200 g/m²; Tray 2 & Tray 3: 60 to 120 g/m²

Memory

256 MB

Minimum dimensions (W x D x H)

16.46 x 14.80 x 11.38 in

Minimum dimensions (W x D x H)

418 x 376 x 289 mm

Minimum System Requirements

Compatible OS (see "Compatible Operating Systems"); CD-ROM drive or Internet connection (for software installation); dedicated USB connection or a network connection (wired or wireless); 1 GB available harddisk space; (For operating system minimum hardware requirements, see the OS manufacturer, such as microsoft.com)

Minimum System Requirements for Macintosh

Compatible OS (see "Compatible Operating Systems"); Internet connection (for software installation); dedicated USB connection or a network connection (wired or wireless); 1 GB available harddisk space; (For operating system minimum hardware requirements, see the OS manufacturer, such as Apple.com)

Mobile printing capability

HP ePrint; Apple AirPrint™; Mopria™-certified

Network capabilities

Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X

Network protocols, supported

TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Web Services Printing, HP ePrint, Apple AirPrint™, Google Cloud Print 2.0, Mopria, FTP Print, IPP Print; Discovery: SLP, Bonjour, Web Services Discovery; IP Config: IPv4 (BootP, DHCP, AutoIP, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; management: SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download

Network ready

Standard (built-in Gigabit Ethernet)

Non-Operating Humidity Range

10 to 90% RH

Number of print cartridges

1 (black)

Number of users

5-15 Users

Operating humidity range

10 to 80% RH

Operating system supported footnote number

[17]

Operating temperature range

15 to 32.5ºC

Operating temperature range

59 to 90.5ºF

Orderable product number

J8H61A#ABO, J8H61A#AB2, J8H61A#ABJ, J8H61A#ACJ, J8H61A#BBU, J8H61A#BGM, J8H61A#ABT, J8H61A#ABY, J8H61A#ACQ, J8H61A#B13, J8H61A#B19, J8H61A#BAZ, J8H61A#696, J8H61A#AC8, J8H61A#AKV, J8H61A#BGJ

Orderable supplies

CF287A HP 87A Black Original LaserJet Toner Cartridge; CF287X HP 87X High Yield Black Original LaserJet Toner Cartridge

Output capacity

Up to 250 sheets

Package dimensions (W x D x H)

19.6 x 15.7 x 18.4 in

Package dimensions (W x D x H)

497 x 398 x 466 mm

Package weight

14.5 kg

Package weight

32.1 Lb

Pallet dimensions

47.2 x 39.4 x 97.7 in

Pallet dimensions (W x D x H)

1200 x 1000 x 2481 mm

Pallet weight

1006.9 Lb

Pallet weight

456.7 kg

Paper handling input, optional

Optional 550-sheet cassette tray (Tray 3)

Paper handling input, standard

100-sheet multipurpose tray and 550-sheet main cassette

Paper handling note number

[16]

Paper handling output, standard

250-sheet face down output tray

Paper trays, maximum

3: 2 x 550 cassettes and 1 x 100-sheet multipurpose tray

Paper trays, standard

2: 1 x 550 cassette and 1 x 100-sheet multipurpose tray

Photo (product photo, jpg, 190x170)

Printers and Multifunction/M501_190x170.jpg

Ports

Hi-Speed USB 2.0 Host/Device Ports; Fast Ethernet 10Base-T/100Base-Tx, Gigabit Ethernet 1000Base-T

Post warranty repair & maintenance

Please consult http://www.hp.com/support for details

Power

Input voltage: 100 to 127 VAC, 60 Hz; Input voltage: 200 to 240 VAC, 50 Hz (Not dual voltage, power supply varies by part number with #option code identifier)

Power consumption

660 watts (active printing), 6.1 watts (ready), 1.3 (sleep), 0.7 watts (Auto-Off/wake on USB connection, disabled at shipment) 0.1 watts (Auto-Off/Manual-On), 0.1 watts (Manual-Off)

Power consumption footnote number

[4]

Power supply type

Internal (Built-in) power supply

Print colors

No

Print languages

HP PCL 5, HP PCL 6, HP postscript level 3 emulation, direct PDF (v 1.7) printing, URF, PCLM, PWG

Print quality black (best)

600 x 600 dpi, Up to 4800 x 600 enhanced dpi

Print quality black (normal)

600 x 600 dpi, Up to 4800 x 600 enhanced dpi

Print resolution black (fine lines)

Up to 1200 x 1200 dpi

Print Resolution Technologies

HP FastRes 1200, HP ProRes 1200, 600 dpi

Print speed

Print speed up to 45 ppm (black)

Print speed (A4/letter) footnote number

[10]

Print speed black (ISO, A4)

Up to 43 ppm

Print speed black (ISO, letter)

Up to 45 ppm

Print speed black (Landscape, A5)

Up to 66 ppm

Print speed duplex (A4)

Up to 34 ipm

Print speed duplex (letter)

Up to 36 ipm

Print speed footnote number (A5)

[11]

Print technology

Laser

Print Technology

Laser

Printer Management

UPD Printer Administrator Resource Kit; Active Directory Administrator Template for UPD, AutoUpgradeUPD, Driver configuration Utility, Driver Deployment Utility, Managed Print Administrator, PRNCON.EXE, HPPRLOG, Migrate-Server-Tools, UpdateNow, RemovePlugPlayDrivers; HP Web JetAdmin Software, HP Proxy Agent Software, HP JetAdvantage Security Manager, HP Utility (Mac), HP Device Toolbox

Printer smart software features

Auto-duplex printing, N-up printing, collation, HP ePrint, Apple AirPrint™, Google Cloud Print, Mopria-certified, HP Auto-On/Auto-Off, 2-line LCD control panel, Built-in Job Storage, JetIntelligence Cartridge Technology

Processor speed

1500 MHz

Product logos

Microsoft Windows (7, 8 and 10), Apple Mac, Energy Star, ePrint, AirPrint

Product long name specifications

HP LaserJet Pro M501 series

Product note

FCC Class A emissions - for use in commercial environments, not residential environments [11]

Quantity per pallet

30

Recommended media weight (duplex)

16 to 46.6 lb bond

Recommended media weight (duplex)

60 to 175 g/m²

Recommended monthly page volume

1500 to 6000

Recommended monthly page volume footnote number

Recommended operating humidity range

30 to 70% RH

Recommended operating temperature range

17.5 to 25°C

Recommended operating temperature range

63.5 to 77ºF

Replacement cartridges

HP 87A Black Original LaserJet Toner Cartridge (~8,550 yield) CF287A, HP 87X Black Original LaserJet Toner Cartridge (~18,000 yield) CF287X

Replacement cartridges footnote number

[7]

Right margin (A4)

5.0 mm

RMN number

BOISB-1403-02

Safety

IEC 60950-1:2005 +A1:2009 +A2:2013 (International); EN60950-1:2006 +A11:2009 +A1:2010 +A12:2011 +A2:2013 (EU); EN 60825-1:2007 / IEC 60825-1:2007 (Class 1 Laser Product); EN 62479:2010 / IEC 62479:2010; Low Voltage Directive 2006/95/EC with CE Mark (Europe); GS Certificate (Germany, Europe); UL/cUL Listed and UC CoC (US/Canada); CAN/CSA C22.2 No. 60950-1-07 2nd Ed. 2011-12 Compliance with Laser safety standards 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser notice No. 50, Dated June 24, 2007; Other safety approvals as required by individual countries

Security management

Embedded Web Server: password-protection, secure browsing via SSL/TLS; Network: enable/disable network ports and features, SNMPv1 & SNMPv2 community password change; HP ePrint: HTTPS with certificate validation, HTTP Basic Access Authentication, SASL authentication; Firewall and ACL; SNMPv3, 802.1X, Secure Boot

Service & support options

http://support.hp.com

Services

Customers can retain their hard disk drive and keep control of sensitive data.

Services

Exchange of hardware at customers' premise the next business day, if the issue cannot be resolved remotely.

Services

Installation services that include onsite installation and network setup of printing product.

Services (Care Pack)

U9CQ0E - HP 3 year Next Business Day + Defective Media Retention LaserJet M501 Hardware Support; U9CQ1E - HP 4 year Next Business Day + Defective Media Retention LaserJet M501 Hardware Support; U9CQ2E - HP 5 year Next Business Day + Defective Media Retention LaserJet M501 Hardware Support; U9CQ4E - HP 3 year Next Business Day Exchange LaserJet M501 Service; U9CR0PE - HP 1 year Post Warranty Next Business Day+Defective Media Retention LaserJet M501 Hardware Support; UC742E - Installation for 1 Network Configuration for Personal or Workgroup printer

Services description headline 01

Next Business Day with Defective Media Retention:

Services description headline 02

Next Business Day Exchange:

Services description headline 03

Installation Service with Network Setup:

Software included

For Windows OS; HP Software Installer/Uninstaller, HP PCL 6 Printer Driver, HP Device Experience (DXP), HP Update, Product Registration Assist, HP Web Services Assist (HP Connected), Online user manuals, HP Device Toolbox, HP Product Improvement Study; For Mac OS; Welcome Screen, (Directs users to HP.com or OS App Source for LaserJet Software)

Standard input capacity (envelopes)

Standard media sizes (duplex)

A4

Standard media sizes (duplex, imperial)

Letter; Legal; 8.5 x 13 in, Oficio (8.5 x 13 in)

Standard output capacity (envelopes)

Up tp 10 envelopes

Standard output capacity (transparencies)

Up to 75 sheets

Storage device and direct print support

USB printing

Storage temperature range

-20 to 60°C

Storage temperature range

-4 to 140°F

Sub-brand name

LaserJet

Supplies feature

HP JetIntelligence Cartridge

SureSupply footnote number

[15]

SureSupply note

[15] HP SureSupply alerts you when your print cartridge is running low and helps you purchase online or locally through HP or a participating retailer. Only available with Original HP supplies; Internet access required. To learn more, visit http://www.hp.com/go/SureSupply.

SureSupply supported

Yes

Target user and print volume

For teams up to 15 users; Prints up to 6,000 pages/month

Tariff numbers

EU Base HTS 8443321090; AM Base HTS 8443321010; AP Base HTS 84433230

Tech spec footnote

[1] EPEAT® registered where applicable. EPEAT registration varies by country. See www.epeat.net for registration status by country.

Tech spec footnote

[10] Measured using ISO/IEC 24734, excludes first set of test documents. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.

Tech spec footnote

[11] Measured using ISO/IEC 24734 Feature Performance Test, excludes first set of test documents. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.

Tech spec footnote

[12] Measured using ISO/IEC 17629. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.

Tech spec footnote

[13] Duty cycle is defined as the maximum number of pages per month of imaged output. This value provides a comparison of product robustness in relation to other HP LaserJet or HP Color LaserJet devices, and enables appropriate deployment of printers and MFPs to satisfy the demands of connected individuals or groups.

Tech spec footnote

[14] HP recommends that the number of printed pages per month be within the stated range for optimum device performance, based on factors including supplies replacement intervals and device life over an extended warranty period.

Tech spec footnote

[15] HP SureSupply alerts you when your print cartridge is running low and helps you purchase online or locally through HP or a participating retailer. Only available with Original HP supplies; Internet access required. To learn more, visit http://www.hp.com/go/SureSupply.

Tech spec footnote

[16] Optional 550-sheet input tray; Optional printer stand.

Tech spec footnote

[17] Not all "Compatible Operating Systems" are supported with inbox software; Full solution software available only for Windows 7 and newer; Legacy Windows Operation Systems (XP, Vista, and equivalent servers) get print drivers only; Windows RT OS for Tablets (32-bit & 64-bit) uses a simplified HP print driver built into the RT OS; UNIX Modelscripts are available on hp.com (Modelscripts are printer drivers for UNIX operating systems); Linux systems use in-OS HPLIP software; HP Software for Mac is no longer included on the CD, but can be downloaded from hp.com - the Mac driver and Mac Utility are installed for Mac operating systems.

Tech spec footnote

[2] Includes control panel height and 4mm side handle protrusions

Tech spec footnote

[3] Includes size-A cartridge

Tech spec footnote

[4] Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty. Power consumption values typically based on measurement of 115V device.

Tech spec footnote

[6] Based on the BA TEC method with the following possible exceptions: 1 minute or less sleep delay setting, Wi-Fi disabled. Typical Electricity Consumption (TEC) rating represents the typical electricity consumed by a product during 1 week, measured in kilowatt-houes (kWh).

Tech spec footnote

[7] Declared yield value in accordance with ISO/IEC 19752 and continuous printing. Actual yields vary considerably based on images printed and other factors. For details see http://www.hp.com/go/learnaboutsupplies.

Tech spec footnote

[8] Acoustic values are subject to change. For current information see http://www.hp.com/support. Configuration tested: Simplex printing using A4 paper at 43 ppm.

Tech spec footnote

[9] 256 MB PC31600

Technical support information

http://www.hp.com/support/ljM501

Technology logo, print 1

Publication logos/AMS_EnergyStar.jpg

Technology logo, print 2

Publication logos/AMS_windows_10.jpg

Technology logo, print 3

Publication logos/AMS_Mopria.jpg

Technology logo, print 4

Publication logos/AMS_mac_hires.jpg

Technology logo, print 5

Publication logos/AMS_Epeat silver.jpg

Technology logo, print 6

Publication logos/AMS_AirPrint.jpg

Top key features

Two-sided printing

Top margin (A4)

5.0 mm

Typical electricity consumption (TEC) footnote number

[4]

Typical electricity consumption (TEC) number

1.623 kWh/Week (Blue Angel); 0.562 kWh/Week (Energy Star 3.0)

UNSPSC code

43212105

UPC number

(201) 889296258483; (ABO) 889296258421; (AB2) 889296258438; (ABJ) 889296258445; (ABT) 725184117558; (ABY) 725184117565; (ACJ) 889296258452; (ACQ) 725184117572; (B13) 725184117589; (B19) 725184117596; (BAZ) 725184117602; (BBU) 889296258469; (BGJ) 889296258506; (BGM) 889296258476

Warranty

NA/EMEA: One-year, next-business day, onsite warranty. Warranty and support options vary by product, country and local legal requirements. Go to hp.com/support to learn about HP award winning service and support options in your region; AP: One year return to bench

Web address for additional information

Solutions: http://www.hp.com/go/gsc; Fonts and IPDS Emulation: http://www.hp/com/go/laserjetfonts; Services: http://www.hp.com/services/printer; Paper: http://www.hp.com/go/paper; HP ePrint center for business apps: http://www.hp.com/go/ePrintCenter

Weight

11.6 kg

Weight

25.6 lb

Weight (imperial) footnote number

[3]

What's in the box

HP LaserJet Pro MFP M501dn; preinstalled introductory HP LaserJet Toner cartridge (Black: ~6000 pages); In-box documentation (Installation Guide, Getting Started Guide, User's Guide, Support Flyer, Warranty Guide); Printer documentation and software on CD-ROM; Software drivers and documentation on CD-ROM; Power cord

Wireless capability

No

© Copyright 2016 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing shall be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.