

# DataSheet :

## LXD2 - Thin Client

The LXD-2 thin client is the perfect desktop appliance for users that require high-end functionality, supporting dual screen and video acceleration.

LXD-2 is a powerful appliance supporting heavy in-session applications and providing full function multimedia video performance.

The combination of ultra-green platform with very low power consumption, state of the art high-reliability hardware design and unparalleled management software position it as the ultimate choice for enterprise users.

- Intel Bay Trail Series Processor Quad-Core Up to 1,83 GHz
- Support DVI-I (Dual Screen)
- Supports Six USB 2.0 ports
- Support Microsoft Windows Terminal Server 2003 / 2008 /2012
- Full Support for Citrix® HDX
- Support VMware View environments
- Xcalibur Global Management
- Wireless & VESA Mounting



# DataSheet :

## LXD2 - Thin Client

Processor	Intel Bay Trail Series Processor Quad-Core up to 1.83 GHz
Operating System	ThinX OS Linux - Windows 10 IoT
Memory	32 GB EMMC / 2 GB RAM DDR3
Input / Output ports	<p>Front Panel I / O      2 x USB 2.0 port 1 x microphone (3.5mm) ; 1 x headphone(3.5mm)</p> <p>Rear Panel I / O      4 x USB 2.0 1 x DVI-I 1 x Power button, power LED</p>
Display Support	<p>One DVI-I port</p> <p>Optional DVI-I to DVI-D plus VGA-monitor splitter cable (sold separately)</p> <p>Optional DVI-I Port to VGA (DB-15) adapter (sold separately)</p> <p>Display Data Control (DDC) for automatic setting of resolution and refresh rate</p>
Resolution	<p>Single: Up to 1920x1200 Pixels @ true color (32 bit)</p> <p>Dual: Up to 1920x1080 Pixels @ true color (24 bit)</p>
Audio	Stereo Audio Output - 3,5 mm (1/8 inch) Audio-Out Jack; 16-bit Stereo, Microphone Input - 3,5 mm (1/8 inch),
Network	RJ-45 jack 10/100/1000 Base-T Ethernet single 802.11 b/g/n
Environment	<p>Temperature range: Operating - 0°C to 40°C (32°F to 104°F)</p> <p>Storage - 0°C to 60°C (32°F to 140°F)</p> <p>Humidity: Operating - 20 to 80% non condensing; Storage – 10 to 90% non condensing Altitude: 0 to 20,000 ft</p>
Dimensions	<p>Dimensions: 152mm×107mm×31.5mm</p> <p>Device weight: 365 gr.</p>
Power	Running : 3W Maximum: 6W Standby: <1W
Security	Built-in Kensington security slot (cable sold separately)
Warranty	<p>Three-year hardware warranty</p> <p>Optional extended Warranty for years 4 &amp; 5.</p>

### FRONT SIDE VIEW

- 1 USB 2.0 ports \* 2
- 2 Power LED
- 3 Audio Out /Mic In



### REAR SIDE VIEW

- 4 DC Jack
- 5 Power Button
- 6 USB 2.0 ports \* 4
- 7 Ethernet -RJ45 LAN port
- 8 DVI-I port



Model	LXD9322W	LXD10322W
Operating System	ThinX OS	Windows 10 IoT
Flash / RAM	32G / 2G	32G / 2G
Network	RJ 45 - Wifi	RJ 45 - Wifi
VDI Connection Brokers	FreeRDP / Citrix XenDesktop / VDI-In-a-Box / HDX, VMware Horizon View w/ PCoIP	RDP 8 / Citrix XenDesktop / VDI-In-a-Box / HDX, VMware Horizon View w/ PCoIP
Part#	CPN06796	CPN06730
Management	Xcalibur Global	Xcalibur Global W