LOW PRESSURE FITTINGS ■ **POLYMERIC**

1/4-28

SPECS

■ For 1/16" and

■ Material:

Fiberglassreinforced

1/8" OD tubing

polypropylene

■ 1/4-28 threads ■ Pressure rating:

<30 bar


(435 psi)

(Varies with

tubing material and ID)







For flanged connections

- Compatible with all 1/4-28 flat-bottom ports
- For 1/16" or 1/8" OD tubing
- Fiberglass-reinforced PP with PP washers

For those systems requiring or preferring flanged connections, use these fiberglass-reinforced fittings with our Easy-Flange flanging tool and polypropylene washers to make a clean connection. The flange on the tubing ensures that the washer never comes in contact with the mobile phase.

Six colors are available.				
Tubing OD: Description	Color	Qty/pkg	1/16" Product No.	1/8" Product No.
Nuts	Green	10	JR-202123-10	JR-202143-10
	Blue	10	JR-202122-10	JR-202142-10
	Yellow	10	JR-202124-10	JR-202144-10
	Red	10	JR-202125-10	JR-202145-10


10

10

10

10





1" long nuts

10 JR-201926-10

JR-201094WH-10

JR-201094BK-10

JR-202120-10

JR-202118-10

JR-201928-10

JR-202119-10

JR-202121-10

JR-201580BK-10



White

Black

White

Black

- Through bore low pressure union
- For flanged 1/4-28 flat-bottom connections
- For 1/16" or 1/8" OD tubing
- Completely inert and biocompatible

Flanged fittings are not included.


Order PPS hex-head flanged nuts or color-coded fingertight flanged nuts separately.

Description Qty/pkg Product No. Union body, polyamide JR-060-5





TECH TIP Use our Easy-Flange kit for forming flanges on





SPECS

1/8" OD tubing

1/4-28

Polyamide ■ 1/4-28 threads





