

Dual Port Gigabit PCI Express Server Network Adapter Card - PCIe NIC

Product ID: ST1000SPEXD4



The ST1000SPEXD4 PCI Express Dual-Port Gigabit Network Card lets you add two gigabit Ethernet ports to a client, server or workstation through a single PCIe slot. Each port provides 10/100/1000 Mbps capable Ethernet and is fully compatible with IEEE 802.3/u/ab standards.

Suitable for any standard PCI Express-enabled system, the 2-port Ethernet card supports full-duplex flow control for maximum data transfer speeds of up to 2000 Mbps - an ideal 2-port NIC for setting up dual-homed, or multi-homed host configurations providing added security to corporate networks.

The dual-port server adapter is compliant with the PCIe 2.0 standard and features support for Jumbo Frames and 802.1q VLAN tagging as well as Wake on LAN (WoL). The adapter includes an optional low-profile / half-height bracket that can be used for installation into a standard or small form-factor computer chassis.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility

Applications

- Ideal for VM environments with multiple operating systems, requiring shared or dedicated NICs
- Provide redundant connectivity to ensure an uninterrupted network connection
- Configure a dual-homed proxy or gateway system for an added layer of security
- Specially designed for desktop PC clients, servers, and workstations with few PCI Express slots available

Features



- Two 10/100/1000Mbps compatible RJ-45 Ethernet ports
- Up to 9K Jumbo Frame support
- Compatible with PCI Express Base Specification 2.0 (backward compatible with 1.0a/1.1)
- Fully Compliant with IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, and supports IEEE 802.1Q VLAN tagging, IEEE 802.1P Layer 2 Priority Encoding and IEEE 802.3x Full Duplex Flow Control
- Supports Microsoft NDIS5 Checksum Offload (IP, TCP, UDP) and Large send Offload
- Wake-on-LAN / Remote Wake-up support
- Configured with standard profile bracket, low profile/half-height bracket included
- Supports Pair Swap / Polarity / Skew Correction

Har	dware
-----	-------

2 Years Warranty

2 Ports

Interface RJ45 (Gigabit Ethernet)

Bus Type **PCI Express**

Card Type Standard Profile (LP bracket incl.)

Port Style Integrated on Card

Industry Standards IEEE 802.3, IEEE 802.3u, IEEE 802.3ab

PCI Express Base Specification 2.0

Chipset ID Realtek - RTL8111

ASMedia - ASM1182E

Performance

Maximum Data Transfer Rate

2000 Mbps (full-duplex), 1000 Mbps (half-duplex)

Compatible Networks 10/100/1000 Mbps

Auto MDIX Yes

Full Duplex Support Yes

Jumbo Frame Support 9K max.



	Promiscuous Mode	Yes
	Supported Protocols	IEEE 802.1Q VLAN tagging, IEEE 802.1P Layer 2 Priority Encoding and IEEE 802.3x Full Duplex Flow Control
Connector(s)		
	Connector Type(s)	PCI Express x1
	External Ports	RJ-45
Software		Windows 2000 VD Viete 7 0 04 40 44
	OS Compatibility	Windows 2000, XP, Vista, 7, 8, 8.1, 10, 11
		Windows Server 2003, 2008 R2, 2012, 2012 R2, 2016, 2019
		Mac OS 10.4 to 10.9
		Linux 2.4.x to 4.11.x <i>LTS Versions only</i>
Special Notes / Requirements		
	System and Cable Requirements	Available PCI Express slot
Indicators	LED Indicators	Yellow - Gigabit Mode
		Green - Link/Activity
Environmental		
	Operating Temperature	0C to 70C (32F to 158F)
	Storage Temperature	0C to 100C (32F to 212F)
	Humidity	10~90% RH
Physical Characteristics		
	Color	Green
	Material	Steel
	Product Length	3.6 in [92.6 mm]
	Product Width	0.7 in [18 mm]
	Product Height	4.7 in [12 cm]



	Weight of Product	1.9 oz [53 g]
Packaging Information		
	Package Length	5.6 in [14.3 cm]
	Package Width	6.7 in [17 cm]
	Package Height	1.2 in [30 mm]
	Shipping (Package) Weight	5.0 oz [142 g]
What's in the Box		
	Included in Package	PCIe Network Card
		Low Profile Bracket
		Instruction Manual

^{*}Product appearance and specifications are subject to change without notice.