

Power Cord C14 to C15 - Heavy-Duty, 15A, 250V, 14 AWG, 6 ft. (1.83 m), Red

MODEL NUMBER: P018-006-ARD



Connects a PDU or UPS system with a C14 input port to network hardware, such as computers, servers and storage drives, with C15 power connectors.

Features

Safe, Reliable Power Solution

- Connects PDU or UPS system with C14 input to network hardware with C15 power connectors
- Ideal for replacing an old or lost cord
- Recommended for Cisco, HP and other C15-compatible hardware

Color-Coded Cable and Connectors

- Colored red for easy identification in crowded rack or workstation

Optimum Construction

- 14 AWG wire
- Flexible SJT jacket
- 250V/15A rating
- UL-listed

Specifications

| OVERVIEW | |
|----------------------|--------------------------|
| UPC Code | 037332199188 |
| Device Compatibility | Network Switch; UPS; PDU |
| Country/Region | North America |

Highlights

- Easy-to-identify red SJT jacket and fully molded red ends
- Flexible 14 AWG wire for easy routing
- 250V/15A rating
- UL-listed
- Recommended for Cisco®, HP and other C15-compatible hardware

Package Includes

- P018-006-ARD Heavy-Duty Computer Power Cord, Red, 6 ft.



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

| INPUT | |
|-------------------------------------|------------------------------|
| Maximum Input Amps | 15 |
| Voltage Compatibility (VAC) | 250 |
| PHYSICAL | |
| Color | Red |
| Number of Conductors | 3 |
| Wire Gauge (AWG) | 14 |
| Wire Gauge (OD - mm ²) | 2.08 |
| Cable Length (ft.) | 6 |
| Cable Length (m) | 1.8 |
| Cable Length (in.) | 72 |
| Cable Length (cm) | 182.88 |
| Power Cord Jacket Type | SJT |
| Shipping Dimensions (hwd / cm) | 25.15 x 17.78 x 1.27 |
| Shipping Dimensions (hwd / in.) | 9.90 x 7.00 x 0.50 |
| Shipping Weight (kg) | 0.32 |
| Shipping Weight (lbs.) | 0.71 |
| ENVIRONMENTAL | |
| Operating Temperature Range | -4 F to 221 F (-20 TO 105 C) |
| Storage Temperature Range | -4 F to 221 F (-20 TO 105 C) |
| Operating Humidity Range | 10-85% RH |
| Storage Humidity Range | 10-85% RH |
| CONNECTIONS | |
| Side A - Connector 1 | IEC-320-C14 |
| Side B - Connector 1 | IEC-320-C15 |
| SPECIAL FEATURES | |
| High Voltage | Yes |
| Locking Plug | No |
| WARRANTY | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>