

RUCKUS® ACCESSORY GUIDE

[Indoor AP accessories](#)




[Outdoor AP accessories](#)

[Electrical](#)





[Fiber accessories](#)

INDOOR	SKU	Compatible Products	Description	Kit Contents
	902-0120-0000	R730 R750 R720 R710 R700* R600* R610* R500* R510* R310 * fits AP, but does not support padlock security	Multipurpose mounting bracket for indoor AP's supports mounting to hard wall, ceiling, pole or truss. Supports padlock security with R710.	(1) Sheet metal mounting bracket (2) #6 wood screws & anchors
	902-0100-0000	R700	Multipurpose mounting bracket for 7982 supports mounting to hard wall, ceiling, electrical outlet box, pole or truss. Supports physical security with padlock or security Torx.	(1) Accessory mounting bracket with security options (1) Torx screw (4) Wood screws (2) Pipe clamps
	902-0108-0000	R500 R510 R600	Multipurpose mounting bracket for 7352 and 7372 models. Supports mounting to hard wall, ceiling, electrical outlet box, pole or truss. Supports physical security with padlock or security Torx.	(1) Accessory mounting bracket with security options (1) Torx screw (4) Wood screws (1) Pipe clamp
	902-0119-0000	H500	Used to mount H500 Wall Switch AP to locations where there is no wall box present for mounting. Note, this bracket is not required for standard wall box mounting.	(1) Plastic bracket (2) Torx screws
	902-0126-000	H510	Optional bracket, used to mount H510 wall switch AP to locations where there is no junction box available for mounting	(1) Plastic bracket (2) Torx screws
	902-1120-0000	H320	Optional bracket, used to mount H320 wall switch AP to location where there is no junction box available for mounting	(1) Plastic bracket (2) Torx screws
	902-0124-0000	C110	Optional bracket, used to mount C110 wall plate AP to locations where there is no junction box available for mounting	(1) Plastic bracket (2) Torx screws




INDOOR

	SKU	Compatible Products	Description	Kit Contents
	902-0123-0000	R710	Flush-frame acoustic ceiling bracket for R710. Flush-frame only—not applicable for standard (recessed-frame) acoustic ceiling.	(1) Mounting bracket (2) Mounting guide
	902-0118-0000	R300	Secure mounting bracket for the R300 access point. Mounts to hard wall or ceiling, or pole / truss with userapplied straps. Supports physical security with Torx or Phillips screw.	(1) Secure mounting bracket (2) #8 screws and wall anchors (1) #4 Torx screw for physical security (1) #4 Phillips screw for physical security
	902-0195-0000	R730 R750 R720 R710 R700 R610 R600 R510 R500 R320 R310 M510	Spare, T-bar ceiling mount kit for mounting to flush frame ceiling	(1) Plastic T-bar bracket (1) Plastic locking tab






OUTDOOR

	SKU	Compatible Products	Description	Kit Contents
	902-0101-0000	Fiber Node 7781CM	Outdoor product mounting bracket for overhead strand. Features a shroud to shield the mounted product from direct sunlight and falling debris as well as external antenna mounting.	<ul style="list-style-type: none"> (1) Strand bracket: coated aluminum (2) Strand clamps (4) 0.25-20 galvanized steel bolts + hex nuts + flat washers + spring washers (1) Spacer block (8) 0.25-28 stainless steel bolt + flat washers + spring washers (4) M4 stainless steel bolt + flat washers + spring washers
	902-0125-0000	P300 T310d T310c T310s T310n T610 T610s T710 T710s T750	Mounting Kit for T610/T610s, T710/T710s	<ul style="list-style-type: none"> (1) Mounting Bracket Hardware Kit (1) U Joint Bracket (1) Wall Mount Bracket (1) AP bracket (2) Linkage Brackets (1) Safety Cable Kit (1) Quick Setup Guide
	902-0182-0003	P300 T310c T310d	Outdoor AP mounting bracket (weatherized aluminum), 180-degree adjustment range in both azimuth and elevation. Mounting support for solid wall or ceiling, vertical or horizontal pole 1" to 4" in diameter using enclosed mounting hardware. Pole diameter greater than 4" can be supported with user-supplied clamps.	<ul style="list-style-type: none"> (1) Mounting bracket: weatherized aluminum (1) Hanger mount: weatherized aluminum (1) Extension: weatherized aluminum (2) M8 hex bolts with spring locks & washers (4) SAE32 steel clamps, 2.5" (4) M4 x 12mm machine screws with spring locks & washers (4) 0.25-28 x 0.625" machine screws with spring locks & washers
	902-0134-0000	Q910 T310n T310s T610 T610s T710 T710s T750	Outdoor AP mounting bracket (weatherized aluminum), 180-degree adjustment range in both azimuth and elevation. Mounting support for solid wall or ceiling, vertical or horizontal pole 1" to 4" in diameter using enclosed mounting hardware. Pole diameter greater than 4" can be supported with user-supplied clamps.	<ul style="list-style-type: none"> (1) Mounting bracket: weatherized aluminum (1) Hanger mount: weatherized aluminum (1) Extension: weatherized aluminum (2) M8 hex bolts with spring locks & washers (4) SAE32 steel clamps, 2.5" (4) M4 x 12mm machine screws with spring locks & washers (4) 0.25-28 x 0.625" machine screws with spring locks & washers

ELECTRICAL

	SKU	Compatible Products	Description	Kit Contents
	902-0162-XX00	R710 P300 R310 T300 H500 T301s H510 T301n R700 T300e R600 T310 R610 T610 R500 T610s R510 E510 R300 M510	Regional PoE Adapter (10/100/1000Mbps)	(Qty: 1) PoE module (10/100/1000 Mbps) LAN port: RJ-45 jack PoE port: RJ-45 jack, 24 Watts PoE AC input: 100-240 VAC ~ 50/60 Hz (Qty: 1) AC cable (length 2ft / 0.6m)
	902-1169-xx00	R610 R700 R710 ZoneDirector 1200 E510 M510	Regional Power Adapter	(1) Country-specific power cord, IEC, 6ft (1) Power adapter Input: 100-240VAC ~ 50/60Hz 0.6A Output: 12VDC 2.0A AC plug: country-specific DC plug: Right-angle, 2.5 x 5.5 x 10 mm (ID x OD x L) female, positive center DC cable length 1.5m
	902-0170-XX00	H500 H510 Fiber Backpack	Regional Power Adapter	(1) Country-specific power cord, IEC, 6ft (1) Power adapter Input: 100-240VAC ~ 50/60Hz 0.8A Output: 48VDC 0.68A DC plug: 0.7 x 2.35 x 13 mm (ID x OD x L) female, positive center DC cable length 1.5m
	902-0173-XX00	R310 R300 R500 R510 R600	Regional Power Adapters	(1) Country-specific power adapter — right angle plug Input: 100-240VAC ~ 50/60Hz 0.4A Output: 12VDC 1.0A AC plug: country-specific DC plug: Right-angle, 2.1 x 5.5 x 9.5 mm (ID x OD x L) female, positive center DC cable length 1.8m



ELECTRICAL

	SKU	Compatible Products	Description	Kit Contents
	902-0174-XX00	ZoneDirector 5000 SmartCell Gateway 200	Regional IEC Power Chord for ZD5000 and SCG 200 Qty 1, MOQ 10.	(1) Country-specific power cord, IEC, 6ft
	902-0180-XX00	T710 T710s R720 R730 R750	Power-over-Ethernet (PoE) adapter for products with 10/100/1000-BaseT PoE inputs. Indoor-rated. Supports power up to 60W.	(1) Country-specific power cord, IEC, 6ft (1) PoE module (10/100/1000Mbps) Input: 100-240VAC ~ 50/60Hz 1.0A Output: 48VDC 1250mA (60W) Data port: RJ-45 jack PoE/data port: RJ-45 jack Dimensions 123 x 61 x 40 mm
	902-0183-0000	T300 T300e T301n T301s T610 T610s T710 T710s 7781CM	Spare cable gland for weatherizing the RJ-45 ports on outdoor APs.	(1) weatherizing cable gland
	902-0185-0000	T710 T710s	Spare Weatherized AC Connector for 7762-AC; contains 4-pin AC connector.	(1) 4-pin female cable connector strain relief with clamping ring compatible with cable diameter 6-12.5mm
	902-1170-XX00	R720 R730 R750	KIT, SPARE, Modular AC/DC Power Adapter, 48V - 36W, w/ AR Power Cord, 1 Unit	(1) Power Supply, DC Switching Mode, 48VDC 0.75A 36W, Inlet-C14, RoHS (1) Power Cord, AR, RoHS, IEC 320, 6Ft Long









ELECTRICAL

	SKU	Compatible Products	Description	Kit Contents
	902-S310-AC00	SmartZone 300	KIT, SPARE, AC Power Supply, SZ-300 (use with 902-1174-xx00 power cord)	(1) Power Supply, AC PSU Module, 1400W (1) Manual, Quick Setup Guide, AC Power Supply, SZ 300 (1) Label, POD, Packaging Box/Bag (1.25 in x 2.25 in) (1) PKG, BOX, Power Supply, 1 Unit (385 x 151 x 118mm) (1) PKG, Foam Insert, Front (145 x 105 x 110mm) (1) PKG, Foam Insert, Rear (145 x 90 x 110mm)
	902-S301-DC00	SmartZone 300	KIT, SPARE, DC Power Supply, SZ-300	(1) Power Supply, DC PSU Module, 1200W (1) Manual, Quick Setup Guide, DC Power Supply, SZ 300 (1) Label, POD, Packaging Box/Bag (1.25 in x 2.25 in) (1) PKG, BOX, Power Supply, 1 Unit (385 x 151 x 118mm) (1) PKG, Foam Insert, Front (145 x 105 x 110mm) (1) PKG, Foam Insert, Rear (145 x 90 x 110mm)
	902-S302-DC00	SmartZone 300	KIT, SPARE, DC Power Cable, SZ-300	(1) Cable, DC Power Supply (1) Manual, Quick Setup Guide, DC Power Cord Accessory (1) Label, POD, Packaging Box/Bag (1.25 in x 2.25 in) (1) PKG, BAG, TBD x TBDmm, 0.05mm THK LDPE, Clear (1) PKG, BOX, Spares, (OD TBD x TBD x TBD mm)
	902-S320-0000	SmartZone 300	KIT, SPARE, FAN ASSY, SZ-300 (6 Fans)	(1) FANS, Set of 6 (1) Manual, Quick Setup Guide, Fan Assembly, (SZ 300) (1) Label, POD, Packaging Box/Bag (1.25 in x 2.25 in) (1) PKG, BOX, Fan Assembly (146 x 96 x 144mm)
	902-S330-0000	SmartZone 300	KIT, SPARES, Slide Rail Rack Mount Kit, SZ-300	(1) KIT, Slide Rail (1) Quick Setup Guide, SmartZone 300 Rack Mount Kit
	902-S340-0000	SmartZone 300	KIT, SPARE, Console Cable, (RJ45 to USB)	(1) CABLE, Console, USB RS232-RJ45, 6FT Lg (1) Manual, Quick Setup Guide, Console Cable (SZ 300) (1) Label, POD, Packaging Box/Bag (1.25 in x 2.25 in) (1) PKG, BAG, 170 x 240mm, 0.04mm THK, LDPE, Clear
	902-S350-0000	SmartZone 300	KIT, SPARE (FRU), Hard Disk Drive, SZ-300	(1) Hard Drive, 1.2 TB, 10K RPM, 64MB Cache 2.5 SAS 6Gb/s, 2.5 Inch Internal (1) Disk Tray, 2.5 HDD (4) SCREW, M3 x 4mm L, x 5.2 DIA, Steel Ni - 4x (1) Manual, Quick Setup Guide, Hard Disk Drive, SZ 300 (1) Label, POD, Packaging Box/Bag (1.25 in x 2.25 in) (1) PKG, BAG, PE, TBD x TBD x TBDmm, ESD (1) PKG, BOX, HDD, 1 Unit (196 x 141 x 84mm)

ELECTRICAL

	SKU	Compatible Products	Description	Kit Contents
	902-S351-0000	SmartZone 300	KIT, SPARE (FRU), Solid State Disk 64GB, SZ-300	<ul style="list-style-type: none"> (1) Storage Module, SQFlash, 64GB SATA III (6.0Gbps), 2.5 SSD (4) SCREW, M3 x 4mm L, x 5.2 DIA, Steel Ni - 4x (1) Disk Tray, 2.5 HDD (1) Manual, Quick Setup Guide, Solid State Drive, SZ 300 (1) Label, POD, Packaging Box/Bag (1.25 in x 2.25 in) (1) PKG, BAG, PE, TBD x TBD x TBDmm, ESD (1) PKG, BOX, HDD, 1 Unit (196 x 141 x 84mm)
	902-0190-0001	SmartZone 300	KIT, SPARES, Ethernet 1G/10G SFP+ SR Transceiver Module	<ul style="list-style-type: none"> (1) Ethernet SFP+ SR Optic Transceiver Module, 1G/10G (1) Manual, Quick Setup Guide, 10GBASE-SR SFP+ Optical Transceiver Module, (SZ 300) (1) Label, POD, Packaging Box/Bag (1.25 in x 2.25 in) (1) PKG, BOX, Outer Carton, (272 x 140 x 109mm) [Transceiver]

POWER CORDS

Outlet Connector	Equipment Connector	SKU	Compatible Products	Description	Kit Contents
		PCAU5	All ICX Switches (except 7150-C08PT)	Power Outlet Connector: AS 3112 Equipment Connector: C13 Length: 2.5m Rating: 250v/10A	Power Cord, Australia, 250V 10A
		PC-C13C14	All ICX Switches (except 7150-C08PT)	Power Outlet Connector: C14 Equipment Connector: C13 Length: 2.0m Rating: 250v/15A	C13/C14 15A Power Cord
		PCCHINA-IEC309	All ICX Switches (except 7150-C08PT)	Power Outlet Connector: IEC 60309 Equipment Connector: C13 Length: 2.5m Rating: 110v/10A	Power Cord, IEC309 TO C13, China, 110V 10A
		PCCHINA2-IEC309	All ICX Switches (except 7150-C08PT)	Power Outlet Connector: IEC 60309 Equipment Connector: C13 Length: 2.5m Rating: 250v/10A	Power Cord, IEC309 TO C13, China, 250V 10A







POWER CORDS

Outlet Connector	Equipment Connector	SKU	Compatible Products	Description	Kit Contents
		PCEURO	All ICX Switches (except 7150-C08PT)	Power Outlet Connector: CEE 7/7 Equipment Connector: C13 Length: 2.5m Rating: 250v/10A	Power Cord for VIIG to C13, Europe, 250V 10A
		PCINDIA	All ICX Switches (except 7150-C08PT)	Power Outlet Connector: BS 546 Equipment Connector: C13 Length: 2.5m Rating: 250v/10A	Power Cord, India, 250V 10A
		PCITALY-CEI	All ICX Switches (except 7150-C08PT)	Power Outlet Connector: CEI 23-16 Equipment Connector: C13 Length: 2.5m Rating: 250v/10A	PWRCD, ITALY, 10A, 250V, 2.5M, CEI 23-16/C13
		PCJAPAN	All ICX Switches (except 7150-C08PT)	Power Outlet Connector: JIS 8303 Equipment Connector: C13 Length: 2.0m Rating: 125v/13A	Power Cord, Japan, 125V 13A
		PCSWISS-C1312G-HF	All ICX Switches (except 7150-C08PT)	Power Outlet Connector: SEV 1011 Equipment Connector: C13 Length: 2.5m Rating: 250v/10A	Power Cord for SEV1011 TO C13, Switzerland, 250V 10A
		PCUK	All ICX Switches (except 7150-C08PT)	Power Outlet Connector: BS 1363 Equipment Connector: C13 Length: 2.5m Rating: 250v/13A	Power Cord, United Kingdom, 250V 13A. 2.5m
		PCUSA	All ICX Switches (except 7150-C08PT)	Power Outlet Connector: NEMA 5-15 Equipment Connector: C13 Length: 2.0m Rating: 125v/10A	Power Cord, USA, NEMA5-15/C13, 10A, 125V, 2m
		PCUSA2	All ICX Switches (except 7150-C08PT)	Power Outlet Connector: NEMA 5-15 Equipment Connector: C13 Length: 2.0m Rating: 125v/13A	Power Cord, USA, NEMA5-15/C13, 13A, 125V, 2m
		PCUSA-3M	All ICX Switches (except 7150-C08PT)	Power Outlet Connector: NEMA 5-15 Equipment Connector: C13 Length: 3.0m Rating: 125v/10A	Power Cord, USA, NEMA5-15/C13, 10A, 125V, 3m

POWER CORDS

Outlet Connector	Equipment Connector	SKU	Compatible Products	Description	Kit Contents
HIGH TEMPERATURE POWER CORDS WITH C15 EQUIPMENT CONNECTOR					
		PCAUS-C15	ICX 7150-C08PT	Power Outlet Connector: AS 3112 Equipment Connector: C15 Length: 1.83m Rating: 250v/10A	Power Cord High Temperature C15, Australia, 250V 10A, 1.83m
		PCC14C15	ICX 7150-C08PT	Power Outlet Connector: C14 Equipment Connector: C15 Length: 1.83m	Power Cord High Temperature, C14 to C15, 125V 13A, 1.83m
		PCC14C15-SHORT	ICX 7150-C08PT	Power Outlet Connector: C14 Equipment Connector: C15 Length: 0.25m	Power Cord High Temperature, C14 to C15, 125V 13A, 0.25m
		PCCHINA-C15	ICX 7150-C08PT	Power Outlet Connector: IEC 60309 Equipment Connector: C15 Length: 1.83m Rating: 250v/10A	Power Cord High Temperature C15, China, 250V 10A, 1.83m
		PCEURO-C15	ICX 7150-C08PT	Power Outlet Connector: CEE 7/7 Equipment Connector: C15 Length: 1.83m Rating: 250v/16A	Power Cord High Temperature C15, Europe, 250V 16A, 1.83m
		PCINDIA-C15	ICX 7150-C08PT	Power Outlet Connector: BS 546 Equipment Connector: C15 Length: 1.83m Rating: 250v/10A	Power Cord High Temperature C15, India, 250V 10A, 1.83m
		PCITALY-C15	ICX 7150-C08PT	Power Outlet Connector: CEI 23-16 Equipment Connector: C15 Length: 1.83m Rating: 250v/10A	Power Cord High Temperature C15, Italy, 250V 10A, 1.83m
		PCJAPAN-C15	ICX 7150-C08PT	Power Outlet Connector: JIS 8303 Equipment Connector: C15 Length: 1.83m Rating: 125v/7A	Power Cord High Temperature C15, Japan, 125V 7A, 1.83m

POWER CORDS

Outlet Connector	Equipment Connector	SKU	Compatible Products	Description	Kit Contents
HIGH TEMPERATURE POWER CORDS WITH C15 EQUIPMENT CONNECTOR					
		PCSWISS-C15	ICX 7150-C08PT	Power Outlet Connector: SEV 1011 Equipment Connector: C15 Length: 1.83m Rating: 250v/10A	Power Cord High Temperature C15, Swiss, 250V 10A, 1.83m
		PCUK-C15	ICX 7150-C08PT	Power Outlet Connector: BS 1363 Equipment Connector: C15 Length: 2.5m Rating: 250v/13A	Power Cord, High Temperature C15, United Kingdom, 250V 13A. 2.5m
		PCUSA-C15	ICX 7150-C08PT	Power Outlet Connector: NEMA 5-15 Equipment Connector: C15 Length: 1.83m Rating: 125v/13A	Power Cord High Temperature C15, USA, 125V 13A, 1.83m







ICX SERIAL MGNT CABLES

SKU	Compatible Products	Description	Kit Contents
CC-RJ45-DB9	All ICX switches with RJ-45 console ports (ICX 7150, ICX 7650, ICX 7850)	Serial Console cable RJ45-RJ45 with RJ-45-DB9 Adapter (for RJ-45 console port)	1 Cable 1 Adapter
CC-USBC-USBA	ICX switches with USB Type-C Mgnt port (ICX 7150, ICX 7650, ICX 7850)	USB 2.0 Cable, Type-C to Type-A, 1 meter (for USB Type-C console port on ICX 7150)	1 Cable
CC-MINIUSB-RJ45	ICX switches with mini-USB Mgnt port (ICX 7250, ICX 7450, ICX 7750)	Console cable, male mini-USB to male RJ-45 with RJ-45 to DB-9 converter	1 Cable 1 Adapter

ICX MOUNT KITS

SKU	Compatible Products	Description
XBR-R000295	ICX 7000 series 24/48 port 1RU models	Universal Rack Mount Kit, 4 post, for ICX 7000 series 24/48 port models
ICX-RMK-4POST-TL	ICX 7850	ICX Tool-less 4-Post Rack Mount Kit
ICX7000-RMK	ICX 7000 series 24/48 port 1RU models	Rack Mount Kit, 2-post for ICX 7000 series 24/48 port models
ICX6400-C12-MGNT	ICX 7150/6450/6430 12 Port Compact Switches	Magnetic Mount Kit for Ruckus ICX 12 port compact switches
ICX7000-C12-WMK	ICX7150-C12P & ICX7150-C08P & ICX7150-C10ZP compact switches	Compact Switch Wall Mount & Under Desk Mount Kit for ICX7150-C12P & ICX7150-C08P ICX7150-C08PT & ICX7150-C10ZP Compact Switch Wall Mount & Under Desk Mount Kit
ICX7000-C12-RMK	ICX7150-C12P & ICX7150-C08P & ICX7150-C08PT compact switches	Compact Switch Rack Mount Kit for ICX7150-C12P & ICX7150-C08P
ICX7000-C10ZP-RMK	ICX7150-C10ZP compact switches	Compact Switch Rack Mount Kit for ICX7150-C10ZP
ICX-ADP-PLT	All ICX Compact switches	ICX Compact Switch Adapter Plate for wall mounting the ICX7150-C08PT and DIN mounting all other ICX compact switch models.
ICX-DIN-MNT	All ICX Compact switches	ICX Compact Switch DIN Rail Mount Kit. Note: Additional adapter plate required (ICX-ADP-PLT) to attach the Din Rail Mount Kit to all ICX compact switches except for the ICX7150-C08PT extended temperature switch.
RMK-LRM-ADP	All ICX switches	Rack Mount Kit for LRM adapters. This 1RU shelf can accommodate up to 8 LRM adapters.

FIBER

	SKU	Compatible Products	Description
	P01-0500-0000	H510	Fiber Optic Enclosure, Fiber-to-Ethernet Media Converter. Field Installable Accessory for H510
	P01-0300-0000	T300/301 series T310c/d P300	Weather-tight Fiber Optic Enclosure, Field Installable Accessory for T300/T301 series and P300
	902-0202-0000	T710 T710s Fiber Node Fiber Backpack	EPON Stick - Pluggable SFP transceiver with patch cable single mode simplex SC/PC - 203mm
	902-0203-0000	T710 T710s Fiber Node Fiber Backpack	1000Base-LX - Pluggable SFP transceiver with patch cable single mode duplex LC-LC 203mm
	902-0501-0000	Fiber Backpack	Installation kit with Backpack cover and installation wall bracket for Standalone Backpack use-case
	902-0502-0000	Fiber Backpack	Cable cover to be installed on Backpack when 902-1100-XXXX (Ruckus IoT module with cover) is installed on H510

commscope.com

Visit our website or contact your local CommScope representative for more information.

© 2020 CommScope, Inc. All rights reserved.

All trademarks identified by ® or ™ are registered trademarks or trademarks, respectively, of CommScope, Inc. This document is for planning purposes only and is not intended to modify or supplement any specifications or warranties relating to CommScope products or services. CommScope is committed to the highest standards of business integrity and environmental sustainability with a number of CommScope's facilities across the globe certified in accordance with international standards, including ISO 9001, TL 9000, and ISO 14001. Further information regarding CommScope's commitment can be found at www.commscope.com/About-Us/Corporate-Responsibility-and-Sustainability.