
**Comparison Guide** 



## Wireless Solutions for Business

**Get Wireless Everywhere from D-Link** 











D-Link offers a breadth of wireless options, from standalone APs, to managed PoE switches, to unified wireless end-to-end solutions, giving businesses the flexibility to choose what's right for their environment. With affordable, reliable D-Link

	Unified Wireless APs					Standalone APs		
					AC	AC		
D-Link Wireless Access Points			C					
	DWL-2600AP	DWL-3600AP	DWL-6600AP	DWL-8600AP	DWL-8610AP	DAP-1665	DAP-2310	
Band	Single-band	Single-band	Dual-band Concurrent	Dual-band Concurrent	Dual-band Concurrent	Dual-band Concurrent	Single-band	
Operation mode	Standalone or Controller-managed	Standalone or Controller-managed	Standalone or Controller-managed	Standalone or Controller-managed	Standalone or Controller-managed	Standalone	Standalone	
Wi-Fi Standard	802.11 b/g/n	802.11 b/g/n	802.11 b/g/n and 802.11 a/n	802.11 b/g/n and 802.11 a/n	802.11 b/g/n and 802.11 a/n/ac	802.11 b/g/n and 802.11 a/n/ac	802.11 b/g/n	
MIMO	2x2	2x2	2x2	2x2	3x3	2x2	2x2	
Wi-Fi Speed	300Mbps @2.4GHz	300Mbps @2.4GHz	300Mbps @2.4GHz 300Mbps @5GHz	300Mbps @2.4GHz 300Mbps @5GHz	450Mbps @2.4GHz 1300Mbps @5GHz	300Mbps @2.4GHz 867Mbps @5GHz	300Mbps @2.4GHz	
Max. Output Power	2.4GHz: 16dBm	2.4GHz: 16dBm	2.4GHz: 19dBm 5GHz: 16dBm	2.4GHz: 18dBm 5GHz: 17dBm	2.4GHz: 17dBm 5GHz: 17dBm	2.4Ghz: 25dBm 5Ghz: 21dBm	2.4GHz: 26dBm	
Antenna Type	Internal omni-directional	4 Internal omni-directional	Internal omni-directional (optional external)	4 External omni-directional	6 Internal omni-directional	2 External omni-directional	2 External omni-directional	
Antenna Gain (dBi)	3 dBi	4.7dBi	5dBi @ 2.4GHz 6dBi @ 5GHz	4dBi @ 2.4GHz 6dBi @ 5GHz	5 dBi @ 2.4GHz 6.5 dBi @ 5GHz	3 dBi @ 2.4GHz 5 dBi @ 5GHz	2dBi	
Antenna Connector			4 RP-SMA Female	4 RP-SMA Female		2 RP-SMA Female	2 RP-SMA Female	
Power-over-Ethernet	Yes (802.3af)	Yes (802.3af)	Yes (802.3af)	Yes (802.3af)	Yes (802.3at)	No	Yes (802.3af)	
Interface Ports	1 10/100	1 10/100/1000	1 10/100/1000	1 10/100/1000	2 10/100/1000	1 10/100/1000	1 10/100/1000	
Console Port	RJ45	RJ45	RJ45	RJ45	RJ45			
Plenum Rated (UL-2043)		~	~	v	v			
Indoor/Outdoor Use	Indoor	Indoor	Indoor	Indoor	Indoor	Indoor	Indoor	
Housing Material	Plastic	Plastic	Plastic	Metal	Metal/Plastic	Plastic	Plastic	
Wireless & Network Features								
AP / WDS / WDS with AP	4	V	v	v	4	v	~	
Wireless Client	✔ (in S/A mode)	🖌 (in S/A mode)	🖌 (in S/A mode)	🖌 (in S/A mode)	✔ (in S/A mode)	<i>v</i>	~	
Multiple SSID / 802.1Q	Up to 16 SSID	Up to 16 SSID	Up to 16 SSID each radio	Up to 16 SSID each radio	Up to 16 SSID each radio	1 SSID each radio	Up to 8 SSID	
WMM-PS/ IEEE 802.11e (U-APSD)	<b>v</b>	~	~	~	~	~	<i>v</i>	
Wi-Fi Scheduler	🖌 (in S/A mode)	🖌 (in S/A mode)	🖌 (in S/A mode)	🖌 (in S/A mode)	🖌 (in S/A mode)		V	
AP Traffic Load Balance	✔ (in S/A mode)	🖌 (in S/A mode)	🖌 (in S/A mode)	🖌 (in S/A mode)	🖌 (in S/A mode)		<i>v</i>	
Built in DHCP server						<i>v</i>	<i>v</i>	
Security/Encryption								
WEP (64/128-bit)	~	<i>v</i>	<i>v</i>	V	~	<i>v</i>	v	
TKIP/AES WPA/WPA2 PSK	<i>v</i>	V	V	V	V	V	V	
WPA/WPA2 Ent. / 802.1X Auth.	V	V	V	V	V	V	V	
MAC Address Filtering	v	<i>v</i>	<i>v</i>	v	v	<ul> <li>✓</li> </ul>	<ul> <li>✓</li> </ul>	
Management								
Web Interface	v	V	V	V	~	<i>v</i>	<i>✓</i>	
Serial Management	~	V	V	V	V			
Telnet & SSH	<i>v</i>	~	~	v	~		<i>v</i>	
SNMP v1, v2c, v3	<i>v</i>	~	V	V	~		v	
Syslog	v	~	~	<i>ب</i>	~	<i>٧</i>	v	
Warranty & Pricing		1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.	1					
Warranty	Limited Lifetime	Limited Lifetime	Limited Lifetime	Limited Lifetime	Limited Lifetime	Limited Lifetime	Limited Lifetime	
MSRP	\$199.99	\$329.99	\$549.99	\$599.99	\$799.99	\$119.99	\$109.99	

wireless solutions, it's never been easier to have wireless everywhere, no matter how large or small the business.

				Standalone APs			
				AC		AC	1.1
D-Link Wireless							
Access Points							
ACCESS FOILLS							T
	DAP-2330	DAP-2360	DAP-2553	DAP-2660	DAP-2690	DAP-2695	DAP-3690
			DAP-2555 Dual-band	DAP-2000 Dual-band	DAP-2090 Dual-band	DAP-2095 Dual-band	DAP-3090 Dual-band
Band	Single-band	Single-band	Selectable	Concurrent	Concurrent	Concurrent	Concurrent
Operation mode	Standalone	Standalone	Standalone	Standalone	Standalone	Standalone	Standalone
Wi-Fi Standard	802.11 b/g/n	802.11 b/g/n	802.11 b/g/n or	802.11 b/g/n and	802.11 b/g/n and	802.11 b/g/n and	802.11 b/g/n and
MIMO	2x2	2x2	802.11 a/n 2x3	802.11 a/n/ac 2x2	802.11 a/n 2x2	802.11 a/n/ac 3x3	802.11 a/n 2x2
MINIO	272	282					
Wi-Fi Speed	300Mbps @2.4GHz	300Mbps @2.4GHz	300Mbps @2.4GHz 300Mbps @5GHz	300Mbps @2.4GHz 867Mbps @5GHz	300Mbps @2.4GHz 300Mbps @5GHz	450Mbps @2.4GHz 1300Mbps @5GHz	300Mbps @2.4GHz 300Mbps @5GHz
Max. Output Power	2.4GHz: 26 dBm	26 dBm	2.4GHz: 21dbm 5GHz: 20dbm	2.4Ghz: 26dBm 5Ghz: 26dBm	2.4Ghz: 23dBm 5Ghz: 23dBm	2.4Ghz: 27.5dBm 5Ghz: 27.5dBm	2.4GHz: 20dBm 5GHz: 22dBm
	21.1		25.4				
Antenna Type	2 Internal omni-directional	2 External omni-directional	3 External omni-directional	4 internal omni-directional	4 External omni-directional	6 External omni-directional	4 External omni-directional
			2.01 0.2.4611	2.10: 0.2.4611			
Antenna Gain (dBi)	3 dBi	5dBi	3dBi @ 2.4GHz 5dBi @ 5GHz	3dBi @ 2.4GHz 4dBi @ 5GHz	4dBi @ 2.4GHz 6dBi @ 5GHz	4dBi @ 2.4GHz 6dBi @ 5GHz	8dBi @ 2.4GHz 10dBi @ 5GHz
Antenna Connector		2 RP-SMA Female	3 RP-SMA Female		4 RP-SMA Female	6 RP-SMA Female	4 RP-N Female
Power-over-Ethernet	Yes (802.3af)	Yes (802.3af)	Yes (802.3af)	Yes (802.3af)	Yes (802.3af)	Yes (802.3at)	Yes (802.3at)
Interface Ports	1 10/100/1000	1 10/100/1000	1 10/100/1000	1 10/100/1000	1 10/100/1000	2 10/100/1000	2 10/100/1000
Console Port					RJ45	RJ45	RJ45
Plenum Rated (UL-2043)		4			v	4	
Indoor/Outdoor Use	Indoor	Indoor	Indoor	Indoor	Indoor	Indoor	Outdoor (IP67)
Housing Material	Plastic	Metal	Plastic	Plastic	Metal	Metal	Metal
Wireless & Network Features							
AP / WDS / WDS with AP Modes	v	~	v	<ul> <li>✓</li> </ul>	v	v	V
Wireless Client Mode	~	~	~	~	~	~	~
Multiple SSID / 802.1Q	Up to 8 SSID	Up to 8 SSID	Up to 4 SSID	Up to 8 SSID each radio	Up to 8 SSID each radio	Up to 8 SSID each radio	Up to 8 SSID each radio
WMM-PS/ IEEE 802.11e (U-APSD)	4	~	v	~	v	v	~
Wi-Fi Scheduler (Green)	4	4	4	4	4	4	<ul> <li>✓</li> </ul>
AP Traffic Load Balance	4	v	v	4	v	v	<ul> <li>✓</li> </ul>
Built in DHCP server	4	4	v	4	v	v	<i>v</i>
Security/Encryption							
WEP (64/128-bit)	4	4	4	4	v	4	<i>v</i>
TKIP/AES WPA/WPA2 PSK	v	v	~	~	~	~	<ul> <li>✓</li> </ul>
WPA/WPA2 Ent. / 802.1X Auth.	v	~	~	v	v	v	~
MAC Address Filtering	4	~	~	~	v	~	~
Management							
Web Interface	v	~	~	~	~	~	V
Serial Management							~
Telnet & SSH	v	~	~	~	~	~	V
SNMP v1, v2c, v3	4	4	4	v	4	4	<i>v</i>
Syslog	v	~	v	~	~	~	<i>v</i>
Warranty & Pricing							
Warranty	Limited Lifetime	Limited Lifetime	Limited Lifetime	Limited Lifetime	Limited Lifetime	Limited Lifetime	Limited Lifetime
MSRP	\$119.99	\$159.99	\$179.99	\$229.99	\$309.99	\$389.99	\$1,059.99

	Unified C	ontrollers			
D-Link Unified Wireless Controllers and Switches		Ten 1			
	DWC-1000	DWC-2000	DWS-3160-24PC	DWS-3160-24TC	DWS-4026
10/100/1000BASE-T Ports	6		20	20	24
Combo 10/100/ 1000BASE-T/SFP Ports		4	4	4	4
Optional 10G Uplink Module					2 Slots for XFP or CX4
Console Port	RJ45	RJ45	RJ45	RJ45	DB-9
Power-over-Ethernet			Yes (802.3at)		Yes (802.3af)
PoE Power Budget			370W (740W w/RPS)		370W
Switching Capacity			48 Gbps	48 Gbps	88 Gbps
Max. AP per unit (default/upgrade)	6/24	64/256	12/48	12/48	64
Max. AP per Switch/Controller Peer Group (default/upgrade)	24/96	256/1024	48/192	48/192	256
Redundant Power Supply			DPS-700	DPS-200	DPS-600
Additional AP License Upgrades	DWC-1000-AP6-LIC	DWC-2000-AP32-LIC DWC-2000-AP64-LIC DWC-2000-AP128-LIC	DWS-3160-24PC-AP12-LIC DWS-3160-24PC-AP24-LIC	DWS-3160-24TC-AP12-LIC DWS-3160-24TC-AP24-LIC	
VPN/Router/Firewall License Upgrade	DWC-1000-VPN-LIC				
Web Content Filtering 12-month License Upgrade	DWC-1000-WCF-12-LIC				

## PoE Power<br/>InjectorsInjectorsDPE-101GIDPE-101GISupported speeds10/100/1000BASE-TMax power19W

## **Comprehensive Service and Support**

D-Link Professional Services and Support for business ensures you get the best fit solution for your unique environment.



## Call or visit us online for more information on the complete line of D-Link Wireless solutions:

www.dlink.com/business 888.331.8686 | Email: getmore@dlink.com

