

## 4-Channel CCTV “Brick” Power Supply

### PA-U0405-NULQ

4 Outputs, Total supply current: 5A

The **PA-U0405-NULQ** is a 4-channel 5-Amp power supply. While normally used in CCTV installations, it is suitable for a wide variety of both CCTV and access control applications. It features adjustable output voltage and built-in 6.8-Amp overcurrent protection.

### Features:

- 4-Channel 5-Amp power distribution
- Can be mounted with the bracket for easy access and reduced power cord clutter
- Universal input voltage: 100~240 VAC
- Adjustable output voltage: 12~13.8 VDC
- Built-in 6.8-Amp overcurrent protection.
- High voltage and over-current protection
- LED Power indicator



### Specifications:

Outputs	4
Total supply current	5A
Max. output power	60W
Over current protection	12VDC/6.8A
Output voltage	12~13.8 VDC
Input fuse	3.15A@250VAC
Input voltage	100~240 VAC
Dimensions	5 <sup>7</sup> / <sub>8</sub> "x2 <sup>3</sup> / <sub>16</sub> "x1 <sup>5</sup> / <sub>16</sub> " (150x55x33 mm)
Weight	13.4-oz (380g)
Operating temperature	14°~113° F (-10°~45° C)

### Overview:

