

MultiSync® E221N LCD 22" Commercial Display

# **Datasheet**





NEC MultiSync ® E221N Ultra-Thin Bezel - The Office Workhorse, combining sleek and elegant design with health-conscious performance

The 22" ultra-thin bezel display targeting reliable office productivity, performance and quality, fulfils demand for future-ready design. Enduring productivity requires high attention to healthcare. Ensuring the well-being of the user, built-in Low Blue Light Plus technology filters out hazardous blue light emissions whilst Flicker-Free technology eliminates the effect of flickering. The users' eyes are protected whilst ensuring a true-to-life display colour performance from all viewing angles. The LED backlight panel with AH-IPS technology supports a high display brightness of 250 cd/m² and in parallel lowers power consumption.

The ultra-narrow bezel display reduces the display footprint without compromising on screen size and gives an office a fresh professional interior with its sleek and elegant design.

### **Benefits**

Future-Ready Design – best in form and function design with 3-sided 1 mm ultra-thin bezel gives an office a fresh professional interior.

**Protecting your eyes from strain and damage** – Built-in Low Blue Light Plus technology filters out hazardous blue light emissions whilst Flicker-Free technology eliminates any backlight flickering, thus protecting your eyes against cataracts and macular degeneration without compromise to true-to-life display colour performance.

Ergonomic Office – full height adjustability (110 mm), swivel, tilt and pivot functionality ensures perfect individual ergonomic set-up.

Business Class Image Quality – IPS (AH-IPS) panel provides the very best viewing angles as well as noticeably better colour production.

Your environmental and social responsibility – NEC's TCO 7 and ENERGY STAR 7 certified display is environmentally designed with minimal hazardous materila meeting the growing demand for more sustainable technologies.

#### **Product Information**

Product Name	MultiSync® E221N
Product Group	LCD 22" Commercial Display
Order Code	60004223 (WH) , 60004224 (BK)

### Display

D 17 1 1	IDO TET VI WI ED I I I'I I
Panel Technology	IPS TFT with W-LED backlight
Screen Size [inch/cm]	21.5 / 54.62
Screen Aspect Ratio	16:9
Pixel Pitch [mm]	0.248
Brightness (typ.) [cd/m²]	250
Contrast Ratio (typ.)	1000:1
Viewing Angle [°]	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
Response Time (typ.) [ms]	6
Colours [Mio.]	16.77
Synchronisation Rate	
Horizontal Frequency [kHz]	31.5 - 81.1
Vertical Frequency [Hz]	56 - 76
Resolution	
Optimum Resolution	1920 x 1080 at 60 Hz
Optimum Resolution	1920 X 1000 at 00 112
Connectivity	
Digital	1 x DisplayPort; 1 x HDMI
Analog	1 x D-sub 15 pin
Electrical	
Power Consumption on Mode [W]	15 (Eco Mode 1); 17 (typ.); 25 (max.)
	( ), (31 // ( )
Power Savings Mode [W]	0.29
Power Savings Mode [W]  Environmental Conditions	0.29
	0.29 +5 to +25
Environmental Conditions	
Environmental Conditions  Operating Temperature [°C]	+5 to +25
Environmental Conditions  Operating Temperature [°C]	+5 to +25
Environmental Conditions  Operating Temperature [°C]  Operating Humidity [%]	+5 to +25
Environmental Conditions  Operating Temperature [°C]  Operating Humidity [%]  Ergonomics	+5 to +25 20 to 80
Environmental Conditions  Operating Temperature [°C]  Operating Humidity [%]  Ergonomics  Height adjustable stand [mm]	+5 to +25 20 to 80  110
Environmental Conditions  Operating Temperature [°C]  Operating Humidity [%]  Ergonomics  Height adjustable stand [mm]  Screen Tilt [°]	+5 to +25 20 to 80  110 5 to 20
Environmental Conditions  Operating Temperature [°C]  Operating Humidity [%]  Ergonomics  Height adjustable stand [mm]  Screen Tilt [°]  Screen Swivel [°]	+5 to +25 20 to 80  110 5 to 20
Environmental Conditions  Operating Temperature [°C]  Operating Humidity [%]  Ergonomics  Height adjustable stand [mm]  Screen Tilt [°]  Screen Swivel [°]	+5 to +25 20 to 80  110 5 to 20 45 to 45
Environmental Conditions  Operating Temperature [°C]  Operating Humidity [%]  Ergonomics  Height adjustable stand [mm]  Screen Tilt [°]  Screen Swivel [°]  Mechanical  Bezel Width [mm]	+5 to +25 20 to 80  110 5 to 20 45 to 45  1 (left and right); 1 (top)
Environmental Conditions  Operating Temperature [°C]  Operating Humidity [%]  Ergonomics  Height adjustable stand [mm]  Screen Tilt [°]  Screen Swivel [°]  Mechanical  Bezel Width [mm]  Dimensions (W x H x D) [mm]	+5 to +25 20 to 80  110 5 to 20 45 to 45  1 (left and right); 1 (top) 488.1 x 359.8 x 213.9
Environmental Conditions  Operating Temperature [°C]  Operating Humidity [%]  Ergonomics  Height adjustable stand [mm]  Screen Tilt [°]  Screen Swivel [°]  Mechanical  Bezel Width [mm]  Dimensions (W x H x D) [mm]  Weight [kg]	+5 to +25 20 to 80  110 5 to 20 45 to 45  1 (left and right); 1 (top) 488.1 x 359.8 x 213.9  With stand: 5
Environmental Conditions  Operating Temperature [°C]  Operating Humidity [%]  Ergonomics  Height adjustable stand [mm]  Screen Tilt [°]  Screen Swivel [°]  Mechanical  Bezel Width [mm]  Dimensions (W x H x D) [mm]  Weight [kg]  VESA Mounting [mm]	+5 to +25 20 to 80  110 5 to 20 45 to 45  1 (left and right); 1 (top) 488.1 x 359.8 x 213.9  With stand: 5
Environmental Conditions  Operating Temperature [°C]  Operating Humidity [%]  Ergonomics  Height adjustable stand [mm]  Screen Tilt [°]  Screen Swivel [°]  Mechanical  Bezel Width [mm]  Dimensions (W x H x D) [mm]  Weight [kg]  VESA Mounting [mm]  Additional Features	+5 to +25 20 to 80  110 5 to 20 45 to 45  1 (left and right); 1 (top) 488.1 x 359.8 x 213.9  With stand: 5 100 x 100
Environmental Conditions  Operating Temperature [°C]  Operating Humidity [%]  Ergonomics  Height adjustable stand [mm]  Screen Tilt [°]  Screen Swivel [°]  Mechanical  Bezel Width [mm]  Dimensions (W x H x D) [mm]  Weight [kg]  VESA Mounting [mm]  Additional Features  Special Characteristics  Colour Versions	+5 to +25 20 to 80  110 5 to 20 45 to 45  1 (left and right); 1 (top) 488.1 x 359.8 x 213.9  With stand: 5 100 x 100  DisplayPort; EcoModes; LED Backlight Technology; NaViSet Administrator 2
Environmental Conditions  Operating Temperature [°C]  Operating Humidity [%]  Ergonomics  Height adjustable stand [mm]  Screen Tilt [°]  Screen Swivel [°]  Mechanical  Bezel Width [mm]  Dimensions (W x H x D) [mm]  Weight [kg]  VESA Mounting [mm]  Additional Features  Special Characteristics  Colour Versions  Cable Management	+5 to +25 20 to 80  110 5 to 20 45 to 45  1 (left and right); 1 (top) 488.1 x 359.8 x 213.9  With stand: 5 100 x 100  DisplayPort; EcoModes; LED Backlight Technology; NaViSet Administrator 2 Black Front Bezel, Black Back Cabinet; White Front Bezel, White Back Cabinet yes
Environmental Conditions  Operating Temperature [°C]  Operating Humidity [%]  Ergonomics  Height adjustable stand [mm]  Screen Tilt [°]  Screen Swivel [°]  Mechanical  Bezel Width [mm]  Dimensions (W x H x D) [mm]  Weight [kg]  VESA Mounting [mm]  Additional Features  Special Characteristics  Colour Versions	+5 to +25 20 to 80  110 5 to 20 45 to 45  1 (left and right); 1 (top) 488.1 x 359.8 x 213.9  With stand: 5 100 x 100  DisplayPort; EcoModes; LED Backlight Technology; NaViSet Administrator 2 Black Front Bezel, Black Back Cabinet; White Front Bezel, White Back Cabinet yes VESA DDC2Bi
Environmental Conditions  Operating Temperature [°C]  Operating Humidity [%]  Ergonomics  Height adjustable stand [mm]  Screen Tilt [°]  Screen Swivel [°]  Mechanical  Bezel Width [mm]  Dimensions (W x H x D) [mm]  Weight [kg]  VESA Mounting [mm]  Additional Features  Special Characteristics  Colour Versions  Cable Management  Plug and Play  Audio	+5 to +25 20 to 80  110 5 to 20 45 to 45  1 (left and right); 1 (top) 488.1 x 359.8 x 213.9  With stand: 5 100 x 100  DisplayPort; EcoModes; LED Backlight Technology; NaViSet Administrator 2  Black Front Bezel, Black Back Cabinet; White Front Bezel, White Back Cabinet yes  VESA DDC2Bi 1W + 1W (De-activateable); Headphone Jack
Environmental Conditions  Operating Temperature [°C]  Operating Humidity [%]  Ergonomics  Height adjustable stand [mm]  Screen Tilt [°]  Screen Swivel [°]  Mechanical  Bezel Width [mm]  Dimensions (W x H x D) [mm]  Weight [kg]  VESA Mounting [mm]  Additional Features  Special Characteristics  Colour Versions  Cable Management  Plug and Play	+5 to +25 20 to 80  110 5 to 20 45 to 45  1 (left and right); 1 (top) 488.1 x 359.8 x 213.9  With stand: 5 100 x 100  DisplayPort; EcoModes; LED Backlight Technology; NaViSet Administrator 2 Black Front Bezel, Black Back Cabinet; White Front Bezel, White Back Cabinet yes VESA DDC2Bi

## **Green Features**

Energy Efficiency	Carbon Footprint Meter / Carbon Savings Meter; ECOMode; Energy efficiency class: A
Ecological Standards	Energy Star 7.0; RoHS compliant; TCO 7.0; WEEE







This document is © 2017 NEC Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 02.05.2017