
Thomas@Betts





4-Way T&B Catalog Number:

TC345A

UPC Number: 78621086804

Status: Active

Description:

Cable Tie 4-Way Mounting Base 1x1" Natural Nylon 6.6 Adhesive/Screw Mounting- #8 Screw For Use with Cable Ties Up to 50 lbs.

Features

Eliminates errors in premounting the base with respect to its orientation to wire bundle direction.

General Nylon 6.6 Color Natural Mounting Method Adhesive/Screw Stud Size #8 Screw Max Tie Width Accepted .19 For Cable Ties Up to 50 lbs. Dimension Information Length (inches) 1.125 Width (inches) 1.125 Specifications Temperature Rating -40°F to 185°F Flammability Rating UL 94 V-2 Packaging UL 94 V-2 Packaging T&B Order Multiple 1000 T&B Inner Pack 1000 Package in Units 5000 Package Type Bulk T&B Sold in UOM Each T&B Weight Per UOM 0.38 lbs. per 100 Application Support Wsd-000068 Material Selection Guide Available on Website Certifications Yes		spect to its orientation to wire bundle direction.
Color Natural Mounting Method Adhesive/Screw Stud Size #8 Screw Max Tie Width Accepted .19 For Cable Ties Up to 50 lbs. Dimension Information Length (inches) 1.125 Width (inches) 1.125 Specifications Temperature Rating -40°F to 185°F Flammability Rating UL 94 V-2 Packaging T&B Order Multiple 1000 T&B Inner Pack 1000 Package in Units 5000 Package Type Bulk T&B Sold in UOM Each T&B Weight Per UOM 0.38 lbs. per 100 Application Support T&B Sales Drawings wsd-000068 Material Selection Guide Available on Website Certifications	General	
Mounting Method Adhesive/Screw Stud Size #8 Screw Max Tie Width Accepted 19 For Cable Ties Dimension Information Length (inches) 1.125 Width (inches) 1.125 Specifications Temperature Rating -40°F to 185°F Flammability Rating UL 94 V-2 Packaging T&B Order Multiple 1000 T&B Inner Pack 1000 Package in Units 5000 Package Type Bulk T&B Sold in UOM Each T&B Weight Per UOM Application Support T&B Sales Drawings Wsd-000068 Material Selection Guide Available on Website Certifications	Material	Nylon 6.6
Stud Size #8 Screw Max Tie Width Accepted .19 For Cable Ties Up to 50 lbs. Dimension Information Length (inches) 1.125 Width (inches) 1.125 Specifications Temperature Rating -40°F to 185°F Flammability Rating UL 94 V-2 Packaging T&B Order Multiple 1000 T&B Inner Pack 1000 Package in Units 5000 Package Type Bulk T&B Sold in UOM Each T&B Weight Per UOM 0.38 lbs. per 100 Application Support T&B Sales Drawings wsd-000068 Material Selection Guide Available on Website Certifications	Color	Natural
Max Tie Width Accepted For Cable Ties Up to 50 lbs. Dimension Information Length (inches) 1.125 Width (inches) 1.125 Specifications Temperature Rating -40°F to 185°F Flammability Rating UL 94 V-2 Packaging T&B Order Multiple 1000 T&B Inner Pack 1000 Package in Units 5000 Package Type Bulk T&B Sold in UOM Each T&B Weight Per UOM Application Support T&B Sales Drawings Wsd-000068 Material Selection Guide Available on Website Certifications	Mounting Method	Adhesive/Screw
For Cable Ties Up to 50 lbs. Dimension Information Length (inches) 1.125 Width (inches) 1.125 Specifications Temperature Rating -40°F to 185°F Flammability Rating UL 94 V-2 Packaging T&B Order Multiple 1000 T&B Inner Pack 1000 Package in Units 5000 Package Type Bulk T&B Sold in UOM Each T&B Weight Per UOM 0.38 lbs. per 100 Application Support T&B Sales Drawings wsd-000068 Material Selection Guide Available on Website Certifications	Stud Size	#8 Screw
Dimension Information Length (inches) 1.125 Width (inches) 1.125 Specifications Temperature Rating -40°F to 185°F Flammability Rating UL 94 V-2 Packaging T&B Order Multiple 1000 T&B Inner Pack 1000 Package in Units 5000 Package Type Bulk T&B Sold in UOM Each T&B Weight Per UOM 0.38 lbs. per 100 Application Support T&B Sales Drawings wsd-000068 Material Selection Guide Available on Website Certifications	Max Tie Width Accepted	.19
Length (inches) Width (inches) Specifications Temperature Rating -40°F to 185°F Flammability Rating UL 94 V-2 Packaging T&B Order Multiple 1000 T&B Inner Pack 1000 Package in Units 5000 Package Type Bulk T&B Sold in UOM Each T&B Weight Per UOM Application Support T&B Sales Drawings Material Selection Guide Certifications	For Cable Ties	Up to 50 lbs.
Width (inches) Specifications Temperature Rating -40°F to 185°F Flammability Rating UL 94 V-2 Packaging T&B Order Multiple 1000 T&B Inner Pack 1000 Package in Units 5000 Package Type Bulk T&B Sold in UOM Each T&B Weight Per UOM Application Support T&B Sales Drawings Material Selection Guide Certifications	Dimension Information	
Width (inches) Specifications Temperature Rating -40°F to 185°F Flammability Rating UL 94 V-2 Packaging T&B Order Multiple 1000 T&B Inner Pack 1000 Package in Units 5000 Package Type Bulk T&B Sold in UOM Each T&B Weight Per UOM Application Support T&B Sales Drawings Material Selection Guide Certifications	Length (inches)	1.125
Temperature Rating -40°F to 185°F Flammability Rating UL 94 V-2 Packaging T&B Order Multiple 1000 T&B Inner Pack 1000 Package in Units 5000 Package Type Bulk T&B Sold in UOM Each T&B Weight Per UOM 0.38 lbs. per 100 Application Support T&B Sales Drawings wsd-000068 Material Selection Guide Available on Website Certifications		1.125
Flammability Rating Packaging T&B Order Multiple T&B Inner Pack Package in Units Package in Units Flammability Rating T&B Order Multiple T&B Inner Pack T&B Inner Pack T&B Inner Pack T&B Inner Pack T&B Solo in Units T&B Solo in UOM Flackage Type Bulk T&B Sold in UOM Each T&B Weight Per UOM Application Support T&B Sales Drawings Wsd-000068 Material Selection Guide Available on Website Certifications		
Flammability Rating Packaging T&B Order Multiple T&B Inner Pack Package in Units Flammability Rating UL 94 V-2 Ul	Temperature Rating	-40°F to 185°F
Packaging T&B Order Multiple 1000 T&B Inner Pack 1000 Package in Units 5000 Package Type Bulk T&B Sold in UOM Each T&B Weight Per UOM 0.38 lbs. per 100 Application Support T&B Sales Drawings wsd-000068 Material Selection Guide Available on Website Certifications		UL 94 V-2
T&B Inner Pack Package in Units 5000 Package Type Bulk T&B Sold in UOM Each T&B Weight Per UOM O.38 lbs. per 100 Application Support T&B Sales Drawings wsd-000068 Material Selection Guide Available on Website Certifications		
T&B Inner Pack Package in Units 5000 Package Type Bulk T&B Sold in UOM Each T&B Weight Per UOM O.38 lbs. per 100 Application Support T&B Sales Drawings wsd-000068 Material Selection Guide Available on Website Certifications		
Package in Units 5000 Package Type Bulk T&B Sold in UOM Each T&B Weight Per UOM Application Support T&B Sales Drawings Material Selection Guide Certifications S000 Bulk Contact on UOM Authorized Support Support Wasd-000068 Available on Website	<u>'</u>	
Package Type Bulk T&B Sold in UOM Each T&B Weight Per UOM 0.38 lbs. per 100 Application Support T&B Sales Drawings wsd-000068 Material Selection Guide Available on Website Certifications	T&B Inner Pack	1000
T&B Sold in UOM Each T&B Weight Per UOM 0.38 lbs. per 100 Application Support T&B Sales Drawings wsd-000068 Material Selection Guide Available on Website Certifications	Package in Units	5000
T&B Weight Per UOM Application Support T&B Sales Drawings wsd-000068 Material Selection Guide Available on Website Certifications	Package Type	Bulk
Application Support T&B Sales Drawings wsd-000068 Material Selection Guide Available on Website Certifications	T&B Sold in UOM	Each
T&B Sales Drawings wsd-000068 Material Selection Guide Available on Website Certifications	T&B Weight Per UOM	0.38 lbs. per 100
Material Selection Guide Available on Website Certifications	Application Support	
Material Selection Guide Available on Website Certifications	T&B Sales Drawings	wsd-000068
		Available on Website
RoHS Compliance Yes	Certifications	
	RoHS Compliance	Yes

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com