





**EN** - For pricing and availability in your local country please visit one of the below links:

**DE** - Informationen zu Preisen und Verfügbarkeit in Ihrem Land erhalten Sie über die unten aufgeführten Links:

FR - Pour connaître les tarifs et la disponibilité dans votre pays, cliquez sur l'un des liens suivants:

MDP2VGAMM3B

# ΕN

This Datasheet is presented by the manufacturer

#### DE

Dieses Datenblatt wird vom Hersteller bereitgestellt

#### FR

Cette fiche technique est présentée par le fabricant



# 3 ft Mini DisplayPort™ to VGA Adapter Converter Cable – mDP to VGA 1920x1200 - Black

StarTech ID: MDP2VGAMM3B



The MDP2VGAMM3B active Mini DisplayPort to VGA converter cable lets you connect your Mini DisplayPort-equipped desktop or laptop directly to a nearby VGA monitor or projector, saving the expense of additional adapters while eliminating the clutter of excess cable.

The adapter cable is compatible with Intel® ThunderboltFriday, September 27, 2013 9:00:45 PMrade;, when connected directly to a supporting DisplayPort over Thunderbolt I/O port. Plus, because the converter cable supports video resolutions up to 1920x1200 you can convert a DisplayPort video source to VGA without sacrificing video quality.

The MDP2VGAMM3B is backed by a 2-year StarTech.com warranty and free lifetime technical support.

# **Applications**

- Use your VGA monitor as a secondary display, connected to a Mini DisplayPort output
- Connect a Mini DisplayPort computer to a VGA projector for presentations or meetings in a boardroom or auditorium setting
- Connect your existing VGA display device (monitor, projector) to a DisplayPort output device (PC, laptop, Mac, Ultrabook)

#### **Features**

- Active Mini DisplayPort to VGA conversion
- Plug-and-Play Installation
- Supports resolutions up to 1920x1200 (WUXGA) and HDTV resolutions up to 1080p
- Compatible with Intel® Thunderbolt™ devices that are capable of outputting a DisplayPort signal



#### **Technical Specifications**

Warranty 2 Years

Audio No

Chipset ID ANALOGIX 9832

Converter Type Active

Connector A 1 - Mini-DisplayPort (20 pin) Male

Connector B 1 - VGA (15 pin; High Density D-Sub) Male

Maximum Analog Resolutions 1920x1200 / 1080p (Output)

Maximum Cable Length 915 mm [36 in]

Maximum Digital Resolutions 1920x1200 / 1080p (Input)

Cable Length 930 mm [36.6 in]

Color Black

Product Height 15 mm [0.6 in]
Product Length 930 mm [36.6 in]
Product Weight 79 g [2.8 oz]
Product Width 34 mm [1.3 in]

Humidity 40%-85%RH

Operating Temperature 0°C to 60°C (32°F to 140°F)
Storage Temperature -10°C to 70°C (14°F to 158°F)

Shipping (Package) Weight 90 g [3.2 oz]

Included in Package 1 - Mini DisplayPort® to VGA Adapter

#### Certifications, Reports and Compatibility













**EN** - For pricing and availability in your local country please visit one of the below links:

**DE** - Informationen zu Preisen und Verfügbarkeit in Ihrem Land erhalten Sie über die unten aufgeführten Links:

FR - Pour connaître les tarifs et la disponibilité dans votre pays, cliquez sur l'un des liens suivants:

MDP2VGAMM3B

# ΕN

This Datasheet is presented by the manufacturer

#### DE

Dieses Datenblatt wird vom Hersteller bereitgestellt

#### FR

Cette fiche technique est présentée par le fabricant