





**EN** - For pricing and availability in your local country please visit one of the below links:

**DE** - Informationen zu Preisen und Verfügbarkeit in Ihrem Land erhalten Sie über die unten aufgeführten Links:

FR - Pour connaître les tarifs et la disponibilité dans votre pays, cliquez sur l'un des liens suivants:

NETRS232

### ΕN

This Datasheet is presented by the manufacturer

## DE

Dieses Datenblatt wird vom Hersteller bereitgestellt

### FR

Cette fiche technique est présentée par le fabricant



### 1 Port RS-232 Serial to IP Ethernet Device Server - DIN Rail Mountable

StarTech ID: NETRS232



The NETRS232 Serial Device Server lets you remotely access and manage an RS232 serial device over a local or wide area network (LAN/WAN), giving you a simple and cost-effective serial-over-IP control solution.

For installation flexibility across a variety of locations or environments, you can power the serial device server using either a 12V DC power adapter (included) or through the integrated 10~30V DC terminal block. Plus, the device server is DIN rail mountable for out-of-the-way installations. To help ensure seamless performance and prevent possible damage to the server and connected devices, the serial device server offers 15KV ESD (Electrostatic Discharge) protection.

This highly-customizable device server is easy to configure to suit your application, with versatile browser-based or Virtual Com port software configuration and integrates support for VCOM, TCP Server/Client, UDP, HTTP, DHCP, ICMP(PING), Static IP, and ARP protocols, while supporting baud rates up to 230.4 Kbps and is compliant with IEEE 802.3. IEEE 802.3u standards.

Backed by a 2-year StarTech.com warranty and free lifetime technical support.

### **Applications**

- Manufacturing (CNC machinery, process control equipment, serial printers)
- Security (UPS control, access key panels, video cameras, card readers)
- Environmental control (lighting, temperature, clocks)
- POS (credit/debit card readers, receipt printers, cash registers, scales)
- Industrial automation (motion controllers, sensors)



### **Features**

- Solid housing design with DIN rail mounting bracket
- Power input via included 12V DC power adapter, or 10~30V DC terminal block
- 15KV ESD (Electrostatic Discharge) Protection
- Up to 230.4 Kbps baud rate
- Supports RS232 serial protocol
- Supports VCOM, TCP Server, TCP Client, UDP, HTTP, DHCP, ICMP(PING), Static IP, ARP
- Configurable via software utility, or web browser
- Compliant with IEEE 802.3 and IEEE 802.3u standards



# **Technical Specifications**

Warranty 2 Years

Ports 1

Interface Serial

Industry Standards IEEE 802.3, IEEE 802.3u

Connector Type(s) 1 - DB-9 (9 pin; D-Sub) Male

Connector Type(s) 1 - RJ-45 Female

Connector Type(s) 1 - Terminal Block (2 Wire)

Serial Protocol RS-232
Max Baud Rate 230.4 Kbps
Data Bits 5, 6, 7, 8

Flow Control RTS/CTS, None

Parity None, Even, Odd, Space, Mark

Stop Bits 1, 1.5, 2

Remote Management Ability Yes

Surge Protection 15KV ESD (Electrostatic Discharge) Protection

Compatible Networks 10/100 Mbps

Auto MDIX Yes

Supported Protocols VCOM, TCP Server, TCP Client, UDP, HTTP, DHCP, ICMP(PING), Static IP, ARP

OS Compatibility Windows® 8 / 8.1 (32/64bit), 7 (32/64), Vista (32/64), XP (32/64), 2000

Windows® Server 2012, 2008 R2, 2003 (32/64)

Color Black
Enclosure Type Plastic

Product Length 95 mm [3.7 in]
Product Width 55 mm [2.2 in]
Product Height 22 mm [0.9 in]
Product Weight 63 g [2.2 oz]
LED Indicators 1 - Power
LED Indicators 1 - Tx
LED Indicators 1 - Rx

LED Indicators 1 - 10/100Mbps LAN

LED Indicators 1 - Link/Activity
Input Voltage 100 ~ 240 AC

Input Current 480 mA
Output Voltage 12 DC
Output Current 1.2 A
Center Tip Polarity Power Consumption 1.45W Max

Operating Temperature 0°C to 60°C (32°F to 140°F)
Storage Temperature -10°C to 70°C (14°F to 158°F)





Humidity 0~90% RH

Shipping (Package) Weight 433 g [15.3 oz]

Included in Package 1 - Serial over IP Device Server

Included in Package 1 - DIN Rail Kit

Included in Package 1 - Terminal Block

Included in Package 1 - Universal Power Adapter (NA/UK/EU)

Included in Package 1 - Software CD

Included in Package 1 - Instruction Manual

# Certifications, Reports and Compatibility



















**EN** - For pricing and availability in your local country please visit one of the below links:

**DE** - Informationen zu Preisen und Verfügbarkeit in Ihrem Land erhalten Sie über die unten aufgeführten Links:

FR - Pour connaître les tarifs et la disponibilité dans votre pays, cliquez sur l'un des liens suivants:

NETRS232

### ΕN

This Datasheet is presented by the manufacturer

## DE

Dieses Datenblatt wird vom Hersteller bereitgestellt

### FR

Cette fiche technique est présentée par le fabricant