

CONNECTIVITY

PRODUCT OVERVIEW



	USB 2.0-LAN Adapter	USB 3.0-LAN-Adapter	VGA Conversion Cable	Slim HDMI Cable	Mini Travel Wireless Router	USB-Port Replicator PR07	USB-Port Replicator PR08
Type	LAN Adapter	LAN Adapter	Cable	Cable	Wireless Router	Port Replicator	Port Replicator
Length	-	-	-	3m	-	-	-
Data Rates	up to 480 Mbps	up to 5 Gbps	-	-	Wireless-N with speed up to 150Mbps	-	-
Frequency range	-	-	-	-	2.4-2.4835GHz	-	-
Wireless Security	-	-	-	-	WPS, WEP, WPA-PSK, WPA2-PSK or WPA-PSK/WPA2-PSK (TKIP/AES)	-	-
Power supply	Bus-powered	Bus-powered	Bus-powered	-	Bus-powered	Power Adapter	Power Adapter
Resolution	-	-	-	-	-	-	-
Required interface	USB Type A	USB Type A	HDMI	male / male	RJ45 Port	USB2.0	USB2.0/3.0
DisplayLink	-	-	-	-	-	-	-
LAN	10/100	10/100/1000	-	-	10/100	RJ45 Port	RJ45 Port
Graphic	-	-	-	-	-	-	-
USB	-	-	-	-	-	2x Downstream USB 2.0 and 1x Upstream USB 2.0 on the back, 2x Downstream USB 2.0 on the front	2x Downstream USB 2.0 and 1x Upstream USB 2.0 on the back, 2x Downstream USB 3.0 on the front
USB downstream	-	-	-	-	-	4 x Downstream USB 2.0 Port (Type A female connector)	2x Downstream USB 3.0 2x Downstream USB 2.0

USB upstream	-	-	-	-	-	1 x Upstream USB 2.0 Port (Type B female Connector)	1 x Upstream USB 2.0 Port (Type B female Connector)
VGA	-	-	-	-	-	via DVI-to-VGA adapter (included)	via DVI-to-VGA adapter (included)
DVI	-	-	-	-	-	1 (DVI-I)	1 (DVI-I)
Kensington Lock support	-	-	-	-	-	Industry-standard Kensington® security slot	Industry-standard Kensington® security slot
Audio	-	-	-	-	-	1 x microphone (3.5 mm stereo audio in) 1 x headphones/speaker (3.5 mm stereo audio out)	1 x microphone (3.5 mm stereo audio in) 1 x headphones/speaker (3.5 mm stereo audio out)
Weight	-	-	-	-	20g	204g	350g
Dimension	-	-	-	-	84 × 31 × 16mm	35 x 110 x 160mm	40 x 78 x 190 mm
P/N	HLCAB0019-01	HLCAB0027A-01	HLCAB0024-01	HLCAB0029A-01	HLROU0003B	S26391-F6007-L300	S26391-F6007-L400