

Internet Office UPS System

All-in-one SOHO solution



Model #: INTERNETOFFICE300

- ▶ 6 outlets (3 UPS/surge, 3 surge-only)
- ▶ Includes 1 line TEL/DSL or 10BaseT ethernet line surge suppression jacks
- ▶ Compact cabinet design fits easily on or under any desk
- ▶ \$100,000 Ultimate Lifetime Insurance (USA, Puerto Rico & Canada only)

DESCRIPTION

Tripp Lite's INTERNETOFFICE300 UPS System provides complete power protection for your entire computer set-up. 300 VA power capacity maintains your Internet connection allowing you to work online through short blackouts or safely shut down during longer ones. Unique design features 6 outlets (3 UPS & surge + 3 surge-only outlets) and diagnostic LEDs. Built-in RJ45 jacks prevent surges from damaging your modem/fax/10BT equipment. A 6-ft. telephone cord is also included. \$100,000 Ultimate Lifetime Insurance (USA & Canada Only) covers connected equipment.

KEY BUYING POINTS

- 300 VA output power rating (150 watts)
- Up to 11 minutes backup time (single PC; 15-in monitor)
- Battery run time: 10 minutes half load / 4 minutes full load
- 6 protected outlets (3 UPS & surge + 3 surge-only outlets); 6-ft. cord
- Built-in RJ45 jacks prevent surges from damaging your modem / fax / 10BT equipment; 6-ft. telephone cord included
- Complete surge protection and EMI/RFI noise filtering
- \$100,000 Ultimate Lifetime Insurance (USA & Canada Only) covers connected equipment
- 5 diagnostic LEDs indicate AC present, line fault, on battery, overload and battery low/replace

TYPICAL APPLICATIONS

- Personal computers with modems, network workstations, home-office workstations, point-of-sale terminals and more.

OPTIONS & ACCESSORIES

- Extended warranties: 3 Year [WEXT3-INTERNET](#), 5 Year [WEXT5-INTERNET](#)

PACKAGE INCLUDES

- INTERNETOFFICE300 UPS System
- 6-ft. telephone cord
- Instruction manual with warranty information

COMPLETE SPECIFICATIONS

SYSTEM OVERVIEW

System overview:

Ultra-compact standby UPS protects PCs, network workstations and other sensitive electronic equipment from blackouts, surges and line noise. Maintains AC output during

blackouts and brownouts starting at 99V. Includes TEL / DSL line surge suppression, surge-only outlets and LED indicators.

Voltage compatibility: 120V AC

Frequency compatibility: 50/60Hz

OUTPUT

Output volt amp capacity (VA): 300

Output watt capacity (watts): 150

Output nominal voltage: 120V AC

Output voltage regulation: LINE MODE: Passes sine wave line voltage from 100-141V to connected equipment unchanged
BATTERY MODE: PWM sine wave output 120V +/-5%

Output frequency regulation: LINE MODE: Passes line frequency of 60Hz +/-10%
BATTERY MODE: Inverter output regulated to 60Hz +/-0.5Hz

Outlet quantity / type: 6 NEMA 5-15R

INPUT

Input connection type: NEMA 5-15P

Input cord length: 6 ft., 14 gauge

Recommended electrical service: 15A 120V

BATTERY

Full load runtime: 4 minutes (300VA)

Half load runtime: 10 minutes (150VA)

DC system voltage: 12 VDC

Typical battery lifespan: 3-6 years, depending on usage

Battery recharge rate: 2-4 hours to 90%

LEDS ALARMS & SWITCHES

Front panel LEDs: 5 LEDs indicate complete UPS operational status

Switches: Power off / on switch

SURGE / NOISE SUPPRESSION

AC surge suppression: 380 joules

AC suppression response time: Instantaneous

Dataline suppression: Tel/DSL or Ethernet

EMI / RFI AC noise suppression: Yes

PHYSICAL

Shipping weight (lbs): 5.4

Shipping weight (kg): 2.5

Unit weight (lbs): 4

Unit weight (kg): 1.8

Unit Dimensions (HWD/in): 2.6 x 11 x 4.5

Unit Dimensions (HWD/cm): 6.6 x 27.9 x 11.4

Shipping Dimensions (HWD/in): 4.5 x 13 x 8.25

Shipping Dimensions (HWD/cm): 11.4 x 33 x 20.9

Material of construction: Plastic

Form factors supported: Ultra-compact

ENVIRONMENTAL

Operating Temperature: +32 to +104 degrees Fahrenheit
0 to +40 degrees Celsius

Storage Temperature: +5 to +122 degrees Fahrenheit
-15 to +50 degrees Celsius

Relative Humidity: 0 to 95%, non-condensing

COMMUNICATIONS

Network monitoring port: -

LINE / BATTERY TRANSFER

Transfer time from line power to battery mode: 2-4 milliseconds

Low voltage transfer to battery power: approx. 99VAC

High voltage transfer to battery power: approx. 141VAC

CERTIFICATIONS

Certifications: Tested to UL1778 (USA), CSA (Canada), Class B (emissions), NOM (Mexico), FCC Part 68 / Industry Canada (telecommunications)

WARRANTY

Optional coverage: Optional 3 and 5 year extended warranties available

Product warranty: 2 years

Connected equipment insurance (USA and Canada Only): \$100,000 connected equipment insurance (USA and Canada only)

SPECIAL FEATURES

Appearance: Attractive black ultra-compact housing

*The policy of Tripp Lite is one of continuous improvement.
Specifications are subject to change without notice.
Therefore, your product may vary slightly from what is currently listed.*



Tripp Lite World Headquarters
1111 W. 35th Street
Chicago, IL 60609 USA

Customer Support
(773) 869-1234

© 2007 Tripp Lite. All Rights Reserved.