

# Allied Telesis AT-SPLX40 Datasheet



Allied Telesis AT-SPLX40 1000LX SFP, LC, SMF, 1310nm, (40 km) SFP Transceiver Module

AT-SPLX40

Allied Telesis AT-SPLX40 1000LX SFP, LC, SMF, 1310nm, (40 km) SFP Transceiver Module

The Allied Telesis SP Series delivers flexible, full-duplex Ethernet connectivity. These hot-swappable fiber and copper interfaces simply plug into the SFP slot on all SFP-compatible devices. Configuration can be optimized to meet a wide variety of distance and service requirements. The SPLX40 offers a long-haul option to extend your network up to 40km.

## Specifications

- Part Number: AT-SPLX40
- Fiber Tyep: SMF
- Connector: LC
- Maximum Distance: 40km
- Wavelength: 1310nm
- DDM: Yes
- Transmit: -4 ~ 1 dBm
- Receive Sensitivity: -23dBm
- Power Budget: 19dBm
- Over-load: -1dBm
- Operating Temperature: 0°C to 70°C (32°F to 158°F)

Fore more information of this Allied Telesis AT-SPLX40, please visit Allied Telesis website:

<https://www.alliedtelesis.com/us/en/products/transceivers/1G/splx40>

[Buy Now](#)