

# Turn Up The Pressure On Dense Coil Beds

Here's a simple way to tackle multi-pass coil cleaning.



## CC-600 – Powerful and Portable

High flow is the way to go for cleaning thick, hard-to-reach coil beds. The CC-600 High Flow CoilPro® is powerful enough to penetrate coil beds up to 8" thick. It connects to a water line for continuous flow or it can draw from two internal 5 gallon tanks for remote or hard-to-reach jobs. The CC-600 applies a thick layer of cleaner through the same custom foaming nozzle featured in our award-winning CC-140 CoilPro. For environmentally friendly, fume-free cleaning, our expanding-foam detergent, CoilShine®, is the only choice. And it's included with the High Flow CoilPro. Whether you're inside or outdoors, the CC-600 High Flow CoilPro is the preferred choice for heavy-duty coils.



PATENT PENDING



### CC-600

High Pressure CoilPro Coil Cleaner, including 25' hose, spray gun with 18" wand, three nozzles (foaming, flat spray and pinpoint), and a 1 gallon bottle of CoilShine

**Note:** Call for accessories.

### Wet/Dry Coil Cleaning System:

An unbeatable package of innovative technology, the CC-600-KIT combines the CC-600 with our CoilVac® (see page 147) for a complete coil cleaning system.



### CC-600-KIT

Same as CC-600 with a CoilVac Dry HEPA Vacuum, CoilVac mounting bracket and tool bin

## FEATURES

- > 600 PSI at 1.6 GPM
- > Integrated 5 gallon water tank and 5 gallon chemical tank
- > Control valve to inject chemicals at 6:1 ratio (can be factory adjusted)
- > 18" wand and four custom nozzles
- > Heavy-duty ergonomic cart with stair glides
- > Wide variety of custom attachments

Specifications	CC-600
Motor Power	1.3 HP
Input Power	Standard: 13 amps, 115 V, 60 Hz AC Optional: 6.5 amps, 230 V, 50 Hz
Water Requirements	Maximum 120 PSI
Output Water Pressure	600 PSI
Output Water Flow	1.6 GPM
Pump	Positive displacement diaphragm
Water Tank	5 gallons
Soap Tank	5 gallons
Dimensions	44" high x 26" wide x 18" deep
Weight	85 lbs net dry



FOR MORE INFORMATION CONTACT



**GOODWAY®**

Goodway Technologies Corporation  
420 West Avenue  
Stamford, CT 06902-6384 U.S.A.  
Tel: +1-203-359-4708 • Fax: +1-203-359-9601  
E-Mail: [goodway@goodway.com](mailto:goodway@goodway.com)  
[www.goodway.com](http://www.goodway.com)