CS-SP200-A0-216WFBS



Key Features

Ultra HD 4K 15FPS Video			
16MP Image Sensor			
Electronic Image Stabilization			
Built-In G-Sensor			
Built-In Dual Mic Noise Reduction,			
wind noise reduce			
Support Micro SD card slot, up to 128GB			
Waterproof housing 40m			
Distortion Correction			
Built-In Touchable IPS Screen (Res: 320*240)			

Introduction

S5 action camera provides a more affordable 4K high-end solution, with 4K 15fps video recording capability and 16MP photos. It supports as high as 15 photos/s burst mode and time lapse mode of 5 minutes intervals. 15 seconds exposure time gives you a perfect solution for night pictures. Besides, in S5 there're highresolution touchable screen and super aspheric lens. Our innovative EIS (electronic stability system) and distortion correction technology is used to ensure a smooth and pleasant experience during video recording.



Dimension



OPTIONAL COLOR



MATT CHAMPAGNE



MATT RED



MATT GREY



MATT BLUE



SPECIFICATION

		Resolution	NTSC(fps)	PAL(fps)	Field Of View	
Video		4K SuperView	15	12.5	Wide	
		4K	15	12.5	Wide	
		2.7k Superview	30	25	Wide	
		2.7K Superview	24/30	23	Wide/Medium	
		2.7K 4:3	30	25	Wide	
		1440P	24/30/48/60	24/25/48/50	Wide	
	Video Format	1080P SuperView	24/30/48/60	24/25/48/50	Wide	
		1080P	24/30/48/60	24/25/48/50	Wide/Medium/Narrow	
		960P	60/120	50/100	Wide	
		720P SuperView	60/120	50/120	Wide	
		720P	30/60/120	25/50/120	Wide/Medium/Narrow	
		WVGA	240	240	Wide	
		H.264 BP/MP/HP Level 5.1 With MP4 Muxer File Format				
	Record Mode	Video, Video+Photo				
	Low Light	Auto Adjust Frame Rate for enough exposure time purpose				
	Distortion Correct	Better X/Y Correct				
	EIS	Advanced EIS with X/Y/Z+rotation correct				
	HiLight Tag	High Light Important Time, used for Post processing				
	Loop Mode	To set up the storage mode according to the time interval set				
	Photo Size	16MP Wide、12MP Wide、8MP Medium、5MP Wide				
	Night	2s、5s、10s、15s				
Single	Distortion Correct	Better X/Y Correct				
Single	Meter Mode	Center, Average, Spot				
	Protune	White Balance, ISO, Sharpness, Ev Comp, Color Pattern				
Burst	Photo Size	16MP Wide、 12MP Wide、 8MP Medium、 5MP Wide				
	Burst Rate	15 pictures 1 second 15 pictures 2 seconds 15 pictures 3 second 10 pictures 1 seconds 10 pictures 2 second 10 pictures 3 second 5 pictures 1 second (default) 3 pictures 1 second				
	Distortion Correct	Better X/Y Correct				
	Meter Mode	Center Average Spot				
	Protune	White Balance、ISO、Sharpness、Ev Comp、Color Pattern				
	Shutter Mode	Timelapse Photo, Timelapse Video				
	Photo Size	16MP Wide、12MP Wide、8MP Medium、5MP Wide				
	Video Resolution	4K SuperView、4K、2.7k Superview、2.7K 4:3、1440P、1080P SuperView				
Timelapse		1080P、960P、720P SuperView、720P、WVGA				
	Shutter Interval	1s、3s、5s、10s、30s、60s、120s、300s				
	Meter Mode					
	Night	Center Average Spot 2s,5s,10s,15s				
	Distortion Correct	Better X/Y Correct				
	Protune	White Balance, ISO, Sharpness, Ev Comp, Color Pattern				



Playback	Decode Photo and V	/ideo Files in sd C	Card and Display it via LCD or HDTV			
	View	Up, Down, Auto				
Setup	Default Mode	Video, Single, Burst, Timelapse				
	Driving Mode	The camera automatically starts and Shutter after the camera detects the motion				
	Vout Mode	Switching HDMI HD output and AV analog output				
	LED	Set it on or off				
	Beeps	Set the Gain of Beeps or Turn it off				
	OSD	Turn on screen display on or off				
	Quickly Capture	Camera will Fastest speed boot and start shutter				
	Auto Off	Set Auto Power Off Time				
	Date And Time	Set Date And Time				
	Mic Gain	Set The Gain of Mic				
	Speaker Gain	Set The Gain of Speaker				
	Camera Reset	Reset Camera to default Settings				
	BLE 4.0	Embedded bluetooth4.0				
		802.11b/g/n、Mobile App Support				
Wireless	WIFI	App&Remote	Select connect Mode with Mobile App Or Wifi Remoter			
	W II I	SSID	Support SSID Modify with Mobile App			
		KEY	Support KEY Modify with Mobile App			
		RESET	Reset SSID and KEY to system default			
Display	HDMI AV	Display With				
Display	Embedded LCD	AV output Use USB Interface bedded LCD 320x240 LCD With Touch Pannel				
Lens Specifica-	1/2.33" CMOS					
tion	Full glass lens for high	gh image quality,	3mm@f2.8 158°Ultra-wide angle of view with less distortion			
Platform	Ambarella new gene	a new generation Video Processor, using advanced 28-nm silicon technology				
Memory	4Gb LPDDR3、2Gb					
Sensor	Panasonic new gener	ration video senso	ration video sensor for sport dv			
	Battery Type	Replaceable Rechargeable li-ion battery				
Battery	Battery Parameters	1160mAh				
	Battery Life		s with different video mode)			
	48kHz (sampling), AAC compression					
Audio	Advanced AGC (automatic gain control) Build-in two microphone for wind noise reduce					
	Single track					
	Beeps for shutter not	-				
Interface	Micro USB3.0	For charging when connect with power cable; For playback/file transportation/charging when connecting with PC;				
		AV output	e dunsportation enarging when connecting with re,			
	Micro HDMI		TV via HDMI cable			
	MicroSD	Storage card				
Storage	Standard	· · ·	o UHS-1 level Micro SD storage card			
Storage	Capacity		6GB、32GB、64GB、128GB			
IMU	Recording Time G sensor/Gyro	Varies with different resolution and frame rate				
Photo/Video Pre-	2	For EIS、Driving Mode、Motion Awake				
view/Playback /	App for Mobile Device	For iOS and Android system Live view, playback, recording, configuration, video file editing, and one-touch				
Setup		share to social media are supported.				
	Camera	40 meters diving with water-proof case				
Protection Grade Operating Condi-	Remote Temperature: -20° C	IP67 to 45° C:				
I DELATING I ODDI	remperature: -20° C	to 45° C;				
tions						
	58mm(W)×45mm(H)×20.6(W)				
tions	58mm(W)×45mm(About 99.7g	H)×20.6(W)				