

HIKTEHRAN

نماینده مجاز فروش محصولات هایک ویژن



آدرس فروشگاه

تهران ، خیابان جمهوری پاساژ امجد طبقه همکف پلاک 28

شماره تماس

66765923 - 66765968 - 09197108350







ایمیل











Info@Hikvisiontehran.com








CONTACT US

HIKVISIONTEHRAN.COM

Turbo HD Camera - DVR

Items	Description	User Price	
Turbo HD - 2MP			
1	DS-2CE16C0T-IRP DS-2CE16C0T-IRPHD720P IR Bullet Camera • 1.0 Megapixel high-performance CMOS • Analog HD output, up to 720P resolution • True Day/Night • DNR, Smart IR • Up to 20m IR distance • IP66 weatherproof	IRR 2,338,000	
2	DS-2CE56C0T-IRP DS-2CE56C0T-IRPHD720P Indoor IR Turret Camera • 1.0 Megapixel high-performance CMOS • Analog HD output, up to 720P resolution • True Day/Night • DNR, Smart IR • Up to 20m IR distance	IRR 2,058,000	
3	DS-2CE56C0T-IRPF HD720P Indoor IR Turret Camera • 1.0 Megapixel high-performance CMOS • Analog HD output, up to 720P resolution • True Day/Night • DNR, Smart IR • Up to 20m IR distance • Switchable TVI/AHD/CVI/CVBS	IRR 2,212,000	
4	DS-2CE56D0T-IRMM HD1080p,2MP CMOS Sensor, 12 pcs LEDs, 20m IR, Indoor IR Dome, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, 3.6/6mm Lens	Call	
5	DS-2CE16D0T-IR HD1080p,2MP CMOS Sensor, 24 pcs LEDs, 20m IR, Outdoor IR Bullet, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, IP66, 3.6/6mm Lens	Call	
6	DS-2CE56D0T-IR HD1080p,2MP CMOS Sensor, 24 pcs LEDs, 20m IR, Outdoor IR Eyeball, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, IP66, 3.6/6mm Lens	Call	

7	DS-2CE56D0T-IRM	HD1080p,2MP CMOS Sensor, 24 pcs LEDs, 20m IR, Outdoor IR Eyeball, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, IP66, 3.6/6mm Lens	Call	
8	DS-2CE16D0T-IT1	HD1080p,2MP CMOS Sensor, 2 pcs EXIR LEDs, 20m IR, Outdoor EXIR Bullet, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, IP66, 3.6/6mm Lens	Call	
9	DS-2CE16D0T-IT3	HD1080p,2MP CMOS Sensor, 2 pcs EXIR LEDs, 40m IR, Outdoor EXIR Bullet, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, IP66, 3.6/6/8/12/16mm Lens	Call	
10	DS-2CE16D0T-IT5	HD1080p,2MP CMOS Sensor, 4 pcs EXIR LEDs, 80m IR, Outdoor EXIR Bullet, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, IP66, 3.6/6/8/12/16mm Lens	Call	
11	DS-2CE16D0T-WL5	HD 1080p White Supplement Light Bullet Camera 2 Megapixel high-performance CMOS, Analog HD output, up to 1080P resolution White supplement light (up to 50 m distance),IP66,Up the Coax(HIKVISION-C)	ناموجود	
12	DS-2CE56D0T-IT1	HD1080p,2MP CMOS Sensor, 2 pcs EXIR LEDs, 20m IR, Outdoor EXIR Eyeball, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, IP66, 3.6/6mm Lens	Call	
13	DS-2CE56D0T-IT3	HD1080p,2MP CMOS Sensor, 2 pcs EXIR LEDs, 40m IR, Outdoor EXIR Eyeball, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, IP66, 3.6/6/8/12/16mm Lens	Call	
14	DS-2CE56D1T-VFIR3	HD1080p,2MP CMOS Sensor, 42 pcs IR LEDs, 40m IR, Outdoor IR Vari-focal Eyeball, ICR, 0.1 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), IP66, 2.8~12mm Lens	Call	
15	2mp+poc			
16	DS-2CE16D0T-IRE	HD1080p,2MP CMOS Sensor, 24 pcs LEDs, 20m IR, Outdoor IR Bullet, ICR, 0.1 Lux/F1.2, 12 VDC & built-in PoC , Smart IR, DNR, IP66, 3.6/6mm Lens	IRR 4,109,000	
17	DS-2CE16D0T-IT1E	HD1080p,2MP CMOS Sensor, 2 pcs EXIR LEDs, 40m IR, Outdoor EXIR Bullet, ICR, 0.1 Lux/F1.2, 12 VDC & built-in PoC , Smart IR, DNR, IP66, 3.6/6/8/12/16mm Lens	IRR 4,893,000	

18	DS-2CE56D0T-IT1E	2M , EXIR, 20m IR, Outdoor EXIR Eyeball, ICR, 12 VDC & built-in PoC , Smart IR DNR, OSD Menu(Up the Coax), IP67, 2.8/3.6/6mm Lens	IRR 4,683,300	
19	DS-2CE56D0T-IT3E	2M , EXIR, 40m IR, Outdoor EXIR Eyeball, ICR, 12 VDC & built-in PoC , Smart IR DNR, OSD Menu(Up the Coax), IP67, 2.8/3.6/6mm Lens	IRR 4,991,500	
20	DS-2CE16D0T-VFIR3E	2 megapixel highperformance CMOS □ Analog HD output, up to 1080p resolution □ Day/Night switch □ Smart IR □ Up to 40m IR distance □ Switchable TVI/AHD/CVI/CVBS- □ IP66-Lens 2.8 - 12 mm @ F1.4 Angle of view: 102.25° - 32 °	IRR 11,280,000	
21	DS-2CE56D0T-VFIR3E	□ 2 megapixel highperformance CMOS □ Analog HD output, up to 1080p resolution □ Day/Night switch □ Smart IR □ Up to 40m IR distance □ Switchable TVI/AHD/CVI/CVBS- □ IP66-Lens 2.8 - 12 mm @ F1.4	IRR 11,280,000	
22	Starlight Value Series			
23	DS-2CE16D8T-ITE	2M Smart FSI CMOS Sensor, EXIR, 20m IR, Outdoor EXIR Bullet, ICR, 0.005 Lux/F1.2, 12 VDC/built-in PoC, Smart IR, 3D DNR, OSD Menu(Up the Coax), True WDR, IP66, 2.8/3.6/6mm Lens	IRR 6,043,400	
24	DS-2CE56D8T-ITME	2M Smart FSI CMOS Sensor, EXIR, 20m IR, Outdoor EXIR Eyeball, ICR, 0.005 Lux/F1.2, 12 VDC & built-in PoC, Smart IR, 3D DNR, OSD Menu(Up the Coax), True WDR, IP67, 2.8/3.6/6mm Lens	IRR 6,043,400	
25	DS-2CE16D8T-IT3E	2M Smart FSI CMOS Sensor, EXIR, 40m IR, Outdoor EXIR Bullet, ICR, 0.005 Lux/F1.2, 12 VDC/built-in PoC, Smart IR, 3D DNR, OSD Menu(Up the Coax), True WDR, IP66, 3.6/6/8/12/16mm Lens	IRR 10,830,000	
26	DS-2CE16D8T-IT3ZE	□ 2 MP high performance COMS □ Ultra-Low Light □ 1920 x 1080 resolution □ Auto focus, 2.8 mm to 12 mm motorized vari-focal lens □ 120 dB true WDR, 3D DNR □ EXIR 2.0, Smart IR, up to 40 m IR distance □ IP67 □ PoC.at □ Up the Coax (HIKVISION-C)	IRR 12,388,300	
27	DS-2CE56D8T-IT1E	2M Smart FSI CMOS Sensor, EXIR, 20m IR, Outdoor EXIR Eyeball, ICR, 0.005 Lux/F1.2, 12 VDC/built-in PoC, Smart IR, 3D DNR, OSD Menu(Up the Coax), True WDR, IP66, 2.8/3.6/6mm Lens	IRR 6,351,600	
28	Turbo HD - 3MP			

29	DS-2CE16F1T-IT	3MP,3MP CMOS Sensor, 18fps at 1920*1536 resolution, EXIR, 20m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), IP66, 2.8/3.6/6mm Lens	IRR 5,330,000	
30	DS-2CE56F1T-ITM	3MP,3MP CMOS Sensor, 18fps at 1920*1536 resolution, EXIR, 20m IR, Outdoor EXIR Eyeball, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), IP66, 2.8/3.6/6mm Lens	IRR 5,330,000	
31	DS-2CE16F1T-IT1	3MP,3MP CMOS Sensor, 18fps at 1920*1536 resolution, EXIR, 20m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), IP66, 2.8/3.6/6mm Lens	IRR 6,020,000	
32	DS-2CE16F1T-IT3	3MP,3MP CMOS Sensor, 18fps at 1920*1536 resolution, EXIR, 40m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), IP66, 3.6/6/8/12/16mm Lens	IRR 6,910,000	
33	DS-2CE16F1T-IT5	3MP,3MP CMOS Sensor, 18fps at 1920*1536 resolution, EXIR, 80m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), IP66, 3.6/6/8/12/16mm Lens	IRR 7,220,000	
34	DS-2CE56F1T-IT1	3MP,3MP CMOS Sensor, 18fps at 1920*1536 resolution, EXIR, 20m IR, Outdoor EXIR Eyeball, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), IP66, 2.8/3.6/6mm Lens	IRR 4,380,000	
35	DS-2CE56F1T-IT3	3MP,3MP CMOS Sensor, 18fps at 1920*1536 resolution, EXIR, 40m IR, Outdoor EXIR Eyeball, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), IP66, 3.6/6/8/12/16mm Lens	IRR 4,912,500	
36	DS-2CE16F7T-IT3Z	3MP,3MP CMOS Sensor, 18fps at 1920*1536 resolution, EXIR, 40m IR, Outdoor EXIR Motorized Vari-focal Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), True WDR , IP66, 2.8~12mm Motorized Vari-focal Lens	IRR 15,108,500	
37	DS-2CE56F7T-IT3Z	3MP,3MP CMOS Sensor, 18fps at 1920*1536 resolution, EXIR, 40m IR, Outdoor EXIR Motorized Vari-focal Eyeball, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, OSD Menu(Up the Coax), True WDR , IP66, 2.8~12mm Motorized Vari-focal Lens	IRR 15,108,500	
38	Turbo HD - 5MP			

39	DS-2CE16H0T-ITF	<p>5 MP Bullet Camera• 5 Megapixel high-performance CMOS</p> <ul style="list-style-type: none"> • Analog HD output, up to 5MP resolution• True Day/Night • OSD menu, 2D DNR, DWDR• EXIR technology, up to 20m IR distance • IP67• 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) <ul style="list-style-type: none"> • Up the Coax(HIKVISION-C) 	IRR 5,364,000	
40	DS-2CE16H0T-IT1F	<p>5 MP Bullet Camera• 5 Megapixel high-performance CMOS• Analog HD output, up to 5MP resolution• True Day/Night• OSD menu, 2D DNR, DWDR</p> <ul style="list-style-type: none"> • EXIR technology, up to 20m IR distance • IP67 • 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) <ul style="list-style-type: none"> • Up the Coax(HIKVISION-C) 	IRR 5,846,400	
41	DS-2CE16H0T-IT3F	<p>5 MP Bullet Camera• 5 Megapixel high-performance CMOS• Analog HD output, up to 5MP resolution• True Day/Night• OSD menu, 2D DNR, DWDR</p> <ul style="list-style-type: none"> • EXIR technology, up to 40m IR distance • IP67 • 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) <ul style="list-style-type: none"> • Up the Coax(HIKVISION-C) 	IRR 6,314,000	
42	DS-2CE16H0T-IT5F	<p>5 MP Bullet Camera• 5 Megapixel high-performance CMOS• Analog HD output, up to 5MP resolution• True Day/Night• OSD menu, 2D DNR, DWDR</p> <ul style="list-style-type: none"> • EXIR technology, up to 80m IR distance • IP67 • 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) <ul style="list-style-type: none"> • Up the Coax(HIKVISION-C) 	IRR 6,790,000	
43	DS-2CE16H0T-IT3ZF	<p>5 MP Bullet Camera• 5 Megapixel high-performance CMOS• Analog HD output, up to 5MP resolution• 2.7-13.5mm motorized vari-focal lens• True Day/Night• OSD menu, 2D DNR, DWDR• EXIR technology, up to 40m IR distance • IP67• PoC.at</p> <ul style="list-style-type: none"> • Up the Coax(HIKVISION-C) 	IRR 10,892,000	
44	DS-2CE56H0T-ITMF	<p>5 MP Turret Camera• 5 Megapixel high-performance CMOS• Analog HD output, up to 5MP resolution• True Day/Night• OSD menu, 2D DNR, DWDR• EXIR technology, up to 20m IR distance • IP67 weatherproof• 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)</p> <ul style="list-style-type: none"> • Up the Coax(HIKVISION-C) 	IRR 4,893,000	
45	DS-2CE56H0T-IT1F	<p>5 MP Turret Camera• 5 Megapixel high-performance CMOS• 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)• True Day/Night</p> <ul style="list-style-type: none"> • OSD menu, 2D DNR, DWDR• EXIR technology, up to 20m IR distance • IP67 weatherproof• 2560 x 1944 resolution• Up the Coax(HIKVISION-C) 	IRR 6,004,000	
46	DS-2CE56H0T-IT3F	<p>5 MP Turret Camera• 5 Megapixel high-performance CMOS• 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)• True Day/Night</p> <ul style="list-style-type: none"> • OSD menu, 2D DNR, DWDR• EXIR technology, up to 40m IR distance • IP67 weatherproof• 2560 x 1944 resolution• Up the Coax(HIKVISION-C) 	IRR 6,170,400	
47	DS-2CE56H0T-IT3ZF	<p>Lens: 2.7-13.5mm/F1.2-Horizontal Field of View: 95.7°-29.1°Resolution: 2560x1944px Image sensor: 5 MP CMOS image sensor-Function: day/night ICR-DNR -D-WDR AGC-BLC-Smart IR-Mirror-Min. Illumination: 0.01Lx-IR distans: 40m-Power supply: DC 12VDC Power consumption: max. 6.3W-Dimensions: 123.86x134.3x110.11mm Weight: 580g-Temperature of work: -40°C~60°C</p>	IRR 10,728,100	
48	Turbo HD - 5MP - Built in PoC			

49









DS-2CE16H1T-ITE











5MP@20fps, 4MP@25fps(P)/30fps(N)(Default), EXIR, 20m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC/built-in PoC, Smart IR, DNR, OSD Menu(Up the Coax), IP66, 2.8/3.6/6mm Lens









IRR 6,636,000









50	DS-2CE16H1T-IT1E	<ul style="list-style-type: none"> 5 MP high-performance CMOS 2560 × 1944 resolution 2.8 mm, 3.6 mm, 6 mm fixed focal lens EXIR 2.0, smart IR, up to 20 m IR distance OSD menu, DNR, DWDR IP67 PoC.af Up the coax (HIKVISION-C) -Lens 2.8 mm, 3.6 mm, 6 mm fixed focal lens 	IRR 7,581,000	
51	DS-2CE16H1T-IT3E	<ul style="list-style-type: none"> 5 MP HD EXIR PoC Bullet Camera 5 Megapixel high-performance CMOS Analog HD output, up to 5MP resolution True Day/Night OSD menu, DNR, Smart IR EXIR technology, up to 20/40/80m IR distance IP67 poC.af Up the Coax(HIKVISION-C)40m IR 	IRR 8,211,000	
52	DS-2CE16H1T-IT5E	5MP@20fps, 4MP@25fps(P)/30fps(N)(Default), EXIR, 80m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC/built-in PoC, Smart IR, DNR, OSD Menu(Up the Coax), IP66, 3.6/6/8/12/16mm Lens	IRR 8,841,000	
53	DS-2CE16H1T-IT3ZE	<ul style="list-style-type: none"> 5 MP HD Motorized VF EXIR PoC Bullet Camera 5 Megapixel high-performance CMOS Analog HD output, up to 5MP resolution 2.8-12mm motorized vari-focal lens True Day/Night OSD menu, DNR, Smart IR EXIR technology, up to 40m IR distance IP67 PoC.at Up the Coax(HIKVISION-C) 	IRR 13,265,000	
54	DS-2CE56H1T-ITME	5MP@20fps, 4MP@25fps(P)/30fps(N)(Default), EXIR, 20m IR, Outdoor EXIR Eyeball, ICR, 0.01 Lux/F1.2, 12 VDC/built-in PoC, Smart IR, DNR, OSD Menu(Up the Coax), IP66, 2.8/3.6/6mm Lens	IRR 6,636,000	
55	DS-2CE56H1T-IT1E	5MP@20fps, 4MP@25fps(P)/30fps(N)(Default), EXIR, 20m IR, Outdoor EXIR Eyeball, ICR, 0.01 Lux/F1.2, 12 VDC/built-in PoC, Smart IR, DNR, OSD Menu(Up the Coax), IP66, 2.8/3.6/6mm Lens	IRR 7,581,000	
56	DS-2CE56H1T-IT3E	<ul style="list-style-type: none"> 5 Megapixel high-performance CMOS Analog HD output, up to 5MP resolution True Day/Night OSD menu, DNR, Smart IR EXIR technology, up to 20/40m IR distance IP67 weatherproof Up the Coax(HIKVISION-C)40m IR 	IRR 8,211,000	
57	DS-2CE56H1T-IT3ZE	5MP@20fps, 4MP@25fps(P)/30fps(N)(Default), EXIR, 40m IR, Outdoor EXIR Motorized Vari-focal , ICR, 0.01 Lux/F1.2, 12 VDC/built-in PoC, Smart IR, DNR, OSD Menu(Up the Coax), IP66, 2.8~12mm Motorized Vari-focal Lens	IRR 13,265,000	
58	DS-2CC52H1T-FITS	HD 5MP IR Fisheye Camera, 5 Megapixel high-performance CMOS, Analog HD output, up to 5MP resolution, 0.01Lux @ (F1.2,AGC ON), 0 Lux with IR, IR cut filter with auto switch, OSD menu, Built-in microphone, 1-ch audio output, Up the Coax(HIKVISION-C)	IRR 21,754,900	
59	TURBO HD 5MP (TURBO HD 5.0) PIR Series			










60	DS-2CE11H0T-PIRL	5 MP high performance CMOS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm fixed focal lens PIR detection, visual alarm - EXIR 2.0, smart IR, up to 20 m IR distance - IP67 - Up the coax (HIKVISION-C) - 0.01 Lux@(F1.2, AGC ON), 0 Lux with IR	IRR 5,530,000	
61	DS-2CE12H0T-PIRL	5 MP high performance CMOS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm fixed focal lens PIR detection, visual alarm - EXIR 2.0, smart IR, up to 20 m IR distance - IP67 - Up the coax (HIKVISION-C) - 0.01 Lux@(F1.2, AGC ON), 0 Lux with IR	IRR 5,999,000	
62	DS-2CE71H0T-PIRL	5 MP high performance CMOS - 2560 × 1944 resolution - 2.8 mm, 3.6 mm fixed focal lens PIR detection, visual alarm - EXIR 2.0, smart IR, up to 20 m IR distance - IP67 - Up the coax (HIKVISION-C) - 0.01 Lux@(F1.2, AGC ON), 0 Lux with IR	IRR 5,530,000	
63	DS-2CE38D8T-PIR	2.0 megapixel progressive scan CMOS - Ultra-Low Light PIR Cube Camera - Color: 0.005 Lux @ (F1.2, AGC ON), 0 Lux with IR - 2.8 mm, 3.6 mm fixed focal lens - Backlight Compensation: WDR/BLC/OFF - Motion Detection: 4 programmable motion areas	IRR 6,314,000	
64	Turbo HD - 8MP			
65	DS-2CE78U8T-IT3	4K Ultra-Low Light Turret Camera• 8.29 Megapixel high-performance CMOS • Ultra-low light• 3840 × 2160 resolution• 2.8 mm, 3.6 mm, 6 mm fixed focal lens• 120 dB true WDR, 3D DNR• EXIR 2.0, smart IR, up to 60m IR distance • IP67• Up the Coax(HIKVISION-C)	IRR 17,225,700	
66	DS-2CE18U8T-IT3	K Ultra-Low Light Bullet Camera• 8.29 Megapixel high-performance CMOS • Ultra-low light• 3840 × 2160 resolution• 2.8 mm, 3.6 mm, 6 mm fixed focal lens • 120 dB true WDR, 3D DNR• EXIR 2.0, smart IR, up to 60m IR distance • IP67• Up the Coax(HIKVISION-C)	IRR 18,130,200	
67	Turbo HD PTZ Camera			
68	DS-2AE5223TI-A (24VAC)	1/3" CMOS, 1920x1080:30fps, TVI & CVBS dual output , 3D DNR, ICR, Color: 0.05lux/F1.4, B/W:0.005lux/F1.4, Optical Zoom:23x, Focus:4.0-92mm, Digital Zoom:16X, Pan range:360° endless; Tilt range: -15°~90°(Auto Flip), Pan Speed: 0.1° -400°/s, Tilt Speed: 0.1° -120°/s, Up the Coax, 150m IR	IRR 53,480,000	
69	DS-2AE7230TI-A (24VAC)	1/2.8" CMOS, 1920x1080:30fps, 3D DNR, ICR, Color: 0.2lux/F1.6, B/W:0.02lux/F1.6, Optical Zoom:30x, Focus:4-120mm, Digital Zoom:16X, Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -120°/s, 120m IR distance, Up the Coax	IRR 68,453,000	
70	Turbo HD DVR 720P			










71	DS-7208HGHI-F1	Support H.264+/H.264 video compression - Support HDTV/AVI/CVI/AVBS/IP video input - Up to 5/10/18-ch 960p IP camera input for DS-7204/7208/7216HGHI-F1/N - Max. 1200 m for 720p HDTV signal - IP Video Input Resolution Up to 2 MP resolution - 1 SATA Interface Up to 6 TB capacity for each disk - 2 USB 2.0 Interfaces	IRR 11,739,000	
72	DS-7216HGHI-F1	Support H.264+/H.264 video compression - Support HDTV/AVI/CVI/AVBS/IP video input - Up to 5/10/18-ch 960p IP camera input for DS-7204/7208/7216HGHI-F1/N - Max. 1200 m for 720p HDTV signal - IP Video Input Resolution Up to 2 MP resolution - 1 SATA Interface Up to 6 TB capacity for each disk - 2 USB 2.0 Interfaces	IRR 14,511,000	
73	Turbo HD DVR 1080p/3Mp			
74	DS-7204HQHI-K1	4 Turbo HD/AVI/Analog interface input, 4-ch video&1-ch audio input, H.265/H.265+ compression, 1 SATA interface, CH01: 3MP @ 15fps, CH02-04:1920x1080P @15 fps/ch , support CVBS output, standalone 1U case	IRR 9,828,900	
75	DS-7108HQHI-K1	<ul style="list-style-type: none"> • Support H.265 Pro+/H.265 Pro/H.265 video compression• Support HDTV/AVI/CVI/AVBS/IP video input• Audio via coaxial cable• Max. 6/12/24 IP cameras input (up to 6 MP) • Max. 800 m for 1080p and 1200 m for 720p HDTV signal transmission • Up to 6TB capacity per HDD 	IRR 14,217,000	
76	DS-7208HQHI-K1/Eco	8 Turbo HD/AVI/Analog interface input, 8-ch video&1-ch audio input, H.265/H.265+ compression, 1 SATA interface, CH01 & 02: 3MP @ 15fps, CH03-08:1920x1080P @15 fps/ch , , support CVBS output, standalone 1U case	IRR 14,455,000	
77	DS-7208HQHI-K1	8 Turbo HD/AVI/Analog interface input, 8-ch video&1-ch audio input, H.265/H.265+ compression, 1 SATA interface, CH01 & 02: 3MP @ 15fps, CH03-08:1920x1080P @15 fps/ch , , support CVBS output, standalone 1U case	IRR 14,546,000	
78	DS-7116HQHI-K1	<ul style="list-style-type: none"> • Support H.265 Pro+/H.265 Pro/H.265 video compression• Support HDTV/AVI/CVI/AVBS/IP video input• Audio via coaxial cable• Max. 6/12/24 IP cameras input (up to 6 MP) • Max. 800 m for 1080p and 1200 m for 720p HDTV signal transmission • Up to 6TB capacity per HDD 	IRR 21,687,900	
79	7216HQHI-K1-Eco	16 Turbo HD/AVI/Analog interface input, 16-ch video&1-ch audio input, H.265 compression, 1 SATA interface, CH01-04: 3MP @ 15fps, CH05-16:1920x1080P @15 fps/ch, 4K UHD output , support CVBS output, standalone 1U case- ECO CASE	IRR 24,451,000	
80	DS-7216HQHI-K1	16 Turbo HD/AVI/Analog interface input, 16-ch video&1-ch audio input, H.265/H.265+ compression, 1 SATA interface, CH01-04: 3MP @ 15fps, CH05-16:1920x1080P @15 fps/ch, 4K UHD output , support CVBS output, standalone 1U case	IRR 26,565,000	
81	DS-7224HQHI-K2	24 Turbo HD/AVI/Analog interface input - H.265+/H.265/H.264+/H.264 encoding for the main stream, and H.265/H.264 for the sub-stream of analog cameras - Self-adaptive HDTV/HDCVI/AVI/AVBS signal input - Connectable to H.265+/H.265/H.264+/H.264 IP cameras - Full channel recording at up to 4 MP lite resolution - HDMI output at up to 4K (3840 x 2160) resolution - Long distance transmission over UTP and coaxial cable: max. 800m for 1080p and 1200m for 720p HDTV signal -16-ch synchronous playback	IRR 48,076,000	










82	DS-7232HQHI-K2	32 Turbo HD/AHD/Analog interface input -H.265+/H.265/H.264+/H.264 encoding for the main stream, and H.265/H.264 for the sub-stream of analog cameras - Self-adaptive HDTV/HDCVI/AHD/CVBS signal input - Connectable to H.265+/H.265/H.264+/H.264 IP cameras - Full channel recording at up to 4 MP lite resolution - HDMI output at up to 4K (3840 x 2160) resolution - Long distance transmission over UTP and coaxial cable: max. 800m for 1080p and 1200m for 720p HDTV signal -16-ch synchronous playback	IRR 51,177,000	
83	Turbo HD DVR 1080p/3MP / 5MP			
84	DS-7204HUHI-K1	4 Turbo HD/AHD/Analog interface input, 4-ch video&4-ch audio input, 1 SATA interface, H.265/H.265+ compression, 5MP: 12fps, 4MP: 15fps, 3MP: 18fps, 1920x1080P: 25(P)/30(N) fps/ch , alarm I/O: 4/1, support CVBS output, standalone 1U case	IRR 14,378,000	
85	DS-7208HUHI-K1	8 Turbo HD/AHD/Analog interface input, 8-ch video&4-ch audio input, 1 SATA interface, H.265/H.265+ compression, 5MP: 12fps, 4MP: 15fps, 3MP: 18fps, 1920x1080P: 25(P)/30(N) fps/ch, 4K UHD output , alarm I/O: 8/4, support CVBS output, standalone 1U case	IRR 21,944,000	
86	DS-7216HUHI-K2	16 Turbo HD/AHD/Analog interface input, 16-ch video&4-ch audio input, 2 SATA interfaces, H.265/H.265+ compression, 5MP: 12fps, 4MP: 15fps, 3MP: 18fps, 1920x1080P: 25(P)/30(N) fps/ch, 4K UHD output , alarm I/O: 16/4, support CVBS output, 380 1U case	IRR 45,084,300	
87	Turbo HD DVR 1080p/3MP / 5MP Built in PoC Series			
88	DS-7204HUHI-K1/P	4 Turbo HD/AHD/Analog interface input, 4-ch video&4-ch audio input, 1 SATA interface, H.265/H.265+ compression, 5MP: 12fps, 4MP: 15fps, 3MP: 18fps, 1920x1080P: 25(P)/30(N) fps/ch, alarm I/O: 4/1, support CVBS output, standalone 1U case, built-in PoC	IRR 17,556,500	
89	DS-7208HUHI-K2/P	8 Turbo HD/AHD/Analog interface input, 8-ch video&4-ch audio input, 2 SATA interfaces, H.265/H.265+ compression, 5MP: 12fps, 4MP: 15fps, 3MP: 18fps, 1920x1080P: 25(P)/30(N) fps/ch, 4K UHD output , alarm I/O: 8/4, support CVBS output, 380 1U case, built-in PoC	IRR 32,084,000	
90	Turbo HD DVR 1080p/3Mp/5Mp / 8MP Built In PoC			
91	DS-7204HTHI-K1	4-ch, RCA (2.0 Vp-p, 1 KΩ)-4-chBNC interface (1.0 Vp-p, 75 Ω), supporting coaxitron connection-2-ch-Up to 8 MP resolution,Supports H.265+/H.265/H.264+/H.264 IP cameras-VGA: 1-ch, 1920 x 1080/60Hz, 1280 x 1024/60Hz, 1280 x 720/60Hz, 1024 x 768/60Hz HDMI: 1-ch, 4K (3840 x 2160)/30Hz, 2K (2560 x 1440)/60Hz, 1920 x 1080/60Hz, 1280 x 1024/60Hz, 1280 x 720/60Hz, 1024 x 768/60Hz-Video Bit Rate: -32 Kbps to 16 Mbps-Stream Type: VidVideo, Video & Audiooe, Video & Audio-Two-way Audio: 1-ch, RCA (2.0 Vp-p, 1 KΩ) (using the 1st audio input)-Audio Output: 1-ch, RCA (Linear, 1 KΩ)-Audio Bit Rate: -64 Kbps	IRR 22,465,100	
92	DS-7208HTHI-K2	4K H265+ TURBO HD DVR-4-ch, RCA (2.0 Vp-p, 1 KΩ)-Video Compression: H.265+/H.265/H.264+/H.264-Analog Video Input: 8-ch,BNC interface (1.0 Vp-p, 75 Ω), supporting coaxitron connection Analog and HD-TVl video input: 8 MP, 5 MP, 4 MP, 3 MP, 1080p30, 1080p25, 720p60, 720p50, 720p30, 720p25 IP Video Input: 4-ch,Up to 8 MP resolution,Supports H.265+/H.265/H.264+/H.264 IP-Interface Type: 2 SATA interfacesCapacity: Up to 8 TB capacity for each disk-Alarm Input: 8-Alarm Output: 4	IRR 43,677,300	





















Network Camera - NVR			
Items	Description	User Price	
Lite Mini Bullet Series			
1	DS-2CD1023G0-E 2.0 MP IR Network Bullet Camera-□ 1/2.8" progressive scan CMOS □ 3D DNR (Digital Noise Reduction)□ 1920 × 1080@30fps □ Up to 30 m IR range □ 2.8 mm/4 mm/6 mm fixed lens □ PoE (Power over Ethernet) □ H.265+, H.265, H.264+, H.264 □ IP67□ Dual stream□ Digital WDR (Wide Dynamic Range)	IRR 8,438,800	
2	DS-2CD1023G0-I 2.0 MP IR Network Bullet Camera-□ 1/2.8" progressive scan CMOS □ 3D DNR (Digital Noise Reduction)□ 1920 × 1080@30fps □ Up to 30 m IR range □ 2.8 mm/4 mm/6 mm fixed lens □ PoE (Power over Ethernet) □ H.265+, H.265, H.264+, H.264 □ IP67□ Dual stream□ Digital WDR (Wide Dynamic Range)	IRR 8,744,800	
3	DS-2CD1031-I 1/3" progressive scan CMOS- Up to 3.0 megapixel- 2.8mm/4mm/6mm fixed focal lens Up to 30 m IR range- Dual stream- Digital WDR (Wide Dynamic Range) 3D DNR (Digital Noise Reduction)- PoE (Power over Ethernet)- IP67 Mobile monitoring via Hik-Connect or iVMS-4500	IRR 10,530,000	
4	DS-2CD1043G0-I 4.0 MP IR Network Bullet Camera, 1/3" progressive scan CMOS , 3D DNR (Digital Noise Reduction), 2560 × 1440@20fps □ Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens □ PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264 , IP67, Dual stream, Digital WDR (Wide Dynamic Range)	IRR 11,961,200	
Lite Dome Series			
6	DS-2CD1123G0-I IP67, 2MP dome Exir, fixed lens 2.8mm,white color-1/2.8" progressive scan CMOS □ 3D DNR (Digital Noise Reduction) □ 1920 × 1080@30fps □ Up to 30 m IR range□ 2.8 mm/4 mm/6 mm fixed lens □ PoE (Power over Ethernet)□ H.265+, H.265, H.264+, H.264 □ IP67, IK10□ Dual stream□ Digital WDR (Wide Dynamic Range)	IRR 13,760,000	
7	DS-2CD1323G0-E 1/2.8" progressive scan CMOS - 1920 × 1080@30fps - 2.8 mm/4 mm/6 mm fixed lens - H.264+, H.264 - Dual stream - Digital WDR (Wide Dynamic Range) - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - PoE (Power over Ethernet) - IP67	IRR 8,438,800	









8	DS-2CD1323G0-I	1/2.8" progressive scan CMOS - 1920 x 1080@30fps - 2.8 mm/4 mm/6 mm fixed lens - H.265+, H.265, H.264+, H.264 - Dual stream - Digital WDR (Wide Dynamic Range) - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - PoE (Power over Ethernet) - IP67	IRR 9,200,400	
9	DS-2CD1131-I	1/3" progressive scan CMOS- Up to 3.0 megapixel- 2.8 mm/4 mm/6 mm fixed focal lens Up to 30 m IR rang-Dual stream- Digital WDR (Wide Dynamic Range)- 3D DNR (Digital Noise Reduction)- PoE (Power over Ethernet) IP67, Ik10- Mobile monitoring via Hik-Connect or iVMS-4500	IRR 10,530,000	
10	DS-2CD1143G0-I	4.0 MP IR Network Dome Camera, 1/3" progressive scan CMOS □ 3D DNR (Digital Noise Reduction), 2560 x 1440@20fps □ Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens ,PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264 □ IP67, IK10, Dual stream, Digital WDR (Wide Dynamic Range)	IRR 18,490,000	
11	Mini Bullet Series			
12	DS-2CD2020F-I	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (6mm optional), H.264/MJPEG, dual-stream, IP66, DWDR, 3D DNR, BLC, Support on-board storage (SD card not included), IR range: up to 30m, Bracket included, Housing: plastic and metallic, DC12V & external PoE cable, , Support Mobile Monitoring via EZVIZ P2P -W: Built-in Wi-Fi	IRR 16,690,000	
13	DS-2CD2023G0-I	2 MP IR Fixed Bullet Network Camera -□ 1/3" Progressive Scan CMOS □ 1920 x 1080@30fps □ 2.8/4/6/8 mm fixed lens □ Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR □ H.265+, H.265, H.264+, H.264 □ Three streams □ 120dB WDR □ 2 Behavior analyses, and face detection -□ BLC/3D DNR/ROI □ IP67 □ Built-in micro SD/SDHC/SDXC card slot, up to 128 GB □ 3-Axis adjustment	IRR 13,900,000	
14	DS-2CD2043G0-I	4 MP IR Fixed Bullet Network Camera -□ 1/3" Progressive Scan CMOS □ 2560 x 1440@30fps □ 2.8/4/6/8 mm fixed lens □ Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR □ H.265+, H.265, H.264+, H.264 □ Three streams □ 120dB WDR □ 2 Behavior analyses, and face detection -□ BLC/3D DNR/ROI □ IP67 □ Built-in micro SD/SDHC/SDXC card slot, up to 128 GB □ 3-Axis adjustment	IRR 15,100,000	
15	DS-2CD2052-I	1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920: 20fps, 4mm/F2.0 lens (6mm optional), H.264+/H.264/MJPEG, 3 streams, IP67, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 30m, Full metallic housing, Hik-Connect cloud service	IRR 15,723,500	
16	DS-2CD2063G0-I	6 MP IR Fixed Bullet Network Camera -□ 1/2.9" Progressive Scan CMOS □ 3072 x 2048@20 fps □ 2.8/4/6/8 mm fixed lens □ Color: 0.01 lux @ (F1.2, AGC ON), 0.028 lux @ (F2.0, AGC ON), 0 lux with IR □ H.265+, H.265, H.264+, H.264 □ 2 Behavior analyses □ 120dB WDR -□ BLC/3D DNR/ROI □ IP67 □ Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 17,225,700	
17	DS-2CD2083G0-I	8 MP IR Fixed Bullet Network Camera -□ 1/2.5" Progressive Scan CMOS □ 3840 x 2160 @15 fps □ 2.8/4/6/8 mm fixed lens □ Color: 0.01 lux @ (F1.2, AGC ON), 0.028 lux @ (F2.0, AGC ON), 0 lux with IR □ H.265+, H.265, H.264+, H.264 □ 2 Behavior analyses □ 120dB WDR -□ BLC/3D DNR/ROI/HLC □ IP67 □ Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 20,247,400	
18	Dome Series			










19	DS-2CD2120F-I	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (2.8mm, 6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 30m, Support on-board storage (SD card not included), Support Mobile Monitoring via EZVIZ P2P	IRR 16,690,000	
20	DS-2CD2120F-IS	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (2.8mm, 6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 30m, Support on-board storage (SD card not included), Support Mobile Monitoring via EZVIZ P2P -S: Audio/Alarm IO connectors	IRR 16,690,000	
21	DS-2CD2123G0-IS	• 1920 x1080@30fps • 2.8/4/6/8mm fixed lens • Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 Lux @ (F2.0, AGC ON), 0 Lux with IR • H.265+, H.265, H.264+, H.264 • Three streams • 120dB WDR • 2 Behavior analyses, and face detection • BLC/3D DNR/ROI/HLC • IP67, IK10 • Built-in micro SD/SDHC/SDXC card slot, up to 128 GB • 3-Axis adjustment	IRR 21,650,000	
22	DS-2CD2143G0-IS	4 MP IR Fixed Dome Network Camera 1/3" Progressive Scan CMOS, 2688 x1520@30fps, 2.8/4/6/8mm fixed lens Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR H.265+, H.265, H.264+, H.264, Three streams, 120dB WDR, 2 Behavior analyses, and face detection, BLC/3D DNR/ROI, IP67, IK10, Built-in micro SD/SDHC/SDXC card slot, up to 128 GB, 3-Axis adjustment	IRR 23,450,000	
23	DS-2CD2152F-IS	1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920: 20fps, 4mm/F2.0 lens (6mm optional), H.264+/H.264/MJPEG, 3 streams, IP67, IK10, DC12V & PoE, DWDR, 3D DNR, BLC, support on-board storage up to 128GB(SD card not included), 3-axis adjustment, IR range: up to 30m, Vandal-proof housing, HIK-Connect cloud service -S: Audio/Alarm IO	IRR 16,549,000	
24	DS-2CD2163G0-I(S)	6 MP IR Fixed Dome Network Camera -□ 1/2.9" Progressive Scan CMOS □ 3072 x 2048@20 fps □ 2.8/4/6/8 mm fixed lens □ Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR □ H.265+, H.265, H.264+, H.264 □ 2 Behavior analyses □ 120dB WDR -□ BLC/3D DNR/ROI □ IP67 □ Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 27,960,000	
25	DS-2CD2183G0-I(S)	8 MP IR Fixed Dome Network Camera -□ BLC/3D DNR/ROI □ IP67, IK10 □ Built-in micro SD/SDHC/SDXC card slot, up to 128 GB □ 1/2.5" Progressive Scan CMOS □ 3840 x 2160 @15 fps □ 2.8/4/6/8 mm fixed lens □ Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR □ H.265+, H.265, H.264+, H.264 □ 2 Behavior analyses □ 120dB WDR	IRR 22,056,400	
26	Bullet Series			
27	DS-2CD2T35FWD-I8	Up to 3 megapixel high resolution-Max. 2048 x 1536 @30fps 2.8 mm/4mm/6mm/8 mm/12mm fixed lens,-optional Ultra-low light-265, H.265+, H.264+, H.264- 120dB Wide Dynamic Range 3D Digital Noise Reduction12 VDC & PoE (802.3af)- IR range: 50m, 80m, optional- Support on-board storage, up to 128 GB-IP67	IRR 20,500,000	
28	DS-2CD2T43G0-I5	1/3" Progressive Scan CMOS,2688 x1520@30fps,2.8/4/6/8mm fixed lens • Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR, H.265+, H.265, H.264+, H.264,Three streams,120dB WDR,2 Behavior analyses, and face detection,BLC/3D DNR/ROI,IP67,Built-in micro SD/SDHC/SDXC card slot, up to 128 GB-up to 50m IR range	IRR 24,360,000	











29	DS-2CD2T52-I5	1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920:20fps, 4mm/F1.4 lens (6mm optional), H.264+/H.264/MJPEG, 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, HIK-Connect cloud service, 2pcs EXIR LEDs, up to 50m IR range	IRR 32,920,000	
30	DS-2CD2T63G0-I5	6 MP IR Fixed Bullet Network Camera - BLC/3D DNR/ROI IP67 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.9" Progressive Scan CMOS 3072 x 2048@20 fps 2.8/4/6/8 mm fixed lens Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR H.265+, H.265, H.264+, H.264 2 Behavior analyses 120dB WDR	IRR 29,320,000	
31	DS-2CD2T63G0-I8	6 MP IR Fixed Bullet Network Camera - BLC/3D DNR/ROI IP67 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.9" Progressive Scan CMOS 3072 x 2048@20 fps 2.8/4/6/8 mm fixed lens Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR H.265+, H.265, H.264+, H.264 2 Behavior analyses 120dB WDR - up to 80m IR range	IRR 31,120,000	
32	DS-2CD2T83G0-I5	8 MP IR Fixed Bullet Network Camera - 1/2.5" Progressive Scan CMOS -3840 x 2160 @15 fps 2.8/4/6/8 mm fixed lens Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR H.265+, H.265, H.264+, H.264 2 Behavior analyses 120dB WDR BLC/3D DNR/ROI IP67 Built-in micro SD/SDHC/SDXC card slot, up to 128 G	IRR 35,180,000	
33	DS-2CD2T83G0-I8	8 MP IR Fixed Bullet Network Camera - 1/2.5" Progressive Scan CMOS -3840 x 2160 @15 fps 2.8/4/6/8 mm fixed lens Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR H.265+, H.265, H.264+, H.264 2 Behavior analyses 120dB WDR BLC/3D DNR/ROI IP67 Built-in micro SD/SDHC/SDXC card slot, up to 128 G-up to 80m IR range	IRR 36,980,000	
34	Exir Dome Series			
35	DS-2CD2342FWD-I	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, EXIR range: up to 30m	IRR 22,190,000	
36	DS-2CD2352-I	1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920:20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264+/H.264/MJPEG, 3 streams, IP67, DC12V & PoE, DWDR, 3D DNR, BLC, EXIR range: up to 30m	IRR 33,150,000	
37	Mini Dome Series			
38	DS-2CD2523G0-IS	1/2.7" Progressive Scan CMOS - 1920 x 1080@30fps - H.265+/H.265/H.264+/H.264/MJPEG - IR: up to 10 m 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR - Color: 0.01 Lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR -S: Built-in MIC, audio/alarm IO	IRR 18,557,200	
39	DS-2CD2542FWD-IS	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F2.0 lens (2.8mm, 6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 10m, support on-board storage up to 128GB(SD card not included), HIK-Connect cloud service -S: Built-in MIC, audio/alarm IO	IRR 20,644,495	












40	DS-2CD2543G0-IS	1/3" Progressive Scan CMOS - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 lux @(F1.6, AGC ON), 0 lux with IR - 2688 x 1520@30fps - IR: up to 10 m - H.265+/H.265/H.264+/H.264/MJPEG - 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR -S: Built-in MIC, audio/alarm IO	IRR 21,460,495	
41	DS-2CD2563G0-IS	1/3" Progressive Scan CMOS - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 lux @(F1.6, AGC ON), 0 lux with IR - 3072 x 2048@20fps - IR: up to 10 m - H.265+/H.265/H.264+/H.264/MJPEG - 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR -S: Built-in MIC, audio/alarm IO	IRR 23,922,400	
42	Lite Bullet Vari-Facal Motorized Series			
43	DS-2CD1623G0-I	Hikvision DS-2CD1623G0-I 2MP (1920 x 1080) Vari-focal IR Bullet Network Camera SPECIFICATIONS 2MP HD1080P 1/2.8" Progressive Scan CMOS 1920 x 1080@30fps (N) 2.8-12mm VF lens IR range: Up to 30m	IRR 17,788,800	
44	DS-2CD1623G0-IZ	S-2CD1623G0-IZ Bullet Network camera 2MP, 2.8-12mm varifocal lens, EXIR, microSD1/2.8" progressive scan CMOS BLC/3D DNR/ROI 1920 x 1080@30fps Up to 30 m IR range IP67 2.8 mm to 12 mm varifocal lens Digital WDR H.265+, H.265, H.264+, H.264 Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Z: Motorized VF lens	IRR 19,644,400	
45	DS-2CD1643G0-I	4 MP EXIR VF Bullet Network Camera, 1/3" progressive scan CMOS □ BLC/3D DNR/ROI, 2560 x 1440@20fps ,Up to 30 m IR range, 2.8 mm to 12 mm varifocal lens, IP67, H.265+, H.265, H.264+, H.264 □ 120 dB WDR, Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 31,570,000	
46	Lite Dome Vari-Facal Serie:			
47	DS-2CD1723G0-I	□ 1/2.8" progressive scan CMOS □ 3D DNR (Digital Noise Reduction) □ 1920 x 1080@30fps □ Up to 30 m IR range □ 2.8 mm to 12 mm manual/motorized (with -Z) vari-focal lens □ PoE (Power over Ethernet) □ IP67, IK10 □ H.265+, H.265, H.264+, H.264 □ Dual stream □ Digital WDR (Wide Dynamic Range)	IRR 17,788,800	
48	DS-2CD1743G0-I	4.0 MP VF Network Bullet Camera, 1/3" progressive scan CMOS □ 3D DNR (Digital Noise Reduction), 2560 x 1440@20fps □ Up to 30 m IR range, 2.8 mm to 12 mm manual/motorized (with-Z) vari-focal lens, PoE (Power over Ethernet), IP67, H.265+, H.265, H.264+, H.264, Dual stream, 120 dB WDR (Wide Dynamic Range)	IRR 19,325,600	
49	Bullet Vari-Facal Motorized Series			
50	DS-2CD2620F-I	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8-12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Support Mobile Monitoring via EZVIZ P2P	IRR 28,870,000	
51	DS-2CD2643G0-IZS	4 MP IR VF Bullet Network Camera - 1/3" Progressive Scan CMOS • 2688 x 1520@30fps • 2.8 to 12 mm varifocal lens • Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with I • H.265+, H.265, H.264+, H.264 • Three streams • 120dB WDR • 2 Behavior analyses, and face detection • BLC/3D DNR/ROI • IP67, IK10 • Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Z: Motorized VF lens	IRR 47,360,000	













52	DS-2CD2663FG0-IZS	<ul style="list-style-type: none"> □ BLC/3D DNR/ROI □ IP67, IK10 □ Built-in micro SD/SDHC/SDXC card slot, up to 128 GB □ □ 1/2.9" Progressive Scan CMOS □ 3072 x 2048@20 fps □ 2.8 to 12 mm varifocal lens □ Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR □ H.265+, H.265, H.264+, H.264 □ 2 Behavior analyses - Z: Motorized VF lens 	IRR 54,570,000	
53	DS-2CD2683G0-IZS	<p>8 MP(4K) IR Vari-focal Bullet Network Camera• 1/2.5" Progressive Scan CMOS</p> <ul style="list-style-type: none"> • 3840 x 2160@15fps • 2.8 to 12 mm varifocal lens • Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR • H.265+, H.265, H.264+, H.264 • 120dB WDR • 2 Behavior analyses, and face detection • BLC/3D DNR/ROI • IP67, IK10 - Z: Motorized VF lens 	IRR 63,140,000	
54	Dome Vari-Facal Motorized Series			
55	DS-2CD2720F-IS	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Vandal-proof, Support Mobile Monitoring via EZVIZ P2P	IRR 16,250,000	
56	DS-2CD2720F-IZ	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Vandal-proof, Support Mobile Monitoring via EZVIZ P2P - Z: Motorized VF lens	IRR 37,430,000	
57	DS-2CD2723G0-IZS	2MP IR Motorized NETWORK DOME CAMERA 1/2.8 " 2MP progressive scan CMOS Up to 1920 x 1080 resolution (25 fps) 2.8~12 mm Motorized lens , 0 lux IR on Max IR distance: 30 meters H.265+,H.265,H.264+,H.264,MJPEG video compression 3DDNR,BLC, WDR(120dB),ROI,VCA,Micro SD (Up to 128 GB), Reset Button 1 Audio I/O , 1 Alarm I/O PoE, DC12V, IP67,IK10,3 axis adjustment Onvif support - Z: Motorized VF lens	IRR 42,850,000	
58	DS-2CD2743G0-IZS	4 MP IR VF Dome Network Camera -□ BLC/3D DNR/ROI □ IP67, IK10 □ Built-in micro SD/SDHC/SDXC card slot, up to 128 GB □ 3-Axis adjustment □ 1/3" Progressive Scan CMOS □ 2560 x 1440@30fps □ 2.8 to 12 mm Varifocal lens □ Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR □ H.265+, H.265, H.264+, H.264 □ Three streams □ 120dB WDR □ 2 behavior analyses, and face detection -WDR-Day & Night IR Cut Filter Digital Noise Reduction 3D DNR - Z: Motorized VF lens	IRR 42,850,000	
59	DS-2CD2763G0-IZS	6 MP IR Vari-focal Dome Network Camera • 1/2.9" Progressive Scan CMOS • 3072 x 2048@20fps • 2.8 to 12 mm varifocal lens • Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR • H.265+, H.265, H.264+, H.264 • 120dB WDR • 2 Behavior analyses, and face detection • BLC/3D DNR/ROI • IP67, IK10 • Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Z: Motorized VF lens	IRR 54,570,000	
60	DS-2CD2783G0-IZS	8 MP(4K) IR Vari-focal Dome Network Camera • 1/2.5" Progressive Scan CMOS • 3840 x 2160@15fps • 2.8 to 12 mm varifocal lens • Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR • H.265+, H.265, H.264+, H.264 • 120dB WDR • 2 Behavior analyses, and face detection • BLC/3D DNR/ROI • IP67, IK10 • Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Z: Motorized VF lens	IRR 63,140,000	
61	Fish Eye Series			
62	DS-2CD2942F-IS	<p>Color: 0.01lux @(F1.2, AGC ON), 0.018lux @(F1.6, AGC ON), 0 lux with IR</p> <p>2560 x 1440</p> <p>1.6mm, F1.6 Angle of view: 186°(horizontal), 106°(vertical)</p> <p>H.264/MJPEG</p> <p>50Hz: 12.5fps(2560 x 1440), 25fps(1920 x 1080, 1280 x 720)
60Hz: 15fps(2560 x 1440), 30fps(1920 x 1080, 1280 x 720)
8 meters</p> <p>12 VDC ± 10%, PoE (802.3af)</p>	ناموجود	








63	DS-2CD2955FWD-IS	5 MP Network Fisheye Camera, Up to 5 megapixel high resolution, 2560 × 1920 @30fps, H.265, H.265+, H.264+, H.264, Support 14 display modes, FOV: horizontal FOV 180°, vertical FOV 180°, Dual video streams, DC12V & PoE (802.3af), Digital Noise Reduction, Support on-board storage, up to 128 GB, Up to 8m IR range, -S: Audio/Alarm IO	IRR 42,848,000	
64	Cube Smart Series			
65	DS-2CD2420F-IW	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (2.8mm, 6mm optional), H.264/MJPEG, dual-stream, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 10m, Support on-board card slot (SD card not included), Support Mobile Monitoring via EZVIZ P2P -W: Built-in Wi-Fi with WPS	IRR 16,690,000	
66	DS-2CD2423G0-IW	1/2.7" Progressive Scan CMOS - 1920 × 1080@30fps - IR: 10 m - PIR: 10m - H.265, H.265+ 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR - Wi-Fi (Optional) - Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 lux @ (F2.0, AGC ON), 0 lux with IR	IRR 12,267,200	
67	DS-2CD2442FWD-IW	1/3" Progressive CMOS, ICR, 0.01lux/F1.2, 2688x1520:20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR range: up to 10m, support on-board storage up to 128GB (SD card not included), built-in WIFI	IRR 23,000,000	
68	Pin Hole Series			
69	DS-2CD2D14WD	1/4" Progressive CMOS, Electronic Day/night, Color: 0.01lux/F1.2, B/W: 0.001lux/F1.2, 1280x720: 25fps(P)/30fps(N), 3.6mm/F1.2 lens, H.264/MJPEG, dual-stream, DC12V, 100dB WDR, 3D DNR, BLC, Support Mobile Monitoring via EZVIZ P2P	IRR 17,250,000	
70	Hologen Series			
71	DS-2CD2E20F-W	1/3" Progressive CMOS, Day/night, 0.1lux/F1.2, 1920x1080:25fps(P)/30fps(N), 4mm lens (2.8/6mm optional), H.264/MJPEG, dual-stream, DC12V & PoE, DWDR, 3D DNR, BLC, Support on-board storage up to 64GB (SD card not included), Support Mobile Monitoring via EZVIZ P2P, Color Lens Cover optional (Black, Silver, Golden) -W: Built-in Wi-Fi	IRR 24,580,000	
72	2Q Smart Series			
73	DS-2CD2Q10FD-IW	1/4" Progressive CMOS, ICR, 0lux with IR, 4mm/F2.0 (2.8/6mm optional), Pan/tilt rotation, 1280x720:25fps(P)/30fps(N), H.264/MJPEG, dual-stream, DC5V, DWDR, 3D DNR, BLC, Support on-board card slot (SD card not included), Audio, Alarm IO, Up to 10m IR, PIR, Wi-Fi with WPS connection, Support Mobile Monitoring via EZVIZ P2P	IRR 13,230,000	
74	DS-2CV2Q21FD-IW	1/2.8" Progressive CMOS, ICR, 0lux with IR, 1920x1080: 25fps(P)/30fps(N), 2.8mm lens, H.264/MJPEG, dual-stream, 3D DNR, 5m IR, PT function (Pan: 0° ~ 355°; Tilt: -10° ~ 90°), support on-board storage up to 128GB, HIK-Connect cloud service, Build-in microphone and speaker, support two-way audio. Built-in Wi-Fi, 12VDC power supply. Default: No SD card included. /32GB-T: Include 16GB sd card.	IRR 19,170,000	
75	2U Smart Series			








76	DS-2CV2U21FD-IW	1/2.8" Progressive CMOS, ICR, 0lux with IR, 1920x1080: 25fps(P)/30fps(N), 2.8mm lens,H.264/MJPEG, dual-stream, 3D DNR, 5m IR, support on-board storage up to 128GB, HIK-Connect cloud service, Build-in microphone and speaker, support two-way audio. Built-in Wi-Fi, 12VDC power supply. /32GB-T: Include 32GB sd card.	IRR 9,204,000	
77	Mini PTZ Series			
78	DS-2CD2F52F-IS	1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920: 20fps,2048x1536: 25fps(P)/ 30fps(N), 4mm/F2.0 lens (2.8/6mm lens optional), H.264+/H.264/MJPEG, 3 streams, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 10m, Support on-board storage up to 128GB(SD card not included), Pan: 0°~180°, Tilt: 0°~75°, HIK-Connect cloud service -S: Audio/Alarm IO	IRR 24,710,000	
79	IP PTZ Camera			
80	DS-2DE4A220IW-DE	1/2.8" Progressive Scan CMOS, Up to 1920 x 1080 resolution 20x Optical Zoom, 16x Digital Zoom, WDR, 3D DNR, HLC, Smart IR Up to 50 m IR distance, 12 VDC & PoE+ (802.3at, class4), Support H.265 video compression	IRR 69,447,000	
81	DS-2CD2202I-DE3	2 MP High Resolution,Compact IR Pan/Tilt/Zoom Camera, 1920 x 1080p HD Real-Time Resolution,2x Zoom, 16x Digital Zoom, 20 Meters IR Distance, PoE and 12 VDC Power Supply, Built-In Mic, WiFi, MicroSD Card Local Storage, Up to 128 GB, Easy To Install and Adjust	IRR 26,400,000	
82	DS-2DE4220IW-DE	2MP, 1/3" CMOS sensor, H.264 codec, Color: 0.02lux/F1.5, B/W:0.02lux/F1.5, Optical Zoom:20x, Focus:4.7-94.0mm, Digital Zoom:16X, Pan range:360° endless; Tilt range: -15°~90°(Auto Flip), Pan Speed: 0.1° - 80°/s, Tilt Speed: 0.1° - 80°/s, 100m IR Distance, POE&12VDC	IRR 77,570,000	
83	DS-2DE4225IW-DE	1/2.8" progressive scan CMOSUp to 1920 x 1080@30fps resolution-Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON)0 Lux with IR25x optical zoom, 16x digital zoom WDR, HLC, BLC, 3D DNR, Defog, EIS, Regional Exposure, Regional Focus Up to 100 m IR distance12 VDC & PoE+ (802.3 at, class4) Support H.265+/H.265 video compression	IRR 56,511,000	
84	DS-2DE5220IW-AE	2MP, 1/3" CMOS, 3D DNR, ICR, Color: 0.02lux/F1.5, B/W:0.02lux/F1.5, Optical Zoom:20x, Focus:4.7-94.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan range:360° endless; Tilt range: -15°~90°(Auto Flip), Pan Speed: 0.1° - 400°/s, Tilt Speed: 0.1° -200°/s, 150m IR Distance, Hi-PoE&24VAC	IRR 90,286,000	
85	DS-2DE5230W-AE	1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom 30x, Focus:4.3-129.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -250°/s, Tilt Speed: 0.1° -150°/s	IRR 134,390,000	
86	DS-2DE7220IW-AE	2MP, 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:20x, Focus: 4.7-94.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -120°/s, 150m IR Distance, Hi-PoE&24VAC	ناموجود	











87	DS-2DE7230IW-AE	2MP, 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:30x, Focus:4.3-129.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -120°/s, 150m IR Distance, Hi-PoE&24VAC	ناموجود	
88	DS-2DE7320IW-AE	1/2.8" Progressive Scan CMOS □ 2048 × 1536@30fps Resolution □ 20× optical zoom, 16× digital zoom □ WDR □ 3D Positioning □ 24VAC & Hi-PoE □ Up to 150m IR distance	IRR 107,961,000	
89	DS-2DE7330IW-AE	1/2.8" Progressive Scan CMOS □ 2048 × 1536@30fps Resolution □ 30× optical zoom, 16× digital zoom □ WDR □ 3D Positioning □ 24VAC & Hi-PoE □ Up to 150m IR distance	ناموجود	
90	DS-2DE7420IW-AE	1/1.9" progressive scan CMOS,Up to 2560 × 1440 resolution,20× Optical Zoom, 16× Digital Zoom,Defog, EIS, 3D DNR, BLC, HLC, Digital WDR,IR distance up to 150 m,24 VAC & Hi-PoE,Support H.265+/H.265 video compression	ناموجود	
91	DS-2DE7430IW-AE	1/1.9" progressive scan CMOS,Up to 2560 × 1440 resolution,30× Optical Zoom, 16× Digital Zoom,Defog, EIS, 3D DNR, BLC, HLC, Digital WDR,IR distance up to 150 m,24 VAC & Hi-PoE,Support H.265+/H.265 video compression	IRR 205,190,000	
92	DS-2DE7530IW-AE	1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:20x, Focus: 4.7-94.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -120°/s, 150m IR Distance, Hi-PoE&24VAC	ناموجود	
93	PanoVu Mini Series IR Network PTZ Camera			
94	DS-2PT3326IZ-DE3(2.8-12mm)	Panoramic Camera:1/2.8" progressive scan CMOS,3-ch1920 × 1080@30fps resolution,Min. illumination: Color: 0.05 Lux @(F2.0, AGC ON),B/W: 0.01 Lux @(F2.0, AGC ON),0 Lux with IR, Support H.265 video compression, Horizontal FOV: 128.5° × 3 PTZ Camera:1/2.8" progressive scan CMOS,Up to 1920 × 1080@30fps resolution,Min. illumination:Color: 0.05 Lux @(F2.0, AGC ON), B/W: 0.01 Lux @(F2.0, AGC ON), 0 Lux with IR Support H.265 video compression,4× optical zoom, 8× digital zoom	IRR 71,960,000	
95	NVR-Monitor			
96	DS-7600NI-E1/A	Advertising files import and preview,The output resolution of LCD is up to 1080P, Third party network cameras supported,Up to 8-ch synchronous playback at 720P resolution,Up to 8 network cameras can be connected,Smart search and smart playback 1TB HDD WD10JUCT pre-installed	IRR 69,190,000	
97	NVR 4 Channel			
98	DS-7104NI-Q1/M	Incoming bandwidth: 40Mbps - P video input: 4-ch Up to 4 MP resolution - H.265+/H.265/ H.264+/H.264 - HDMI/VGA output at 1080p resolution - 1 SATA hard disks can be connected with 6TB capacity - Supports line crossing and intrusion detection	IRR 7,282,800	
99	DS-7104NI-Q1/4P/M	Incoming bandwidth: 40Mbps - P video input: 4-ch Up to 4 MP resolution - H.265+/H.265/ H.264+/H.264 - HDMI/VGA output at 1080p resolution - 1 SATA hard disks can be connected with 6TB capacity - Supports line crossing and intrusion detection	IRR 12,390,000	










100	DS-7604NI-E1	40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interface, standalone 1U case	IRR 14,670,000	
101	DS-7604NI-E1/4P	40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interfaces, 4 independent PoE network interfaces, standalone 1U case	IRR 20,980,000	
102	DS-7604NI-Q1	IP video input 4-ch,Up to 8 MP resolution,Incoming bandwidth 40 Mbps , Outgoing bandwidth 80 Mbps , Audio output 1-ch,Decoding format H.265/H.265+/H.264/H.264+/MPEG4, 1 SATA interface Capacity Up to 6TB capacity for each disk,	IRR 11,220,000	
103	DS-7604NI-Q1/4P	IP video input 4-ch,Up to 8 MP resolution,Incoming bandwidth 40 Mbps , Outgoing bandwidth 80 Mbps , Audio output 1-ch,Decoding format H.265/H.265+/H.264/H.264+/MPEG4, 1 SATA interface Capacity Up to 6TB capacity for each disk, 4 independent PoE network interfaces	IRR 23,000,000	
104	DS-7604NI-K1	40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interface, standalone 1U case	IRR 16,500,000	
105	DS-7604NI-K1/4P	40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interfaces, 4 independent PoE network interfaces, standalone 1U case	IRR 23,000,000	
106	NVR 8 Channel			
107	DS-7108NI-Q1/M	Incoming bandwidth: 60Mbps - P video input: 8-ch Up to 4 MP resolution - H.265+/H.265/ H.264+/H.264 - HDMI/VGA output at 1080p resolution - 1 SATA hard disks can be connected with 6TB capacity - Supports line crossing and intrusion detection	IRR 9,128,000	
108	DS-7108NI-Q1/8P/M	Incoming bandwidth: 60Mbps - P video input: 8-ch Up to 4 MP resolution - H.265+/H.265/ H.264+/H.264 - HDMI/VGA output at 1080p resolution - 1 SATA hard disks can be connected with 6TB capacity - Supports line crossing and intrusion detection	IRR 17,444,000	
109	DS-7608NI-E2	80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 380 1U case	IRR 20,540,000	
110	DS-7608NI-E2/8P	80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 8 independent PoE network interfaces, 380 1U case	IRR 33,132,000	
111	DS-7608NI-Q1	IP video input 8-ch,Up to 8 MP resolution,Incoming bandwidth 80 Mbps , Outgoing bandwidth 80 Mbps , Audio output 1-ch,Decoding format H.265/H.265+/H.264/H.264+/MPEG4, 1 SATA interface Capacity Up to 6TB capacity for each disk,	IRR 22,850,000	











112	DS-7608NI-Q1/8P	IP video input 8-ch,Up to 8 MP resolution,Incoming bandwidth 80 Mbps , Outgoing bandwidth 80 Mbps , Audio output 1-ch,Decoding format H.265+/H.264+/H.264+/MPEG4, 1 SATA interface Capacity Up to 6TB capacity for each disk,8 independent PoE network interfaces	IRR 37,065,000	
113	DS-7608NI-Q2	sales, [05.01.19 11:19] IP video input 8-ch, Up to 8 MP resolution, Incoming bandwidth: 80 Mbps,Outgoing bandwidth: 80 Mbps, 2 SATA interfaces,Two-way audio	IRR 25,180,000	
114	DS-7608NI-K2	80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 380 1U case, alarm I/O: 4/1(optional)	IRR 25,180,000	
115	DS-7608NI-K2/8P	80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 8 independent PoE network interfaces, 380 1U case, alarm I/O: 4/1(optional)	IRR 39,820,000	
116	NVR 16 Channel			
117	DS-7616NI-E2	160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 380 1U case	IRR 22,630,000	
118	DS-7616NI-E2/8P	160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 8 independent PoE network interfaces, 380 1U case	IRR 34,742,000	
119	DS-7616NI-E2/16P	160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 16 independent PoE network interfaces, 380 1U case	IRR 46,490,000	
120	DS-7616NI-Q1	IP video input 16-ch, Incoming bandwidth 160 Mbps Outgoing bandwidth 80 Mbps, 1 SATA interfaces ,Two-way audio 1-ch	IRR 23,760,000	
121	DS-7616NI-Q2/16P	IP video input 16-ch, Incoming bandwidth 160 Mbps Outgoing bandwidth 80 Mbps, 2 SATA interfaces ,Two-way audio 1-ch, 16 independent PoE network interfaces	IRR 52,800,000	
122	DS-7616NI-K2	160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 380 1U case, alarm I/O: 4/1(optional)	IRR 27,240,000	
123	DS-7616NI-K2/16P	160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 16 independent PoE network interfaces, 380 1U case, alarm I/O: 4/1(optional)	IRR 52,800,000	
124	DS-7716NI-E4	160Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 1.5U case,19"	IRR 34,552,000	










125	DS-7716NI-E4/16P	160Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, 16 independent PoE network interfaces, alarm I/O: 16/4, 1.5U case,19"	IRR 51,856,000	
126	DS-7716NI-K4	160Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 1.5U case,19"	IRR 42,700,000	
127	DS-7716NI-K4/16P	160Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, 16 independent PoE network interfaces, alarm I/O: 16/4, 1.5U case,19"	IRR 58,443,000	
128	NVR 32 Channel			
129	DS-7732NI-E4	200Mbps Bit Rate Input Max(up to 32-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 1.5U case,19"	IRR 45,311,000	
130	DS-7732NI-E4/16P	200Mbps Bit Rate Input Max(up to 32-ch IP video), 4 SATA Interfaces, 16 independent PoE network interfaces, alarm I/O: 16/4, 1.5U case,19"	IRR 88,479,000	
131	DS-7732NI-K4	256Mbps Bit Rate Input Max(up to 32-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 1.5U case,19"	IRR 53,781,000	
132	DS-7732NI-K4/16P	256Mbps Bit Rate Input Max(up to 32-ch IP video), 4 SATA Interfaces, 16 independent PoE network interfaces, alarm I/O: 16/4, 1.5U case,19"	IRR 68,411,000	

Accessories				
Items	Description	User Price		
Switches				
1	DS-3E0105P-E	L2, Unmanaged, 4 100M PoE port, 1 100M uplink port, 802.3af/at, PoE power budget 58W	IRR 5,439,000	
2	DS-3E0109P-E	L2, Unmanaged, 8 100M PoE port, 1 100M uplink port, 802.3af/at, PoE power budget 123W	IRR 14,171,000	
3	DS-3E0318P-E	L2, Unmanaged, 16 100M PoE port, 2 1000M combo port, 802.3af/at, PoE power budget 230W	IRR 31,701,600	
4	DS-3E0326P-E	L2, Unmanaged, 24 100M PoE port, 2 1000M combo port, 802.3af/at, PoE power budget 370W	IRR 47,937,200	
5	DS-3E0109P-E/M	1. L2, Unmanaged, 8 100M PoE port, 1 100M uplink port; 2. 802.3af/at self- adaptive, PoE power budget 58W; 3. Long distance transmission: max. 250m per port in "Extend" mode;4. VIP port: Port1-2, QoS priority;5. Lightning Protection: 6KV per port;6. Metal casing;	IRR 15,576,000	
6	DS-3E1310P-E	L2, Web managed, 8 100M PoE port, 2 1000M combo port, 802.3af/at, PoE power budget 123W	IRR 17,582,400	
7	DS-3E1318P-E	802.3af/at PoE standard 8-core power supply technology, reducing the power circuit loss,Data monitor and control for the important ports, EXTEND mode available to extend the network cable transmission distance to 250 meters Buffer optimization to guarantee the video data transmission,VLAN configurable Port trunk, multicast and port mirroring,WEB management,Store-and-forward switching IEEE802.3, IEEE802.3u and IEEE802.3x network standards available MTBF (Mean Time Between Failure) ≥ 100,000 hours All-metal enclosed construction Table-mounted and rack-mouted design for convenient installation	IRR 58,340,000	
8	Cables			

9	DS-1LN6-UE-W	UTP / CAT.6 / Indoor PVC / 23AWG, Full 305m, OFC / 0.530mm, CM Rating, Default Color: BLUE. TEST FLUKE	IRR 14,160,000	
10	DS-1LN6-UU	UTP / CAT.6 / Indoor PVC / 23AWG Full 305m OFC / 0.565mm CM Rating Default Color: Orange	IRR 15,580,000	
11	Brackets			
12	DS-1602ZJ	Wall mount , Hik white , Aluminum alloy , 97x182x305mm Suitable for:-DS-2DE/AE4xxx-DS-2DE/AE5xxx-DS-2DE/AE7xxx-DS-2DF8xxx-DS-2DF6xxx DS-2DF7xxx-DS-2DF5xxx	IRR 3,730,000	
13	DS-1602ZJ-pole	Vertical pole mount, Hik white , Aluminum alloy , 117x194x310mm , Suitable for:DS-2DE/AE5xxx-DS-2DE/AE7xxx-DS-2DF8xxx--DS-2DF6xxx-DS-2DF7xxx-DS-2DF5xxx	IRR 5,283,000	
14	DS-1605ZJ	Wall Mount bracket Parameters: Wall mounting bracket-Colour: Hik White-Feature: Suitable for speed dome cameras Dimensions: Ø171.7 x 158 x 228.6mm	***	
15	DS-1661ZJ	Pendent Mounting Bracket In/Outdoor,-Color: -Hik white-Material: -Aluminum alloy-Dimensin: - 116.5x200mm-Weight: -600g	IRR 3,654,000	
16	DS-1662ZJ	Pendant mount , Hik white , Aluminum alloy , Φ116.5x500mm Suitable for:-DS-2DE/AE4xxx-DS-2DE/AE5xxx-DS-2DE/AE7xxx-DS-2DF8xxx-DS-2DF6xxx-DS- 2DF7xxx-DS-2DF5xxx	IRR 4,194,000	
17	DS-1663ZJ	Ceiling mount , Hik white , Aluminum alloy , Φ116.5x57mm-Suitable for:-DS-2DE/AE4xxx DS-2DE/AE5xxx-DS-2DE/AE7xxx-DS-2DF8xxx-DS-2DF6xxx-DS-2DF7xxx-DS-2DF5xxx	IRR 1,810,000	
18	DS-1693ZJ	Wall mount , Hik white , steel , 190x200x500mm , 5700g Suitable for PTZ positioner	IRR 3,000,000	
19	DS-1681ZJ	Ceiling mount , Hik white , Aluminum alloy -Suitable for:-DS-2DE/AE4xxx-DS-2DE/AE5xxx DS-2DE/AE7xxx-DS-2DF8xxx-DS-2DF6xxx-DS-2DF7xxx-DS-2DF5xxx	IRR 1,224,000	

20	DS-1273ZJ-135B	Wall mount , White , Aluminum alloy , with junction box , Φ 135x182x120mm Suitable for: DS-2CD27xx	Call	
21	Keyboard			
22	DS-1100KI	Network Keyboard, 7" TFT touch screen, up to 256 units of DVR/Network Cameras/Speed Dome management, 1-ch HD 1080p video steam decoding, USB 2.0 interface for video backup	IRR 188,180,000	
23	DS-1005KI	network Keyboard, USB interface, support Hikvision VMS, NVR, DVR	IRR 45,100,000	
24	Tester			
25	IPC-4300H	IPC-4300 IP camera tester 4.3 inch capacitive touch screen / ONVIF/ Hikvision, Dahua, etc more than 40 IP camera brands test /IP Camera view /12 V/2A power output / 5V 2A power bank / PoE power supply / HDMI output / WIFI	IRR 40,920,000	
26	DS-TT-X41T	7" LCD Screen, Support HDTVl camera, Up the Coax, 12 VDC output	IRR 65,150,000	
27	Access Control			
28	DS-K2804	Four-door Access Controller, Accessible Card Reader: 4 Wiegand readers; Input interface: Door Magneticx4, Door Switchx4, Case Inputx4; Output interface: Door Switch Relayx4, Alarm Relayx4; Uplink Communication Interface: TCP/IP Network Interface; Storage with 10,000 cards information and 50,000 access control events	Call	
29	DS-K1100 Series Card Reade			
30	DS-K1101MK	Mifare 1 card, with keypad, Supports RS485 and Wiegand(W26/W34) protocol, Tamper-proof alarm, Dust-proof, IP 64, Applied for 120 Gang Box Only	Call	
31	DS-K1102M	Mifare 1 card, Supports RS485 and Wiegand(W26/W34) protocol, Tamper-proof alarm, Dust-proof, IP 64, Applied for 86 &120 Gang Box	Call	
32	DS-K1102MK	Mifare 1 card, with keypad, Supports RS485 and Wiegand(W26/W34) protocol, Tamper-proof alarm, Dust-proof, IP 64, Applied for 86 & 120 Gang Box	Call	

33	DS-K1104M	Mifare 1 card, Supports RS485 and Wiegand(W26/W34) protocol, Tamper-proof alarm, Dust-proof, Vandal Proof, IP 65, Applied for 86 & 120 Gang Box	Call	
34	DS-K1801M	Mifare 1 card, with keypad, Supports Wiegand(W26/W34) protocol, Dust-proof, IP 65	Call	
35	DS-K1801MK	Mifare 1 card, with keypad, Supports Wiegand(W26/W34) protocol, Dust-proof, IP 65	Call	
36	Card Sender			
37	DS-K1F100-D8E	Plug-and-play USB with no-driver technology, Supports various card types (Mifare card, and EM card)	Call	
38	Pro Magnetic Lock			
39	DS-K4T100	Electric Bolt, Polished and Brushed Stainless Steel, Support Thrust of 800kg; Working Current: 900mA(Startup Current), 100mA (Standby), DC12V	Call	
40	DS-K4H250S	Single-door Magnetic Lock, supports static linear thrust of 250kg, Working Current: DC12V(500 mA) / 24VAC(250 mA)	Call	
41	DS-K4H250D	Double-door Magnetic Lock, supports static linear thrust of 2 x 250kg, Working Current: 12V/500mAx2 24V/250mAx2	Call	
42	Eco Magnetic Lock			
43	DS-K4H188S	Single-door Magnetic Lock, supports static linear thrust of 188kg, Working Current: DC12V(500 mA) / 24VAC(250 mA)	Call	
44	Pro Bracket for Magnetic Loc			
45	DS-K4T100-U2	Upper and lower U-bracket of Electric Bolt, for Using with DS-K4T100	Call	
46	DS-K4H250-LZ	LZ-Bracket of Magnetic Lock, for DS-K4H250S/D	Call	

47	DS-K4H250-U	U-Bracket of Magnetic Lock, for DS-K4H250S/D	Call	
48	Eco Bracket for Magnetic Lock			
49	DS-K4H188-LZ	LZ-Bracket of Magnetic Lock, for DS-K4H188S/D	Call	
50	Door release button			
51	DS-K7P01	aluminum alloy panel, metal button, Dimension(LxWxH): 86x86x20mm(3.39x3.39x0.79")	Call	
52	DS-K1T8 Series			
53	DS-K1T803MF	LCD Display Standalone Access Control Terminal, Support Access Control and Time Attendance Function, Optical Fingerprint Module, 3,000 Fingerprints Capacity, Support Wi-Fi & TCP-IP, Stand-alone Operation, Multiple Authentication: Card(EM or Mifare-1 Card), Fingerprint, etc	Call	
54	DS-K1T200 Series			
55	DS-K1T200MF-C	2.8 inch LCD-TFT Screen IP-based Fingerprint Access Control Terminal, Built-in Mifare card reading module and 2 Megapixels camera, Max. 9500 fingerprints, Max. 100,000 cards No. and Max. 300,000 access control events records, TCP/IP, WIFI, RS-485, Wiegand Protocol communication supported, 17 Keys keyboard and doorbell, DC 12V/1A	Call	
56	DS-K1T105 Series			
57	DS-K1T105M-C	2.8 inch LCD-TFT Screen Standalone Access Control Terminal, Built-in Mifare card (EM card) reading module, 2 Megapixels camera, Max. 100,000 cards No., and Max. 300,000 access control events records, TCP/IP, WIFI, RS-485, Wiegand Protocol communication supported, 17 Keys keyboard and doorbell, DC 12V/1A	Call	
58	DS-K1T801M	Standalone Access Control Terminal, Built-in Mifare card reading module, Max. 3,000 cards No., TCP/IP, 12 Keys keyboard and doorbell, DC 12V/1A	Call	
59	DS-K1T802M	LCD Display Screen Standalone Access Control Terminal, Built-in Mifare card reading module, Max. 3,000 cards No., and Max. 10,000 access control events records, TCP/IP, 12 Keys keyboard and doorbell, DC 12V/1A	Call	
60	Card			
61	S50+TK4100	EM + Mifare	Call	

62

Adapters

63

Power Adapter

12V/1A

IRR 238,000



HIKTEHRAN

نماینده مجاز فروش محصولات هایک ویژن



آدرس فروشگاه

تهران ، خیابان جمهوری پاساژ امجد طبقه همکف پلاک 28

شماره تماس

66765923 - 66765968 - 09197108350







ایمیل

Info@Hikvisiontehran.com










CONTACT US

HIKVISIONTEHRAN.COM

Hilook-DVR

Items	Description	User Price	
1	THC-B120-P 2 MP high-performance CMOS-1920 × 1080 resolution- 2.8 mm, fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-Switchable TVI/AHD/CVI/CVBS- IP66	IRR 3,300,000	
2	THC-B120-M 2 MP high-performance CMOS-1920 × 1080 resolution- 2.8 mm, fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-Switchable TVI/AHD/CVI/CVBS- IP66-METAL	IRR 3,800,000	
3	THC-B140-P 4 MP high-performance CMOS-2560 × 1440 resolution- 2.8 mm fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- -DWDR-BLC-IP66	IRR 4,670,000	
4	THC-B140-M 4MP high-performance CMOS - 2560 × 1440 resolution- 2.8 mm- fixed focal lens-Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) -DWDR-IP 66-BLC-Full Metal	IRR 5,350,000	
5	THC-B220 2 MP high-performance CMOS-1920 × 1080 resolution- 2.8 mm fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 40 m IR distance-Switchable TVI/AHD/CVI/CVBS-IP66	IRR 4,300,000	
6	THC-B220-M 2MP CMOS Sensor, 40m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR,DWDR- OSD Menu, IP66, 2.8/3.6/6mm Lens, Support HD-TVI/AHD/CVI/CVBS video output- Full Metal	IRR 4,895,000	

7	THC-B240	4MP high-performance CMOS - 2560 x1440 resolution- 2.8 mm - fixed focal lens-Day/Night switch- EXIR 2.0, smart IR, up to 40 m IR distance- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS) - DWDR-BLC-IP 66	IRR 5,600,000	
8	THC-B240-M	4MP CMOS Sensor, EXIR Bullet, 40m IR , ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR-DWDR, OSD Menu , IP66, 2.8/3.6/6mm Lens ,Support HD-TVI/AHD/CVI/CVBS video output-Full Metal	IRR 5,900,000	
9	THC-T120-P	2 MP high-performance CMOS- 1920 x 1080 resolution- 2.8 mm , fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC	IRR 3,050,000	
10	THC-T120	2 MP high-performance CMOS- 1920 x 1080 resolution- 2.8 mm , fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC	IRR 3,450,000	
11	THC-T120-M	2 MP high-performance CMOS- 1920 x 1080 resolution- 2.8 mm , fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC-METAL	IRR 4,100,000	
12	THC-T140-P	4 MP high-performance CMOS-2560 x 1440 resolution- 2.8 mm , Fixed focal lens- Day/Night switch-EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS) DWDR-BLC-IP66	IRR 4,400,000	
13	THC-T140	4 MP high-performance CMOS-2560 x 1440 resolution- 2.8 mm , Fixed focal lens- Day/Night switch-EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS) DWDR-BLC-IP66	IRR 4,750,000	
14	THC-T140-M	4 MP high-performance CMOS-2560 x 1440 resolution- 2.8 mm , Fixed focal lens- Day/Night switch-EXIR 2.0, smart IR, up to 20 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS) DWDR-BLC-IP66-METAL	IRR 5,650,000	
15	THC-T220-P	2 MP high-performance CMOS-1920 x 1080 resolution- 2.8 mm ,fixed focal lens-Day/Night switch-EXIR 2.0, smart IR, up to 40 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC	IRR 3,650,000	
16	THC-T220-M	2 MP high-performance CMOS-1920 x 1080 resolution- 2.8 mm ,fixed focal lens-Day/Night switch-EXIR 2.0, smart IR, up to 40 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- IP66-DWDR-BLC-METAL	IRR 4,700,000	

17	THC-T240-P	4 MP high-performance CMOS-2560 × 1440 resolution-2.8 mm fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 40 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- DWDR-BLC-IP66	IRR 5,200,000	
18	THC-T240-M	4 MP high-performance CMOS-2560 × 1440 resolution-2.8 mm fixed focal lens- Day/Night switch- EXIR 2.0, smart IR, up to 40 m IR distance-4 in 1 video output (switchable TVI/AHD/CVI/CVBS)- DWDR-BLC-IP66-METAL	IRR 5,980,000	
19	Vari-Focal Series			
20	THC-B320-VF	2MP CMOS Sensor, 40m IR, Outdoor EXIR Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR,,DWDR- DNR, OSD Menu, IP66, 2.8-12mm Vari Focal Lens, Support HD-TVI/AHD/CVI/CVBS video output-Front cover: Metal-Main body: Plastic-Bracket: Metal	IRR 7,880,000	
21	THC-B340-VF	4MP CMOS Sensor - 2.8-12mm Vari Focal Lens, EXIR Bullet, 40m IR, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR,DWDR, OSD Menu, IP66, Support HD-TVI/AHD/CVI/CVBS video output- Front cover: Metal-Main body: Plastic-Bracket: Metal	IRR 8,950,000	
22	THC-D320-VF	2MP CMOS Sensor, 40m IR, EXIR Dome, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, DWDR- OSD Menu, IP66, 2.8-12mm Vari Focal Lens--support HD-TVI/AHD/CVI/CVBS video output-,IK10- Full Metal	IRR 8,300,000	
23	THC-D340-VF	4MP CMOS Sensor, EXIR Dome, 40m IR, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR,DWDR- OSD Menu, IP66, 2.8-12mm Vari Focal Lens,IK10. Support HD-TVI/AHD/CVI/CVBS video output-Full Metal	IRR 9,375,000	
24	THC-T320 VF	2MP CMOS Sensor, 40m IR, EXIR Eyeball, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, DWDR- OSD Menu, IP66, 2.8-12mm Vari Focal Lens, Support HD-TVI/AHD/CVI/CVBS video output- Cover&Base:Plastic- Eyeball: Metal	IRR 7,880,000	
25	THC-T340-VF	4MP CMOS Sensor, EXIR Eyeball, 40m IR, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR,DWDR- OSD Menu, IP66, 2.8-12mm Vari Focal Lens, Support HD-TVI/AHD/CVI/CVBS video output-Cover&Base:Plastic-Eyeball: Metal	IRR 8,950,000	
26	Turbo HD PTZ Camera			
27	PTZ-T4225I-D2 MP IR	1/2.8" HD progressive scan CMOS 1920 × 1080 resolution 25x optical zoom, 16x digital zoom 120 dB true WDR (Wide Dynamic Range) Up to 100 m IR distance 3D intelligent positioning Switchable TVI/AHD/CVI/CVBS video outputs	IRR 49,100,000	

28	PTZ-T4215I-D	<p>1/2.8" HD progressive scan CMOS 1920 x 1080 resolution 5x optical zoom, 16x digital zoom 20 dB true WDR (Wide Dynamic Range) Up to 100 m IR distance 3D intelligent positioning Switchable TVI/AHD/CVI/ CVBS video outputs</p>	IRR 39,500,000	
29	PTZ-T5225I-A	<p>1/2.8" HD progressive scan CMOS 1920 x 1080 resolution 25x optical zoom DWDR (Digital Wide Dynamic Range) Up to 150 m IR distance 3D intelligent positioning Switchable turbo HD and CVBS outputs</p>	IRR 58,400,000	
30	DVR 4 Channel			
31	DVR-204G-F1	<p>Recording Capability HD1080p Lite 4-ch -HD-TVI/AHD/CVI/ CVBS video & 1-ch audio input, - 1-ch Up to 960P resolution), 1 SATA (6TB) interface, HD1080p Lite @ 25 fps/ch, 260 1U case--HDMI output HD1080p-Metal</p>	IRR 7,580,000	
32	DVR-204Q-F1	<p>Recording Capability 3MP 4-ch -HD-TVI/AHD/CVI/ CVBS video & 1-ch audio input, 1-ch IP video input(up to HD1080p resolution), 1 SATA(6TB) interface, CH 1: 3MP @ 12 fps, CH 2-4:1920x1080P: 12 fps/ch, 260 1U case--HDMI outputHD1080p-Metal</p>	IRR 9,700,000	
33	DVR-204Q-K1	<p>H265+ compression saving up to 50% on bandwidth and storage. Recording 2MP@15FPS on 1080P or @25FPS on 1080PLite (3MP@15FPS on channel 1) Support self-adaptive HDTV/HDCVI/AHD/CVBS signal input.Add up to 2 x 6MP IP cameras.HDMI output at 1920 x 1080 resolution Up to 4-ch synchronous playback at 1080p resolution playback at up to 256X speed.</p>	IRR 10,700,000	
34	DVR-204U-F1	<p>Recording Capability 5MP/3MP 4-ch -HD-TVI/AHD/CVI/ CVBS video & 1-ch audio input, - 2-ch IP video input(up to 6MP resolution), 1 SATA (6 TB)- interface,5MP@12fps,4MP@15fps,3MP@18fps,1080p/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N), 315 1U case--HDMI output HD1080p-Metal</p>	IRR 15,700,000	
35	DVR-204U-K1	<p>Self-adaptive HDTV/HDCVI/AHD/CVBS signal input I Up to 8/16-ch 8 MP IP cameras input for DVR-204/208U-K1 I 8 MP/5 MP/4 MP HDTV video input and live view for DVR-208U-K1, and 5MP/4 MP for DVR-204U-K1 I Defogging function enabled for the supported analog cameras I Long distance transmission over UTP and coaxial cable: max. 800m for 1080p and 1200m for 720p HDTV signal</p>	IRR 16,710,000	
36	DVR 8 Channel			
37	DVR-208G-F1	<p>Recording Capability HD1080p Lite 8-ch -HD-TVI/AHD/CVI/ CVBS video & 1-ch audio input, -2-ch Up to 960P resolution), 1 SATA(6TB) interface, HD1080p Lite @ 12 fps/ch, 260 1U case--HDMI output HD1080p-Metal</p>	IRR 9,850,000	

38	DVR-208Q-F1	Recording Capability 3MP 8-ch -HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, -2-ch IP video input(up to HD1080p resolution), 1 SATA (6TB) interface, CH 1 & 2: 3MP @ 12 fps, CH 3 - 8:1920x1080P: 12 fps/ch, 260 1U case- HDMI output HD1080p-Metal	IRR 16,300,000	
39	DVR-208Q-K1	Connectable to turbo HD, AHD, HDCVI and analog cameras. 2-ch 1080p IP cameras input. Long distance transmission over UTP and coaxial cable One key enable H.264+ compression. Up to 3 MP resolution for recording of the first 2 channels. Supports real-time 1080p lite. Simultaneous HDMI/VGA output at up to 1920 x 1080 resolution. One SATA interface (up to 6TB capacity per HDD).	IRR 17,200,000	
40	DVR-208U-F1	Recording Capability 5MP/3MP 8-ch -HD-TVI/AHD/CVI/CVBS video & 1-ch audio input- 4-ch IP video input(up to 6MP resolution) , 1 SATA (6 TB) interface,5MP@12fps,4MP@15fps,3MP@18fps,1080p/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N), 315 1U case- HDMI output 4K-Metal	IRR 25,100,000	
41	DVR-208U-K1	8 Channel DVR,Support HD-TVI, AHD, HD-CVI and analog cameras Supports 4 x IP Camera,1080P resolution real-time recording 8MP recording @ 8fps,VGA output at up to 1920 x 1080P resolution HDMI output at up to 4K (3840 x 2160) resolution,Supports h.265+ Support up to 8-ch synchronous playback,Internet & Smart Phone compatible	IRR 26,700,000	
42	Digital Video Recorder			
43	DVR-216G-F1	Recording Capability HD1080p Lite 16-ch -HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, -2-ch Up to 960P resolution, 1 SATA (6TB)interface, HD1080p Lite @ 12 fps/ch, 260 1U case- HDMI output HD1080p-Metal	IRR 15,430,000	
44	DVR-216Q-F1	Recording Capability 3MP 16-ch HD-TVI/AHD/CVI/CVBS video & 1-ch audio input, -2-ch IP video input(up to HD1080p resolution), 1 SATA (6TB)- interface, CH 1 - 4: 3MP @ 12 fps, CH 5 - 16:1920x1080P: 12 fps/ch, 260 1U case- HDMI output 1ch 4k-Metal	IRR 25,750,000	
45	DVR-216Q-K1	One-key enable H.265+ compression Self adaptive: TVI Turbo HD, AHD, HD-CVI & analog inputs Accepts 16 BNC analog video inputs Up to 8ch IP video input (6MP) Max 24ch: 16 HD and 8 IP Long distance transmission over UTP & coaxial cable Supports real-time 1080P lite	IRR 26,112,000	
46	DVR-216U-F2	Recording Capability 5MP/3MP 16-ch -HD-TVI/AHD/CVI/CVBS video & 1-ch audio input,- 8-ch IP video input(up to 6MP resolution) , 2 SATA (6 TB)- interface,5MP@12fps,4MP@15fps,3MP@18fps,1080p/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N), 380 1U case- HDMI output 1ch 4K-Metal-	IRR 53,500,000	

DVR-216U-K2

DVR 16 Channels HD 8 Megapixel, Interfaces input: 16 video / 1 Audio,
(Support TVI - AHD – CVI - CVBS, HDMI, VGA Outputs, 2 USB
Support H.265+ compression, 2SATA up to 8TB capacity per HDD, Up to 8-ch, 6MP IP
cameras input, Up to 8 MP resolution for recording

IRR 54,500,000

HIKTEHRAN

نماینده مجاز فروش محصولات هایک ویژن

آدرس فروشگاه

تهران ، خیابان جمهوری پاساژ امجد طبقه همکف پلاک 28

شماره تماس

66765923 - 66765968 - 09197108350

ایمیل

Info@Hikvisiontehran.com



CONTACT US
HIKVISIONTEHRAN.COM

Hilook-NVR

Items

Description

User Price

1

IPC-B120

1/2.8" progressive scan CMOS-1920 x 1080@30fps -2.8 mm fixed lens- H.264+, H.264- Color: 0.01 Lux @(F1.2, AGC ON), 0.028 Lux @(F2.0, AGC ON)-BLC/3D DNR-IP67-Digital WDR

IRR 8,700,000



2

IPC-B120H

2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H265/H.264+&H.264, 3D DNR, -2.8/4/6mm fixed lensBLC, DC12V & PoE,-up to 30m IR-Support mobile monitoring via Hik-Connec *power supply no included-DWDR-Front Cover: Metal-Back Cover & Bracket: Plastic-IP67

IRR 9,300,000



3

IPC-B140H

4MP- 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, 3D DNR, BLC, DWDR- DC12V & PoE,2.8/4/6mm fixed lens, Support mobile monitoring via Hik-up to 30m IR, Connec *power supply no included-Front Cover: Metal
Back Cover & Bracket: Plastic-IP67

IRR 11,950,000



4

IPC-B220

1/2.8" progressive scan CMOS
- Up to 2.0 megapixel high resolution-H264- 4 mm Lens-Up to 30 m IR distance-Dual stream-DWDR-3D DNR (Digital Noise Reduction)-BLC-IP67- Mobile monitoring via mobile application

IRR 10,771,200



5

IPC-B220-D

1/2.8" progressive scan CMOS
- Up to 2.0 megapixel high resolution-H264- 4 mm Lens-Up to 30 m IR distance-Dual stream-DWDR-3D DNR (Digital Noise Reduction)-BLC-IP67- Mobile monitoring via mobile application- D model only support 12VDC power supply

IRR 7,950,000



6

IPC-T120

2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N),DWDR - H.264+&H.264-,2.8/4/6mm fixed lens- BLC, - DC12V & PoE ,-up to 10m IR- Support mobile monitoring via Hik-Connect *power supply no included-Eyeball:Plastic-Cover: Plastic-Indoor-ip67

IRR 8,300,000












7








IPC-T120-D

1/2.8" progressive scan CMOS-Up to 2.0 megapixel
-2.8 mm fixed focal lens-H264+ - 10 m IR range-Dual stream-DWDR-3D DNR (Digital Noise Reduction)- Mobile monitoring via mobile application-IP 67- D model only support 12VDC power supply










IRR 7,900,000



8	IPC-T220-H	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H265/H.264+&H.264, 3D DNRDWDR, BLC, DC12V & PoE,-up to 30m IR-Support mobile monitoring via HikConnec *power supply no included2.8/4/6mm fixed lens-Eyeball: MetalCover: Plastic-IP67	IRR 9,300,000	
9	IPC-T240H	4MP-1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, up to 30m IR- 3D DNR-DWDR, BLC, DC12V & PoE-2.8/4/6mm fixed lens,--Support mobile monitoring via Hik-Connec *power supply no included-Eyeball: Metal-Cover: Plastic- IP67	IRR 11,950,000	
10	IPC-D120	1/2.8" progressive scan CMOS-2 MP-1920 x 1080@30fps-2.8mm fixed lens-H.264+, H.264-Color: 0.01 Lux @(F1.2, AGC ON), 0.028 Lux @(F2.0, AGC ON)-BLC/3D DNR-IP67-Digital WDR- IK 10	IRR 8,300,000	
11	IPC-D120H	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H265/H.264+&H.264, 3D DNR,--2.8/4/6mm fixed lens- BLC, DC12V & PoE,DWDR- Support mobile monitoring via Hik-Connect *power supply no included-up to 30m IR-Base: Metal-Cover: Plastic-IP67, IK10	IRR 9,950,000	
12	IPC-D140H	4MP-1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264-,2.8/4/6mm fixed lens- 3D DNR-up to 30m IR, BLC,DWDR- DC12V & PoE,Support mobile monitoring via Hik-Connect *power supply no included-Base: Metal-Cover: Plastic--IP67, IK10-	IRR 11,850,000	
13	Vari-Focal Series			
14	IPC-B620H-V	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N),H.265+/H265/H.264+&H.264, 3D DNR ,DWDR- BLC, DC12V & PoE, TF card slot,up to 30m IR-Support mobile monitoring via Hik-Connect *power supply no included-2.8~12mm vari-focal lens-Body&Bracket: Metal-SunShield: Plastic-IP67	IRR 17,050,000	
15	IPC-B620H-Z	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N),H.265+/H265/H.264+&H.264, 3D DNR, BLC, -up to 30m IR-DC12V & PoE, -DWDR- TF card slot,-Support mobile monitoring via Hik-Connect *power supply no included-2.8~12mm motorized vari-focal lens-Body&Bracket: Metal-SunShield: Plastic-IP67	IRR 19,500,000	
16	IPC-B640H-V	4MP- 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, 3D DNR, BLC,up to 30m IR- DC12V & PoE, TF card slot, WDR- Support mobile monitoring via Hik-Connect *power supply no included-2.8~12mm vari-focal lens-Body&Bracket: Metal-SunShield: Plastic--IP67	IRR 19,500,000	
17	IPC-B640H-Z	4MP- 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, 3D DNR, BLC,up to 30m IR- DC12V & PoE, TF card slot,-WDR- Support mobile monitoring via Hik-Connect *power supply no included-2.8~12mm motorized vari-focal lens-Body&Bracket: Metal-SunShield: Plastic-IP67	IRR 22,600,000	

18	IPC-T620-Z	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.264+&H.264, 3D DNR, BLC,-WDR- up to 30m IR-DC12V & PoE,Support mobile monitoring via Hik-Connect *power supply no included2.8~12mm VF lens-Eyeball: MetalCover: Plastic-IP67	IRR 24,763,200	
19	IPC-D620H-V	2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H265/H.264+&H.264,DWDR- 3D DNR, BLC,2.8~12mm varifocal lens - DC12V & PoE, TF card slot,-up to 30m IR - Support mobile monitoring via Hik-Connect *power supply no included -Full Metal- IP67 , IK10	IRR 17,050,000	
20	IPC-D620H-Z	1/2.8" progressive scan CMOS-2 MP-1920 x 1080@30fps- 2.8 mm to 12 mm manual/motorized (with -Z) vari-focal lens- H.265+, H.265, H.264+, H.264-Dual stream-DWDR -3D DNR (Digital Noise Reduction)-Up to 30 m IR range-PoE (Power over Ethernet)- IP67 , IK10	IRR 19,500,000	
21	IPC-D640H-V	4MP-1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264,WDR, 3D DNR, BLC,up to 30m IR - DC12V & PoE, TF card slot-- 2.8~12mm vari-focal lens - Support mobile monitoring via Hik-Connect *power supply no included - Full Metal- IP67 , IK10	IRR 19,500,000	
	IPC-D640H-Z	4MP-1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264,WDR, 3D DNR, BLC,up to 30m IR - DC12V & PoE, TF card slot-- 2.8~12mm vari-focal lens - Support mobile monitoring via Hik-Connect *power supply no included - Full Metal- IP67 , IK10	IRR 22,600,000	
22	PanoVu Mini Series IR Network PTZ Camera			
23	PTZ-P332ZI-DE3	System Functions I 3-ch panoramic images in different directions and 1-ch close-up image I PTZ linkagel Up to 10 m IR radius Panoramic Cameral Three 1/2.8" progressive scan CMOSI 3-ch 1920 x 1080@30fps resolutionI Horizontal FOV: 128.5° x 3 PTZ Cameral 1/2.8" progressive scan CMOSI Up to 1920 x 1080@30fps resolutionI 4x optical zoom, 8x digital zoom	IRR 74,400,000	
24	IP PTZ Camera			
25	PTZ-N2204I-DE3	1/2.8" progressive scan CMOS .Up to 1920 x 1080@30fps resolution Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR 4x optical zoom, 16x digital zoom 20 dB WDR, 3D DNR, HLC, EIS, Regional Exposure, Regional Focus 2 VDC & PoE .Up to 20 m IR distanceIK10, IP66Support H.265+/H.265 video compression	IRR 25,670,000	

26	PTZ-N2404I-DE3	<p>1/3" progressive scan CMOS .Up to 2560 × 1440@25fps resolution Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR 15x optical zoom, 16x digital zoom 120dB WDR, 3D DNR, HLC, EIS, Regional Exposure, Regional Focus 2 VDC & PoE .Up to 20 m IR distance. IK10, IP66 Support H.265+/H.265 video compression</p>	IRR 29,400,000	
27	PTZ-N4215-DE3	<p>1/2.8" progressive scan CMOS Up to 1920 × 1080 resolution Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR 15x optical zoom, 16x digital zoom 120dB WDR, 3D DNR, HLC, BLC 12 VDC & PoE+ (802.3at, class4) Support H.265+/H.265 video compression Up to 24 programmable privacy masks Support ROI</p>	IRR 42,780,000	
28	PTZ-N4215I-DE	<p>1/2.8" progressive scan CMOS Up to 1920 × 1080 resolution Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR Up to 100 m IR distance 15x optical zoom, 16x digital zoom 120dB WDR, 3D DNR, HLC, BLC, Smart IR 12 VDC & PoE+ (802.3at, class4) Support H.265+/H.265 video compression Up to 24 programmable privacy masks Support ROI</p>	IRR 45,750,000	
29	PTZ-N4225I-DE	<p>1/2.8" progressive scan CMOS Up to 1920 × 1080 resolution Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR Up to 100 m IR distance 25x optical zoom, 16x digital zoom 120dB WDR, 3D DNR, HLC, BLC, Smart IR 12 VDC & PoE+ (802.3at, class4) Support H.265+/H.265 video compression Up to 24 programmable privacy masks Support ROI</p>	IRR 61,750,000	
30	PTZ-N5225I-AE	<p>1/2.8" progressive scan CMOS Up to 1920 × 1080 resolution Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR Up to 150 m IR distance 25x optical zoom, 16x digital zoom 120dB WDR, 3D DNR, HLC, BLC, Smart IR 24 VAC & PoE+ (802.3at, class4) Support H.265+/H.265 video compression Up to 24 programmable privacy masks Support ROI Support smart detection</p>	IRR 68,100,000	
31	Network Video Recorder			
32	NVR-104-B	<p>Full channel recording at up to 4 MP resolution-40Mbps Bit Rate Input Max (up to 4-ch IP video),Output Bandwidth 40Mbps- H.264, 1 SATA interface 6TB, mini 1U case(Plastic)-HDMI Output 1, up to 1080P-Decoding Capability- 2-ch@ 4MP-4-ch@1080p</p>	IRR 8,100,000	

33	NVR-104-B/4P	Full channel recording at up to 4 MP resolution-40Mbps Bit Rate Input Max (up to 4-ch IP video),Output Bandwidth 40Mbps- H.264, 1 SATA interface 6TB , 4 independent PoE network interfaces, mini 1U case(Plastic)-HDMI Output 1, up to 1080P-Decoding Capability-4-ch 1080P,or 2-ch 4MP	IRR 14,823,600	
34	NVR-108-B	Full channel recording at up to 4 MP resolution-60Mbps Bit Rate Input -Max (up to 8-ch IP video),,Output Bandwidth 40Mbps- H.264, 1 SATA interface 6TB, mini 1U case(Plastic)-HDMI Output 1, up to 1080P-Decoding Capability-2-ch@4 MP, 4-ch@1080p	IRR 10,300,000	
35	NVR-108-B/8P	Full channel recording at up to 4 MP resolution-60Mbps Bit Rate Input Max (up to 8-ch IP video),Output Bandwidth 40Mbps- H.264, 1 SATA interface 6TB ,8 independent PoE network interfaces, mini 1U case(Plastic)-HDMI Output 1, up to 1080P-Decoding Capability-4-ch 1080P,or 2-ch 4MP	IRR 20,869,200	
36	NVR-104MH-C	Recording at up to 8 MP resolution40Mbps Bit Rate -Input Max (up to 4-ch IP video UP to 8MP), Output Bandwidth 80Mbps- H.265-, 1 SATA (6TB)interface, standalone 1U 315 case(Metal)-HDMI Output 1CH 4K, --Decoding Capability 1-ch @ 8 MP / 4-ch @ 1080p	IRR 11,200,000	
37	NVR-104MH-C/4P	Recording at up to 8 MP resolution-40Mbps Bit Rate Input- Max (up to 4-ch IP video UP to 8 MP) ,Output Bandwidth 80Mbps- H.265-, 1SATA(6TB) interface, 4 independent PoE network interfaces, 1U 315 case(Metal)-HDMI Output 1ch 4k-Decoding Capability 1-ch @ 8 MP 4-ch @ 1080P	IRR 20,930,000	
38	NVR-108MH-C	Recording at up to 8 MP resolution-80Mbps Bit Rate Input- Max (up to 8-ch IP video UP to 8 MP),Output Bandwidth 80Mbps- H.265, 1 SATA interface(6TB), standalone 1U 315 case(Metal)-HDMI Output 1CH 4K,Decoding Capability: -1-ch @ 8 MP / 4-ch @ 1080p	IRR 15,600,000	
39	NVR-108MH-C/8P	Recording at up to 8 MP resolution-80Mbps Bit Rate Input- Max (up to 8-ch IP video UP tp 8mp),Output Bandwidth 80Mbps-, H.265, 1 SATA interface(6 TB),8 independent PoE network interfaces, standalone 1U 315 case(Metal)--HDMI Output 1ch 4k, - Decoding Capability:1-ch @ 8 MP / 4-ch @ 1080p	IRR 29,600,000	
40	NVR-116MH-C	Recording at up to 8 MP resolution-160Mbps Bit Rate Input- Max (up to 16-ch IP video UP to 8MP),Output Bandwidth 80Mbps-, H.265, 1 SATA interface(6TB), standalone 1U 315 case(Metal)-HDMI Output 1CH 4K, Decoding Capability: 1-ch @ 8 MP / 4-ch @ 1080p	IRR 18,430,000	
41	NVR-216MH-C	Recording at up to 8 MP resolution-160Mbps Bit Rate Input Max (up to 16-ch IP video),Output Bandwidth 80Mbps, - H.265-2,SATA up to 6TB per HDD interface, standalone 1U 385 case(Metal)-HDMI Output1 ch 4k -Decoding Capability: 1-ch @ 8 MP / 4-ch @ 1080p	IRR 22,500,000	

NVR-216MH-C/16P

Recording at up to 8 MP resolution-160Mbps Bit Rate Input Max (up to 16-ch IP video)Output Bandwidth 80Mbps, H.265, 2 SATA(up to 6TB per HDD) interface,16 independent PoE network interfaces, standalone 1U 385 case(Metal)-HDMI Output1 ch 4k,-Decoding Capability 1-ch @ 8 MP / 4-ch @ 1080p

IRR 42,000,000

HOME - Bussiness

Items

Description

User Price

Modem Router

1	X6200-EU	Linksys X6200 ADSL2+ Modem; 802.11a/b/g/n/ac; Dual Band; Max 433Mbps + 300Mbps; 4 x 10/100/1000 Ports; 1 x USB Port; MIMO2x2; Internal Antennas	IRR 12,400,000
2	XAC1200-EK	Linksys XAC1200 ADSL2+ Modem; 802.11a/b/g/n/ac; Dual Band; Max 867Mbps + 300Mbps; 4 x 10/100/1000 Ports; 1 x USB Port; MIMO2x2; Internal Antennas	IRR 18,230,000
3	XAC1900-EK	Linksys XAC1900 ADSL2+ Modem; 802.11a/b/g/n/ac; Dual Band; Max 1300Mbps + 600Mbps; 4 x 10/100/1000 Ports; 2 x USB Ports; MIMO3x3; External Antennas	IRR 28,260,000
4	Wireless Router E-series		
5	E900-EE	Linksys E900 Wireless-N Router; 802.11b/g/n; Single Band; Max 300Mbps; 4 x 10/100 Ports; No USB; MIMO2x2; Internal Antennas	IRR 2,990,000
6	E1200-M2	Linksys E1200 Wireless-N Router; 802.11b/g/n; Single Band; Max 300Mbps; 4 x 10/100 Ports; No USB; MIMO2x2; Internal Antennas	IRR 4,490,000
7	E1700-EK	Linksys E1700 Wireless-N Router; 802.11b/g/n; Single Band; Max 300Mbps; 4 x 10/100/1000 Ports; No USB; MIMO2x2; External Antennas	IRR 5,430,000
8	E2500-M2	Linksys E2500 Wireless-N Router; 802.11a/b/g/n; Dual Band; Max 300Mbps; 4 x 10/100/100 Ports; 1xUSB; MIMO2x2; Internal Antennas	IRR 6,550,000

9	Wireless Router EA-series		
10	EA2750-M2	Linksys EA2750 Wireless-N Router; 802.11a/b/g/n; Dual Band Concurrent; Max 300Mbps + 300Mbps; 4x10/100/1000 Ports; 1xUSB; MIMO2x2; External Antennas	IRR 9,170,000
11	EA6100-EK	Linksys EA6100 Wireless-AC Router; 802.11a/b/g/n/ac; Dual Band Concurrent; Max 867Mbps + 300Mbps; 4x10/100 Ports; 1xUSB; MIMO2x2; External Antennas	IRR 9,260,000
12	EA6350-EK	Linksys EA6350 Wireless-AC Router; 802.11a/b/g/n/ac; Dual Band Concurrent; Max 867Mbps + 300Mbps; 4x10/100/1000 Ports; 1xUSB; MIMO2x2; External Antennas	IRR 15,350,000
13	EA6900-M2	Linksys EA6900 Wireless-AC Router; 802.11a/b/g/n/ac; Dual Band Concurrent; Max 1300Mbps + 600Mbps; 4x10/100/1000 Ports; 2xUSB; MIMO3x3; External Antennas	IRR 21,930,000
14	EA7500-EU	Linksys EA7500 Wireless-AC Router; 802.11a/b/g/n/ac; Dual Band Concurrent; Max 1300Mbps + 600Mbps; 4x10/100/1000 Ports; 2xUSB; MU-MIMO3x3; External Antennas	IRR 25,270,000
15	EA8500-EU	Linksys EA8500 Wireless-AC Router; 802.11a/b/g/n/ac; Dual Band Concurrent; Max 1733Mbps + 800Mbps; 4x10/100/1000 Ports; 2xUSB; MU-MIMO4x4; External Antennas	IRR 32,760,000
16	EA9500-EU	Linksys EA9500 Wireless-AC Router; 802.11a/b/g/n/ac; Dual Band Concurrent; Max 2166Mbps + 1000Mbps; 8x10/100/1000 Ports; 2xUSB; MU-MIMO4x4; External Antennas	IRR 53,360,000
17	Wireless Router WRT-series		
18	WRT1900ACS-EU	Linksys WRT1900ACS Wireless-AC Router; 802.11a/b/g/n/ac; Dual Band Concurrent; Max 1300Mbps + 600Mbps; 4x10/100/1000 Ports; 2xUSB; MU-MIMO4x4; External Antennas	IRR 22,280,000
19	WRT1200AC-EU	Linksys WRT1200AC Wireless-AC Router; 802.11a/b/g/n/ac; Dual Band Concurrent; Max 867Mbps + 300Mbps; 4x10/100/1000 Ports; 2xUSB; MIMO2x2; External Antennas	IRR 17,780,000
20	WRT3200ACM-EU	Linksys WRT3200ACS Wireless-AC Router; 802.11a/b/g/n/ac; Dual Band Concurrent; Max 2600Mbps + 600Mbps; 4x10/100/1000 Ports; 2xUSB; MU-MIMO4x4; External Antennas	IRR 35,560,000
21	WRT32X-EU	LINKSYS WRT32X WIFI ROUTER,AC3200 DUAL-BAND WI-FI GAMING ROUTER WITH KILLER PRIORITIZATION ENGINE; 4 Gigabit ports; 4 detach Antenna; 2 USB Ports	IRR 39,320,000
22	USB Adapter		
23	AE1200-EE	Linksys AE1200 Wireless-N USB Adapter; Single Band; Max 300Mbps	IRR 2,430,000

24	AE2500-EE	Linksys AE2500 Wireless-N USB Adapter; Dual Band; Max 300Mbps	IRR 9,390,000
25	AE6000-EE	Linksys AE6000 Wireless-AC USB Adapter; Dual Band; Max 433Mbps	IRR 9,390,000
26	WUSB6100M-EU	Linksys WUSB6100M Wireless-AC USB Adapter; Dual Band; Max 433Mbps	IRR 6,550,000
27	WUSB6300-EK	Linksys WUSB6300 Wireless-AC USB Adapter; Dual Band; Max 867Mbps	IRR 5,990,000
28	USB3GIG-EJ	Linksys USB 3.0 Gigabit Ethernet Adapter	IRR 2,990,000
29	Range Extender		
30	RE3000W-EK	Linksys RE3000W Range Extender; Single Band; 802.11b/g/n; Max 300Mbps; 1x10/100 Port	IRR 5,270,000
31	RE4100W-EU	Linksys RE4100W Range Extender; Dual Band; 802.11a/b/g/n; Max 300Mbps; 1x10/100 Port	IRR 6,360,000
32	RE6300-EU	Linksys RE6300 Range Extender; Dual Band; 802.11a/b/g/n/ac; Max 433Mbps; 1x10/100/1000 Port	IRR 9,300,000
33	RE6400-EU	Linksys RE6400 Range Extender; Dual Band; 802.11a/b/g/n/ac; Max 867Mbps; 1x10/100/1000 Port	IRR 9,730,000
34	RE6500-EU	Linksys RE6500 Range Extender; Dual Band; 802.11a/b/g/n/ac; Max 867Mbps; 4x10/100/1000 Port; Audio Jack; Desktop	IRR 12,540,000
35	RE6700-EG	Linksys RE6700 Range Extender; Dual Band; 802.11a/b/g/n/ac; Max 867Mbps; 1x10/100/1000 Port; Audio Jack; Power Out	IRR 13,480,000
36	Switches (HOME)		
37	SE2500-EU	Linksys SE2500 Gigabit Switch; 5x10/100/1000 Ports; Plastic Case; Desktop; Power Saving	IRR 4,120,000
38	SE2800-EU	Linksys SE2800 Gigabit Switch; 8x10/100/1000 Ports; Plastic Case; Desktop; Power Saving	IRR 5,782,000
39	SE4008	Linksys SE4008 Gigabit Switch; 8x10/100/1000 Ports; Plastic Case; Desktop; Power Saving; Stacks over WRT1900AC	IRR 6,550,000
40	Switches (Business)		

41	LGS105-EU	5-Ports Auto-Sensing; Unmanaged; Gigabit; Metal Case; Desktop or Wall Mount; Fanless; Power Saving; Adapter Included	IRR 4,100,000
42	LGS108-EU	8-Ports Auto-Sensing; Unmanaged; Gigabit; Metal Case; Desktop or Wall Mount; Fanless; Power Saving; Adapter Included	IRR 4,900,000
43	LGS116-EU	16-Ports Auto-Sensing; Unmanaged; Gigabit; Metal Case; Desktop; Wall Mount; Fanless; Power Saving; Adapter Included	IRR 15,110,000
44	LGS124-EU	24-Ports Gigabit ,Unmanaged, QOS, Metal, RackMount; 24x10/100/1000 Ports	IRR 21,520,000
45	LGS308-EU	8-Ports Gigabit; Smart, Advanced QOS, TFTP Upgrade, Port Mirroring (up to 4 Ports), Metal, Wallmount, RMON, VLAN 802.1Q	IRR 9,770,000
46	LGS318-EU	18-Ports Gigabit 2 Combo Ports (RJ45 + SFP) , Advanced QOS, TFTP Upgrade, Port Mirroring (up to 4 Ports), Metal, Rackmount, RMON, VLAN 802.1Q	IRR 22,590,000
47	LGS326-EU	26-Ports Gigabit, 2 Combo Ports (RJ45 + SFP) Enhanced QOS, TFTP Upgrade, Port Mirroring (up to 4 Ports), Metal, Rackmount, RMON	IRR 27,060,000
48	LGS528-EU	28-Ports Gigabit , Layer 3 Static Routing, 28Ports , 2 Combo Ports (RJ45 + SFP) Advanced QOS, TFTP Upgrade, Port Mirroring , Metal, Rackmount, RMON.VLAN 802.1Q, Auto Voice VLAN, IGMP Snooping, HOL blocking pervation, Storm Control, SNMP V1-V2c, Copper FE/GE Ports, Total System Ports: 28GE-	IRR 43,760,000
49	LGS552-EU	52-Ports Gigabit , Layer 3 Static Routing, 2 Combo Ports (RJ45 + SFP), 2 X 10GB uplink Ethernet SFP+, advanced QOS, TFTP Upgrade, Port Mirroring , Metal, Rackmount, RMON.VLAN 802.1Q, Auto Voice VLAN, IGMP Snooping, HOL blocking pervation, Storm Control, SNMP V1-V2c, Copper FE/GE Ports, Total System Ports:	IRR 78,150,000
50	Switches POE		
51	LGS108P-EU	8-Ports Gigabit ,Unmanaged, 4 Ports POE, 50W, QOS, Metal,Wall Mount	IRR 13,020,000
52	LGS116P-EU	Gigabit ,Unmanaged, 16-Port (8POE), 80W, QOS, Metal, Wall Mount	IRR 21,160,000
53	LGS124P-EU	Gigabit, Unmanaged, 24-Port (12POE), 120W, QOS, Metal, RackMount	IRR 32,810,000
54	LGS308P-EU	8-Ports Gigabit ,Smart, 8Port POE 802.3af & 802.3at, 72W, Advances QOS, TFTP Upgrade, Port Mirroring (up to 4 Ports), Metal, Wallmount, RMON, VLAN 802.1Q	IRR 18,310,000
55	LGS318P-EU	Gigabit ,Smart, 18-Ports (16POE) 802.3af & 802.3at, 125W, 2 Combo Ports (RJ45 + SFP) Enhanced QOS, TFTP Upgrade, Port Mirroring (up to 4 Ports), Metal, Rackmount, RMON.VLAN 802.1Q	IRR 46,650,000

56	LGS326P-EU	Gigabit ,Smart, 26-Ports (24POE) 802.3af & 802.3at, 192W, 2 Combo Ports (RJ45 + SFP) Enhanced QOS, TFTP Upgrade, Port Mirroring (up to 4 Ports), Metal, Rackmount, RMON	IRR 65,000,000
57	LGS326MP-EU	Gigabit ,Smart, 26-Ports (24POE) 802.3af & 802.3at, 384W, 2 Combo Ports (RJ45 + SFP) Enhanced QOS, TFTP Upgrade, Port Mirroring (up to 4 Ports), Metal, Rackmount, RMON	IRR 68,800,000
58	LGS528P-EU	28-Ports Gigabit , Layer 3 Static Routing, 24Ports POE 192W Budget, 2 Combo Ports (RJ45 + SFP),, advanced QOS, TFTP Upgrade, Port Mirroring , Metal, Rackmount, RMON.VLAN 802.1Q, Auto Voice VLAN, IGMP Snooping, HOL blocking perevention, Storm Control, SNMP V1-V2c, Copper FE/GE Ports, Total System Ports: 28GE	IRR 71,070,000
59	LGS552P-EU	Gigabit , Layer 3 Static Routing, 52-Ports (48 POE) 375W, 2 Combo Ports (RJ45 + SFP), 2 X 10GB uplink Ethernet SFP+, advanced QOS, TFTP Upgrade, Port Mirroring , Metal, Rackmount, RMON.VLAN 802.1Q, Auto Voice VLAN, IGMP Snooping, HOL blocking perevention, Storm Control, SNMP V1-V2c, Copper FE/GE Ports, Total System Ports: 52GE	IRR 117,230,000
60	Access Point		
61	LAPN300-EU	Single Band; 802.11n; Max 300Mbps; Bridge; Schedule; VLAN; PoE or Adapter; Desktop/Ceiling/Wall; Rate Limit; 1*GigaEthernet; MIMO2x2	IRR 12,010,000
62	LAPN600-EU	Dual Band; 802.11n; Max 300 + 300Mbps; Bridge; Schedule; VLAN; PoE or Adapter; Desktop/Ceiling/Wall; Rate Limit; 1*GigaEthernet; MIMO2x2	IRR 18,850,000
63	LAPAC1200-EU	Dual Band; 802.11ac; Max 867 + 300Mbps; Bridge; Schedule; VLAN; PoE or Adapter; Desktop/Ceiling/Wall; Rate Limit; 1*GigaEthernet; MIMO2x2	IRR 23,250,000
64	LAPAC1750-EU	Dual Band; 802.11ac; Max 1300 + 450Mbps; Bridge; Schedule; VLAN; PoE or Adapter; Desktop/Ceiling/Wall; Rate Limit; 1*GigaEthernet; MIMO 3x3	IRR 31,650,000
65	LAPAC1750 PRO-EU	Dual Band; 802.11ac; Max 1300 + 450Mbps; Bridge; Schedule; VLAN; PoE or Adapter; Desktop/Ceiling/Wall; Rate Limit; 2*GigaEthernet; MIMO 3x3; High Gain Antenna	IRR 49,040,000
66	LAPAC2600-EU	Linksys Business Dual-Band Access Point AC2600	IRR 52,750,000
67	WAP300N-EE	Dual Band; 802.11n;Max 300Mbps;Bridge; Adapter only; Desktop;1*Fast Ethernet ; MIMO 2*2	IRR 5,610,000
68	WHW0302-ME new	LINKSYS VELOP	IRR 50,880,000
69	WAP750AC	Linksys WAP750AC AC750 Wi-Fi Access Point	IRR 8,930,000

70	VPN Router		
71	LRT214-EU	Linksys VPN Router; Site-to-Site VPN; Remote-Access VPN; Router; Firewall; 4x10/100/1000 Ports; 1xWAN Port; Metal Case	IRR 19,140,000
72	LRT224-EU	Linksys VPN Router; Site-to-Site VPN; Remote-Access VPN; Router; Firewall; 4x10/100/1000 Ports; 2xWAN Port; Metal Case; Load Balance; Smart Backup; Aggregate WAN1 + WAN2	IRR 19,930,000
73	Poe Injector		
74	LACPI30-EU	Linksys PoE Injector; 802.3af and 802.3at; 30Watts; Gigabit Ethernet; Wall Mount	IRR 5,470,000



Equip Rack

Items

Description

User Price

ER Standing Rack IP42

1	ERS - 4761	رک ۴۷ یونیت-عمق ۱۰۰-عرض ۶۰ - درب جلو شیشه ای فریم دار،درب پشت فلزی	۴۲,۰۰۰,۰۰۰
2	ERS - 4281	رک ۴۲ یونیت-عمق ۱۰۰-عرض ۸۰ - درب جلو مشبک، درب پشت ۲ لنگه مشبک	۴۹,۸۵۰,۰۰۰
3	ERS - 4261	رک ۴۲ یونیت-عمق ۱۰۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۲۹,۷۰۰,۰۰۰
4	ERS - 4268	رک ۴۲ یونیت-عمق ۸۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۲۷,۲۰۰,۰۰۰
5	ERS - 4266	رک ۴۲ یونیت-عمق ۶۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۲۴,۷۵۰,۰۰۰
6	ERS - 3761	رک ۳۷ یونیت-عمق ۱۰۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۲۷,۹۰۰,۰۰۰
7	ERS - 3868	رک ۳۸ یونیت-عمق ۸۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۲۴,۷۵۰,۰۰۰
8	ERS - 3866	رک ۳۸ یونیت-عمق ۶۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۲۲,۳۰۰,۰۰۰
9	ERS - 3261	رک ۳۲ یونیت-عمق ۱۰۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۲۵,۹۰۰,۰۰۰

10	ERS - 3268	رک ۳۲ یونیت-عمق ۸۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۲۳,۳۵۰,۰۰۰
11	ERS - 3266	رک ۳۲ یونیت-عمق ۶۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۲۱,۹۵۰,۰۰۰
12	ERS - 2861	رک ۲۷ یونیت-عمق ۱۰۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۲۳,۳۵۰,۰۰۰
13	ERS - 2868	رک ۲۷ یونیت-عمق ۸۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۲۰,۸۵۰,۰۰۰
14	ERS - 2866	رک ۲۷ یونیت-عمق ۶۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۱۸,۹۰۰,۰۰۰
15	ERS - 2261	رک ۲۲ یونیت-عمق ۱۰۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۲۰,۸۵۰,۰۰۰
16	ERS - 2168	رک ۲۲ یونیت-عمق ۸۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۱۸,۵۰۰,۰۰۰
17	ERS - 2266	رک ۲۲ یونیت-عمق ۶۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۱۷,۰۰۰,۰۰۰
18	ERS - 1868	رک ۱۸ یونیت-عمق ۸۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۱۶,۹۸۰,۰۰۰
19	ERS-1766	رک ۱۷ یونیت-عمق ۶۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۱۵,۹۵۰,۰۰۰
20	ERS-1468	رک ۱۴ یونیت-عمق ۸۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۱۵,۵۰۰,۰۰۰
21	ERS-1466	رک ۱۴ یونیت-عمق ۶۰-عرض ۶۰ - درب جلو شیشه ای فریم دار، درب پشت فلزی	۱۳,۸۵۰,۰۰۰
22	ER Wall Mount		
23	ERW - 1266	رک دیواری - ۱۲ یونیت- عمق ۶۰ ، عرض ۶۰	۶,۸۰۰,۰۰۰
24	ERW - 0966	رک دیواری - ۹ یونیت- عمق ۶۰ ، عرض ۶۰	۵,۱۵۰,۰۰۰
25	ERW - 0664	رک دیواری - ۶ یونیت- عمق ۴۵ ، عرض ۶۰	۳,۹۰۰,۰۰۰
26	ERW - 0465D	DVR رک دیواری - ۴ یونیت- عمق ۵۰ ، عرض ۶۰	Call
27	Wall Mount Economic		

28	ERC - 0450	DVR رک دیواری -۴ یونیت- عمق ۵۰	۱,۳۸۰,۰۰۰
29	ERC - 0630	رک دیواری - ۶ یونیت- عمق ۳۲ ، عرض ۴۵	۱,۸۵۰,۰۰۰
30	ERC - 0740	رک دیواری - ۷ یونیت- عمق ۴۵ ، عرض ۶۰	۲,۱۰۰,۰۰۰
31	ERC - 0960	رک دیواری - ۹ یونیت- عمق ۶۰ ، عرض ۶۰	۳,۵۵۰,۰۰۰
32	ERC - 1260	رک دیواری - ۱۲ یونیت- عمق ۶۰ ، عرض ۶۰	۳,۸۶۰,۰۰۰
33	شامل تخفیف نمی گردد Economic لازم به ذکر است رک های		
34	ER OUTDOOR RACK		
35	ERO - 0745	OUTDOOR رک ۷ یونیت - عمق ۴۵	۱۹,۸۰۰,۰۰۰
36	ERO - 0966	OUTDOOR رک ۹ یونیت - عمق ۶۰	۲۳,۰۰۰,۰۰۰
37	ERO - 1266	OUTDOOR رک ۱۲ یونیت - عمق ۶۰	۲۸,۵۰۰,۰۰۰
38	ERO - 1866	OUTDOOR رک ۱۸ یونیت - عمق ۸۰	۳۴,۵۰۰,۰۰۰
39	شامل تخفیف نمی گردد OUTDOOR لازم به ذکر است رک های		
40	ER MAIN FRAME		
41	ERM - 4202	رک ۴۲ یونیت - آزمایشگاهی - دو پنل	۱۳,۰۰۰,۰۰۰
42	ERM - 4201	رک ۴۲ یونیت - آزمایشگاهی - تک پنل	۹,۵۰۰,۰۰۰
43	ERM - 3202	رک ۳۲ یونیت - آزمایشگاهی - دو پنل	۸,۸۰۰,۰۰۰
44	Shelf		
45	ERA - SSW	طبقه ثابت رک های دیواری	۴۸۰,۰۰۰
46	ERA - SS 60	طبقه ثابت رک ، ۶۰ سانتیمتر	۷۲۰,۰۰۰
47	ERA - SS 80	طبقه ثابت رک ، ۸۰ سانتیمتر	۹۹۰,۰۰۰
48	ERA - SS 10	طبقه ثابت رک ، ۱۰۰ سانتیمتر	۱,۲۰۰,۰۰۰
49	ERA - SM 60	سینی متحرک رک ۶۰ سانتیمتر	۱,۹۵۰,۰۰۰
50	ERA - SM 80	سینی متحرک رک ۸۰ سانتیمتر	۱,۹۵۰,۰۰۰
51	ERA - SM 10	سینی متحرک رک ۱۰۰ سانتیمتر	۱,۹۵۰,۰۰۰
52	Power Module		

53	PMM - 08	پاور ماژول ۱۹ اینچ یک یونیت ، تک کلید ، بدنه آلومینیومی ، هشت پورت	۷۹۰,۰۰۰
54	PMM - 03	پاور ماژول بدنه آلومینیومی ارت دار با یک متر کابل ، سه پورت	۴۰۰,۰۰۰
55	Accessories		
56	ERA - LI - 10	لایت پنل ۱۹ اینچ جهت روشنایی تجهیزات	۹۵۰,۰۰۰
57	ERA - SCR - 20	پیچ و کزنات مخصوص رک بسته ۱۰ تایی	۷۰,۰۰۰
58	ERA - TR - 20	حرارت سنج یک یونیت دیجیتال تنظیم دما،رطوبت، ولتاژ و جریان	۱۰,۱۰۰,۰۰۰
59	ERA - FN - 20	فن پوشی ۲۲۰ ولت با بدنه فلزی ، سایز ۱۲*۱۲ سانتیمتر	۷۸۰,۰۰۰
60	ERA - CM - 10	نگهدارنده افقی کابل ۱۹ اینچ	۴۲۰,۰۰۰
61	ERA - CM - 20	نگهدارنده عمودی کابل	۷۰,۰۰۰
62	ERA - CM - 30	نگهدارنده کابل درپوش دار	۳۵۰,۰۰۰
63	ERA - SL - 10	قفل سوئیچی درب رک های دیواری و پنل های جانبی	۲۰۰,۰۰۰
64	Blank Panel		
65	ERA - BLA - 10	بلانک پنل ، ۱ یونیت	۱۷۵,۰۰۰
66	ERA - BLA - 20	بلانک پنل ، ۲ یونیت	۲۲۰,۰۰۰
67	ERA - BLA - 30	بلانک پنل ، ۳ یونیت	۲۵۰,۰۰۰
68	ERA - BLA - 40	بلانک پنل ، ۴ یونیت	۳۰۰,۰۰۰
69	ERA - BLA - 50	بلانک پنل ، ۱ یونیت فرچه ای	۳۵۰,۰۰۰
70	Doors		
71	EDM - 4261	درب مشبک ۴۲ یونیت ساده عرض ۶۰ به همراه قفل	۳,۹۵۰,۰۰۰
72	EDM - 3801	تفاوت قیمت درب مشبک ۳۸ یونیت تک لنگه با درب شیشه ای	۲,۷۰۰,۰۰۰
73	EDM - 3201	تفاوت قیمت درب مشبک ۳۲ یونیت تک لنگه با درب شیشه ای	۲,۷۰۰,۰۰۰
74	EDM - 2801	تفاوت قیمت درب مشبک ۲۸ یونیت تک لنگه با درب شیشه ای	۲,۲۰۰,۰۰۰

لازم به ذکر است درب مشبک شامل تخفیف نمی گردد.

