

#1 in North America for High-Pressure Cleaning Equipment



Electric / Direct Drive

Easy to understand **operating instructions** and warnings

A **36-ft electrical safety cord** with Ground Fault Circuit Interrupter (GFCI)

Industrial-strength 1725 RPM Baldor Motor with full-service factor and solid performance for years of service

Rugged **all-steel 10-gauge chassis** and protected with an all-weather, epoxy powder coat finish



steel and color-coded for easy spray pattern selection: 0°, 15°, 25° & 40° and a detergent nozzle.

Five quick-couple nozzles

made of hardened stainless

The reliable Hotsy direct-drive pump carries a 7-year limited warranty...best in the industry! Insulated, fatigue-free spring-loaded **trigger gun** with detachable, two-piece, insulated spray wand make for easy point-and-shoot cleaning action

> Hose and gun hanger keeps spray wand and hose safely stored

Water resistant electrical box for added safety and easy servicing

easy servicing

50-ft of steel-wire braid **highpressure hose** rated for up to 3000 PSI and with 24-inch **hose guard** for burst protection and swivel swedge fitting for ease in handling

Quick-couple **detergent injection**

allows for easy a application of soap

Thermal pump protector to prevent

excessive heat or pressure build-up for

10" 2-ply tubed pneumatic tires for easy maneuvering

FEATURES

- 1.5 to 5 HP Baldor motors
- 2 to 3.5 GPM / 1000 to 2000 PSI
- Compact, lightweight design
- Hotsy 7-yr pump warranty

Two **rubber pad feet** absorb vibration and keep machine from"walking"

Durable pressure trapping **unloader** diverts water flow when trigger gun is not activated

www.Hotsy.com

added safety

1.5-5 HP Baldor motors

2 to 3.5 GPM @ 1000 to 2000 PSI

Compact / lightweight design

7-yr Hotsy pump warranty

The Hotsy EP Series: The Right Choice for Tough, Cold-Water Cleaning

SPECIFICATIONS									DIRECT DRIVE	
MODEL	GPM	PSI	HP	MOTOR RPM	VOLT/PH	AMPS	TRIPLEX PUMP MODEL	DRIVE	HOSE	SHIP WT (lbs)
EP-201009D	2.0	1000	1.5	1725	120/1	15	Hotsy HE2020S.1	DIRECT	50'	151
EP-301009D	3.0	1000	2	1725	120/1	20	Hotsy HE28255.1	DIRECT	50'	163
EP-301509A	3.0	1500	3	1725	230/1	15	Hotsy HE2825S.1	DIRECT	50'	157
EP-352009A	3.5	2000	5	1725	230/1	20	Hotsy HHC456R.1	DIRECT	50′	210

Dimensions: 35"l x 21"w x 24"h

DON'T FORGET THE SOAP!

Hotsy pressure washers clean best when matched with specially formulated Hotsy detergents. Nearly all contain Hotsy's exclusive advanced-formula HCC additives to help prevent scale build-up and to fight corrosion in your equipment. All are highly concentrated, so a little goes a long way

> HOTSY SOLUTION SELECTOR What's the best detergent for your next job? Find out with our solution selector. Scan this QR code or visit HOTSY.com

SERVICE & REPAIR

Hotsy has more than 175 local dealers in North America, all factory-trained to properly evaluate your high-pressure cleaning needs.

Hotsy has factory-trained service technicians who will provide on-site maintenance for your cleaning equipment. Our techs have most common replacement parts on their service truck, and will quickly have your washer running smoothly.



ø

OPTIONS FOR EP SERIES

- 100' Hose Reel Kit*
- * Kit includes hose reel and mounting hardware

PARTS & ACCESSORIES

Your local Hotsy dealer stocks a number of accessories designed to speed cleaning. The most common accessories are telescoping wands, pivot and non-pivot hose reels, flat surface cleaners and high pressure turbo nozzles.

Hotsy dealers also stock thousands of pressure washer replacement parts such as high pressure hose,

trigger guns, high pressure nozzles, pumps, unloaders, filters and wands.

FIND OUT MORE ONLINE: HOTSY.COM



 Tel: (800) 525-1976
 Fax: (888) 880-9631

 www.Hotsy.com
 email: info@Hotsy.com

 P/N 8.914-200.0
 Effective 3/16

Specifications & product descriptions subject to change without notice. Hotsy's manufacturing facilities have established and apply a quality and environmental management system to be ISO 9001:2008 and ISO 14001:2001 certified. A member of KÅRCHER North America ©2016 Hotsy

NOTE: We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models. Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We meet the CETA testing specs for machine performance at \pm 10% and in some cases are tighter within \pm 5% of listed specifications.

Distributed by: